

































-  Secrets
-  ABAP
-  Apex
-  C
-  C++
-  CloudFormation
-  COBOL
-  C#
-  CSS
-  Flex
-  Go
-  HTML
-  Java
-  JavaScript
-  Kotlin
-  Kubernetes
-  Objective C
-  PHP
-  PL/I
-  **PL/SQL**
-  Python
-  RPG
-  Ruby
-  Scala
-  Swift
-  Terraform
-  Text
-  TypeScript
-  T-SQL
-  VB.NET
-  VB6
-  XML

PL/SQL

PL/SQL static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your PL/SQL code

All rules 188


 Vulnerability 4













 Bug 45

 Security Hotspot 2

 Code Smell 137

Tags ▾

Search by name... 

	
Procedures should have parameters	
	
"EXECUTE IMMEDIATE" should be used instead of DBMS_SQL procedure calls	
	
"NATURAL JOIN" queries should not be used	
	
"END" statements of labeled loops should be labeled	
	
In labeled loops "EXIT" should exit the label	
	
"EXIT WHEN" should be used rather than "IF ... THEN EXIT; END IF;"	
	
"FOR" loop end conditions should not be hard-coded	
	
Large item lists should not be used with "IN" clauses	
	
"GOTO" should not be used within loops	
	
"FULL OUTER JOINS" should be used with caution	
	
"CASE" should be used rather than "DECODE"	
	
"CROSS JOIN" queries should not be used	

Procedures should have parameters

Analyze your code

 Code Smell

 Major



 design

Procedures which don't accept parameters are likely to either not be reused that often or to depend on global variables instead. Refactoring those procedures to take parameters will make them both more flexible and reusable.

Noncompliant Code Example

```
SET SERVEROUTPUT ON

DECLARE
    name VARCHAR2(42) := 'John';

    PROCEDURE print_name; -- Noncompliant

    PROCEDURE print_name AS -- Noncompliant
    BEGIN
        DBMS_OUTPUT.PUT_LINE('Name: ' || name);
    END;

BEGIN
    print_name;
END;
/
```

Compliant Solution

```
SET SERVEROUTPUT ON

DECLARE
    PROCEDURE print_name(name VARCHAR2) AS -- Compliant
    BEGIN
        DBMS_OUTPUT.PUT_LINE('Name: ' || name);
    END;
BEGIN
    print_name('John');
END;
/
```

Available In:

sonarlint 

sonarcloud 

sonarqube  Developer Edition