Using Terraform to create the IAM Roles and Policies for EKS

Terraform files explanation

▼ 5. Linking the Cloud9 IDE
 & CI/CD VPC to the EKS
 Network

Connect the Cloud9
IDE & CICD VPC to the
EKS VPC

Terraform files explanation

▼ 6. Deploy the CICD Infrastructure

Create the CI/CD Components

Terraform files explanation

▼ 7. EKS Cluster Creation

Creating the EKS Cluster

Terraform files explanation

 8. Create a customized managed Node Group Amazon EKS Terraform Workshop > 5. Creating a private EKS Cluster with Terraform > 7. EKS Cluster Creation > Creating the EKS Cluster

Creating the EKS Cluster

1 cd ~/environment/tfekscode/cluster



Initialize Terraform:

1 terraform init



Initializing the backend...

** OUTPUT TRUNCATED FOR BREVITY as similar to previous examples **

Validate the Terraform code

1 terraform validate



Success! The configuration is valid.

Using Terraform to create the IAM Roles and Policies for EKS

Terraform files explanation

▼ 5. Linking the Cloud9 IDE
 & CI/CD VPC to the EKS
 Network

Connect the Cloud9
IDE & CICD VPC to the
EKS VPC

Terraform files explanation

▼ 6. Deploy the CICD Infrastructure

Create the CI/CD Components

Terraform files explanation

▼ 7. EKS Cluster Creation

Creating the EKS Cluster

Terraform files explanation

 8. Create a customized managed Node Group Plan the deployment:

terraform plan -out tfplan



```
data.aws_ssm_parameter.cicd-vpc: Reading...
data.aws_ssm_parameter.eks-cidr: Reading...
** OUTPUT TRUNCATED FOR BREVITY **
data.aws_ssm_parameter.tf-eks-keyarn: Read complete after 0s [id=/workshop/tf-eks/keyar
data.aws_kms_key.ekskey: Read complete after 0s [id=3c922c67-3466-4ba6-98a7-052be67d4be
data.aws_caller_identity.current: Read complete after 0s [id=440018911661]
Terraform used the selected providers to generate the following execution plan. Resource
  + create
Terraform will perform the following actions:
 # aws_eks_addon.vpc-cni will be created
 + resource "aws_eks_addon" "vpc-cni" {
                             = "vpc-cni"
      + addon name
     + addon version
                             = "v1.12.1-eksbuild.1"
                             = (known after apply)
      + arn
                             = (sensitive value)
      + cluster name
      + configuration_values = jsonencode(
              + env = {
                  + AWS_VPC_K8S_CNI_CUSTOM_NETWORK_CFG = "true"
                             = (known after apply)
      + created_at
                             = (known after apply)
      + id
                             = (known after apply)
      + modified at
      + preserve
                             = true
      + resolve conflicts
                             = "OVERWRITE"
      + tags_all
                             = (known after apply)
```

Using Terraform to create the IAM Roles and Policies for EKS

Terraform files explanation

5. Linking the Cloud9 IDE
 & CI/CD VPC to the EKS
 Network

Connect the Cloud9
IDE & CICD VPC to the
EKS VPC

Terraform files explanation

▼ 6. Deploy the CICD Infrastructure

Create the CI/CD Components

Terraform files explanation

▼ 7. EKS Cluster Creation

Creating the EKS Cluster

Terraform files explanation

 8. Create a customized managed Node Group

```
}
** OUTPUT TRUNCATED FOR BREVITY **
  # aws_ssm_parameter.oidc_provider_arn will be created
  + resource "aws_ssm_parameter" "oidc_provider_arn" {
                       = (known after apply)
      + arn
                       = (known after apply)
      + data_type
                       = "The EKS cluster oidc arn"
      + description
      + id
                       = (known after apply)
      + insecure_value = (known after apply)
      + key_id
                       = (known after apply)
                       = "/workshop/tf-eks/oidc_provider_arn"
      + name
      + tags
          + "workshop" = "tf-eks-workshop"
      + tags_all
                       = {
          + "workshop" = "tf-eks-workshop"
                       = (known after apply)
      + tier
                       = "String"
      + type
                       = (sensitive value)
      + value
                       = (known after apply)
      + version
    }
  # null_resource.gen_cluster_auth will be created
  + resource "null_resource" "gen_cluster_auth" {
                 = (known after apply)
      + id
      + triggers = {}
    }
Plan: 10 to add, 0 to change, 0 to destroy.
```

You can see from the plan the following resources will be created

Using Terraform to create the IAM Roles and Policies for EKS

Terraform files explanation

5. Linking the Cloud9 IDE
 & CI/CD VPC to the EKS
 Network

Connect the Cloud9
IDE & CICD VPC to the
EKS VPC

Terraform files explanation

▼ 6. Deploy the CICD Infrastructure

Create the CI/CD Components

Terraform files explanation

▼ 7. EKS Cluster Creation

Creating the EKS Cluster

Terraform files explanation

 8. Create a customized managed Node Group

- An EKS Cluster
- Configure the cluster with an OIDC provider and add support for ISRA (IAM Roles for Service Accounts)
- A null resource which runs a small script to test connectivity to EKS with nmap and write the local .kubeconfig file

Build the environment:

terraform apply tfplan



** THE OUTPUT IS TRUNCATED FOR BREVITY INDICATED WITH '....' **

```
aws_eks_cluster.cluster: Creating...
aws_eks_cluster.cluster: Still creating... [10s elapsed]
aws_eks_cluster.cluster: Still creating... [10m10s elapsed]
aws_eks_cluster.cluster: Provisioning with 'local-exec'...
aws_eks_cluster.cluster (local-exec): Executing: ["/bin/sh" "-c" "until curl --output /
aws_eks_cluster.cluster: Creation complete after 10m11s [id=mycluster1]
aws_ssm_parameter.ca: Creating...
aws_ssm_parameter.cluster-name: Creating...
aws_ssm_parameter.cluster-sq: Creating...
aws_eks_identity_provider_config.oidc: Creating...
aws_ssm_parameter.endpoint: Creating...
aws_eks_addon.vpc-cni: Creating...
aws_security_group_rule.eks-add-clustersg: Creating...
aws_ssm_parameter.endpoint: Creation complete after 0s [id=/workshop/tf-eks/endpoint]
aws_ssm_parameter.cluster-sq: Creation complete after 0s [id=/workshop/tf-eks/cluster-sq:
aws_ssm_parameter.ca: Creation complete after 0s [id=/workshop/tf-eks/ca]
aws_ssm_parameter.cluster-name: Creation complete after 0s [id=/workshop/tf-eks/eks-clu
aws_security_group_rule.eks-add-clustersg: Creation complete after 0s [id=sgrule-176315]
aws_eks_addon.vpc-cni: Still creating... [10s elapsed]
aws_eks_identity_provider_config.oidc: Still creating... [10s elapsed]
aws_eks_addon.vpc-cni: Still creating... [20s elapsed]
```

Using Terraform to create the IAM Roles and Policies for EKS

Terraform files explanation

5. Linking the Cloud9 IDE
 & CI/CD VPC to the EKS
 Network

Connect the Cloud9
IDE & CICD VPC to the
EKS VPC

Terraform files explanation

▼ 6. Deploy the CICD Infrastructure

Create the CI/CD Components

Terraform files explanation

▼ 7. EKS Cluster Creation

Creating the EKS Cluster

Terraform files explanation

 8. Create a customized managed Node Group

```
aws_eks_addon.vpc-cni: Still creating... [2m30s elapsed]
aws_eks_identity_provider_config.oidc: Still creating... [2m30s elapsed]
aws_eks_addon.vpc-cni: Creation complete after 2m36s [id=mycluster1:vpc-cni]
null_resource.gen_cluster_auth: Creating...
null_resource.gen_cluster_auth: Provisioning with 'local-exec'...
null_resource.gen_cluster_auth (local-exec): (output suppressed due to sensitive value
null_resource.gen_cluster_auth (local-exec): (output suppressed due to sensitive value
aws_eks_identity_provider_config.oidc: Still creating... [2m40s elapsed]
null_resource.gen_cluster_auth (local-exec): (output suppressed due to sensitive value
null_resource.gen_cluster_auth (local-exec): (output suppressed due to sensitive value
null_resource.gen_cluster_auth: Creation complete after 6s [id=4595653272837574562]
aws_eks_identity_provider_config.oidc: Still creating... [2m50s elapsed]
aws_eks_identity_provider_config.oidc: Still creating... [6m40s elapsed]
aws_eks_identity_provider_config.oidc: Creation complete after 6m40s [id=mycluster1:myc
aws_ssm_parameter.oidc_provider_arn: Creating...
aws_ssm_parameter.oidc_provider_arn: Creation complete after 0s [id=/workshop/tf-eks/oi
Apply complete! Resources: 10 added, 0 changed, 0 destroyed.
```

Previous

Next