



 **kubernetes**

default

 Search







Settings

Cron Jobs

Daemon Sets

Deployments

Jobs

Pods

Replica Sets

Replication Controllers

Stateful Sets

Service

Ingresses

Ingress Classes

Services

Config and Storage

Config Maps

Persistent Volume Claims

Secrets

Storage Classes

Cluster

Cluster Role Bindings

Cluster Roles

Events

Namespaces

Network Policies

Nodes

Persistent Volumes

Role Bindings

Roles

Service Accounts

Custom Resource Definitions

Global settings

Global settings are stored in config map, so all of them are applied for every instance of the a

Cluster name

Cluster name appears in the browser window title if it is set.

Default namespace

Namespace that should be selected by default after logging in.

Namespace fallback list

List of namespaces that should be presented to user without namespace list privileges.

Items per page

Max number of items that can be displayed on every list view.

Labels limit

Max number of labels that are displayed by default on most views.

Logs auto-refresh time interval

Number of seconds between every auto-refresh of logs.

Resource auto-refresh time interval

Number of seconds between every auto-refresh of every resource. Set 0 to disable.

Disable access denied notification

Hides all access denied warnings in the notification panel.

Save

Reload

Local settings

Local settings are stored in the browser cookies, so they are not synchronized between multip

Theme

Choose color theme of the dashboard

Language

Change the language of the dashboard

Settings

About

127.0.0.1:8001/api/v1/namespaces/kubernetes-dashboard/services/https:kubernetes-dashboard:/proxy/#!/settings?namespace=default

1/1