


-  Secrets
-  ABAP
-  Apex
-  C
-  C++
-  CloudFormation
-  COBOL
-  C#
-  CSS
-  Flex
-  Go
-  HTML
-  Java
-  JavaScript
-  Kotlin
-  Kubernetes
-  **Objective C**
-  PHP
-  PL/I
-  PL/SQL
-  Python
-  RPG
-  Ruby
-  Scala
-  Swift
-  Terraform
-  Text
-  TypeScript
-  T-SQL
-  VB.NET
-  VB6
-  XML




Objective C static code analysis


Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your OBJECTIVE C code


All rules 315

 Vulnerability 10

 Bug 75

 Security Hotspot 18

 Code Smell 212

 Quick Fix 13

Tags

Search by name...



"memset" should not be used to delete sensitive data

 Vulnerability

POSIX functions should not be called with arguments that trigger buffer overflows

 Vulnerability

Function-like macros should not be invoked without all of their arguments

 Bug

The address of an automatic object should not be assigned to another object that may persist after the first object has ceased to exist

 Bug

"pthread_mutex_t" should be unlocked in the reverse order they were locked

 Bug

"pthread_mutex_t" should be properly initialized and destroyed

 Bug

"pthread_mutex_t" should not be consecutively locked or unlocked twice

 Bug

Functions with "noreturn" attribute should not return

 Bug

"memcpy" should only be called with pointers to trivially copyable types with no padding

 Bug

Stack allocated memory and non-owned memory should not be freed

 Bug

Closed resources should not be accessed

 Bug

Dynamically allocated memory should be released

 Bug

Deprecated attributes should include explanations

Analyze your code

 Code Smell  Major  obsolete bad-practice

The deprecated attribute can be applied with or without explanations, but marking something deprecated without including advice as to why it's deprecated or on what to use instead will lead maintainers to waste time trying to figure those things out - every single time the warning is encountered.

Noncompliant Code Example

```
[[deprecated]] // Noncompliant
void foo1();

__attribute__((deprecated)) // Noncompliant
void foo2();

__declspec(deprecated) // Noncompliant
void foo3();
```

Compliant Solution

```
[[deprecated("use 'bar' instead")]]
void foo1();

__attribute__((deprecated("use 'bar' instead")))
void foo2();

__declspec(deprecated("use 'bar' instead"))
void foo3();
```

Available In:

sonarcloud  | sonarqube  Developer Edition

<div>Freed memory should not be used</div> <div> Bug</div>
<div>Memory locations should not be released more than once</div> <div> Bug</div>
<div>Memory access should be explicitly bounded to prevent buffer overflows</div> <div> Bug</div>
<div>Printf-style format strings should not lead to unexpected behavior at runtime</div> <div> Bug</div>
<div>Recursion should not be infinite</div> <div> Bug</div>
<div>Resources should be closed</div> <div> Bug</div>
<div>Hard-coded credentials are security-sensitive</div> <div> Security Hotspot</div>
<div>"goto" should jump to labels declared later in the same function</div> <div> Code Smell</div>
<div>Only standard forms of the "defined" directive should be used</div> <div> Code Smell</div>
<div>Switch labels should not be nested inside non-switch blocks</div> <div> Code Smell</div>