

-  Secrets
-  ABAP
-  Apex
-  C
-  C++
-  CloudFormation
-  COBOL
-  C#
-  CSS
-  Flex
-  Go
-  HTML
-  Java
-  JavaScript
-  Kotlin
-  Kubernetes
-  **Objective C**
-  PHP
-  PL/I
-  PL/SQL
-  Python
-  RPG
-  Ruby
-  Scala
-  Swift
-  Terraform
-  Text
-  TypeScript
-  T-SQL
-  VB.NET
-  VB6
-  XML



Objective C static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your OBJECTIVE C code

All rules 315

Vulnerability 10

Bug 75

Security Hotspot 18

Code Smell 212

Quick Fix 13

Tags

Search by name...



"memset" should not be used to delete sensitive data

Vulnerability

POSIX functions should not be called with arguments that trigger buffer overflows

Vulnerability

Function-like macros should not be invoked without all of their arguments

Bug

The address of an automatic object should not be assigned to another object that may persist after the first object has ceased to exist

Bug

"pthread_mutex_t" should be unlocked in the reverse order they were locked

Bug

"pthread_mutex_t" should be properly initialized and destroyed

Bug

"pthread_mutex_t" should not be consecutively locked or unlocked twice

Bug

Functions with "noreturn" attribute should not return

Bug

"memcpy" should only be called with pointers to trivially copyable types with no padding

Bug

Stack allocated memory and non-owned memory should not be freed

Bug

Closed resources should not be accessed

Bug

Dynamically allocated memory should be released

Bug

Limited dependence should be placed on operator precedence

Analyze your code

Code Smell Major cwe cert

The rules of operator precedence are complicated and can lead to errors. For this reason, parentheses should be used for clarification in complex statements. However, this does not mean that parentheses should be gratuitously added around every operation.

Parentheses are not needed:

- with a unary operator, except when ! is used as left operand in comparison expressions
- when all the operators in an expression are the same
- when only a single operator is involved
- around the right-hand side of an assignment operator unless the right-hand side itself contains an assignment

Parentheses are needed:

- in the condition of a ternary operator if it uses operators
- when overloaded shift operator << or >> is used in an expression with comparison operators

Noncompliant Code Example

```
x = a + b;
x = a * -1;
x = a + b + c;
x = f ( a + b, c );

x = a == b ? a : a - b; // Noncompliant
x = a + b - c + d; // Noncompliant
x = a * 3 + c + d; // Noncompliant

if (a = f(b,c) == true) { ... } // Noncompliant; == evaluated
x - b ? a : c; // Noncompliant; "-" evaluated first
s << 5 == 1; // Noncompliant; "<<" evaluated first
```

Compliant Solution

```
x = a + b;
x = a * -1;
x = a + b + c;
x = f ( a + b, c );

x = ( a == b ) ? a : ( a - b );
x = ( a + b ) - ( c + d );
x = ( a * 3 ) + c + d;

if ( (a = f(b,c)) == true) { ... }
(x - b) ? a : c; // Compliant
(s << 5) == 1; // Compliant
```

See

- MISRA C:2004, 12.1 - Limited dependence should be placed on C's operator precedence rules in expressions
- MISRA C:2004, 12.2 - The value of an expression shall be the same under any order of evaluation that the standard permits.
- MISRA C:2004, 12.5 - The operands of a logical && or || shall be primary-expressions.

<div>Freed memory should not be used</div> <div> Bug</div>
<div>Memory locations should not be released more than once</div> <div> Bug</div>
<div>Memory access should be explicitly bounded to prevent buffer overflows</div> <div> Bug</div>
<div>Printf-style format strings should not lead to unexpected behavior at runtime</div> <div> Bug</div>
<div>Recursion should not be infinite</div> <div> Bug</div>
<div>Resources should be closed</div> <div> Bug</div>
<div>Hard-coded credentials are security-sensitive</div> <div> Security Hotspot</div>
<div>"goto" should jump to labels declared later in the same function</div> <div> Code Smell</div>
<div>Only standard forms of the "defined" directive should be used</div> <div> Code Smell</div>
<div>Switch labels should not be nested inside non-switch blocks</div> <div> Code Smell</div>

- MISRA C++:2008, 5-0-1 - The value of an expression shall be the same under any order of evaluation that the standard permits.
- MISRA C++:2008, 5-0-2 - Limited dependence should be placed on C++ operator precedence rules in expressions
- MISRA C++:2008, 5-2-1 - Each operand of a logical && or || shall be a postfix-expression.
- MISRA C:2012, 12.1 - The precedence of operators within expressions should be made explicit
- [CERT, EXP00-C](#) - Use parentheses for precedence of operation
- [CERT, EXP53-J](#) - Use parentheses for precedence of operation
- [MITRE, CWE-783](#) - Operator Precedence Logic Error

Available In:

sonarcloud



sonarqube



Developer Edition