

- Secrets
- ABAP
- Apex
- C
- C++
- CloudFormation
- COBOL
- C#
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Kubernetes
- Objective C
- PHP
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



Objective C static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your OBJECTIVE C code

All rules 315

Vulnerability 10

Bug 75

Security Hotspot 18

Code Smell 212

Quick Fix 13

Tags

Search by name...



"memset" should not be used to delete sensitive data

Vulnerability

POSIX functions should not be called with arguments that trigger buffer overflows

Vulnerability

Function-like macros should not be invoked without all of their arguments

Bug

The address of an automatic object should not be assigned to another object that may persist after the first object has ceased to exist

Bug

"pthread_mutex_t" should be unlocked in the reverse order they were locked

Bug

"pthread_mutex_t" should be properly initialized and destroyed

Bug

"pthread_mutex_t" should not be consecutively locked or unlocked twice

Bug

Functions with "noreturn" attribute should not return

Bug

"memcpy" should only be called with pointers to trivially copyable types with no padding

Bug

Stack allocated memory and non-owned memory should not be freed

Bug

Closed resources should not be accessed

Bug

Dynamically allocated memory should be released

Bug

Two branches in a conditional structure should not have exactly the same implementation

Analyze your code

Code Smell Major design suspicious

Having two cases in a switch statement or two branches in an if chain with the same implementation is at best duplicate code, and at worst a coding error. If the same logic is truly needed for both instances, then in an if chain they should be combined, or for a switch, one should fall through to the other.

Noncompliant Code Example

```
switch (i) {
    case 1:
        doFirstThing();
        doSomething();
        break;
    case 2:
        doSomethingDifferent();
        break;
    case 3: // Noncompliant; duplicates case 1's implementation
        doFirstThing();
        doSomething();
        break;
    default:
        doTheRest();
}

if (a >= 0 && a < 10) {
    doFirstThing();
    doTheThing();
}
else if (a >= 10 && a < 20) {
    doTheOtherThing();
}
else if (a >= 20 && a < 50) {
    doFirstThing();
    doTheThing(); // Noncompliant; duplicates first condition
}
else {
    doTheRest();
}
```

Exceptions

Blocks in an if chain that contain a single line of code are ignored, as are blocks in a switch statement that contain a single line of code with or without a following break.

```
if (a == 1) {
    doSomething(); //no issue, usually this is done on purpose
} else if (a == 2) {
    doSomethingElse();
} else {
    doSomething();
}
```

But this exception does not apply to if chains without else-s, or to switch-es without default clauses when all branches have the same single line of code. In case of if chains with else-s, or of switch-es with default clauses, rule {rule:cpp:S3923} raises a bug.

<div>Freed memory should not be used</div> <div> Bug</div>
<div>Memory locations should not be released more than once</div> <div> Bug</div>
<div>Memory access should be explicitly bounded to prevent buffer overflows</div> <div> Bug</div>
<div>Printf-style format strings should not lead to unexpected behavior at runtime</div> <div> Bug</div>
<div>Recursion should not be infinite</div> <div> Bug</div>
<div>Resources should be closed</div> <div> Bug</div>
<div>Hard-coded credentials are security-sensitive</div> <div> Security Hotspot</div>
<div>"goto" should jump to labels declared later in the same function</div> <div> Code Smell</div>
<div>Only standard forms of the "defined" directive should be used</div> <div> Code Smell</div>
<div>Switch labels should not be nested inside non-switch blocks</div> <div> Code Smell</div>

```
if (a == 1) {
    doSomething(); //Noncompliant, this might have been done o
} else if (a == 2) {
    doSomething();
}
```

Available In:

sonarcloud



sonarqube



Developer Edition