

## Question1

Create a function that takes an integer and returns a list from 1 to the given number, where:

1. If the number **can be divided** evenly by 4, amplify it by 10 (i.e. return 10 times the number).
2. If the number **cannot be divided** evenly by 4, simply return the number.

## Examples

```
amplify(4) ➔ [1, 2, 3, 40]
```

```
amplify(3) ➔ [1, 2, 3]
```

```
amplify(25) ➔ [1, 2, 3, 40, 5, 6, 7, 80, 9, 10, 11, 120, 13, 14, 15, 160, 17, 18, 19, 200, 21, 22, 23, 240, 25]
```

## Notes

- The given integer will always be equal to or greater than 1.
- Include the number (see example above).
- To perform this problem with its intended purpose, try doing it with list comprehensions. If that's too difficult, just solve the challenge any way you can.

## Question2

Create a function that takes a list of numbers and return the number that's unique.

## Examples

```
unique([3, 3, 3, 7, 3, 3]) ➔ 7
```

```
unique([0, 0, 0.77, 0, 0]) ➔ 0.77
```

```
unique([0, 1, 1, 1, 1, 1, 1, 1]) ➔ 0
```

## Notes

Test cases will always have exactly one unique number while all others are the same.

## Question3

Your task is to create a Circle constructor that creates a circle with a radius provided by an argument. The circles constructed must have two getters `getArea()` ( $\pi r^2$ ) and `getPerimeter()` ( $2\pi r$ ) which give both respective areas and perimeter (circumference).

For help with this class, I have provided you with a Rectangle constructor which you can use as a base example.

## Examples

```
circo = Circle(11)
circo.getArea()

# Should return 380.132711084365

circo = Circle(4.44)
circo.getPerimeter()

# Should return 27.897342763877365
```

## Notes

Round results up to the nearest integer.

### Question4

Create a function that takes a list of strings and return a list, sorted from shortest to longest.

## Examples

```
sort_by_length(["Google", "Apple", "Microsoft"])
→ ["Apple", "Google", "Microsoft"]

sort_by_length(["Leonardo", "Michelangelo", "Raphael", "Donatello"])
→ ["Raphael", "Leonardo", "Donatello", "Michelangelo"]

sort_by_length(["Turing", "Einstein", "Jung"])
→ ["Jung", "Turing", "Einstein"]
```

## Notes

All test cases contain lists with strings of *different* lengths, so you won't have to deal with multiple strings of the same length.

### Question5

Create a function that validates whether three given integers form a **Pythagorean triplet**. The sum of the squares of the *two smallest integers* must equal the square of the *largest number* to be validated.

## Examples

```
is_triplet(3, 4, 5) ➔ True  
#  $3^2 + 4^2 = 25$   
#  $5^2 = 25$ 
```

```
is_triplet(13, 5, 12) ➔ True  
#  $5^2 + 12^2 = 169$   
#  $13^2 = 169$ 
```

```
is_triplet(1, 2, 3) ➔ False  
#  $1^2 + 2^2 = 5$   
#  $3^2 = 9$ 
```

## Notes

Numbers may not be given in a sorted order.