Status	Finished
Started	Saturday, 10 October 2026, 9:56 AM
Completed	Saturday, 10 October 2026, 10:05 AM
Duration	9 mins 21 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
t = (58, 47, 36, 25, 14, 3)
x = t[2:-1]
print(x)
```

a. (3,14,25)

b. Error

c. (36, 25, 14) ✓

d. (58,47,36,25)

Question **2**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
t1 = (55, 44, 33, 22, 11)
x = [t1[i] for i in range(0, len(t1), 2)]
print(x)
```

a. [55, 33, 11] ✓

b. [(55,33,11)]

c. ([55,33,11])

d. (55,33,11)

Question **3**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {1, 2, 3, 4, 5}
set2 = {6, 7, 1, 3, 4, 8, 2, 5}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. False
False

b. True
False

c. False
True

d. True ✓
True

Question **4**

Correct

Mark 1.00 out of 1.00

Select which is true for Python tuple?

a. None of these

b. We can change the tuple once created

c. A tuple is unordered

d. A tuple maintains the order of items ✓

Question **5**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={0,0,9}

print(set1)
```

a. It will throw an error as there are two 0 while creating the set.

b. {0,9} ✓

c. {9}

d. {0,0,9}

Question **6**

Correct

Mark 1.00 out of 1.00

Which of the following Python code will create a set?

(i) set1=set((0,9,0))
(ii) set1=set([0,2,9])
(iii) set1={}

a. i,ii ✓

b. All of the above

c. ii

d. iii

Question **7**

Correct

Mark 1.00 out of 1.00

If a=(15,16,17,18,19,25), then a[1:-1] will be

Note :

a=(15,16,17,18,19,25)

print((a[1:-1]))

a. (25,19,18,17)

b. (16,17,18,19) ✓

c. Error

d. (16,17,18)

Question **8**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
t1 = (1,2,3,(4,5))
t2 = (3,2,1,(4,5))
print(t1>t2)
```

a. Error

b. True

c. False ✓

d. Error

Question **9**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
t1 = (1,2,3)
t2 = (4,5,6)
x = t1+t2
print(x)
```

- a. (1,2,3,4,5,6) ✓
- b. (1,2,3,3,2,1)
- c. Error
- d. (1,2,3)(4,5,6)

Question **10**

Correct

Mark 1.00 out of 1.00

```
What is the output of the following code?
```

```
aTuple = (10, 20, 30, 40, 50, 60, 70, 80)
print(aTuple[2:5], aTuple[:4], aTuple[3:])
```

- a. (10, 20, 30, 40) (40, 50, 60, 70, 80)
- b. (30, 40, 50) (10, 20, 30, 40) (40, 50, 60, 70, 80) ✓
- c. (30, 40, 50) (10, 20, 30, 40)
- d. (30, 40, 50)(40, 50, 60, 70, 80)

Question **11**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={2,5,3}

set2={3,1}

set3={}

set3=set1&set2

print(set3)
```

a. {}

b. {2,5,1}

c. {3} ✓

d. {2,5,3,1}

Question **12**

Correct

Mark 1.00 out of 1.00

What will be the output of below Python code?

```
tupl=("python","programming","Computer")
print(tupl[-3:0])
```

a. (Computer)

b. () ✓

c. Error

d. Computer

Question **13**

Correct

Mark 1.00 out of 1.00

What is the output of the following set operation

```
sampleSet = {"Yellow", "Orange", "Black"}
sampleSet.update(["Blue", "Green", "Red"])
print(sampleSet)
```

a. Name Error

b. {'Yellow', 'Orange', 'Red', 'Black', 'Green', 'Blue'} ✓

c. {'Yellow', 'Orange', 'Black', ["Blue", "Green", "Red"]}

d. TypeError: update() doesn't allow list as a argument.

Question **14**

Correct

Mark 1.00 out of 1.00

Choose the correct option.

a. In Python, a tuple can contain both integers and strings as its elements. ✓

b. In Python, a tuple can contain only strings as its elements.

c. In Python, a tuple can contain only integers as its elements.

d. In Python, a tuple can contain either string or integer but not both at a time.

Question **15**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
list1=[1,3,4,2]

x=list1.pop(2)

print(set([x]))
```

a. {1,3,2}

b. {1,3,4}

c. {2}

d. {4} ✓