/*concatination of two single linked list*/

```
#include<stdio.h>
#include<stdlib.h>
struct node
        int data;
        struct node*link;
};
struct node*header1;
struct node*header2;
struct node*headerconcatinate;
struct node*create_II(struct node*);
struct node*display(struct node*);
struct node*concatination(struct node*,struct node*,struct node*);
int main()
{
        int choice=0;
        while(choice!=7)
        {
                printf("**main menu**\n");
                printf("1.create 1st list\n2.display 1st list\n3.create 2nd list\n4.display 2nd
list\n5.concatinate 2 lists\n6.display the result of concatination\n7.exit\n");
                printf("enter your choice\n");
                scanf("%d",&choice);
                switch(choice)
                {
                        case 1:header1=create_ll(header1);
                        break;
                        case 2:header1=display(header1);
                        break;
                        case 3:header2=create_II(header2);
```

```
break;
                       case 4:header2=display(header2);
                       break;
                       case
5:headerconcatinate=concatination(header1,header2,headerconcatinate);
                       break;
                       case 6:headerconcatinate=display(headerconcatinate);
                       break;
                       case 7:exit(0);
                       default:
                               printf("invalid choice\n");
         }
  }
}
struct node*create_II(struct node*header)
{
       struct node*new_node,*ptr;
       int item;
       printf("enter -1 to end\n");
       printf("enter the data: \n");
       scanf("%d",&item);
       while(item!=-1)
       {
               new_node=(struct node*)malloc(sizeof(struct node*));
               new_node->data=item;
               if(header==NULL)
                                    //list is empty
               {
                       new_node->link=NULL;
                       header=new_node;
               }
               else
```

```
{
                        ptr=header;
                       while(ptr->link!=NULL)
                       {
                                ptr=ptr->link;
                  }
                                ptr->link=new_node;
                               new_node->link=NULL;
               }
               printf("enter the data: \n");
               scanf("%d",&item);
       }
        printf("link list is created\n");
        return header;
}
struct node*display(struct node*header)
{
        printf("the linked list is below\n");
       struct node*ptr;
        ptr=header;
       while(ptr!=NULL)
                             //list is not empty
       {
               printf("%d\n",ptr->data);
               ptr=ptr->link;
  }
  return header;
}
struct node*concatination(struct node*header1,struct node*header2,struct
node*headerconcatinate)
{
        struct node*ptr;
```

```
ptr=header1;
while(ptr->link!=NULL)
{
    ptr=ptr->link;
}
ptr->link=header2;
headerconcatinate=header1;
printf("2 lists are concatinated\n");
return headerconcatinate;
}
```



