```
# Use the Iris and Heart Disease databases to perform the following:
# 1. Perform classification tasks with 50%-50% training and testing using the SVM
# classifier.
# 2. Apply PCA to the dataset.
# 3. Perform classification with 50%-50% training and testing on:
# • 1st PCA component
# • 2nd PCA component
# Import necessary libraries
import pandas as pd
import numpy as np
from sklearn.model_selection import train_test_split
from sklearn.svm import SVC
from sklearn.metrics import accuracy_score, classification_report, confusion_matrix
from sklearn.decomposition import PCA
import matplotlib.pyplot as plt
import seaborn as sns
# Function to preprocess data
def preprocess_data(file_path, target_column):
  data = pd.read_csv(file_path)
  X = data.drop(columns=[target_column])
  y = data[target_column]
  return X, y
# Function to split data
def split_data(X, y, test_size=0.5):
  return train_test_split(X, y, test_size=test_size, random_state=42)
# Function to train and evaluate SVM model
def train_and_evaluate_svm(X_train, X_test, y_train, y_test, dataset_name):
```

```
model = SVC(kernel='linear', random_state=42)
  model.fit(X_train, y_train)
  y_pred = model.predict(X_test)
  print(f"{dataset_name} - Classification Report:\n", classification_report(y_test, y_pred))
  print(f"{dataset_name} - Confusion Matrix:\n", confusion_matrix(y_test, y_pred))
  print(f"{dataset_name} - Accuracy: {accuracy_score(y_test, y_pred)}")
# Function to apply PCA and plot the results
def apply_pca_and_plot(X, y, dataset_name, n_components=2):
  pca = PCA(n_components=n_components)
  X_pca = pca.fit_transform(X)
  explained_variance = pca.explained_variance_ratio_
  print(f"{dataset_name} - Explained Variance by Principal Components: {explained_variance}")
  if n_components == 2:
    plt.figure(figsize=(8, 6))
    sns.scatterplot(x=X_pca[:, 0], y=X_pca[:, 1], hue=y, palette='viridis', s=60)
    plt.title(f"{dataset_name} - PCA (2 Components)")
    plt.xlabel("Principal Component 1")
    plt.ylabel("Principal Component 2")
    plt.legend(title="Class")
    plt.show()
  return X_pca
# Paths to datasets and target columns
iris_file = 'C:/Users/HP/OneDrive/Desktop/ml 7th sem codes/datasets/iris.csv'
heart_file = 'C:/Users/HP/OneDrive/Desktop/ml 7th sem codes/datasets/heart.csv' # Update path
iris_target = 'variety'
heart_target = 'target'
# Process Iris dataset
```

```
X_iris, y_iris = preprocess_data(iris_file, iris_target)
X_train_iris, X_test_iris, y_train_iris, y_test_iris = split_data(X_iris, y_iris)
# Process Heart Disease dataset
X_heart, y_heart = preprocess_data(heart_file, heart_target)
X_train_heart, X_test_heart, y_train_heart, y_test_heart = split_data(X_heart, y_heart)
# Train and evaluate SVM for original datasets
print("Evaluating SVM on Original Iris Dataset")
train_and_evaluate_svm(X_train_iris, X_test_iris, y_train_iris, y_test_iris, "Iris")
print("Evaluating SVM on Original Heart Disease Dataset")
train_and_evaluate_svm(X_train_heart, X_test_heart, y_train_heart, y_test_heart, "Heart Disease")
# Apply PCA and evaluate SVM for PCA-reduced datasets
print("Applying PCA on Iris Dataset")
X_pca_iris = apply_pca_and_plot(X_iris, y_iris, "Iris")
X_train_iris_pca, X_test_iris_pca, y_train_iris_pca, y_test_iris_pca = split_data(X_pca_iris, y_iris)
print("Applying PCA on Heart Disease Dataset")
X_pca_heart = apply_pca_and_plot(X_heart, y_heart, "Heart Disease")
X_train_heart_pca, X_test_heart_pca, y_train_heart_pca, y_test_heart_pca =
split_data(X_pca_heart, y_heart)
print("Evaluating SVM on PCA-Reduced Iris Dataset")
train_and_evaluate_svm(X_train_iris_pca, X_test_iris_pca, y_train_iris_pca, y_test_iris_pca, "PCA-
Reduced Iris")
print("Evaluating SVM on PCA-Reduced Heart Disease Dataset")
train_and_evaluate_svm(X_train_heart_pca, X_test_heart_pca, y_train_heart_pca,
y_test_heart_pca, "PCA-Reduced Heart Disease")
```