

07 | Using Table Expressions



Graeme Malcolm | Senior Content Developer, Microsoft
Geoff Allix | Principal Technologist, Content Master

Module Overview

- Views
- Temporary Tables
- Table Variables
- Table-Valued Functions
- Derived Tables
- Common Table Expressions

Querying Views

- Views are **named queries with definitions stored in a database**
 - Views can provide abstraction, encapsulation and simplification
 - From an administrative perspective, views can provide a security layer to a database
- Views may be **referenced in a SELECT statement just like a table**

```
CREATE VIEW Sales.vSalesOrders
```

```
AS
```

```
SELECT  oh.OrderID, oh.Orderdate, oh.CustomerID,  
        od.LineItemNo, od.ProductID, od.Quantity
```

```
FROM Sales.OrderHeaders AS oh
```

```
JOIN Sales.OrderDetails AS od
```

```
ON od.OrderID = oh.OrderID;
```

```
SELECT OrderID, CustomerID, ProductID  
FROM Sales.vSalesOrder  
ORDER BY OrderID;
```

DEMO

Querying Views

Temporary Tables

```
CREATE TABLE #tmpProducts  
(ProductID INTEGER,  
 ProductName varchar(50));  
GO  
  
...  
SELECT * FROM #tmpProducts;
```

- Temporary tables are used to hold temporary result sets within a user's session
 - Created in tempdb and deleted automatically
 - Created with a # prefix
 - Global temporary tables are created with ## prefix

Table Variables

```
DECLARE @varProducts table  
(ProductID INTEGER,  
  ProductName varchar(50));  
...  
SELECT * FROM @varProducts
```

- Introduced because temporary tables can cause recompilations
- Used similarly to temporary tables but scoped to the batch
- Use only on very small datasets

DEMO

Temporary Tables and Table Variables

Table-Valued Functions

```
CREATE FUNCTION Sales.fn_GetOrderItems (@OrderID AS Integer)
RETURNS TABLE
AS
RETURN
(SELECT ProductID, UnitPrice, Quantity
FROM Sales.OrderDetails
WHERE OrderID = @OrderID);
...
SELECT * FROM Sales.fn_GetOrderItems (1025) AS LineItems;
```

- TVFs are named objects with definitions stored in a database
- TVFs return a virtual table to the calling query
- Unlike views, TVFs support input parameters
 - TVFs may be thought of as parameterized views

DEMO

Using Table-Valued Functions

Derived Tables

Introduction

```
SELECT orderyear, COUNT(DISTINCT custid) AS cust_count  
FROM  
    (SELECT YEAR(orderdate) AS orderyear, custid  
     FROM Sales.Orders) AS derived_year  
GROUP BY orderyear;
```

- Derived tables are named query expressions **created within an outer SELECT statement**
- Not stored in database – represents a virtual relational table
- Scope of a derived table is the query in which it is defined

Derived Tables

Guidelines

- Derived tables **must**:
 - Have an alias
 - Have unique names for all columns
 - Not use an ORDER BY clause (without TOP or OFFSET/FETCH)
 - Not be referred to multiple times in the same query
- Derived tables **may**:
 - Use internal or external aliases for columns
 - Refer to parameters and/or variables
 - Be nested within other derived tables

Derived Tables

Specifying Column Aliases

- Column aliases may be **defined inline**:

```
SELECT orderyear, COUNT(DISTINCT custid) AS cust_count  
FROM ( SELECT YEAR(orderdate) AS orderyear, custid  
        FROM Sales.Orders) AS derived_year  
GROUP BY orderyear;
```

- Or **externally**:

```
SELECT orderyear, COUNT(DISTINCT custid) AS cust_count  
FROM ( SELECT YEAR(orderdate), custid  
        FROM Sales.Orders) AS  
        derived_year(orderyear, custid)  
GROUP BY orderyear;
```

DEMO

Using Derived Tables

Common Table Expressions (CTEs)

```
WITH CTE_year (OrderYear, CustID)
AS
(
    SELECT YEAR(orderdate), custid
    FROM Sales.Orders
)
SELECT OrderYear, COUNT(DISTINCT CustID) AS Cust_Count
FROM CTE_year
GROUP BY orderyear;
```

- CTEs are named table expressions defined in a query
- CTEs are similar to derived tables in scope and naming requirements
- Unlike derived tables, CTEs support multiple references and recursion

Common Table Expressions

Recursion

```
WITH OrgReport (ManagerID, EmployeeID, EmployeeName, Level)
AS
(
    SELECT e.ManagerID, e.EmployeeID, EmployeeName, 0
    FROM HR.Employee AS e
    WHERE ManagerID IS NULL
    UNION ALL
    SELECT e.ManagerID, e.EmployeeID, e.EmployeeName, Level + 1
    FROM HR.Employee AS e
    INNER JOIN OrgReport AS o ON e.ManagerID = o.EmployeeID
)
SELECT * FROM OrgReport
OPTION (MAXRECURSION 3);
```

- Specify a query for the anchor (root) level
- Use UNION ALL to add a recursive query for other levels
- Query the CTE, with optional MAXRECURSION option

DEMO

Using Common Table Expressions

Using Table Expressions

- Views
- Temporary Tables
- Table Variables
- Table-Valued Functions
- Derived Tables
- Common Table Expressions

- Lab: Using Table Expressions



Microsoft

©2014 Microsoft Corporation. All rights reserved. Microsoft, Windows, Office, Azure, System Center, Dynamics and other product names are or may be registered trademarks and/or trademarks in the U.S. and/or other countries. The information herein is for informational purposes only and represents the current view of Microsoft Corporation as of the date of this presentation. Because Microsoft must respond to changing market conditions, it should not be interpreted to be a commitment on the part of Microsoft, and Microsoft cannot guarantee the accuracy of any information provided after the date of this presentation. MICROSOFT MAKES NO WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, AS TO THE INFORMATION IN THIS PRESENTATION.