GPR 1000 Product Profile

ANSCER ROBOTICS


GPR1000

Autonomous Mobile Robot

The GPR 1000 is a compact underride pallet handling AMR built for handling open and closed pallets. It enables reliable pallet movement in space constrained, high-throughput warehouses.




1 HUMAN-SAFE OPERATIONS




- PLd category 3 certified
- Laser safety fields respond before a person gets close
- No cages
- No zone restrictions

2 UNDERRIDE PALLET HANDLING



- 30 mm (1.18 in) ground clearance & 200 mm (7.87 in) lift stroke (eletric actuated)
- 1000 kg (2204.62 lbs) payload capacity
- Compatible with open and closed standard pallets

3 AUTONOMOUS NAVIGATION



- Detects obstacles in time, reroutes autonomously without interruption
- No floor tape, no manual intervention, no down-time

4 INTEROPERABLE ARCHITECTURE



- VDA 5050 compliant
- Enables vendor-agnostic scalability

5 REAL-TIME ALERTS & STATUS INDICATION




- Audio alerts for operator notification
- No screen dependency

6 MULTI-SIDE STATUS LIGHTING



- LED indicators
- Workers know the robot's intent before it reaches them

7 OPPORTUNITY CHARGING



- Autonomous opportunity charging during task intervals sustains continuous operation without scheduled downtime

8 BUILT-IN MISSION CREATOR



- Configure tasks, update routes, and adapt to layout changes on the fly
- No programmer required, just an intuitive interface your team can own

ANSCER ROBOTICS

Technical Specification

Sensors
2D LiDAR - 3 units
3D LiDAR - 1 unit
3D Camera - 2 units

Communication
WiFi (2.4/ 5GHz)
802.11 (b/n/ac)

Max. Speed
1.1 m/s
(2.46 mph or 3.96 Km/h)

Vertical Lift
0.2 m (7.87 in)

Safety Control
PLd cat. 3 Safety Scanners, Emergency Stop buttons - 4 units

Dimensions
1780 x 1200 x 1390 mm
(70.0 x 47.2 x 54.7 in)

Max. Payload
1000 Kg (2204 lbs)

Charging Time
1.5 Hours

Docking Accuracy
X,Y : ± 15 mm (0.59 in)
Yaw : ± 1.5°

Run Time
8 Hours