An empirical study of the naïve REINFORCE algorithm for predictive maintenance of industrial milling machines

Rajesh Siraskar

June 26, 2023

Abstract

In this empirical study, we document the performance of a simple, early reinforcement learning algorithm, REINFORCE, implemented for a predictive maintenance problem – an optimal tool replacement policy for a milling machine. We compare a naïve implementation of REINFORCE against the predictions of industry-grade Stable-Baselines3 (SB-3) implementations of three advanced algorithms, namely, Deep Q-Network (DQN), Advantage Actor-Critic (A2C) and Proximal Policy Optimization (PPO). This work is aimed at industrial practitioners not accustomed to the complex hyperparameter tuning often required to get reinforcement learning algorithms to work. Our broad goal was to understand the performance of *untuned* algorithms under various scenarios such (1) simulation-based environment (2) three sets of real tool-wear data (the benchmark IEEE NUAA Ideahouse dataset) (3) increased difficulty level by adding noise levels and a random chance of break-down.

Model performance was measured by how accurately the predictive maintenance agent suggested tool replacement when compared to a deterministic preventive maintenance rule based on the tool-wear threshold. Across variants of the environment, selected REINFORCE models demonstrated an incredibly high tool replacement precision of 0.866 against 0.448 for A2C, 0.415 for DQN, and 0.447 for PPO. The recall, F1-score, and F1-beta (0.5) scores were all significantly higher as well. While the selected REINFORCE models demonstrated better

performance for each variant, it was observed that the training was unstable, occasionally producing poor performance models (these were discarded). On the other hand, the SB-3 implementations training was more stable, almost always producing significantly low performing models. Our findings indicate that the REINFORCE performs significantly well for this particular problem. Consequently, for this particular problem, selecting the naïve REINFORCE could be a more suitable and effective policy generating alternative to more advanced complex algorithms.

For reproducibility, model training and testing code, data and the *selected RE-INFORCE* models have been uploaded to https://github.com/Link

Keywords: Predictive maintenance, milling machines, Reinforcement Learning, REINFORCE

Abbreviations

Deep Q-Network	A2C	Advantage Actor-Critic
Proximal Policy Optimization		
Single-variable state	MS	Multi-variate state
True positive	TN	True negative
False positive	FN	False negative
Reinforcement Learning	SB-3	Stable-Baselines3
	Proximal Policy Optimization Single-variable state True positive False positive	Proximal Policy Optimization Single-variable state MS True positive TN False positive FN

1 TOC

- 1. Introduction including previous work? End by "The rest of the paper is designed in the following style."
- 2. The REINFORCE algo.
 - 3. Data Description and Evaluation Metrics.
- Table 1 The general characteristics of the selected benchmarks
- 4 Empirical Result
- 5 Discussions and Future Research Suggestions
- This section discusses the accomplishments of this survey, followed by some recommendations for future research The following issues are some of the potential research gaps for future works:
- 6. Conclusion

2 Introduction

Milling machines are highly versatile, ubiquitous tools serving a variety of industries. A milling machine removes metal from the work piece by rotating and driving a cutting device into it. Abrasive forces cause tool wear, and optimal tool replacement reduces direct costs and optimizes the machines' downtime. With the 2023 milling machine market valued at USD 68.3 billion (Future Market Insights, 2023), this is an important goal for the industry.

The cutting tool experiences multiple types of wear as it cuts through metal. Tool wear depends in several factors such as the cutting speed, force applied to the tool, lubrication and materials of the work piece and cutting tool. Tool wear is

IEEE NUAA Ideahouse dataset has been used in this paper for the RUL estimation of the milling cutter. Yingguang et al. (2021)

The 14th-century friar, William of Ockham, has been attributed for giving us the "Occam's razor" principle – when there are two competing "theories"

predicting the same phenomenon, one should prefer the simpler of two.

Such preventive solution increases not only the machine downtime but also the manufacturing cost

applications, tool wear has proved difficult to understand and predict. However, most tool wear can be described by a few mechanisms, which include: abrasion, adhesion, chemical reaction, plastic deformation and fracture. These mechanisms produce wear scars that are referred to as flank wear, crater wear, notch wear and edge chipping as illustrated in figure 1 [25]. S

Reinforcement learning (RL) is an autonomous learning artifical intelligence technique.

Tool wear modeling is the first step to assist in predicting

Literature search conducted on the $Scopus^{TM}$ and $Web\ Of\ Science^{TM}\ did$ not return any articles for the application of reinforcement learning for predictive maintenance of milling machines. Search strings we tried - "reinforcement learning AND tool wear AND maintenance", RL + milling + policy, RL + milling + maintenance, RL + tool wear + policy, RL + tool wear + maintenance"

Running the search "reinforcement learning AND milling AND tool wear" using the $Scopus^{TM}$ and Web Of $Science^{TM}$ services

Dai et al. (2021) is the only article we found that tackles the

Machine learning methods have been applied for example – Oshida et al. (2023) proposes real-time tool wear detection during the milling process. They use a stacked LSTM encoder-decoder model for anomaly detection.

No results for "reinforcement learning" AND "milling machine" AND "tool wear" - on scopus or wos as of 23-jun-2023 "reinforcement learning" AND "milling machine" - 1 not relevant " *Conference Paper* • Open access "Online Learning of Stability Lobe Diagrams in Milling" Friedrich, J. Torzewski, J. Verl, A.

"reinforcement learning" AND "tool wear" - 10 results

3 Literature Review

4 Method

The methodology explains in detail what the researcher did to undertake the research. Various aspects of the research have to be outlined: The overall structure and operation of the experiment or observational experience. The groups studied in the research including the size of each group and any features of the subjects which may be relevant to the topic being researched. The variables that were changed between groups and the variables measured as a result of the changes. The conditions under which the research was undertaken and any factors or variations in conditions which may have an impact on the results. The methods of data analysis used in order to analyse and collate the results. ***Any limitations of the data collected. We normalize the tool wear and other state features, $x \in [0, 1] \subset \mathbb{R}$. This allows for adding white noise of similar magnitudes across experiments of different data-sets

4.1 RL environment description

4.2 Data description

4.3 Procedure

- training
- selecting the model
- conducting the experiments

4.4 Evaluation method

4.5 Tools

2 different laptops

• why classifction metrics

• why F1beta

4.6 Method - training and testing

- Training: SB-3 10 k eps. 3 times. Average their outputs
- Testing:
 - Avg. over 5 rounds.
 - Each round avg over 40 test cases x 10 test rounds
 - Total: $40 \times 10 \times 5 = 2000 \text{ cases}$
 - Avgs over: 10 rounds (of 40 cases each) X 5 rounds of re-trained
 SB-3 agents = 50 rounds

4.7 Inference

- \bullet Training: SB-3 is also unstable show examples of results such as A2C/DQN 0.00
- Training: SB-3 is also unstable SHOW SB-3 tensorboard plots
- Training: SB-3 is also unstable EXCEL plots of results over the 10 rounds

5 Introduction

Introduced in 1992, the REINFORCE algorithm is considered as a basic reinforcement learning algorithm. It is a policy-based, on-policy as well as off-policy algorithm, capable of handling both discrete and continuous observation and action domains.

In practice the REINFORCE algorithm is considered as "weak" learner and superseded by several algorithms developed since. Most notably the Q-Learning and its deep-neural network version, the DQN, followed by Actor-Critic and one of the most robust modern day algorithms, the PPO.

	A2C	DQN	PPO	REINFORCE
Network architecture	input dim x [64 Tanh x 64 Tanh] x output dim	input dim x [64 Tanh x 64 Tanh] x output dim	input dim x [64 Tanh x 64 Tanh] x output dim	input dim x [64 ReLU] x output dim
Layers	2	2	2	1
Units	64×64	64×64	64 × 64	64
Activation	Tanh, Tanh	Tanh, Tanh	Tanh, Tanh	ReLU
Learning rate	0.0007	0.0001	0.0003	0.01
Gamma	0.99	0.99	0.99	0.99
Optimizer	RMSprop	Adam	Adam	Adam

Table 1: Hyper-parameters of the RL algorithms

Reinforcement Learning in Robotics: A Survey - Jens Kober J. Andrew Bagnell Jan Peters - Initial gradient-based approaches such as finite differences gradients or REINFORCE (Williams, 1992) have been rather slow. The weight perturbation algorithm is related to REINFORCE but can deal with non-Gaussian distributions which significantly improves the signal to noise ratio of the gradient (Roberts et al., 2010). Recent natural policy gradient approaches (Peters and Schaal, 2008c,b) have allowed for faster convergence which may be advantageous for robotics as it reduces the learning time and required real-world interactions.

6 Hyper-parameters

soure of ppo implementation details https://iclr-blog-track.github.io/2022/03/25/ppo-implementation-details/

source of SB-3 network mp: https://github.com/openai/baselines/blob/ea25b9e8b234e6ee1bca43083f8f3cf974143998/baselines/common/models.

6.1 PPO hyperparms

implementation guide source » https://iclr-blog-track.github.io/2022/03/25/ppoimplementation-details/

By default, PPO uses a simple MLP network consisting of two layers of 64 neurons and Hyperbolic Tangent as the activation function. Then PPO builds a policy head and value head that share the outputs of the MLP network. Below is a pseudocode:

6.2 dqn hyperparms

default hyperparms : https://stable-baselines3.readthedocs.io/en/
master/_modules/stable_baselines3/common/policies.html

overridden in indiv policies for example SB3 DQN hypoerparms for example were taken from ; Paper: https://arxiv.org/abs/1312.5602, https://www.nature.com/articles/Default hyperparameters are taken from the Nature paper, except for the optimizer and learning rate that were taken from Stable Baselines defaults

- 7 Results
- 8 Results
- 8.1 Detailed metrics

		REINF	ORCE			A2	2C			D	QN			PF	O,	
Environment	Prec.	Recall	F1	F0.5	Prec.	Recall	F1	F0.5	Prec.	Recall	F1	F0.5	Prec.	Recall	F1	F0
Simulated - No noise	0.999	0.645	0.782	0.898	0.335	0.359	0.344	0.338	0.348	0.597	0.410	0.352	0.392	0.211	0.252	0.30
Simulated - Low noise	0.943	0.954	0.948	0.945	0.409	0.318	0.349	0.379	0.273	0.064	0.076	0.108	0.359	0.173	0.205	0.25
Simulated - High noise	0.889	0.974	0.929	0.904	0.471	0.439	0.443	0.455	0.423	0.408	0.295	0.284	0.402	0.205	0.248	0.30
PHM C01 SS - No noise	0.886	0.978	0.928	0.902	0.294	0.337	0.305	0.296	0.350	0.405	0.291	0.269	0.517	0.494	0.471	0.47
PHM C01 SS - Low noise	0.916	0.893	0.903	0.911	0.526	0.645	0.568	0.540	0.321	0.591	0.404	0.343	0.490	0.415	0.443	0.46
PHM C01 SS - High noise	0.757	0.926	0.831	0.784	0.499	0.632	0.542	0.513	0.399	0.402	0.308	0.292	0.403	0.223	0.270	0.32
PHM C04 SS - No noise	0.865	0.959	0.908	0.881	0.515	0.676	0.575	0.535	0.365	0.497	0.383	0.348	0.431	0.239	0.265	0.31
PHM C04 SS - Low noise	0.722	0.980	0.831	0.762	0.399	0.393	0.391	0.393	0.409	0.589	0.410	0.361	0.438	0.299	0.334	0.37
PHM C04 SS - High noise	0.770	0.809	0.787	0.776	0.375	0.456	0.397	0.381	0.408	0.411	0.296	0.282	0.491	0.324	0.362	0.40
PHM C06 SS - No noise	0.996	0.609	0.751	0.879	0.463	0.454	0.455	0.459	0.538	0.780	0.585	0.523	0.402	0.410	0.374	0.37
PHM C06 SS - Low noise	0.968	0.854	0.905	0.941	0.508	0.615	0.548	0.522	0.395	0.593	0.411	0.362	0.454	0.342	0.367	0.40
PHM C06 SS - High noise	0.699	0.912	0.790	0.732	0.480	0.512	0.466	0.467	0.581	0.499	0.417	0.433	0.424	0.199	0.252	0.31
PHM C01 MS - No noise	0.824	0.895	0.856	0.836	0.444	0.284	0.315	0.358	0.313	0.215	0.165	0.175	0.513	0.347	0.395	0.44
PHM C04 MS - No noise	0.752	0.678	0.709	0.733	0.506	0.326	0.368	0.425	0.588	0.642	0.492	0.486	0.472	0.455	0.444	0.45
PHM C06 MS - No noise	1.000	0.643	0.779	0.896	0.499	0.731	0.575	0.523	0.520	0.239	0.209	0.256	0.509	0.260	0.330	0.40

Table 2: Model performance comparison all variants of the environments.

8.2 Overall summary performance

	Precision		Recall			F1-score			F1-beta score		
	Mean	SD	Mean	SD		Mean	SD		Mean	SD	
A2C	0.448	0.074	0.478	0.084		0.443	0.071		0.439	0.069	
DQN	0.415	0.196	0.462	0.033		0.343	0.038		0.325	0.063	
PPO	0.447	0.147	0.306	0.090		0.334	0.093		0.375	0.107	
REINFORCE	0.866	0.042	0.847	0.054		0.842	0.043		0.852	0.042	

Table 3: Model performance summary - averaged over all environment.

8.3 Simulated environment

	Precision		Re	Recall		F1-score			F1-beta score		
	Mean	SD	Mean	SD		Mean	SD		Mean	SD	
A2C	0.405	0.079	0.372	0.086		0.379	0.076		0.391	0.076	
DQN	0.348	0.217	0.356	0.033		0.260	0.041		0.248	0.068	
PPO	0.385	0.175	0.196	0.064		0.235	0.080		0.289	0.110	
REINFORCE	0.944	0.029	0.858	0.041		0.886	0.032		0.916	0.030	

Table 4: Model performance summary - averaged over simulated environments.

8.4 Real data – simple single-variable environment

	Precision		Re	Recall		F1-score			F1-beta score		
	Mean	SD	Mean	SD		Mean	SD		Mean	SD	
A2C	0.451	0.064	0.524	0.085		0.472	0.067		0.456	0.063	
DQN	0.418	0.172	0.530	0.032		0.389	0.034		0.357	0.055	
PPO	0.450	0.146	0.327	0.095		0.349	0.095		0.384	0.106	
REINFORCE	0.842	0.043	0.880	0.053		0.848	0.043		0.841	0.042	

Table 5: Model performance summary - averaged over PHM-2010 environments with simple single-variable environment.

8.5 Real data – complex multi-variate environment

	Precision		D _o	Recall		F1-score			E1 hata saara		
		ISIOII		Call		r 1-score			F1-beta score		
	Mean	SD	Mean	SD		Mean	SD		Mean	SD	
A2C	0.483	0.101	0.447	0.081		0.419	0.075		0.435	0.079	
DQN	0.474	0.248	0.365	0.038		0.289	0.049		0.306	0.082	
PPO	0.498	0.121	0.354	0.103		0.390	0.101		0.436	0.104	
REINFORCE	0.859	0.053	0.739	0.069		0.781	0.055		0.822	0.052	

Table 6: Model performance summary - averaged over PHM-2010 environments with complex multi-variate environment.

Environment	REINFORCE	A2C	DQN	PPO
Simulated - No noise	214.23	41.19	4.03	41.13
Simulated - Low noise	199.89	41.52	3.55	40.66
Simulated - High noise	134.16	17.88	1.53	20.90
PHM C01 SS - No noise	330.54	18.85	2.08	32.65
PHM C01 SS - Low noise	426.79	30.66	3.69	38.59
PHM C01 SS - High noise	333.13	17.58	1.80	19.16
PHM C04 SS - No noise	299.31	19.56	1.86	19.64
PHM C04 SS - Low noise	264.90	18.27	2.00	19.69
PHM C04 SS - High noise	256.44	17.65	1.58	19.11
PHM C06 SS - No noise	339.65	17.64	2.26	19.50
PHM C06 SS - Low noise	266.98	19.33	1.84	19.19
PHM C06 SS - High noise	308.20	34.21	4.18	30.94
PHM C01 MS - No noise	655.21	38.55	4.96	42.21
PHM C04 MS - No noise	615.58	33.85	7.36	43.49
PHM C06 MS - No noise	625.37	39.30	5.85	41.68
Overall average (s)	351.36	27.07	3.24	29.90

Table 7: Training time for each model, across different environments. Averaged over 3 runs. Time is in seconds (s).

9 training times

10 Stable Baseline algorithms - default architectures

11 A2C - architecture

Actor-Critic Policy: Two fully interconnected layers of 64 units with tanh activation.

• Policy network:

- Linear (input dimensions = 2, output dimensions = 64, bias=True)
- $\operatorname{Tanh}()$
- Linear(input dimensions = 64, output dimensions = 64, bias=True)
- Tanh()

• Value network:

- Linear(input dimensions = 2, output dimensions = 64, bias=True)
- Tanh()
- Linear(input dimensions = 64, output dimensions = 64, bias=True)
- Tanh()

11.1 Algorithm timelines

• 1947: Monte Carlo Sampling

• 1959: Temporal Difference Learning

• 1989: Q-Learning

• 1992: REINFORCE

• 2013: DQN

• 2016: A3C

• 2017: PPO

12 The REINFORCE algorithm

Three key features of any RL algorithm:

- 1. Policy: π_{θ} = Probablities of all actions, given a state. Parameterized by θ
- 2. Objective function:

$$\max_{\theta} J(\pi_{\theta}) = \underset{\tau \sim \pi_{\theta}}{\mathbb{E}} [R(\tau)] \tag{1}$$

3. Method: Way to udate the parameters = Policy Gradient

12.1 Policy gradient numerical computation

1. Plain vanilla:

$$\nabla \theta J(\pi_{\theta}) = \mathbb{E}_{\tau \sim \pi_{\theta}} \left[\sum_{t=0}^{T} R_{t}(\tau) \nabla_{\theta} \ln \pi_{\theta}(a_{t}|s_{t}) \right]$$
 (2)

2. With Monte Carlo sampling and approximation: $\nabla_{\theta} J(\pi_{\theta}) \approx \left[\sum_{t=0}^{T} R_{t}(\tau) \nabla_{\theta} \ln \pi_{\theta}(a_{t}|s_{t}) \right]$

- 3. With baseline: $\nabla_{\theta} J(\theta) \approx \left[\sum_{t=0}^{T} (R_t(\tau) b(s_t)) \nabla_{\theta} \ln \pi_{\theta}(a_t | s_t) \right]$
- 4. Where, baseline does not change per time-step, it is for the entire trajectory
- 5. One baseline option: V^{π} leads to Actor-Critic algorithm
- 6. Simpler option: Average returns over trajectory: $b = \frac{1}{T} \sum_{t=0}^{T} R_t(\tau)$

Algorithm

13 About Stable-Baselines-3

- SB3- paper (Raffin et al., 2021), Raffin et al. (2021)
- sb-3 main doc (SB3, b)
- sb-3 ppo doc (SB3, a)

14 Discussion

limitiongs of the slecting model for evaluation

15 Conclusion

References

Stable-baselines docs - reliable reinforcement learning implementations,

a. URL https://stable-baselines3.readthedocs.io/en/master/modules/ppo.html#how-to-replicate-the-results.

Ppo, b. URL https://stable-baselines3.readthedocs.io/en/master/index.html. Accessed: 2023-05-14.

- Zixiang Dai, Mingyan Jiang, Xiaogang Li, Dongfeng Yuan, and Xiaotian Zhou. Reinforcement lion swarm optimization algorithm for tool wear prediction. In 2021 Global Reliability and Prognostics and Health Management (PHM-Nanjing), pages 1–7. IEEE, 2021.
- Future Market Insights. Milling machine market outlook (2023 to 2033), 1 2023. URL https://www.futuremarketinsights.com/reports/milling-machine-market. Accessed: 2023-06-23.
- Taisuke Oshida, Tomohiro Murakoshi, Libo Zhou, Hirotaka Ojima, Kazuki Kaneko, Teppei Onuki, and Jun Shimizu. Development and implementation of real-time anomaly detection on tool wear based on stacked lstm encoder-decoder model. The International Journal of Advanced Manufacturing Technology, pages 1–16, 2023.
- Antonin Raffin, Ashley Hill, Adam Gleave, Anssi Kanervisto, Maximilian Ernestus, and Noah Dormann. Stable-baselines3: Reliable reinforcement learning implementations. *J. Mach. Learn. Res.*, 22(1), jan 2021. ISSN 1532-4435.
- LI Yingguang, LIU Changqing, LI Dehua, HUA Jiaqi, and WAN Peng. Tool wear dataset of nuaa ideahouse, 2021. URL https://dx.doi.org/10.21227/3aa1-5e83.