Event ends in 1 day 6 hours 5 minutes.

Types of Custom Agent Configuration

Custom agents in Kiro CLI can be configured in multiple ways depending on scope, complexity, and organizational needs. Each configuration type serves different use cases and provides varying levels of functionality and control.

1. **Global Agent Configuration**

- **Location:** `~/.kiro/agents/`
- **Characteristics:**
  - **System-wide availability** across all projects and directories
  - **User-specific** configuration tied to individual developer accounts
  - **Persistent** across different working directories
  - **Shared baseline** for consistent development practices
- **Use Cases:**
  - **Personal productivity agents** (code reviewer, documentation writer)
  - **Individual developer preferences** (preferred tools and workflows)
- **Example Structure:**

```
~/.kiro/agents/
├── aws-expert.json
├── security-auditor.json
├── documentation-writer.json
└── personal-assistant.json
```

2. **Project-Specific Agent Configuration**

- **Location:** `{project-root}/.kiro/agents/`
- **Characteristics:**
  - **Project-scoped** availability only within specific project directory
  - **Team-shareable** through version control systems
  - **Context-aware** with project-specific knowledge and constraints
  - **Workflow-integrated** with project development practices
- **Use Cases:**
  - **Project-specific experts** (frontend specialist for React project)
  - **Team collaboration** (shared code review standards)
- **Example Structure:**

```
my-project/
├── .kiro/agents/
│   ├── frontend-expert.json
│   ├── backend-specialist.json
│   └── deployment-manager.json
├── src/
└── docs/
```

EXERCISE 1: CREATE GLOBAL AGENTS

1. Create a new custom global agent

Kiro Chat | Shell

- Access to Kiro chat

```
kiro-cli chat
```

- Create new agent
  - Invoke chat command

```
/agent create global-01 --manual
```

  - Save file (`esc` and then `wq!` and hit **Enter**)
  - Expected result

```
Agent global-01 has been created successfully
Changes take effect on next launch
```

- Check that the new custom agent configuration exists

```
!ls -l ~/.kiro/agents/global-01.json
```

```
!cat ~/.kiro/agents/global-01.json
```

- Exit and enter Kiro chat

```
/quit
```

```
kiro-cli chat
```

2. List agents

Kiro Chat | Shell

- List agents

```
/agent list
```

Expected result

```
> /agent list
global-01
```

EXERCISE 2: CREATE PROJECT-SPECIFIC AGENTS

1. Create working directory

```
mkdir /workshop/custom-agents && cd /workshop/custom-agents
```

2. Create a new custom project-specific agent

Kiro Chat | Shell

- Access to Kiro chat

```
kiro-cli chat
```

- Create new agent
  - Invoke chat command

```
/agent create workspace-01 --directory workspace --manual
```

  - Save file (`esc` and then `wq!` and hit **Enter**)
  - Expected result

```
Agent workspace-01 has been created successfully
Changes take effect on next launch
```

- Check that the new custom agent configuration exists

```
!ls -l .kiro/agents/workspace-01.json
```

```
!cat .kiro/agents/workspace-01.json
```

- Exit and enter Kiro chat

```
/quit
```

```
kiro-cli chat
```

3. List agents

Kiro Chat | Shell

- List agents

```
/agent list
```

Expected result

```
> /agent list
global-01
workspace-01
```

EXERCISE 3: USE CUSTOM AGENTS

1. Ensure that you are in the working directory

```
cd /workshop/custom-agents
```

2. Use custom global agent

```
kiro-cli chat --agent global-01
```

Expect



Swap custom agent

```
/agent swap workspace-01
```

Exit from Kiro CLI

```
/exit
```

3. Use custom workspace-specific agent

```
kiro-cli chat --agent workspace-01
```

Expect



Swap custom agent

```
/agent swap global-01
```

Exit from Kiro CLI

```
/exit
```

EXERCISE 4: SET DEFAULT AGENTS

1. Set default agent

Kiro Chat | Shell

- Access to Kiro chat

```
kiro-cli chat
```

- Set default agent
  - Invoke chat command

```
/agent set-default global-01
```

  - Expected result

```
✓ Default agent set to 'global-01'. This will take effect the next time kiro-cli chat is launched.
```

- Exit

```
/quit
```

2. Check default agent

- Enter Kiro Chat **without** specific agent name

```
kiro-cli chat
```

Expect



- List agents

```
/agent list
```

Expected result

```
> /agent list
* global-01
  workspace-01
```

- Exit from Kiro CLI

```
/quit
```