ORABOND® 1343

Description
This double-sided tape consists of a tissue carrier, layered on both sides with an acrylate adhesive. This powerful adhesive has excellent humidity and water resistance as well as high resistance to ageing and high temperatures. The adhesive has good initial adhesion, which increases over time, and high cohesion. The adhesive also has very good adhesion to substrates with high (like PS) and good adhesion to substrates with low surface energy such as PE.

Carrier
Paper tissue (12,7 g/m², white, opaque)

Liner
Double-sided siliconised paper, (90 g/m², white with blue ORAFOL Logo)

Adhesive
Acrylate

Area of use
This tape is extremely flexible and especially suitable for bonding various plastics with smooth and rough surfaces as well as felts and foams. Due to its high water resistance, the adhesive tape can also be used for applications in wet and humid areas.

Technical Data

Thickness* (adhesive and carrier)	100 micron
Temperature resistance***	-40° C to +140° C
Adhesion* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 20 min: 18 N/25 mm after 24 h: 21 N/25 mm
Adhesion* (FINAT TM 1, on PS, one side covered with 50 micron polyester film)	after 20 min: 18 N/25 mm after 24 h: 24 N/25 mm
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	at 70° C: > 20 min
Shelf life**	2 years
Application temperature	> +15° C

* average ** in original packaging, at 20°C and 50% relative humidity *** 1 h, normal climate of Central Europe

IMPORTANT NOTICE
All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.