ORATAPE® MT95

APPLICATION TAPE — TECHNICAL DATA SUMMARY

Product description

Transparent, polyethylene-based mounting/application film with a finely grained surface for transferring die-cut and computer-cut lettering and symbols. Designed for use with many glossy and matt-finished films. The medium-strength adhesive supports transfer and can be removed without leaving residue when used appropriately.

Technical specifications

Property	Typical value / specification
Film material	HDPE (high-density polyethylene)
Film thickness (face material)	95 µm
Total thickness (film with adhesive)	147 µm (average)
Weight (film with adhesive)	107 g/m² (average)
Adhesive type	Modified polyacrylate
Adhesive strength / tack	Medium adhesive strength; 2 N/25 mm after 20 min on stainless steel (FINAT TM 1, av
Tensile strength	Minimum 20 MPa, lengthwise and crosswise (DIN EN ISO 527)
Elongation at break	Minimum 450%, lengthwise and crosswise (DIN EN ISO 527)
Application temperature	Above +10 °C
Temperature resistance	–40 °C to +80 °C; short-term exposure up to +100 °C (manufacturer product informatio
Shelf life	2 years in original packaging at 20 °C and 50% relative humidity
Standard widths (Europe)	500, 610, 1000 and 1220 mm
Standard lengths (Europe)	50 m and 100 m

Recommended use

For transferring die-cut or computer-cut vinyl lettering and symbols to the application surface. Test compatibility and removal on the actual film, substrate, and application method before production use.

Important notice

This is a professionally formatted technical summary based on ORAFOL's published European MT95 product information and technical data sheet (version 2023/49); it is not an official manufacturer-issued document. Values are typical/average where indicated and may change. Confirm the latest specifications with ORAFOL before making contractual or safety-critical decisions.

Official manufacturer TDS: Download ORAFOL MT95 TDS (PDF)