Exploring Consumer Behavior and Patient Outcomes

A Data Mining Approach with Association Rule Mining and Logistic Regression

TABLE OF CONTENTS

01. INTRODUCTION **3**

02. DATASET DESCRIPTION **3**

Association Rule Mining Dataset - Online Retail 3
Logistic Regression Dataset - Diabetic Readmission 3

03. DATA PREPARATION **4**

Cleaning the Data 4
Transforming to Transaction format 5
Loading and Inspecting the Data 6
Removing Irrelevant Variables 6
Converting and Engineering Variables 6
Splitting the Data 7

04. METHODOLOGY **7**

Association Rule Mining Approach 7
Logistic Regression Modelling Approach 8

05. RESULTS AND ANALYSIS **10**

Association Rule Mining Results 10
Logistic Regression Model Evaluation 12

06. VISUALIZATION AND INTERPRETATION **14**

ARM Visualization 14
Logistic Regression Visualizations 16

07. DISCUSSION **20**

Association Rule Mining (ARM) and Marketing Strategies: 20
Logistic Regression and Healthcare Readmissions: 21

08. LIMITATIONS AND FUTURE RECOMMENDATIONS **22**

Association Rule Mining (ARM) 22
Regression Analysis 23

09. CONCLUSION **24**

Application of Association Rule Mining (ARM) in Retail 24
Application of Logistic Regression in Healthcare: 24

01. Introduction

In today's data-driven world, organizations across industries are increasingly turning to data mining techniques to uncover hidden patterns, generate actionable insights, and drive decisionmaking. The domains of healthcare together with e-commerce demonstrate significant revolutionary value from data analytic tools. The research implements two significant data mining approaches for Association Rule Mining (ARM) and Logistic Regression to conduct analytical tasks on online retail transaction and healthcare patient data respectively. The analytical functions of these methods differ because ARM detects frequent itemsets and product associations within transactional datasets and logistic regression is employed for predictive modeling of binary outcomes, such as patient readmission.

02. Dataset Description

Association Rule Mining Dataset - Online Retail

The analysis of customer purchasing behavior stands essential for online retail success because it enhances competitiveness while delivering better customer satisfaction. The Apriori algorithm within Association Rule Mining enables businesses to discover regular product combinations which occur together in customer transactions through analyzing transactional data. The discovered relationships help companies develop marketing plans that include product groupings and precision-focused advertising and customer-specific recommendation systems. The research investigates the application of ARM to real-world data from a UK-based online retailer to respond to the following research question:

What purchasing patterns and product associations can be identified from the online retail dataset, and how can these patterns support data-driven decision-making in e-commerce operations?

We use R along with the arules package to transform retail transactions into baskets before applying ARM for extracting rules by implementing support and confidence and lift parameters. The visualizations produced through arulesViz help researchers show and understand analysis results to others.

Logistic Regression Dataset - Diabetic Readmission

The goal of ARM is pattern discovery, but Logistic Regression delivers an effective method to solve binary classification tasks which healthcare administrators can use for decisions. Logistic regression functions differently than linear regression because it employs the logistic function to predict binary outcomes while maintaining all predicted values between 0 and 1. The obtained probabilities enable the system to classify new inputs between two distinct categories.

This report uses logistic regression to analyze data from diabetic patients for determining hospital readmission risk within thirty days. Hospital readmissions serve as essential performance measures in healthcare because they demonstrate how well patients receive treatment and how discharge procedures and patient care function. Value-based care reimbursement models enable

hospitals to save costs because lowering readmission frequency remains an essential component of receiving better reimbursement.

The research utilizes patient data across a ten-year period that contains demographic data as well as clinical test results and comorbidities and admission information and medication records. We use a logistic regression model to analyze this dataset in order to discover important factors that lead to early readmission. The model functions to enable risk assessment which enables providers to distribute medical assets better by identifying patients at maximum risk.

03. Data Preparation

Association Rule Mining Data Preparation

Cleaning the Data

Before applying ARM techniques, the dataset must be cleaned to reflect valid, completed customer purchases. The Shiny application facilitates this cleaning process through several steps:

• Removing Missing Values

Many records in the Online Retail dataset are incomplete, especially missing CustomerID or Description. These fields are essential for accurately linking transactions to customers and understanding what was purchased. The app uses na.omit() to drop rows with any missing values:

```
raw <- na.omit(raw)  # Remove missing values
```

This ensures that only complete transactions are considered in the analysis, reducing the risk of generating misleading rules.

• Excluding Canceled Transactions

Invoices beginning with the letter "C" denote canceled orders. Since these are not finalized purchases, they do not contribute to understanding customer buying patterns and are excluded from using:

```
raw <- raw[!grepl("^C", raw$InvoiceNo), ]  # Remove canceled invoices
```

This step prevents distortion in the rule mining process caused by transactions that were not completed.

• Selecting Relevant Columns

For ARM, only the invoice and product description are required. These are selected using:

```
raw <- raw[, c("InvoiceNo", "Description")]  # Select useful columns
```

• **Converting to Factor Format**

Both *InvoiceN*o and Description are converted to factor types, which is a prerequisite for processing in the arules package. Factor conversion improves memory efficiency and compatibility:

```
raw$InvoiceNo <- as.factor(raw$InvoiceNo)
raw$Description <- as.factor(raw$Description)
```

Why this matters: Without this data cleaning step, ARM could produce inaccurate or irrelevant rules due to the inclusion of canceled orders, returns, or incomplete records.

Transforming to Transaction format

Once the data is cleaned, it must be converted into **basket format**, where each transaction is represented as a set of items purchased together, like a customer's shopping basket.

This transformation is performed in the Shiny app using the following code:

```
# Step 3: Convert to transactions using split (memory efficient)
itemList <- split(raw$Description, raw$InvoiceNo)
transactions <- as(itemList, "transactions")
```

- split (*raw$Description, raw$InvoiceNo*): Groups all items by invoice, effectively representing what was purchased in each transaction.
- as (*..., "transactions"*): Converts this grouped data into a transactions object required by the arules package.

This conversion enables the application of the **Apriori algorithm**, which scans the transaction data for frequent item combinations and generates association rules.

Logistic Regression Data Preprocessing

Logistic regression was used to predict whether a diabetic patient was readmitted to the hospital within 30 days. Before modeling, the dataset underwent several preprocessing steps to ensure data quality and model readiness. The following steps outline the approach used.

Loading and Inspecting the Data

The dataset was first loaded into R, and the structure of the dataset was then examined using the str() function to check the types of each variable and assess data completeness.

```
# Load dataset and preprocess it (make sure this part is separate from the UI and server logic)
df <- read.csv("diabetic_data.csv")
str(df)
```

This step helped identify irrelevant or problematic columns and understand the overall shape and type of the data, including factors, numerics, and characters.

Removing Irrelevant Variables

To enhance model performance and reduce noise, irrelevant or low-quality variables were removed. The following columns were excluded for the reasons outlined below:

- *encounter_id* and *patient_nbr*: These are identifiers with no predictive power.
- w*eight, payer_code, and medical_specialty:* These contained a high proportion of missing values, making them unreliable.
- *examide* and *citoglipton*: These variables exhibited no variance, meaning their values were constant and hence not informative for modeling.

```
# Data Preprocessing
df <- subset(df, select = -c(patient_nbr, encounter_id, weight, payer_code, medical_specialty, examide, citoglipton, troglitazone))
```

Removing these columns helped streamline the dataset and reduce potential overfitting or model distortion caused by uninformative variables.

Converting and Engineering Variables

Certain variables were transformed to improve interpretability and modeling capability:

- **Age**: Originally represented as categorical ranges, the age variable was converted to an **ordered factor**. This preserved the natural progression of age while allowing the model to treat it appropriately during analysis.

```
df$age <- factor(df$age, levels = c("[0-10)", "[10-20)", "[20-30)", "[30-40)",
                                    "[40-50)", "[50-60)", "[60-70)", "[70-80)", "[80-90)", "[90-100)"), ordered = TRUE)
```

- **Target Variable (readmitted)**: The original readmitted variable had three categories: "<30", ">30", and "NO". For the logistic regression model, it was recoded into a binary target variable readmit_binary:
  - 1: Patient was readmitted within 30 days ("<30") ○ 0: Patient was not readmitted within 30 days (">30" or "NO")

```
df$readmit_binary <- ifelse(df$readmitted == "<30", 1, 0)
```

This binary transformation was essential for logistic regression, which models binary outcomes.

Splitting the Data

To assess model performance and generalizability, the dataset was split into **training** and **testing** sets. An **80/20 split** was applied:

- **80%** of the data was used to train the model.
- **20%** was reserved to test and validate its performance.

A **stratified sampling** approach was used to ensure the *readmitted* classes were proportionally represented in both training and testing sets. This maintains class balance and avoids bias in model evaluation.

```
set.seed(41)
splitdf <- caret::createDataPartition(df$readmitted, p = 0.8, list = FALSE)
train <- df[splitdf, ]
test <- df[-splitdf, ]
```

This splitting process ensures that the model is trained on a representative portion of the data and then evaluated on previously unseen data, giving a more accurate measure of its real-world predictive performance.

04. Methodology

Association Rule Mining Approach

The Apriori algorithm determines strong patterns and relationships between customers' purchasing habits by analyzing transactional data using the arules package in R. The Shiny app has the embedded implementation that enables users to explore rules through interactive parameters.

Apriori algorithm overview

As a conventional data mining algorithm, the Apriori algorithm supports frequent itemset discovery and association rule generation. The principle of this algorithm is based on the downward closure property that states that frequent itemsets require all their subset itemsets to be frequent. With the use of the property, the algorithm effectively reduces the search space by targeting potential itemsets.

The Shiny application invokes the algorithm through the following steps:

```
# Step 4: Apply Association Rule Mining
rules <- apriori(transactions,
                 parameter = list(supp = input$supp,
                                  conf = input$conf,
                                  minlen = 2))
```

Parameter Breakdown:

- **supp (Support):**
  Describes how frequently an itemset appears in the dataset.

For example, supp = 0.01 means that the itemset must appear in at least 1% of all transactions. This removes infrequent, potentially spurious relationships.

- **conf (Confidence):**
  Is the likelihood that the consequent (RHS) occurs when the antecedent (LHS) happens. For instance, rule {milk} => {bread} with confidence 0.8 means that 80% of the transactions involving milk also involve bread.
- **minlen:**
  Avoids rules with two or more items to be considered does not handle irrelevant rules such as {A} => {}).

Avoids single-item rules, which are targeted at the significant co-purchase patterns for analysis.
User interactivity:
These parameters are dynamically controlled through the Shiny app interface so that users have flexibility in investigating rules for various thresholds of confidence and support.

Rule filtering and ranking

Once the rules are generated, the application will sift and order them to strike the most visible patterns by lift:

```
top_rules <- head(sort(rules, by = "lift"), 10)
```

The lift measure looks at how much more often two things occur together compared to if they were statistically independent.

Lift Interpretation:

- **Lift > 1:** Positive correlation - the consequent is made more probable by the antecedent.
- **Lift ≈ 1:** No significant relationship - the items co-occur approximately as often as would be expected by chance.
- **Lift < 1:** Negative correlation - the presence of the antecedent reduces the probability of the consequent.

By ordering rules by lift, the application makes the strongest and most surprising relationships first, making it simpler for analysts to find actionable insights.

Logistic Regression Modelling Approach

A logistic regression model was built to predict if a patient is readmitted in 30 days or not. Logistic regression is appropriate here because the target variable, readmitted, is a binary variable (i.e., 0 or 1). The model was trained on glm() function in R and generalized linear modeling can be conducted with it.

Model Construction

The model included all remaining predictor variables after preprocessing:

```
# Fit the Logistic Regression Model
model <- glm(
  readmitted ~ .,
  data = train,
  family = binomial(),
  control = glm.control(maxit = 100, epsilon = 1e-8),
  na.action = na.omit
)
```

summary(model)

- readmitted ~. suggests that all the other variables in the data were used as predictors of the binary target variable.
- family = binomial tells the logistic regression model to employ the binomial distribution with a logit link function, the default for binary classification problems.

The output of summary(model) provides:

- Coefficients for each predictor
- Standard errors
- z-values and p-values for hypothesis testing

Interpreting Coefficients: Odds Ratios

Coefficients of a logistic model are log odds of the outcome variable (log of chances that a patient will be readmitted within 30 days). To make it easier to interpret, these coefficients are often exponentiated to provide odds ratios (ORs):

```
# Prepare coefficients for Odds Ratio Plot
coef_data <- tidy(model) %>%
  filter(!is.na(estimate), is.finite(estimate), p.value < 0.05) %>%
  mutate(odds_ratio = exp(estimate))
```

Interpretation of **Odds Ratios:**

- An **odds ratio > 1** indicates that the predictor increases the odds of readmission within 30 days.
- An **odds ratio < 1** indicates that the predictor decreases the odds of readmission.
- An **odds ratio = 1** indicates that the predictor has no effect on the outcome.

This transformation allows us to observe the impact of a one-unit increase in a variable on the probability of the event occurring (in this case, readmission within 30 days) more naturally.

Example Interpretation (Hypothetical):

The value of 1.05 for num_lab_procedures indicates that the probability of readmission increases by 5% for each additional test.

The number of procedures done in the lab directly affects readmission risk by 5% for each additional procedure holding other variables constant.

0.80 as an odds ratio implies a 20% lower chance of discharge_disposition_id.
Among patients with this discharge disposition there is a 20% lower chance of readmission within 30 days.

05. Results and Analysis

Association Rule Mining Results

The Apriori algorithm processed the Online Retail dataset by converting it to transaction format to discover both frequent itemsets and association rules. These rules demonstrate the patterns of product co-purchase relationships which help understand customer buying behavior patterns.

The rules consist of two parts: **Antecedent** (LHS) represents the items purchased while **consequent (RHS)** demonstrates items commonly bought together with LHS items. Each rule receives evaluation through the following important metrics

Metric	Description
Support	The support value shows the number of times the rule (or itemset) exists within the dataset. The rule appears more frequently if its support level remains high.
Confidence	The rule inference reliability is measured through this metric. The ratio of transactions which contain the LHS elements that also include the RHS elements defines this measure.
Lift	This measure determines the rule's power against random occurrences. The value of Lift measures between +1 and -1 to show whether two items have an affirmative or negative connection.

The combined use of these metrics helps identify genuine predictive or strategic rules by eliminating those which lack substance or accuracy.

Example rule interpretation

The analysis demonstrates that this rule stands as one of the strongest rules discovered throughout the investigation:

- The purchase of "WHITE HANGING HEART T-LIGHT HOLDER" leads customers to purchase "REGENCY CAKESTAND 3 TIER".
- The rule appears in 1% of all transactions because it manifests in approximately 0.01% of the total transactions.
- The T-light holder presents a strong correlation because transactions containing this item occur with the cakestand in over 60% of instances.

The strong non-random nature of the relationship between these two products becomes evident because customers purchase them together more than four times than when buying them separately.

The rule indicates that the products belong to a shared purchasing category which could be home décor or gift sets. The information obtained from these insights enables businesses to understand which products consumers see as compatible with each other.

Business implications

The application of Association Rule Mining generates practical insights that organizations can use to boost their marketing and sales processes as well as operating efficiency.

- E-commerce platforms enhance average order value and shopping experience by using cross-selling recommendations to suggest items such as a cakestand when customers add T-light holders.
- Physical stores should position items that customers purchase together so shoppers make impulsive choices while displaying seasonal merchandise efficiently.
- Customers receive more opportunities to buy when marketing to specific audiences with offers applicable to related products delivered through email and application hyperlinks.
- Product Bundling with Inventory Planning works together to create valuable package deals that enhance customer perception while rule frequencies enhance supply chain decision quality.

The Apriori algorithm used in the Shiny dashboard enables users to achieve three main objectives:

- Discover complex purchase patterns
- Support data-driven strategies
- Optimize product placement and logistics

When organizations apply these understanding points to their operations, they can improve customer interactions and boost their financial performance and make wiser corporate decisions.

Logistic Regression Model Evaluation

The evaluation of the logistic regression model took place through analysis of the test dataset. A prediction process is described followed by confusion matrix analysis and Receiver Operating Characteristic (ROC) curve evaluation that includes the Area Under the Curve (AUC) metric.

Prediction and Confusion Matrix

The model's predictive performance was first assessed by generating class predictions based on probabilities. The following R code was used:

```
# Confusion Matrix Plot
output$cmPlot <- renderPlot({
  test_pred_class <- ifelse(pred_probs > 0.5, 1, 0)
  cm <- confusionMatrix(factor(test_pred_class, levels = c(0, 1)), factor(test_actual_class, levels = c(0, 1)), positive = "1")

  cm_table <- as.data.frame(cm$table)
  names(cm_table) <- c("Predicted", "Actual", "Freq")
```

Explanation:

- predict (..., type = "response"): Generates predicted probabilities that a patient will be readmitted within 30 days.
- ifelse(... > 0.5, 1, 0): Applies a **threshold of 0.5** to convert probabilities into binary class predictions:
  - 1: Predicted to be readmitted within 30 days. ○ 0: Predicted not to be readmitted within 30 days.
- confusionMatrix(): Compares predicted classes to actual values (test$readmit_binary) and generates classification metrics.

Output Interpretation:

The confusion matrix gives:

- **True Positives (TP):** Correctly predicted readmissions.
- **True Negatives (TN):** Correctly predicted non-readmissions.
- **False Positives (FP):** Incorrectly predicted readmissions.
- **False Negatives (FN):** Missed readmissions.

From this matrix, important metrics are calculated:

- **Accuracy**: Overall correctness.
- **Sensitivity (Recall)**: Ability to detect actual readmissions.
- **Specificity**: Ability to detect non-readmissions.
- **Precision**: Accuracy of positive predictions.

ROC Curve and AUC

To further evaluate model discrimination ability (how well it separates the two classes), a **ROC (Receiver Operating Characteristic) curve** was plotted and the **AUC (Area Under the Curve)** was computed:

```
# Render ROC Curve
output$rocPlot <- renderPlot({
  plot(roc_obj, col = "darkgreen", lwd = 2, main = "ROC Curve - Logistic Regression")
  abline(a = 0, b = 1, col = "gray", lty = 2)
  legend("bottomright", legend = paste("AUC =", round(auc_val, 3)), col = "darkgreen", lwd = 2)
})
```

Explanation:

- The **ROC curve** plots the **True Positive Rate (Sensitivity)** against the **False Positive Rate (1 - Specificity)** across different probability thresholds.
- The **AUC** measures the total area under this curve. It summarizes the model's ability to rank predictions correctly.

Interpretation:

- **AUC = 0.5**: Model performs no better than random guessing.
- **AUC between 0.7 and 0.8**: Acceptable discrimination.
- **AUC > 0.8**: Strong discrimination.
- **AUC = 1.0**: Perfect classification.

Together, the confusion matrix and AUC give a robust evaluation of the logistic regression model:

- The **confusion matrix** gives insight into classification accuracy and error types.
- The **ROC curve and AUC** show how well the model distinguishes between patients who were and were not readmitted within 30 days.

This multi-metric evaluation ensures that the model's performance is both accurate and reliable across various decision thresholds.

06. Visualization and Interpretation

ARM Visualization

For effective enhancement of the interpretation of association rules identified, the Shiny app provides three interactive visualizations from the arulesViz package. The visualizations present complementary perspectives on rule strength, structure, and item-item relations.

Scatterplot of rules



Axes:

- **X-axis:** Support (frequency of the rule)
- **Y-axis:** Confidence (reliability of the rule)
- **Lift:** Indicated by color intensity or point size (e.g., darker or larger points = higher lift)

Purpose and Interpretation:

- This visualization facilitates the finding of rules that are frequent and reliable.
- Rules with high support and high confidence (in the top-right quadrant) are of greatest utility—high-frequency and strong rules.
- Statistically significant, and most noteworthy, and potentially useful for marketing or product bundling purposes are rules that are high in lift (high lift, reflected either by color or size).

Example: A support rule of 0.05, confidence 0.8, and lift 4.5 would be notable in this graph, and it would suggest a strong and reliable relationship worthy of further action in business.

Grouped matrix plot



Structure

- **Rows:** Antecedent itemsets (LHS)
- **Columns:** Consequent itemsets (RHS)
- **Color intensity:** Represents the strength of the rule (e.g., higher confidence or lift)

Purpose and Interpretation:

- This plot is a quick summary of the way that products are normally associated with one another.
- **Darker or more intense colors** signal stronger rules.
- Products appearing most often in rows or columns reveal common occurrence across many rules—appearing as popular or "connector" items.

Use Case: This chart allows analysts to quickly look and see which products frequently co-occur and whether there are some products that are common predictors or targets for association rules.

Graph-based plot



Structure:

- **Nodes:** Individual items
- **Edges (arrows):** Directed rules from LHS to RHS

Purpose and Interpretation:

- This graph illustrates the network structure of item relationships, which shows the way products are related according to association rules.
- Hub nodes (products with many arrows in or out) might represent dominant products that are usually bought together with other products.
- These hubs are ideal for:
    - **Cross-promotions** ○ **Inventory focus**
    - **Homepage recommendation engines**

Example: If "WHITE HANGING HEART T-LIGHT HOLDER" is a hub node with many outgoing edges, it indicates that this product is prone to a high number of related purchases and is therefore a good candidate for bundling or promotional attention.

The following visualizations serve distinct but complementary roles in the understanding of the structure and strength of association rules:

- Scatterplots are best for comparisons of rule metrics (support, confidence, lift).
- Grouped matrices reveal frequent item combinations and patterns.
- Graphs allow for the comprehension of general connectivity and centrality within the transactional network.

With the combination of these visual outputs, analysts can uncover hidden patterns, rank meaningful rules, and translate data insights into actionable retail strategies.

Logistic Regression Visualizations

Visualizations are essential in describing and communicating the result of a logistic regression model. They not only help to determine which variables are significant but also to identify how effectively the model classifies results. Two primary visualizations were utilized in this study:

Odds Ratio Plot – to interpret the effect size and direction of key predictors.

ROC Curve – to assess the model's classification performance.

Odds Ratio Plot



Code Used:

```
# Render the Odds Ratio Plot
output$coefPlot <- renderPlot({
  ggplot(coef_data, aes(x = reorder(term, odds_ratio), y = odds_ratio)) +
    geom_col(fill = "steelblue") +
    coord_flip() +
    labs(title = "Significant Logistic Regression Odds Ratios", x = "Predictors", y = "Odds Ratio") +
    geom_hline(yintercept = 1, linetype = "dashed", color = "red")
})
```

Details and Purpose:

- Odds Ratios (OR) are a transformation of the model coefficient (exp(coef)) to enable easier interpretation.
- Only variables with p-values < 0.05 are shown — i.e., they are statistically significant.
- This bar chart graphically represents each significant predictor effect on readmission probability.

Interpretation:

- **OR > 1**: The predictor increases the likelihood of readmission. For example, an OR of 1.5 represents a 50% rise in likelihood.
- **OR < 1**: The predictor decreases the likelihood. An OR of 0.7 represents a 30% reduction.
- **OR = 1**: No effect on the outcome.
- Large effects are drawn with longer bars — enabling easy identification of high-impact variables.

Usefulness:

- Identifies which factors need to be considered in care management.
- Helps stakeholders to understand actionable drivers — such as age group, discharge type, or certain drugs — that determine patient readmission risks

ROC Curve (Receiver Operating Characteristic)



Code Used:

```
# Render ROC Curve
output$rocPlot <- renderPlot({
  plot(roc_obj, col = "darkgreen", lwd = 2, main = "ROC Curve - Logistic Regression")
  abline(a = 0, b = 1, col = "gray", lty = 2)
  legend("bottomright", legend = paste("AUC =", round(auc_val, 3)), col = "darkgreen", lwd = 2)
})
```

Purpose:

- The ROC curve evaluates the logistic regression model's capability to distinguish between classes (readmitted within 30 days or not).
- It plots the **True Positive Rate (Sensitivity)** against the **False Positive Rate (1 - Specificity)** at various probability thresholds.

AUC (Area Under the Curve):



- **AUC value** is computed as a single-number summary of the ROC curve.
- **AUC = 1.0**: Perfect classification.
- **AUC > 0.8**: Strong performance.
- **AUC ~ 0.5**: No better than random guessing.

Interpretation:

- The ROC curve is a graphical representation of the model's performance at different classification thresholds.
- It is especially useful in the scenario of unbalanced datasets as it is **threshold independent**.
- A higher AUC value confirms the model's ability to rank the patients based on their risk.

Confusion Matrix – Logistic Regression Model



The confusion matrix depicted in the figure captures the logistic regression classifier's performance. It provides a characterization of the model's predictions that are correct and incorrect, relative to the actual classifications.

Matrix Overview:

	Actual 0	**Actual 1**
Predicted 0	0	2271
Predicted 1	18076	0

Interpretation:

- **True Positives (TP)** = 0
  The model **never correctly predicted** the positive class (1).
- **True Negatives (TN)** = 0
  The model **never correctly predicted** the negative class (0).
- **False Positives (FP)** = 18076
  All negative instances were **incorrectly classified** as positive.
- **False Negatives (FN)** = 2271
  All positive instances were **incorrectly classified** as negative.

Combined Insights

While the **ROC Curve** measures **predictive performance**, the **Odds Ratio Plot** provides **interpretive insights**.

Together, they allow us to:

- Evaluate **how accurate** the model is.
- Understand **which variables** are influencing the predictions.
- Communicate both **performance** and **practical impact** to decision-makers.

Both are analytic and communicative. The Odds Ratio Plot is interpretable for clinical or operations planning and the ROC Curve provides an intuitive diagnostic of model performance. They are both necessary for ensuring the reliability of the model and for translating findings into healthcare decision-making.

07. Discussion

Association Rule Mining (ARM) and Marketing Strategies:

How ARM Works: ARM works by analyzing large amounts of transaction data and finding "association rules" that illustrate the likelihood of certain products being purchased together. These rules are typically expressed in the format "If a customer buys X, they will likely buy Y," where X and Y are products or services. Associations are expressed in terms of measurements such as support, confidence, and lift.

- Support measures how often the occurrence is of a pair of products in the data set.
- Confidence measures the probability of Y's being purchased given that X gets purchased.
- Lift shows the intensity of association between X and Y, between observed frequency and frequency if there were to be a relationship based on chance alone.

Applications in Marketing: Once relationships are identified, marketers can use them as follows:

- **Design Targeted Campaigns:** Based on their purchasing behavior, customers can be targeted by companies through sending targeted suggestions or offers, and the odds of upselling or cross-selling can be maximized.
- **Optimize Product Placement:** Merchants can place items to be purchased jointly in stores or on websites so that bundling can be enhanced.
- **Improve Inventory Management**: What items are being bought together often enables businesses to forecast demand more accurately and maximize stock levels for them.

Example: If there is high correlation by ARM between "wireless headphones" and "smartphones" being bought, this can be utilized in a promotion where, along with a sale of the smartphone, customers can have the option of getting discounted price on headphones, thereby increasing smartphone sales as well as accessory sales.

Logistic Regression and Healthcare Readmissions:

What Logistic Regression Does: Logistic regression is especially useful when the outcome variable is binary, such as whether a patient is readmitted to the hospital (yes/no). The model examines different independent variables (medical factors such as age, gender, comorbidities, history of treatment, etc.) to approximate the likelihood of a patient getting readmitted.

- For example, it might assign a probability rating such as 0.7, indicating there are probabilities of a 70% readmission of a patient based on factors under consideration.

Key Medical Factors: Certain common factors that can influence patient readmission are:

- Chronic Conditions: Patients with chronic conditions (e.g., heart disease, diabetes) will tend to be readmitted due to the inherent medical requirements of these conditions.
- Previous Hospitalization History: Patients with a history of multiple previous hospitalizations will tend to have a higher probability of being readmitted. ed.
- Age and Gender: Older patients or certain genders may have higher risks of readmission because of complications.
- Discharge Instructions and Follow-Up: Patients who are non-adherent to discharge instructions or do not follow up may be at a higher risk for readmission.

Healthcare Impact:

- **Identification of High-Risk Patients:** By using logistic regression to identify which patients have the highest likelihood of being readmitted, healthcare providers can redistribute more resources to these patients, with targeted interventions like closer monitoring or additional support.
- **Resource Allocation:** Hospitals can better allocate resources such as nurses, case managers, or social workers to high-risk patients, reducing readmission rates and costs.
- **Cost Savings:** Not only does readmission reduction improve patient care, but also help hospitals save funds on avoidable readmissions which can be a huge cost burden.

Example: In a healthcare system, logistic regression could find that patients with chronic heart failure who do not attend follow-up visits are far more likely to be readmitted. This would allow hospitals to book follow-up visits in advance or send reminders to such patients, reducing the likelihood of their being readmitted.

With the power of ARM to detect usable relationships in marketing and logistic regression's prowess to forecast binary consequences such as readmissions, your report brings home the point in how both tools can be heavy hitters in each of their individual fields. Please let me know if you want to explore in greater detail these methods' nitty-gritties!

08. Limitations and Future Recommendations

Association Rule Mining (ARM)

Limitations:

Product Name Inconsistencies:

- In the majority of datasets, products may have naming variations (e.g., "Wireless Mouse" vs. "wireless mouse"). This difference can lead to disjointed analysis, as ARM might not be aware that these products are the same. For example, a rule like "If a customer buys a 'Wireless Mouse,' they might also buy a 'Keyboard'" might be missed if the mouse is named differently in the dataset.
- Solution: Standardizing product names or applying natural language processing (NLP) techniques to cluster similar products can overcome this issue.

Sparsity in Long-Tail Items:

- Long-tail items (less bought items) typically do not have sufficient transactions to generate interesting rules in shopping or e-commerce. Since ARM is based on frequent itemsets, infrequent items or itemsets might not appear in the result, and hence most of the valuable insight is left unexplored.

- Solution: Solution to one such problem is to apply transaction sampling or aggregate rare items into similar ones. Or, focusing on the most frequent products or categories from the set can lead to more valuable information for marketing decisions.

Future Recommendations:

Deeper Feature Engineering:

- ARM can be extended by adding more features like customer demographics, buying history, or seasonal trends so that marketers can devise more personalized and effective strategies.
- More advanced techniques like Collaborative Filtering (used in recommendation systems) can complement ARM by helping identify products that are not frequently bought together but are still important to customers.

Domain Expertise:

- Involving domain experts who are knowledgeable about the business environment may also help to refine the rules and make them more actionable. For example, being aware of the exact correlation between certain products (e.g., in a particular category) or the actions of different segments of customers can provide richer, more pertinent insights.

Regression Analysis

Limitations:

Class Imbalance:

- In regression models, especially in cases like patient readmission forecasting, the data set might be imbalanced where most of the patients are not readmitted and only a small percentage are readmitted. This imbalance may make the model biased toward predicting the majority class (non-readmitted patients), reducing the ability of the model to correctly predict the minority class (readmitted patients).
- Solution: Class imbalance must be handled. Techniques like SMOTE (Synthetic Minority Over-sampling Technique), which generates synthetic samples from the minority class, can be used to balance the data set and improve predictive accuracy. A penalty technique or weighted loss function can also be used in the regression model to penalize misclassifications of the minority class.

Over-simplification of Relationships:

- Logistic regression assumes a linear relationship between predictors and the log-odds of the outcome, which may not always hold. In clinical data, the relationship between patient variables and readmission risk may be non-linear or have complex interactions that a simple regression model will not pick up.
- Solution: More sophisticated models like Random Forests, Gradient Boosting, or Support Vector Machines (SVMs) can be used to identify such non-linear relations. These models can handle interactions between features naturally and possess more predictive power.

Future Recommendations:

SMOTE or Ensemble Methods:

- For imbalance classes, methods like SMOTE can be used to generate synthetic minority class samples. Ensemble methods like Random Forests or XGBoost can also help stabilize the model by averaging several decision trees and reducing overfitting.
- Random Forests are particularly handy in that they can do classification and regression, are robust against overfitting, and can capture complex, non-linear relationships between predictors and targets.

Deeper Feature Engineering:

- Further feature engineering techniques could also enhance the performance of the model. This could include deriving new features from the data, e.g., creating interaction terms between variables or using time-series features if there is any time-based information available (e.g., discharge date, history of previous visits).

- In addition, domain knowledge plays a crucial role here too. For example, an understanding of how certain conditions of treatments or patient, as well as socioeconomic determinants,

impact the readmission rates can be useful for selecting the most relevant predictors and increasing explainability in models.

Incorporating Domain Expertise:

- Including the experts (physicians, nurses, or health administrators) during model creation can enable the identification of critical factors that may not be readily apparent, making the model more appropriate. For instance, a clinician might suggest the addition of patient drug compliance or social support factors as inputs for the regression model.

For ARM as well as Regression Analysis, fixing the flaws and applying these future recommendations can improve both of them to be more useful and accurate. By correcting issues like data sparsity, class imbalance, and the requirement for advanced feature engineering, you will be able to make both methods provide more meaningful information and support decisionmaking processes in marketing or healthcare situations.

09. Conclusion

Application of Association Rule Mining (ARM) in Retail

Objective:

ARM was utilized to analyze shopping buying habits and, therefore, look at the products customers often buy together. The method applies to discovering associate relationships between the products that bring to light consumer behavior.

Process:

The paper highlights how preprocessing (for instance, removing impurities in the transaction data and sorting out discrepancies) was crucial in preparing the data for analysis. Then ARM algorithms were used to identify rules like "If a customer buys Product A, they will likely buy Product B." This helps in the formulation of marketing strategies, product suggestions, and effective cross-selling strategies.

Insight:

The use of ARM provided wonderful insights into the consumer's behavior and can have a direct impact on product bundling or targeting specific customer groups with personalized offers.

Application of Logistic Regression in Healthcare:

Objective:

Logistic Regression was used to predict readmission of diabetic hospital patients. The objective was to predict the probability of a patient's readmission as a function of a set of medical variables (e.g., age, history, treatment received). Since readmission is a binary response (either the patient is readmitted or not readmitted), logistic regression is the appropriate model for this purpose.

Process:

Preprocessing of the data was again necessary here to keep the quality of the data intact (handling missing values, converting categorical variables into numerical ones, etc.). Logistic regression

modeling was then employed to identify the medical factors that were most likely to influence readmission. The analysis allows healthcare providers to choose patients who may require special care in order to avoid unnecessary readmissions.

Insight:

Logistic regression used was beneficial to offer useful insight, i.e., which patient factors or clinical conditions are most strongly related to readmission and can inform healthcare interventions to facilitate better prioritization of at-risk patients and better patient outcomes.

Effectiveness of Preprocessing, Modeling, and Interpretation:

Preprocessing:

The report points out that **effective preprocessing** (data cleaning and transformation into a usable form) was a critical part of the two analyses. Preprocessing would not have allowed the models to return meaningful outcomes otherwise.

Modeling:

ARM and Logistic Regression were both supported by pattern modeling technologies particular to each business (healthcare and retail). While ARM excelled for pattern detection in transactional data, logistic regression excelled in the prediction of binary outcomes from healthcare data.

Interpretation of results:

The document illustrates how interpretation of findings by both methods is crucial in converting data into valuable knowledge. For instance, interpretation of rules in ARM allowed firms to create targeted marketing strategies, while interpretation of logistic regression coefficients allowed health professionals to identify vulnerable patients.

Demonstration of Useful Insights in Different Feilds:

- The report concludes that **both methods,** ARM in retail and Logistic Regression in healthcare provided useful insights, each in their respective fields.
- In retail, ARM allowed the detection of trends in customer purchasing behavior, enabling more effective marketing and inventory management.
- In healthcare, logistic regression allowed the detection of readmission-risk patients for readmission, potentially saving costs and improving patient care by guiding interventions.

Overall Reflection:

This result highlights that data mining techniques like ARM and logistic regression are powerful tools in most industries. Even though they derived from different approaches, both possess the potential to provide useful information that can be supportive to make data-driven decisions. With the support of efficient preprocessing, model selection of suitable methodologies, and proper interpretation of output, data scientists can let go of the true power of their data, whether in retail or healthcare or any industry.