

C-Programming / C / C Programs.md

 Rajiv-0920 2 minutes ago

2950 lines (1906 loc) · 50.6 KB

Preview

Code

Blame

Basic Simple C Programs

1. WAP(Write a program) to print "Hello World".

Expected Output

Hello World

Source Code

```
#include <stdio.h>

int main(){
    printf("Hello World");
    return 0;
}
```

2. WAP. to input a number and print them.

Test Data

Enter a number: 5

Expected Output

Number is 5

Source Code

```
#include <stdio.h>

int main(){
```

```
int num;

printf("Enter a number");
scanf("%d", &num);

printf("Number is %d", num);

return 0;
}
```

3. WAP. to accept two numbers and print their addition, subtraction, multiplication, division.

Test Data

Enter 2 number: 5 10



Expected Output

Addition = 15
Subtraction = -5
Multiplication = 50
Division = 0



Source Code

```
#include <stdio.h>

int main(){

    int add, mul, sub, div, num1, num2;

    printf("\nEnter 2 number:");
    scanf("%d %d", &num1, &num2);

    add = num1 + num2;
    sub = num1 - num2;
    mul = num1 * num2;
    div = num1 / num2;

    printf("Addition = %d \nSubtraction = %d \nMultiplication = %d \nDivision = %d"
        , add, sub, mul, div);

    return 0;
}
```



4. WAP. to input a number and change the sign.

Test Data

Enter a number: 5
Enter a number: -5



Expected Output

Changed number = -5
Changed number = 5



Source Code

```
#include <stdio.h>

int main(){
    int num;

    printf("Enter a number: ");
    scanf("%d", &num);

    num = num * -1;

    printf("Changed number = %d", num);
    return 0;
}
```



5. WAP. to input two number and display quotient and remainder.

Test Data

input number : 98 4



Expected Output

quotient = 24
remainder = 2



Source Code

```
#include <stdio.h>

int main(){
    int dividend, divisor, quotient, remainder;

    printf("Enter Dividend and Division: ");
    scanf("%d %d", &dividend, &divisor);

    quotient = dividend / divisor;
    remainder = dividend % divisor;

    printf("Quotient = %d Remainder = %d", quotient, remainder);
}
```



```
    return 0;
}
```

6. WAP. to display last digit of a number.

Test Data

Enter a number: 153



Expected Output

Last digit = 3



Source Code

```
#include <stdio.h>

int main(){
    int num;

    printf("Enter a number: ");
    scanf("%d", &num);

    num = num % 10;

    printf("Last digit = %d", num);

    return 0;
}
```



7. WAP. to accept a number from user and print it's square & cube in C language.

Test Data

Enter a number = 5



Expected Output

Square = 25 Cube = 125



Source Code

```
#include <stdio.h>

int main(){
```



```

int num, cube, square;

printf("Enter a number: ");
scanf("%d", &num);

cube = num * num * num;
square = num * num;

printf("Square: %d Cube: %d \n", square, cube);

return 0;
}

```

8. WAP. to calculate Area and Circumference of a Circle.

Formula

Area of a Circle = πr^2

Circumference of a circle = $2\pi r$

Test Data

Enter Radius: 15



Expected Output

Area of a circle = 78.525002
Circumference of a circle = 31.410000



Source Code

```

#include <stdio.h>

int main(){

    float area, circum, radius, pi = 3.14153;

    printf("\nEnter Radius: ");
    scanf("%f", &radius);

    area = radius * radius * pi;
    circum = 2 * pi * radius;

    printf("Area of the circle: %f \n", area);
    printf("Circumference of the circle: %f \n", circum);

    return 0;
}

```



9. WAP. to input a number to compute the perimeter and area of a rectangle.

Formula

Perimeter of the rectangle = $2(\text{height} + \text{width})$

Area of Rectangle = $\text{height} * \text{width}$

Test Data

Enter height and width of the rectangle respectively: 12 5



Expected Output

Area of a rectangle = 60 square inches
Perimeter of a rectangle = 34 inches



Source Code

```
#include <stdio.h>

int main(){
    int height, width, area, perimeter;

    printf("Enter height and width of the rectangle respectively: ");
    scanf("%d %d", &height, &width);

    area = height * width;
    perimeter = 2 * (height + width);

    printf("Area of a rectangle = %d square inches\nPerimeter of a rectangle = %d inches", area, perimeter);

    return 0;
}
```



10. WAP. to Calculate Percentage of 5 Subjects.

Test Data

Enter marks of 5 subjects:72 93 56 80 57



Expected Output

Your Overall Percentage: 71.599998



Source Code

```
#include <stdio.h>
```



```

int main(){

    float sanskrit, math, eng, hin, accounts, percentage, total;

    printf("Enter marks of 5 subjects:");
    scanf("%f %f %f %f %f", &sanskrit, &hin, &eng, &math, &accounts);

    total = sanskrit + hin + eng + math + accounts;
    percentage = total / 500 * 100;

    printf("\nTotal Marks = %f \nYour Overall Percentage: %f", total,
percentage);

    return 0;
}

```

11. WAP. to Calculate Simple Interest.

Formula

Simple Interest = $(p * r * t) / 100$;

p = Principal, **r** = Rate of interest, **t** = Time period

Test Data

```

Enter Principal Amount: 4500
Enter Rate of Interest: 9.5
Enter Time: 6

```



Expected Output

```

Simple interest: 2565.000000

```



Source Code

```

#include <stdio.h>

int main(){

    float si, amount, interest, time;

    printf("Enter Principal Amount: ");
    scanf("%f", &amount);

    printf("Enter Rate of Interest: ");
    scanf("%f", &interest);

    printf("Enter Time: ");
    scanf("%f", &time);

    si = (amount * interest * time) / 100;

    printf("Simple interest: %f", si);
}

```



```
    return 0;
}
```

12. WAP. to print area of a triangle.

Formula

Triangle = $0.5 * Base * Height$

Test Data

Enter BASE and HEIGHT: 15 30



Expected Output

Area of Triangle : 225.000000



Source Code

```
#include <stdio.h>

int main(){

    float area, base, height;

    printf("Enter BASE and HEIGHT: ");
    scanf("%f %f", &base, &height);

    area = 0.5 * base * height;

    printf("Area of Triangle : %f", area);

    return 0;
}
```



13. WAP. to accept marks of 3 subjects of a student, Calculate total of 3 subjects and average in c language

Formula

Average = $Sanskrit + Hindi + Math / 3$

Test Data

Enter Marks of 3 subjects: 75 50 80



Expected Output

Total marks: 205.000000
Average marks: 68.333336



Source Code

```
#include <stdio.h>

int main(){

    float sub1, sub2, sub3, average, total;

    printf("Enter marks of 3 subjects: ");
    scanf("%f %f %f", &sub1, &sub2, &sub3);

    total = (sub1 + sub2 + sub3);
    average = total / 3;

    printf("\nTotal marks: %f", total);
    printf("\nAverage marks: %f", average);

    return 0;
}
```



14. WAP. to input paisa and convert it into rs. and paisa

Test Data

Enter paisa:2150



Expected Output

Total 21 ₹ and 50 Paisa



Source Code

```
#include <stdio.h>

int main(){
    int paisa, rs;

    printf("Enter paisa:");
    scanf("%d", &paisa);

    rs = paisa / 100;
    paisa = paisa % 100;

    printf("Total %d ₹ and %d Paisa", rs, paisa);

    return 0;
}
```



15. WAP. to print the following outputs: `https:\\www.google.com\\` in C language

Expected Output

Google Link: `https:\\www.google.com\\`

Source Code

```
#include <stdio.h>

int main(){

    printf("Google Link: https:\\\\www.google.com\\ ");

    return 0;
}
```

16. WAP. For Converting Temperature Celsius Into Fahrenheit and Fahrenheit to Celsius

Formula

Fahrenheit = $((9/5) * c) + 32$ // or you can use `1.8` in place of `9/5`

celsius = $(f - 32) \times 5/9$

Test Data

Enter Celsius or Fahrenheit: 55

Expected Output

Celsius to Fahrenheit: 131.000000
Fahrenheit to Celsius: 12.777778

Source Code

```
#include <stdio.h>

int main(){
    float celFah, fahrenheit, celsius;

    printf("\nEnter Celsius or Fahrenheit: ");
    scanf("%f", &celFah);

    fahrenheit = (9.0 / 5.0 * celFah) + 32.0;
    celsius = (celFah - 32.0) * (5.0 / 9.0);
}
```

```
printf("\nCelsius to Fahrenheit: %f", fahrenheit);
printf("\nFahrenheit to Celsius: %f", celsius);

return 0;
}
```

17. WAP. to Calculate Gross Salary of an Employee whose dearness allowance is 40% of basic salary and house rent allowance is 20% of basic salary.

Formula

Gross Salary = $b + da + o$

b = Basic Salary, **da** = Dearness Allowance **o** = Other Allowance

Test Data

Enter Basic Salary: 20000



Expected Output

Gross Salary = 32000



Source Code

```
#include <stdio.h>

int main(){

    int gs, bs, da, hra;

    printf("Enter Basic salary: ");
    scanf("%d", &bs);

    da = bs * 40 / 100;
    hra = bs * 20 / 100;
    gs = bs + da + hra;

    printf("Gross Salary = %d \n", gs);

    return 0;
}
```



18. WAP. to print profit and profit percentage. Selling price and cost price is given by user.>

Formula

Profit = $selling - cost$

$$\text{Profit Percentage} = \frac{\text{profit}}{\text{cost}} * 100$$

Test Data

Enter Selling price and Cost price respectively: 200 150

Expected Output

Total Profit = 50% and Profit percentage = 33%

Source Code

```
int main(){
    int profit, profitPercentage, sellingPrice, costPrice;

    printf("Enter Selling price and Cost price respectively: ");
    scanf("%d %d", &sellingPrice, &costPrice);

    profit = sellingPrice - costPrice;
    profitPercentage = (profit * 100) / costPrice;

    printf("Total Profit = %d%% and Profit percentage = %d%%",
        profit, profitPercentage);

    return 0;
}
```

19. WAP. to calculate the remainder of 2 numbers without using % operator.

Test Data:

Enter 2 number: 10 5

Expected Output:

Remainder = 0

Source Code

```
#include <stdio.h>

int main(){
    int divisor, dividend, remainder, quotient;

    printf("Enter 2 dividend and divisor: ");
    scanf("%d %d", &dividend, &divisor);

    remainder = dividend - divisor * (dividend / divisor);

    printf("\nRemainder = %d", remainder);
}
```

```
    return 0;
}
```

20. WAP. that accepts two item's weight (floating points' values) and number of purchase (floating points' values) and calculate the average value of the items.

Test Data :

```
Weight - Item1: 15
No. of item1: 5
Weight - Item2: 25
No. of item2: 4
```

Expected Output:

```
Average Value = 19.444444
```

Source Code

```
#include <stdio.h>

int main(){
    float weight1, weight2, itemNum1, itemNum2, average;

    printf("Weight - Item1: ");
    scanf("%f", &weight1);

    printf("No. of Item1: ");
    scanf("%f", &itemNum1);

    printf("Weight - Item2: ");
    scanf("%f", &weight2);

    printf("No. of Item1: ");
    scanf("%f", &itemNum2);

    average = (weight1 * itemNum1 + weight2 * itemNum2) / (itemNum1 + itemNum2);

    printf("Average value of the item = %f", average);

    return 0;
}
```

21. WAP. to show swap of two numbers.

- i) using three variable
- ii) without using third variable.

iii) swap within a single line.

Test Data :

Input two number a and b: 5 10

Expected Output:

a = 10 and b = 5

Source Code

```
#include <stdio.h>

int main(){
    int a, b, temp;

    printf("Enter two number a and b:");
    scanf("%d %d", &a, &b);

    // swap two number using third variable.
    // temp = a;
    // a = b;
    // b = temp;

    // Swap two number without using third variable.
    // a = a + b;
    // b = a - b;
    // a = a - b;

    // Swap two number within single line.
    b = a + b - (a = b);

    printf("a = %d and b = %d", a, b);

    return 0;
}
```

22. WAP. to SWAP three numbers (any format).

i) using four variable

ii) without using four variable.

iii) swap within a single line.

Test Data:

Enter 3 number : 5 10 15

Expected Output:

changed number = 15 5 10

Source Code

```
#include <stdio.h>

int main(){
    int a, b, c, temp;

    printf("Enter 3 number a, b and c: ");
    scanf("%d %d %d", &a, &b, &c);

    // using four variable
    // temp = a;
    // a = b;
    // b = c;
    // c = temp;

    // Without using four variable.
    // a = a + b + c;
    // b = a - b - c;
    // c = a - b - c;
    // a = a - b - c;

    // Swap numbers within a single line.
    a = (temp = a + b + c) - (b = temp - b - c) -
        (c = temp - b - c);

    printf("Changed number = %d %d %d", a, b , c);

    return 0;
}
```

23. WAP. to merge three number. E.g. a= 1, b= 2, c = 8 is 128.

Test Data:

Enter 3 number: 1 2 3

Expected Output:

merge number = 123

Source Code

```
#include <stdio.h>

int main(){
    int a, b, c, merge;
```

```

printf("Enter 3 number:\n");
scanf("%d %d %d", &a, &b, &c);

merge = a * 10;
merge = merge + b;
merge = merge * 10;
merge = merge + c;

printf("merge number = %d", merge);

return 0;
}

```

24 .WAP. to Print the range of a number. E.g. number 78 is between 70 and 79, 102 is between 100 and 109.

Test Data:

```

Enter a number : 78

Enter a number : 102

```

Expected Output:

```

78 number is between 70 and 79

102 number is between 100 and 109

```

Source Code

```

#include <stdio.h>

int main(){
    int num, x, y;

    printf("Enter a number:");
    scanf("%d", &num);

    x = num / 10 * 10;
    y = x + 9;

    printf("%d number is between %d and %d", num, x, y);

    return 0;
}

```

25. WAP. to input a 3 digit number and reverse it.

Test Data:


```
number = 123
```



Expected Output:

```
reverse number = 321
```



Source Code

```
#include <stdio.h>

int main(){
    int num, rev, rem;

    printf("Enter a 3 digit number: ");
    scanf("%d", &num);

    rem = num % 10;
    num = num / 10;
    rev = rev * 10 + rem;
    rem = num % 10;
    num = num / 10;
    rev = rev * 10 + rem;
    rem = num % 10;
    num = num / 10;
    rev = rev * 10 + rem;

    printf("Reverse number = %d\n", rev);

    return 0;
}
```



26. WAP. to calculate sum of the digits of three digit number.

Test Data

```
Enter a 3 digit number: 123
```



Expected Output

```
Sum = 6
```



Source Code

```
#include <stdio.h>

int main(){
    int num, sum = 0;

    printf("Enter a number: ");
    scanf("%d", &num);
```



```
sum = sum + num % 10;
num = num / 10;
sum = sum + num % 10;
sum = sum + num / 10;

printf("Sum = %d", sum);

return 0;
}
```

27. WAP. to input a 5 digit number and calculate the sum of last and first digit number.

Test Data:

number : 12345



Expected Output:

sum = 6



Source Code

```
#include <stdio.h>

int main(){
    int num, sum;

    printf("Enter a 5 digit number: ");
    scanf("%d", &num);

    sum = (num % 10) + (num / 10000);

    printf("Sum = %d", sum);

    return 0;
}
```



28. WAP. to convert specified days into years, weeks and days.

Note: Ignore leap year.

Test Data

Enter number of days: 415



Expected Output

Years = 1 Weeks = 7 Days = 1



Source Code

```
#include <stdio.h>

int main(){
    int days, years, weeks;

    printf("Enter number of days: ");
    scanf("%d", &days);

    years = days / 365;
    weeks = (days % 365) / 7;
    days = (days % 365) % 7;

    printf("Years = %d Weeks = %d Days = %d", years, weeks, days);

    return 0;
}
```



29. WAP. to convert a given integer (in seconds) to hours, minutes and seconds.

Test Data :

Input seconds: 25300



Expected Output:

There are:
H:M:S - 7:1:40



Source Code

```
#include <stdio.h>

int main(){
    int seconds, minutes, hours;

    printf("Enter seconds: ");
    scanf("%d", &seconds);

    hours = seconds / 3600;
    seconds = seconds % 3600;
    minutes = seconds / 60;
    seconds = seconds % 60;

    printf("\nThere are:\nH:M:S - %d:%d:%d", hours, minutes, seconds);

    return 0;
}
```



30. WAP. to convert a given integer (in millimeters) to kilometers, meters and centimeters.

```
1 centimeter = 10 millimeters.  
1 meter = 100 centimeters.  
1 meter = 1,000 millimeters.  
1 kilometer = 1,000 meters.
```



Test Data :

Input millimeters: 2535220



Expected Output:

```
2.53 kilometers  
2535.22 Meters  
253522.0 Centimeters
```



Source Code

```
#include <stdio.h>  
  
int main(){  
    float millimeters, kilometers, meters, centimeters;  
  
    printf("Enter millimeters:");  
    scanf("%f", &millimeters);  
  
    centimeters = millimeters / 10;  
    meters = centimeters / 100;  
    kilometers = meters / 1000;  
  
    printf("Kilometers = %f Meters = %f Centimeters = %f",  
        kilometers, meters, centimeters);  
  
    return 0;  
}
```



31. WAP. to read an amount (integer value) and break the amount into smallest possible number of bank notes.

Test Data :

Input the amount: 375



Expected Output:

There are:

3 Note(s) of 100.00
1 Note(s) of 50.00
1 Note(s) of 20.00
0 Note(s) of 10.00
1 Note(s) of 5.00
0 Note(s) of 2.00
0 Note(s) of 1.00



Source Code

```
#include <stdio.h>

int main(){
    int amount, hundred, fifty, twenty, ten, five, two, one;

    printf("Enter amount: ");
    scanf("%d", &amount);

    hundred = amount / 100;
    fifty = (amount % 100) / 50;
    twenty = ((amount % 100) % 50) / 20;
    amount = ((amount % 100) % 50) % 20;
    ten = amount / 10;
    amount = amount % 10;
    five = amount / 5;
    amount = amount % 5;
    two = amount / 2;
    amount = amount % 2;
    one = amount;

    printf("\n%d Note(s) of 100.00", hundred);
    printf("\n%d Note(s) of 50.00", fifty);
    printf("\n%d Note(s) of 20.00", twenty);
    printf("\n%d Note(s) of 10.00", ten);
    printf("\n%d Note(s) of 5.00", five);
    printf("\n%d Note(s) of 2.00", two);
    printf("\n%d Note(s) of 1.00", one);

    return 0;
}
```



32. Write a C program to calculate the distance between the two points

Formula

$$\sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2}$$

Test Data :

Input x1: 25
Input y1: 15



Input x2: 35
Input y2: 10

Expected Output:

Distance between the said points: 11.1803



Source Code

```
#include <stdio.h>
#include <math.h>

int main(){
    float x1, x2, y1, y2, distance;

    printf("Enter x1, y1, x2 and y2 respectively:");
    scanf("%f %f %f %f", &x1, &y1, &x2, &y2);

    distance = sqrt(pow((x1 - x2), 2) + pow((y1 - y2), 2));

    printf("The distance between the two points = Square root(%f)", distance);

    return 0;
}
```



33. WAP. to Print the Ascii Value of the Character.

Test Data

Enter The Character: c



Expected Output

Value = 99



Source Code

```
#include <stdio.h>

int main(){
    char a;

    printf("Enter The Character: ");
    scanf("%c", &a);

    printf("Value = %d", a);

    return 0;
}
```



34. WAP. to accept 3 characters and print the sum of their [ascii](#).

Test Data

Enter 3 character: a b c



Expected Output

Sum of the 3 character = 294



Source Code

```
#include <stdio.h>

int main(){
    char a, b, c;
    int sum;

    printf("Enter 3 character: ");
    scanf("%c %c %c", &a, &b, &c);

    sum = (int)a + (int)b + (int)c;

    printf("Sum of the 3 character = %d", sum);

    return 0;
}
```



35. WAP. to Display The Size of Different Data Types

Data Type	Size (bytes)	Range	Format Specifier
int	2	-2,147,483,648 to 2,147,483,647	%d
long int	4	-2,147,483,648 to 2,147,483,647	%ld
float	4	1.2E-38 to 3.4E+38	%f
double	8	1.7E-308 to 1.7E+308	%lf
long double	12	3.4E-4932 to 1.1E+4932	%Lf
char	1	-128 to 127	%c

Source Code

```
#include <stdio.h>

int main() {
```



```
printf("Size of Int Data Types in C = %2d bytes \n", sizeof(short int));

printf("Size of Long Int Data Types in C = %2d bytes \n", sizeof(long int));

printf("Size of Float Data Types in C = %2d bytes \n", sizeof(float));

printf("Size of Double Data Types in C = %2d bytes \n", sizeof(double));

printf("Size of Long Double Data Types in C = %2d bytes \n", sizeof(long double));

printf("Size of Char Data Types in C = %2d bytes \n", sizeof(char));

return 0;
}
```

If/Else Statement

1. WAP. to print greatest among the two numbers.

Test Data

Enter 2 Numbers: 15 20



Expected Output

Greater number = 20



Source Code

```
#include <stdio.h>

int main(){
    int num1, num2, great;

    printf("Enter 2 numbers: ");
    scanf("%d %d", &num1, &num2);

    if(num1 > num2)
        great = num1;
    else
        great = num2;

    printf("\nGreater number = %d", great);
    return 0;
}
```



2. WAP. to check the given number is positive or negative.

Test Data

Enter a number: 15



Expected Output

Number is 'Positive'.



Source Code

```
#include <stdio.h>

int main(){
    int num;

    printf("Enter a number:");
    scanf("%d", &num);

    if(num < 0)
        printf("number is 'Negative'.");
    else
        printf("number is 'Positive'.");
    return 0;
}
```



3. WAP. to check the given number is even or odd.

Test Data

Enter a number: 12



Expected Output

number is 'Even'.



Source Code

```
#include <stdio.h>

int main(){
    int num;

    printf("\nEnter a number:");
    scanf("%d", &num);

    if(num % 2 == 0)
        printf("\nnumber is 'Even'.");
    else
```



```
        printf("\nnumber is 'Odd'.");  
        return 0;  
    }
```

4. WAP. to check the person is eligible for vote or not.

Test Data

Enter your age: 17



Expected Output

Your are not eligible for vote.



Source Code

```
#include <stdio.h>  
  
int main(){  
    int age;  
  
    printf("\nEnter your age:");  
    scanf("%d", &age);  
  
    if(age < 18)  
        printf("\nYour are not eligible for vote.");  
    else  
        printf("\nYour are eligible for vote.");  
    return 0;  
}
```



5. WAP. to input a character and check whether it is vowel or consonant.

Test Data

Enter a character: a



Expected Output

Character is 'Vowel'.



Source Code

```
#include <stdio.h>  
  
int main(){  
    char ch;
```



```
printf("Enter a character:");
scanf("%c", &ch);

if(ch == 'a' || ch == 'e' || ch == 'i' || ch == 'o' || ch == 'u'
|| ch == 'A' || ch == 'E' || ch == 'I' || ch == 'O' || ch == 'U')
    printf("Character is 'Vowel'.");
else
    printf("Character is 'Consonant'.");

return 0;
}
```

6. WAP. to check the given year is leap year or not.

Test Data

Enter a year: 2023



Expected Output

Not a leap year



Source Code

```
#include <stdio.h>

int main(){
    int year;

    printf("Enter a year:");
    scanf("%d", &year);

    if(year % 4 == 0 && year % 100 != 0 || year % 400 == 0)
        printf("\nYear is Leap Year.");
    else
        printf("\nYear is Not a Leap Year.");

    return 0;
}
```



7. WAP. to check the given number is buzz number or not.

Buzz number

Buzz numbers are those numbers that are *divisible by 7* or *end with 7*.

Test Data

Enter a number: 47



Expected Output

47 is a Buzz Number.



Source Code

```
#include <stdio.h>

int main(){
    int num;

    printf("\nEnter a number:");
    scanf("%d", &num);

    if(num % 7 == 0 || num % 10 == 7)
        printf("%d is a Buzz number.", num);
    else
        printf("%d is not a Buzz number.", num);

    return 0;
}
```



8. WAP. to input cost and sales price and calculate percentage of profit or loss.

Test Data

Enter Cost price and Sales price : 20 45



Expected Output

Total Profit = 25 and Percentage of Profit =



Source Code

```
#include <stdio.h>

int main(){
    int costPrice, sellingPrice, profit, perProfit, loss, perLoss;

    printf("Enter Cost price and Sales price: ");
    scanf("%d %d", &costPrice, &sellingPrice);

    if(costPrice > sellingPrice){
        loss = costPrice - sellingPrice;
        perLoss = loss * 100 / costPrice;
        printf("\nTotal Loss = %d₹ and Percentage of Loss = %d%%",
            loss, perLoss);
    } else{
```



```

        profit = sellingPrice - costPrice;
        perProfit = profit * 100 / costPrice;
        printf("\nTotal Profit = %d₹ and Percentage of Profit = %d%%",
            profit, perProfit);
    }

    return 0;
}

```

9. WAP. to input two number and check they are proper division or not.

Test Data

Enter 2 numbers: 45 90
Enter 2 numbers: 45 5



Expected Output

They are not a proper division.
They are a proper division.



Source Code

```

#include <stdio.h>

int main(){
    int num1, num2;

    printf("\nEnter 2 number:");
    scanf("%d %d", &num1, &num2);

    if(num1 % num2 == 0)
        printf("\nThey are a proper division.");
    else
        printf("\nThey are not a proper division.");
    return 0;
}

```



10. WAP. to input age and marks. If age ≥ 18 and marks ≥ 80 then the student is eligible for admission otherwise not.

Test Data

Enter age and marks: 18 85



Expected Output

You are eligible for Admission.



Source Code

```
#include <stdio.h>

int main(){
    int age, marks;

    printf("\nEnter your age and marks:");
    scanf("%d %d", &age, &marks);

    if(age >= 18 && marks >= 80)
        printf("\nYou are eligible for admission.");
    else
        printf("\nYou are not eligible for admission.");
    return 0;
}
```



11. WAP. to check the given number is perfect square or not.

Test Data

Enter a number: 25



Expected Output

25 is a Perfect Square.



Source Code

```
#include <stdio.h>
#include <math.h>

int main(){
    int num, sqr;

    printf("\nEnter a number:");
    scanf("%d", &num);

    sqr = sqrt(num);

    if(sqr * sqr == num)
        printf("%d is a Perfect Square.", num);
    else
        printf("%d is not a Perfect Square.", num);

    return 0;
}
```



12. WAP. to check the given number is 3 digit number or not.

Test Data

Enter a number: 22



Expected Output

22 is not a 3 digit number



Source Code

```
#include <stdio.h>

int main(){
    int num;

    printf("\nEnter a number:");
    scanf("%d", &num);

    if(num > 99 && num < 1000)
        printf("\n%d is a 3 digit number.", num);
    else
        printf("\n%d is not a 3 digit number.", num);

    return 0;
}
```



13. WAP. to calculate greatest among the 3 numbers.

Test Data

Enter 3 numbers: 15 20 25



Expected Output

Greater number is 25



Source Code

```
#include <stdio.h>

int main(){
    int num1, num2, num3, great;

    printf("\nEnter 3 numbers:");
    scanf("%d %d %d", &num1, &num2, &num3);
```



```
if(num1 > num2 && num1 > num3)
    great = num1;
else if(num1 < num2 && num2 > num3)
    great = num2;
else
    great = num3;

printf("Greater number = %d", great);
return 0;
}
```

14. WAP. to calculate the grade of a student after the input of marks of that student.

Grade

Percentage ≥ 90 grade is 'A'

Percentage ≥ 70 grade is 'B'

Percentage ≥ 50 grade is 'C'

Percentage ≥ 35 grade is 'D'

Percentage < 35 grade is 'F'

Test Data

Enter marks: 80



Expected Output

Grade is 'B'.



Source Code

```
#include <stdio.h>

int main(){
    int marks;

    printf("\nEnter marks:");
    scanf("%d", &marks);

    if(marks >= 90)
        printf("\nGrade is 'A'.");
    else if(marks >= 70)
        printf("\nGrade is 'B'.");
    else if(marks >= 50)
        printf("\nGrade is 'C'.");
    else if(marks >= 35)
        printf("\nGrade is 'D'.");
}
```




```
else
    printf("\nGread is 'F'.");
return 0;
}
```

15. WAP. to Calculate Telephone Bill:-

calls	Rate/call
First 50 calls	free
next 100 calls	₹3/call
next 200 calls	₹5/call
next 350 calls	₹7/call

Test Data

Enter numbers of call: 155



Expected Output

Total Telephone Bill = 325



Source Code

```
#include <stdio.h>

int main(){
    int calls, totalBill;

    printf("\nEnter numbers of call:");
    scanf("%d", &calls);

    if(calls <= 50)
        totalBill = 0;
    else if(calls > 50 && calls < 150)
        totalBill = (calls - 50) * 3;
    else if(calls > 150 && calls < 350)
        totalBill = 300 + (calls - 150) * 5;
    else
        totalBill = 1300 + (calls - 350) * 7;

    printf("\nTotal Telephone Bill = %d", totalBill);

    return 0;
}
```



16. WAP. to input 3 sides of a triangle and check whether it is possible or not. If possible then check whether the triangle is an equilateral, isosceles or scalene triangle.

Triangle

- **Equilateral Triangle:** A triangle is considered to be an equilateral triangle *when all three sides have the same length.*
- **Isosceles triangle:** *When two sides of a triangle are equal or congruent,* then it is called an isosceles triangle.
- **Scalene triangle:** *When none of the sides of a triangle are equal,* it is called a scalene triangle.

Test Data

Enter 3 sides of a triangle: 2 2 1



Expected Output

Isosceles Triangle.



Source Code

```
#include <stdio.h>

int main(){
    int s1, s2, s3;

    printf("Enter 3 sides of a triangle:");
    scanf("%d %d %d", &s1, &s2, &s3);

    if(s1 + s2 > s3 || s1 + s3 > s2 || s2 + s3 > s1){
        if(s1 == s2 && s2 == s3)
            printf("\nEquilateral Triangle.");
        else if(s1 != s2 && s2 != s3)
            printf("\nScalene Triangle.");
        else
            printf("\nIsosceles Triangle.");
    } else
        printf("\nNot a Valid Triangle.");
    return 0;
}
```



17. WAP. to compute income tax paid by an employee:

Annual Salary	Rate of Income Tax
up to ₹100000	NO TAX
₹100001 to 150000	10% of amount exceeding ₹100000
RS.150001 to ₹250000	₹5000 + 20% of the amount exceeding ₹150000

Annual Salary	Rate of Income Tax
Above ₹250000	₹25000 + 30% of the amount exceeding ₹250000

Test Data

Enter your salary: 275000



Expected Output

Total tax paid by him = 32500.000000



Source Code

```
#include <stdio.h>

int main(){
    float salary, taxableAmount;

    printf("\nEnter your salary:");
    scanf("%f", &salary);

    if(salary < 100000)
        taxableAmount = 0;
    else if(salary > 100000 && salary <= 150000)
        taxableAmount = (salary - 100000) * 10 / 100;
    else if(salary > 150000 && salary <= 250000)
        taxableAmount = 5000 + (salary - 150000) * 20 / 100;
    else
        taxableAmount = 25000 + (salary - 250000) * 30 / 100;

    printf("\nTotal Tax paid by him = %f", taxableAmount);
    return 0;
}
```



18. WAP. to accept three numbers from user and print them in ascending and descending order in c.

Test Data

Enter 3 numbers: 3 4 1



Expected Output

Ascending order = 1 3 4
Descending order = 4 3 1



Source Code

```

#include <stdio.h>

int main(){
    int num1, num2, num3;

    printf("\nEnter 3 numbers: ");
    scanf("%d %d %d", &num1, &num2, &num3);

    if(num1 > num2 && num1 > num3){
        if(num2 > num3){
            printf("\nAscending order: %d %d %d",
                num1, num2, num3);
            printf("\nDescending order: %d %d %d",
                num3, num2, num1);
        } else{
            printf("\nAscending order: %d %d %d",
                num1, num3, num2);
            printf("\nDescending order: %d %d %d",
                num2, num3, num1);
        }
    } else if(num2 > num1 && num2 > num3){
        if(num1 > num3){
            printf("\nAscending order = %d %d %d",
                num2, num1, num3);
            printf("\nDescending order = %d %d %d",
                num3, num1, num2);
        } else {
            printf("\nAscending order = %d %d %d",
                num2, num3, num1);
            printf("\nDescending order = %d %d %d",
                num1, num3, num2);
        }
    } else{
        if(num1 > num2){
            printf("\nAscending order = %d %d %d",
                num3, num1, num2);
            printf("\nDescending order = %d %d %d",
                num2, num1, num3);
        } else{
            printf("\nAscending order = %d %d %d",
                num3, num2, num1);
            printf("\nDescending order = %d %d %d",
                num1, num2, num3);
        }
    }

    return 0;
}

```



19. WAP. to check the given date is correct or not.

Test Data

Enter Date month and year e.g.(dd mm yyyy): 29 2 2023



Expected Output

29-2-2023 is not a valid date.



Source Code

```
#include <stdio.h>

int main(){
    int date, month, year, valid = 0;

    printf("\nEnter Date month and year (dd mm yyyy):");
    scanf("%d %d %d", &date, &month, &year);

    if(year % 4 == 0 && year % 100 != 0 || year % 400 == 0){
        if(month == 2 && (date <= 29 && date >= 1)){
            valid = 1;
        } else {
            valid = 0;
        }
    } else {
        if(month == 2 && (date <= 28 && date >= 1)){
            valid = 1;
        } else {
            valid = 0;
        }
    }

    if(valid == 1 ||
        ((month == 1 || month == 3 || month == 5 || month == 7 || month == 8 ||
          month == 10 || month == 12) && (date <= 31 && date >= 1)) ||
        ((month == 4 || month == 6 || month == 9 || month == 11) &&
          (date <= 30 && date >= 1))))
        printf("\n%d-%d-%d is a Valid Date.",
            date, month, year);
    else
        printf("\n%d-%d-%d is not a Valid Date.",
            date, month, year);

    return 0;
}
```



20. WAP. to input week number and print weekday.

Test Data

Enter Week number: 4



Expected Output

Thursday



Source Code

```
#include <stdio.h>

int main(){
    int weekNO;

    printf("\nEnter Week number:");
    scanf("%d", &weekNO);

    if(weekNO == 1)
        printf("\nMonday");
    else if(weekNO == 2)
        printf("\nTuesday");
    else if(weekNO == 3)
        printf("\nWednesday");
    else if(weekNO == 4)
        printf("\nThursday");
    else if(weekNO == 5)
        printf("\nFriday");
    else if(weekNO == 6)
        printf("\nSaturday");
    else if(weekNO == 7)
        printf("\nSunday");
    else
        printf("\nEnter a valid week number.");

    return 0;
}
```

21. WAP. to input month number and print number of days in that month.

Test Data

Enter month number: 4

Expected Output

30 Days

Source Code

```
#include <stdio.h>

int main(){
    int monthNum, flag;

    printf("\nEnter month number:");
    scanf("%d", &monthNum);

    if(monthNum == 1 || monthNum == 3 || monthNum == 5 || monthNum == 7 ||
        monthNum == 8 || monthNum == 10 || monthNum == 12)
        flag = 1;
```

```

else if (monthNum == 2)
    flag = 3;
else if(monthNum == 4 || monthNum == 6
        || monthNum == 9 || monthNum == 11)
    flag = 2;
else
    flag = 0;

if(flag == 1)
    printf("\n31 Days");
else if(flag == 2)
    printf("\n30 Days");
else if(flag == 3)
    printf("\n28 or 29 Days");
else
    printf("\nNot a Valid month.");

return 0;
}

```

22. WAP. to check whether a triangle is valid or not, when the three angles of the triangle are entered through the keyboard.

Condition

A triangle is valid if the sum of all the three angles is *equal to 180 degrees*.

Test Data

Enter 3 angles of a triangle: 90 45 45



Expected Output

Valid Triangle



Source Code

```

#include <stdio.h>

int main(){
    int a1, a2, a3;

    printf("\nEnter 3 angles of a triangle:");
    scanf("%d %d %d", &a1, &a2, &a3);

    if(a1 + a2 + a3 == 180)
        printf("\nValid Triangle");
    else
        printf("\nnot a Valid Triangle");
}

```



```
    return 0;
}
```

23. WAP. to print the second largest out of three numbers.

Test Data

Enter 3 numbers: 45 99 53



Expected Output

Second largest number = 53



Source Code

```
#include <stdio.h>

int main(){
    int num1, num2, num3, secLargest;

    printf("Enter 3 numbers:");
    scanf("%d %d %d", &num1, &num2, &num3);

    if((num1 < num3 || num1 < num2) &&
        (num1 > num2 || num1 > num3))
        secLargest = num1;
    else if((num2 < num3 || num2 < num1) &&
        (num2 > num1 || num2 > num3))
        secLargest = num2;
    else
        secLargest = num3;

    printf("\nSecond Largest number = %d", secLargest);

    return 0;
}
```



24. WAP. to compute the pension of an employee.

If the person is male.

Age	Pension
Age >= 90	pension is 4000
Age >= 60	pension is 6000
Age < 60	pension is 0

If the person is female.

Age	Pension
Age >= 90	pension is 3000
Age >= 60	pension is 5000
Age < 60	pension is 0

Test Data

Enter Your Age and Gender: 99 f



Expected Output

Pension = 3000



Source Code

```
#include <stdio.h>

int main(){
    int age, pension;
    char gender;

    printf("\nEnter Your Age and Gender: ");
    scanf("%d %c", &age, &gender);

    if(age >= 90){
        if(gender == 'm')
            pension = 4000;
        else if(gender == 'f')
            pension = 3000;
        else
            printf("\nEnter a Valid Gender.");
    } else if(age >= 60){
        if(gender == 'm')
            pension = 6000;
        else if(gender == 'f')
            pension = 5000;
        else
            printf("\nEnter a Valid Gender.");
    } else {
        pension = 0;
    }

    printf("\nPension = %d", pension);
    return 0;
}
```



25. WAP. to check whether a 3 digit number is a magic number or not.
(Palindrome) A number is a magic number if its reverse is same as the original number.

Test Data

Enter number 121



Expected Output

121 is a magic number



Source Code

```
#include <stdio.h>

int main(){
    int num, rev, temp;

    printf("\nEnter a number:");
    scanf("%d", &num);

    temp = num;

    rev = num % 10;
    temp = temp / 10;
    rev = (rev * 10) + temp % 10;
    rev = (rev * 10) + temp / 10;

    printf("%d %d", rev, num);
    if(rev == num)
        printf("\n%d is a magic number.", num);
    else
        printf("\n%d is not a magic number.", num);

    return 0;
}
```



26. WAP. to Find the absolute value of a number entered through the keyboard.

Test Data

Enter a number: 11
Enter a number: -23



Expected Output

Absolute number = 11
Absolute number = 23



Source Code

```
#include <stdio.h>
```



```

int main(){
    int num;

    printf("\nEnter a number:");
    scanf("%d", &num);

    if(num < 0)
        num = num * -1;

    printf("Absolute number = %d", num);
    return 0;
}

```

27. WAP. to to accept users marital status, gender and age to check if he/she is eligible for marriage or not.

Test Data

```

Enter MaritalStatus: m (married) / u (unmarried): u
Enter your gender: m (male) / f (female): m
Enter your age: 24

```



Expected Output

```

You can marry!

```



Source Code

```

#include <stdio.h>

int main(){

    int age;
    char maritalStatus, gender;

    printf("\nEnter MaritalStatus: m (married) / u (unmarried): ");
    scanf(" %c", &maritalStatus);

    printf("\nEnter your gender: m (male) / f (female): ");
    scanf(" %c", &gender);

    printf("\nEnter your age: ");
    scanf(" %d", &age);

    if(maritalStatus == 'm')
        printf("\nYou can not marry!");
    else if(maritalStatus == 'u'){
        if(gender == 'm'){
            if(age >= 21)
                printf("\nYou can marry!");
            else
                printf("\nYou can not marry!");
        } else if(gender == 'f'){

```



```

        if(age >= 18)
            printf("\nYou can marry!");
        else
            printf("\nYou can not marry!");
    } else
        printf("\nEnter valid gender: ");
} else
    printf("\nEnter valid Marital Status: ");
return 0;
}

```

28. WAP. to Count the total numbers of notes in given amount.

Test Data

Enter the amount: 375



Expected Output

```

2000 = 0
500 = 2
200 = 1
100 = 0
50 = 0
20 = 1
10 = 0
5 = 0
2 = 0
1 = 1

```



Source Code

```

#include <stdio.h>

int main(){
    int amount, twoThousand = 0, fiveHundred = 0, twoHundred = 0,
    oneHundred = 0, fifty = 0, twenty = 0, ten = 0,
    five = 0, two = 0, one = 0;

    printf("\nEnter amount:");
    scanf("%d", &amount);

    if(amount > 2000){
        twoThousand = amount / 2000;
        amount = amount % 2000;
    }

    if(amount > 500){
        fiveHundred = amount / 500;
        amount = amount % 500;
    }

    if(amount > 200){
        twoHundred = amount / 200;

```



```

        amount = amount % 200;
    }

    if(amount > 100){
        oneHundred = amount / 100;
        amount = amount % 100;
    }

    if(amount > 50){
        fifty = amount / 50;
        amount = amount % 50;
    }

    if(amount > 20){
        twenty = amount / 20;
        amount = amount % 20;
    }

    if(amount > 10){
        ten = amount / 10;
        amount = amount % 10;
    }

    if(amount > 5){
        five = amount / 5;
        amount = amount % 5;
    }

    if(amount > 2){
        two = amount / 2;
        amount = amount % 2;
    }

    if(amount >= 1){
        one = amount;
    }

    printf("\n2000 = %d", twoThousand);
    printf("\n500 = %d", fiveHundred);
    printf("\n200 = %d", twoHundred);
    printf("\n100 = %d", oneHundred);
    printf("\n50 = %d", fifty);
    printf("\n20 = %d", twenty);
    printf("\n10 = %d", ten);
    printf("\n5 = %d", five);
    printf("\n2 = %d", two);
    printf("\n1 = %d", one);
    return 0;
}

```

29. WAP. to determine whether the given character is a capital letter, a small case letter, a digit or a special symbol.

Hint

ASCII value of the **digit** is between 48 to 58 and **lowercase characters** in the range of 97 to 122, and **uppercase** is between 65 and 90, and **special symbol** is between (32 to 47, 58 to 64, 91 to 96, 123 to 127).

Test Data

Enter Any Character: c



Expected Output

Character is 'Lowercase'.



Source Code

```
#include <stdio.h>

int main(){

    char ch;

    printf("Enter Any Character: ");
    scanf("%c", &ch);

    if(ch >= 48 && ch < 58){
        printf("Character is 'Digit'.");
    } else if(ch >= 32 && ch <= 47 || ch >= 58 && ch <= 64
        || ch >= 91 && ch <= 96 || ch >= 123 && ch <= 127){
        printf("Character is 'Special Character'.");
    } else if(ch >= 65 && ch <= 90){
        printf("Character is 'UpperCase'.");
    } else if(ch >= 97 && ch <= 121){
        printf("Character is 'Lowercase'.");
    }

    return 0;
}
```



30. WAP. to input the length and breadth of a rectangle, find whether the area of the rectangle is greater than its perimeter.

Test Data

Enter the length and breadth of a rectangle: 5 4



Expected Output

Area of rectangle is greater than its perimeter.



Source Code

```
#include <stdio.h>

int main(){
    int length, breadth, area, perimeter;

    printf("\nEnter the length and breadth of a rectangle:");
    scanf("%d %d", &length, &breadth);

    area = length * breadth;
    perimeter = 2 * (length + breadth);

    if(area > perimeter)
        printf("\nArea is greater than it's perimeter.");
    else
        printf("\nArea is not greater than it's perimeter.");

    return 0;
}
```

31. WAP. to input three points (x1, y1), (x2, y2) and (x3, y3), check if all the three points fall on one straight line.

Test Data

```
Enter points (x1, y1):1 2
Enter points (x2, y2):3 4
Enter points (x3, y3):5 6
```

Expected Output

```
All the three points fall on the straight line:
```

Source Code

```
#include <stdio.h>

int main(){
    int x1, y1, x2, y2, x3, y3, m, n;

    printf("Enter points (x1, y1):");
    scanf("%d %d", &x1, &y1);

    printf("Enter points (x2, y2):");
    scanf("%d %d", &x2, &y2);

    printf("Enter points (x3, y3):");
    scanf("%d %d", &x3, &y3);

    m = (y2 - y1) / (x2 - x1);
    n = (y3 - y2) / (x3 - x2);

    if(m == n)
        printf("All the three points fall on the straight line:");
}
```

```
else
    printf("All 3 points do not lie on the same line\n");

return 0;
}
```

32. WAP. to input a point (x, y), find out if it lies on the x-axis, y-axis or at the origin, viz. (0, 0).

Condition

In point (x, y), if x = 0 and y = 0, then the point lies on the origin. If value of x is zero and y is greater than zero, then the point lies on y-axis. If y is zero and x is greater than zero, then the point lies on x-axis.

Test Data

Enter point (x, y): 35 20



Expected Output

Point (35, 20) neither lie on x-axis nor on y-axis



Source Code

```
#include <stdio.h>

int main(){
    int x1, y1;

    printf("Enter (x, y): ");
    scanf("%d %d", &x1, &y1);

    if(x1 == 0 && y1 == 0)
        printf("\nThe point (%d, %d) lies on the origin.", x1, y1);
    else if(x1 == 0 && y1 > 0)
        printf("\nThe point (%d, %d) lies on the y-axis.", x1, y1);
    else if(x1 > 0 && y1 == 0)
        printf("\nThe point (%d, %d) lies on the x-axis.", x1, y1);
    else
        printf("Point (%d, %d) neither lie on x-axis nor on y-axis", x1, y1);
}
```



33. WAP. to check whether a given number is even or odd without using modulo (%) operator

Test Data:

Enter a number: 12



Expected Output:

Even number



Source Code

```
#include <stdio.h>

int main(){
    int num, rem;

    printf("Enter a number: ");
    scanf("%d", &num);

    rem = num - num / 2 * 2;

    if(rem == 0)
        printf("\nEven number");
    else
        printf("\nOdd number");

    return 0;
}
```



34. WAP. An electricity board charges the following rates for the use of electricity:

Unit	Price
first 200 units	Rs. 0.80 per unit
next 100 units	Rs. 0.90 per unit
Beyond 300 units	Rs. 1 per unit

All users are charged a minimum of Rs. 100 as meter charge.

If the total amount is more than Rs. 400, then an additional surcharge of 15% of total amount is charged.

Test Data

Enter number of units: 417



Expected Output

Total Charges = 437.05



Source Code

```
#include <stdio.h>

int main(){
    float units, price;

    printf("\nEnter number of units: ");
    scanf("%f", &units);

    if(units <= 200 && units > 0)
        price = units * 0.80;
    else if(units <= 300 && units > 200)
        price = 160 + (units - 200) * 0.90;
    else if(units > 300)
        price = 250 + (units - 300) * 1;
    else
        price = 0;

    price = price + 100;

    if(price > 400)
        price = price + (price * 15 / 100);

    printf("\nTotal Charges = %.2f", price);

    return 0;
}
```

Conditional or Ternary Operator

1. WAP. to input a number and print even or odd.

Test Data

Enter a number: 5

Expected Output

5 is a Odd number.

Source Code

```
#include <stdio.h>

int main(){
    int num;

    printf("Enter a number:");
```

```
scanf("%d", &num);

num % 2 == 0 ? printf("Even Number.") : printf("Odd number");

return 0;
}
```

2. WAP. to find the greatest of the two numbers.

Test Data

Enter two number: 5 10



Expected Output

Greater number = 10



Source Code

```
#include <stdio.h>

int main(){
    int num1, num2, great;

    printf("Enter two number: ");
    scanf("%d %d", &num1, &num2);

    great = num1 > num2 ? num1 : num2;

    printf("Greater number = %d", great);

    return 0;
}
```



3. WAP. to find the greatest of the three numbers.

Test Data

Enter Three number: 22 43 10



Expected Output

Greater number = 43



Source Code

```
#include <stdio.h>

int main(){
    int num1, num2, num3, great;

    printf("\nEnter three number: ");
    scanf("%d %d %d", &num1, &num2, &num3);

    great = num1 > num2 ? num1 > num3 ?
    num1 : num3 : num2 > num3 ? num2 : num3;

    printf("\nGreater number = %d", great);

    return 0;
}
```

4. WAP. using conditional operators to determine whether a year entered through the keyboard is a leap year or not

Test Data

Enter a year: 2021

Expected Output

Not a leap year.

Source Code

```
#include <stdio.h>

int main(){
    int year;

    printf("\nEnter a year:");
    scanf("%d", &year);

    year % 4 == 0 ? printf("\nLeap year.") :
    year % 100 != 0 && year % 400 == 0 ?
    printf("\nLeap year.") : printf("\nNot a Leap year.");

    return 0;
}
```

5. WAP. The cost of one type of mobile service is Rs. 250 plus Rs. 1.25 for each call made over and above 100 calls. print the bill. (ternary operator)

Test Data

Enter number of Calls: 200



Expected Output

Total Bill = 251.25



Source Code

```
#include <stdio.h>

int main(){
    float calls, bill;

    printf("Enter number of Calls: ");
    scanf("%f", &calls);

    bill = calls > 100 ? (250 + (calls - 100) * 1.25 ) : 250;

    printf("Total Bill = %.2f", bill);

    return 0;
}
```



6. WAP. to find Whether the character entered through the keyboard is a lower case alphabet or uppercase.

Test Data

Enter a character: a



Expected Output

Character is Lowercase.



Source Code

```
#include <stdio.h>

int main(){
    char ch;

    printf("Enter a character: ");
    scanf("%c", &ch);

    ch >= 65 && ch <= 90 ? printf("Character is Uppercase.") :
    ch >= 97 && ch <= 121 ? printf("Character is Lowercase.") :
    printf("Not a character.");
}
```



```
return 0;  
}
```

Hi 🙌, I'm Rajiv Kumar

A passionate frontend developer from India



Connect with me:



GITHUB



TWITTER



Tech Stack:
