

CSS

Box model, text , units

```
<!doctype html>
<html lang="en">
  <head>
    <meta charset="UTF-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0" />
    <title>Units</title>
    <style>
      /* h1{
        font-size: 60px; fixed size in all devices screen
      } */

      html {
        /* font-size: 20px; */
      }
      div {
        font-size: 15px;
        height: 50vh;
        background-color: aqua;
        /* width: 50vw; */
        width: 50%;
        /* vw -> viewport width */
      }

      p {
        /* font-size: 2rem; */
        /* font-size: 2em; */
        /* text-align: center; */
        /* text-transform: lowercase; */
        /* text-transform: uppercase; */
        /* text-transform: capitalize; */
        /* color: yellow; */
        /* indentation */
        /* text-indent: 70px; */
        /* word-spacing: 20px; */
        /* letter-spacing: 10px; */
        /* line-height: 2; */
        /* text-shadow:10px 10px 5px blue ; */
        /* h-sh , v-sh, blur ,color */
        /* text-decoration-line: underline;
        text-decoration-color: red;
        text-decoration-thickness: 2px;
        text-decoration-style:double; */
        /* text-decoration: underline 20px red dotted; shorthand property */
```

```

    /* font-size:20px ; */
    border: 2px solid black ;
    padding: 10px;
    font-weight: 900;
    font-style: italic;
    font-family:
        "Franklin Gothic Medium", "Arial Narrow", Arial, sans-serif;
}

    /* vh = viewport height */
</style>
</head>
<body>
    <!-- units , text, font , box model -->

    <!-- text properties -->

    <!-- <del>Delete</del> -->

    <p>Lorem</p>
    <p>Lorem</p>
    <em>Lorem</em>

    <h1>Units</h1>

    <div>
        <p>Hello there 30px</p>
    </div>

    <span>span element</span>

    <!-- units -> absolute, relative -->

    <!-- absolute -> pixel -->
    <!-- relative -> rem, em, vh, vw, % -->
</body>
</html>

```

Theory Notes

1. CSS Units

- **Absolute units** → fixed size, not responsive.
 - px (pixels), pt (points), cm, mm, in.

- **Relative units** → scale based on parent or viewport.
 - em → relative to parent's font size.
 - rem → relative to root (html) font size.
 - % → relative to parent element.
 - vh → viewport height (1vh = 1% of viewport height).
 - vw → viewport width (1vw = 1% of viewport width).

2. Text Properties

- text-align → alignment.
- text-transform → uppercase, lowercase, capitalize.
- text-indent → indentation.
- word-spacing, letter-spacing, line-height.
- text-shadow → adds shadow effect.
- text-decoration → underline, overline, strike-through.

3. Box Model

- **Content → Padding → Border → Margin.**
- padding → space inside border.
- margin → space outside border.
- border → thickness, style, color.

Coding Round Questions

1. Create a <div> with width 50vw and height 50vh.
2. Style a <p> tag with text-transform: uppercase and letter-spacing: 5px.
3. Demonstrate the difference between em and rem units in font sizing.
4. Add a shadow to text using text-shadow.
5. Create a box with padding: 20px, margin: 30px, and border: 2px solid black.
6. Use % to make a child <div> occupy 50% of its parent's width.