CSS

```html
<!doctype html>
<html lang="en">
  <head>
    <meta charset="UTF-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0" />
    <title>Units</title>
    <style>
      p {
        /* font-size: 32px; */
        /* font-size: 5cm; */
        /* font-size: 20mm; */
        /* font-size: 1in; */
        /* 1in -> 96px */
        /* font-size: 12pt; */
        /* font-size: 2pc; */
        /* fixed on all screen devices */
        /* text-align: justify; */
        /* word-spacing: 40px; */
        /* letter-spacing: 20px; */
        /* line-height: 50px; */
        text-indent: 90px;
      }

      div {
        /* width: 25%;
            height: 100px;   */
        background-color: yellow;
        font-size: 40px;
        width: 100px;

        /* vw => viewport width */
        height: 100vh;
      }
      html {
        font-size: 30px;
      }

      span {
        font-size: 2rem;
        width: 2em;
        /* root element  */
        color: red;
      }
      h1 , a {
        text-align: center;
        /* text-decoration: underline; */
```

```
        /* text-decoration: overline; */
        text-decoration: none;
        /* text-transform: uppercase; */
        /* text-transform: lowercase; */
        text-transform:capitalize ;
        text-shadow: 10px 10px 10px yellow;
      }

    </style>
  </head>
  <body>
    <a href="">Hello</a>
    <!-- browser has user agent stylesheet inbuild  -->

    <h1>units</h1>
    <del>Hello</del>
    <p>Units</p>


    <!-- container -->
    <div>
      <span>Em element example </span>
    </div>
    <!-- <p>Hello</p> -->
    <!-- 16 px  -->

    <p>
      Lorem ipsum dolor sit amet consectetur adipisicing elit. Quos
      reprehenderit optio eveniet doloribus corrupti, illum adipisci ducimus
      aliquid omnis magni veniam eos accusantium rem amet asperiores quam
natus,
      alias sunt.
    </p>
  </body>
</html>
```

John Doe

Frontend developer passionate about CSS units and selectors.

Portfolio
Download Resume

CSS Units

1. Create three `<p>` elements and style each with different font units: `px`, `em`, and `rem`. Compare how they behave when you change the root font size.
2. Make a `<div>` that is `50vw` wide and `50vh` tall. Resize the browser window and observe how it changes.
3. Style a heading using absolute units (`cm`, `mm`, `in`, `pt`, `pc`). Compare across different screen sizes.
4. Create a container with `width: 50%` and another with `width: 200px`. Compare how they behave when resizing the window.

🎯 Text Properties

5. Create three headings and apply `uppercase`, `lowercase`, and `capitalize` using `text-transform`.
6. Style links with `underline`, `overline`, and `line-through` using `text-decoration`.
7. Write a paragraph and apply `word-spacing: 20px`, `letter-spacing: 10px`, and `line-height: 2`. Observe readability changes.
8. Add a `text-shadow` to a heading. Then add multiple shadows separated by commas.

🎯 Selectors

9. Style all `<p>` tags with blue text using a type selector.
10. Style an element with `id="special"` using an ID selector.
11. Style elements with `class="highlight"` using a class selector.
12. Use an attribute selector to style all `<input type="text">` with a border.

🎯 Combinators

15. Use a **descendant selector** (`div p`) to style only `<p>` inside `<div>`.
16. Use a **child selector** (`div > p`) to style direct child `<p>` of `<div>`.
17. Use an **adjacent sibling selector** (`h1 + p`) to style the first `<p>` immediately after `<h1>`.
18. Use a **general sibling selector** (`h1 ~ p`) to style all `<p>` after `<h1>`.