CSS

```html
<!doctype html>
<html lang="en">
  <head>
    <meta charset="UTF-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0" />
    <title>Introduction</title>
    <link rel="stylesheet" href="./introSelector.css" />
    <style>
      h2 {
        color: red;
      }

      p {
        /* color: brown; */
        /* background-color: yellowgreen; */
        /* text-align: center; */
      }
    </style>
  </head>
  <body>
    <!-- 1 -> inline css -> style attribute -->

    <h1
      style="color: blue; padding: 10px; margin: 10px; border: 5px solid
black"
    >
      Inline css
    </h1>

    <!-- 2-> internal css -> style tag  -->

    <h2>internal css</h2>

    <!-- 3-> external css -> separate file + link -->
    <p>above h3 element</p>
    <h3>External css</h3>

    <p style="color: blue; background-color: bisque">
      inline-internal-external
    </p>

    <p>Brindha</p>
    <p id="fiit">FIIT</p>

    <section>
      <h1>Section h1 tag</h1>
```

```html
    </section>

    <section class="sec">
      <h1>Section h1 tag</h1>
    </section>

    <section class="sec">
      <h1>Section h1 tag</h1>
    </section>

    <div>
      <h1>Div h1 tag</h1>
    </div>

    <div>
      <h1 class="sec">div h1 tag</h1>

      <div>
        <h1>Div h1 tag</h1>
        <div>
          <h1>Div h1 tag</h1>
        </div>

        <div>
          <h1>Div h1 tag</h1>
        </div>
      </div>
    </div>

    <div class="child-selector">
      <h1>Child element</h1>
      <div>
        <h1>Grand child element</h1>
      </div>

      <h1>Child element</h1>
    </div>

    <h3>H3 element</h3>
    <span>in between adjacent</span>
    <p>Adjacent sibling element</p>
    <p>sibling element</p>

    <input type="text">
    <input type="password">
  </body>
</html>
```

```
h3 {
  color: yellow;
}

/* p {
  color: white;
  background-color: #333;
} */

#fiit {
  color: orange;
}

.sec {
  color: aqua;
  background-color: brown;
}

* {
  /* background-color: yellowgreen; */
  /* text-align: center; */
}
/*
div h1 {
  color: yellow;
} */

.child-selector > h1 {
  color: purple;
}

h3 + p {
  background-color: aqua;
}

h3 ~ p {
  background-color: gold;
}


input[type="text"]{
    border: 10px solid black;
}
```

Coding Exercises

1. Create a CSS rule that makes all `<p>` tags inside `<section>` blue.
2. Style only the **first child** `<li>` of a list to be bold.
3. Use an attribute selector to style all password inputs with a red border.
4. Add a universal selector that sets all text to `font-family: Arial`.
5. Create a class `.highlight` that changes background color to yellow and apply it to multiple elements.
6. Use `h3 + p` to style only the paragraph immediately after an `<h3>`.
7. Use `h3 ~ p` to style all paragraphs after an `<h3>`.