

## ➔ Find mongodb data

Use of route where you want display data ➔

`Model_name.find({})`

## ➔ Example of create, read

### Index.js

```
let express = require('express');
let bodyParser = require('body-parser')
let mongoose = require('mongoose')
// import session and flash
let session = require('express-session');
let flash = require('connect-flash')

let app = express()
app.set('view engine', 'ejs')
app.use(bodyParser.urlencoded({extended:true}))

//mongoose connect, schema and model
mongoose.connect('mongodb://localhost:27017/testdb')
let myschema = mongoose.Schema({
  pageTitle :String,
  pageDetails : String
})
let mymodel = mongoose.model('dbtale', myschema)

//session and flash middle weare
app.use(session({
  secret:'nodejs',
  resave:true,
  saveUninitialized:true
}))
app.use(flash())

// global variable and set message
app.use((req, res, next)=>{
  res.locals.sucess = req.flash('sucess')
  res.locals.err = req.flash('err')
  //Note: yahan 'sucess' & 'err' globally message set kiya jaa raha hai jiska use puer
  application men kahin bhi kiya jaa sakta hai
  next()
})

//route here
```

```

app.get('/', (req, res)=>{

  mymodel.find({})
  .then((x)=>{
    res.render('index', {x})
  })
  .catch((y)=>{
    console.log(y)
  })

})

app.get('/add-page', (req, res)=>{
  res.render('add-file')
})

app.post('/add-page', (req, res)=>{
  // here read post for data
  let data = {
    pageTitle : req.body.pagetitle,
    pageDetails : req.body.pagedetails

  }
  mymodel.create(data)
  .then((x)=>{
    req.flash('sucess', 'Your Data has been created on Data base')
    res.redirect('/')
  })
  .catch((y)=>{
    req.flash('err', 'Your Data has been not created')
    res.redirect('/')

  })

})

})

app.listen(200, ()=>{
  console.log('200 Port Working')
})

```

## add-file.ejs

```

<form method="post" action="/add-page">
  <input type="text" class="form-control" name="pagetitle" placeholder="page Title"><br><br>
  <textarea name="pagedetails" class="form-control" placeholder="page
details.."></textarea><br><br>
  <button>Submit</button>
</form>

```

## index.ejs

```
<%if(sucess && sucess != ''){%>
  <div class="alert alert-success" role="alert">
    <%= sucess%>
  </div>
<%}else if(err && err != ''){%>
  <div class="alert alert-danger" role="alert">
    <%= err%>
  </div>
<%}%>

<a href="add-page">Add File</a><br><br>

<table cellpadding='10' cellspacing='10' border="1">
  <tr>
    <td>Page Title</td>
    <td>Page details</td>
    <td>Edit</td>
    <td>Delete</td>
  </tr>
  <%x.forEach((y)=>{%>
    <tr>
      <td><%=y.pageTitle%></td>
      <td><%=y.pageDetails.slice(0, 20)%></td>
      <td><a href="">Edit</a></td>
      <td><a href="">Delete</a></td>
    </tr>
  <%})%>
</table>
<br>
<strong>Note :-</strong>.slice(0, 20) kaa use limit charcter ke liye kiya gaya hai
```