

# Attention in Seq2Seq Models

Tanmoy Chakraborty  
Associate Professor, IIT Delhi  
<https://tanmoychak.com/>



**Introduction to Large Language Models**



# NMT: The First Big Success Story of NLP Deep Learning

Neural Machine Translation went from a fringe research attempt in 2014 to the leading standard method in 2016

- 2014: First seq2seq paper published [Sutskever et al. 2014]
- 2016: Google Translate switches from SMT to NMT – and by 2018 everyone had
  - <https://www.nytimes.com/2016/12/14/magazine/the-great-ai-awakening.html>



- This was amazing!
  - SMT systems, built by hundreds of engineers over many years, were outperformed by NMT systems trained by small groups of engineers in a few months

# Issues With RNN


- Linear interaction distance
- Bottleneck problem
- Lack of parallelizability

# ATTENTION

Attention

# Sequence-to-Sequence: The Bottleneck Problem


Encoding of the source sentence



# Sequence-to-Sequence: The Bottleneck Problem

Encoding of the source sentence


This needs to capture *all* information about the source sentence.



# Attention


- **Attention** provides a solution to the bottleneck problem.
- **Core idea:** on each step of the decoder, use **direct connection to the encoder** to **focus on a particular part of the source sequence**
- Let's start with the visualization of the attention mechanism.

# Sequence-to-Sequence With Attention







# Sequence-to-Sequence With Attention




# Sequence-to-Sequence With Attention




# Sequence-to-Sequence With Attention




# Sequence-to-Sequence With Attention




# Sequence-to-Sequence With Attention




# Sequence-to-Sequence With Attention



# Sequence-to-Sequence With Attention




# Sequence-to-Sequence With Attention







# Sequence-to-Sequence With Attention



# Sequence-to-Sequence With Attention



# Sequence-to-Sequence With Attention



# Attention: In Equations

- We have encoder hidden states  $h_1, \dots, h_N \in \mathbb{R}^h$
- On timestep  $t$ , we have decoder hidden state  $s_t \in \mathbb{R}^h$
- We get the attention scores  $e^t$  for this step:

$$e^t = [s_t^T h_1, \dots, s_t^T h_N] \in \mathbb{R}^N$$

- We take softmax to get the attention distribution  $\alpha^t$  for this step (this is a probability distribution, sums to 1)

$$\alpha^t = \text{softmax}(e^t) \in \mathbb{R}^N$$

- We use  $\alpha^t$  to take a weighted sum of the encoder hidden states to get the attention output  $a_t$

$$a_t = \sum_{i=1}^N \alpha_i^t h_i \in \mathbb{R}^h$$

- Finally we concatenate the attention output  $a_t$  with the decoder hidden state  $s_t$  and proceed as in the non-attention seq2seq model


$$[a_t; s_t] \in \mathbb{R}^{2h}$$

# Attention is Great

- Attention significantly improves NMT performance
  - It's very useful to allow decoder to focus on certain parts of the source
- Attention solves the bottleneck problem
  - Attention allows decoder to look directly at source; bypass bottleneck
- Attention helps with vanishing gradient problem
  - Provides shortcut to faraway states
- Attention provides some interpretability
  - By inspecting attention distribution, we can see what the decoder was focusing on
  - We get (soft) alignment for free!
  - This is cool because we never explicitly trained an alignment system
  - The network just learned alignment by itself

	he	hit	me	with	a	pie
il						
a						
m'						
entarté						

# Seq2Seq+Attention for LM




# Attention is a *General* Deep Learning Technique

- We've seen that attention is a great way to improve the sequence-to-sequence model for Machine Translation.
- However: You can use attention in *many architectures* (not just seq2seq) and *many tasks* (not just MT)
- *More general definition of attention*:
  - Given a set of vector *values*, and a vector *query*, *attention* is a technique to compute a weighted sum of the values, dependent on the query.
- We sometimes say that the *query attends to the values*.
- For example, in the seq2seq + attention model, each decoder hidden state (query) *attends to* all the encoder hidden states (values).
- **Intuition**:
  - The weighted sum is a *selective summary* of the information contained in the values, where the query determines which values to focus on.
  - Attention is a way to obtain a *fixed-size representation of an arbitrary set of representations* (the values), dependent on some other representation (the query).

# Attention

Encoding




Input Sequence



# Attention


**Key vectors** represent what **information** is **encoded** at each encoder time step.

Encoding



Input Sequence

# Attention




Input Sequence

Decoding

**Query vectors** represent what information we are **looking for** at each decoder time step.

# Attention




**Softmax** converts the similarity scores into a **probability distribution**.

**Dot product** between query vector and every key vector gives **similarity score**.

**Decoding**

# Attention



The output of attention mechanism is the **weighted sum** of hidden vectors.

Instead of simply summing up the hidden vectors, we can transform them using a learned function to generate **value vectors** and then compute a weighted sum.

**Decoding**

# Variants of Attention

- Original formulation:  $a(\mathbf{q}, \mathbf{k}) = w_2^T \tanh(W_1[\mathbf{q}; \mathbf{k}])$
- Bilinear product:  $a(\mathbf{q}, \mathbf{k}) = \mathbf{q}^T W \mathbf{k}$  Luong et al., 2015
- Dot product:  $a(\mathbf{q}, \mathbf{k}) = \mathbf{q}^T \mathbf{k}$  Luong et al., 2015
- Scaled dot product:  $a(\mathbf{q}, \mathbf{k}) = \frac{\mathbf{q}^T \mathbf{k}}{\sqrt{|\mathbf{k}|}}$  Vaswani et al., 2017

**More information:**

“Deep Learning for NLP Best Practices”, Ruder, 2017. <http://ruder.io/deep-learning-nlp-best-practices/index.html#attention>

“Massive Exploration of Neural Machine Translation Architectures”, Britz et al, 2017, <https://arxiv.org/pdf/1703.03906.pdf>

# Self-Attention