

Each Question carries 1 mark.(Multiple options may be correct)

1. The method to execute stored procedures is

- a> execute()
- b> executeUpdate()
- c> executeParam()
- d> executeQuery()

2. EJBs are present in

- a> Presentation layer.
- b> Application Layer
- c> Web Server layer
- d> Business Layer

3. EJBs depend on JavaBean specification for their support. State true or false.

- a> True
- b> False

4. JavaBeans can be deployed as an ActiveX control. State true or false.

- a> True
- b> False.

5.The distributed services like persistence,transaction support etc in EJBs are provided by

- a> Client application developer
- b> EJB developer

c> EJB container

d> Web Server

6. Which beans can have instance variables and require only semi-persistence storage.

a> Stateful session beans

b> Stateless session beans

c> Container managed Entity beans

d> Bean managed Entity beans.

7.Database connection pooling leads to optimization of container resources. State true or false.

a> True

b> False

8. EJB server(Application server) communicates with the EJB directly. State true or false.

a> True

b> False

9. The error handling attributes in JSP are : (Multiple options can be correct)

a> scope attribute

b> session attribute

c> isError attribute

d> errorPage attribute

10. Java code can be inserted in JSP using

a> JSP directives

b> JSP declarations

c> JSP expressions

d> scriptlet tag.

11. To create custom tags in JSP use :

a> JSP expressions

b> Servlet support

c> scriptlet tags

d> taglib directive

12. In JSP1.0 , jsp:param tags can be used within include or forward tags. State true or false.

a> True

b> False

13. In RMI the type of method arguments can be :(Multiple options can be correct)

a> Java primitive data types

b> Remote Objects

c> Serializable objects

d> Socket object

14. If the client object tries to invoke bind() method of the Naming class, it will result in :

a> RemoteException

b> AlreadyBoundException

c> MarshalException

d> IllegalAccessException

15. The role of distributed garbage collection is performed by

a> Stub layer

b> Remote Reference Layer on Client side

c> Remote Reference Layer on Server side

d> Skeleton layer

16. Multicast addressing is supported by the RMI architecture currently. State true or false.

a> True

b> False

17. The default port for running Rmiregistry service is

a> 1090

b> 1099

c > 8080

d> 9090

18. The session state is shared among all the servlets accessed by a single client. State true or false.

a> True

b> False

19. Cookies are sent as a data part of HTTP response from server to the client application. State true or false.

a> True

b> false

20. Session Tracking is supported as a part of Generic Servlet. State true or false.

a> True

b> False

21. In JavaBeans, Property change can be vetoed if the bean property is of the type :

a> Simple property

b> Indexed property

c> Bound property

d> Constrained property

22. In JDBC API, unknown or multiple results can be handled by :

a> execute()

b> executeUpdate()

c> PreparedStatement

d> executeQuery()

23. In JavaBeans if the property change has to be controlled by external JavaBeans then the external bean has to implement the interface of

a> SimpleBeanInfo

b> VetoableChangeListener

c> PropertyChangeListener

d> EventListener

24. In RMI , the method execution actually takes place on Server object side. State true or false .

a> True

b> False

25. RMI is language independant solution for distributed architecture. State true or false.

a> True

b> False

26. In JDBC, multiple resultsets are handled sequentially by the method

a>next()

b>getResultSet()

c>getUpdateCount()

d>getMoreResults()

27. Batch Handling and scrollable result sets are the features of JDBC2.0 State true or false.

a> true

b> false

28. Servlets are better than CGI because of

a>persistence

b>Windows Support

c>Light weight context.

d>Java Library support

29. In servlets , the interface required for reading initialization parameters is

a> ServletConfig

b>ServletContext

c>ServletRequest

d>GenericServlet

30. The Web Server will create the multithreading support for the servlet only if

- a> Servlet methods are synchronized
- b> synchronized blocks are created
- c>SingleThreadModel interface is implemented
- d>Monitor is created for the servlet

31. With JSDK 2.0, servlet initialization parameters are stored in the file

- a> servlet.config
- b>servlet.properties
- c>servlet.init
- d>servlet.param

32.HTTP Post request can be bookmarked. State true or false.

- a>True
- b>False

33. HTTP is the stateless protocol. State true or false.

- a>True
- b>False

34. Applets can work with JDBC-ODBC bridge type of driver. State true or false.

- a>True
- b>False

35. Client application communicates with EJB through the interfaces :

- a> EJB Container interface
- b> EJB Home interface
- c> EJB Remote interface.
- d>Application server interface.

36. EJBs classified into separate categories based on the persistence are

- a> Entity Beans
- b> Java Beans
- c> Stateless Bean
- d> Session beans

37. In JDBC API, the method to create the connection instance is

- a>DriverManager.createConnection(...)
- b>DriverManager.getConnection(....)
- c>Class.forName(...)
- d>DriverManager.registerDriver(.....)

38. While using <jsp:include>, an included page cannot set headers or cookies. State true or false.

- a> True
- b> False

39. Using "include" as a JSP directive, the file is included at ----- time.

- a> Translation time
- b> Compile time
- c> Run time

d> Request time.

40. Choose the standard action tags defined in JSP

a>jsp:include

b>page

c> jsp:forward

d> jsp:useBean

Answer Bank

1. a

2. d

3. b

4. a

5. c

6. a

7. a

8. b

9 c & d

10 d

11 d

12 b

13 a,b, and c

14 d

15 c

16 b

17.b

18.a

19.b

20.b

21.d

22.a

23 b

24 a

25. b

26. d

27. a

28. a,c,d

29.a

30. c

31. b

32. b

33 a

34 b

35. b,c

36 a,d

37 b

38.a

39.a

40 a,c,d

J2EE

Q. No. 1

Question:

Which of the following is not a job of web container?

Answer Choices

A: Multi threading support

B: Applying thread safety

C: Providing Http Servlet request & response objects

D: Life cycle management of servlet & JSP

Q. No. 2

Question:

Your web application named bank uses WelcomeServlet. Where will you store WelcomeServlet.class ?

Answer Choices

A: bank/WEB-INF/classes

B: bank/WEB-INF/lib/classes

C: root/WEB-INF/lib

D: bank/WebContent/build/classes

Q. No. 3

Question:

Name most suitable execution method in JDBC , for firing DML queries

Answer Choices

A: executeQuery

B:executeUpdate

C:execute

D:executeDynamicQuery

Q. No. 4

Question:

In the following code sample

```
Class.forName("oracle.jdbc.OracleDriver");
```

```
String dbURL = "jdbc:oracle:thin:@host1:1521:xe";
```

```
Connection cn = DriverManager.getConnection(dbURL, "user", "pass");
```

How to create a Prepared Statement , to support scrollable & read only Result Set?

Answer Choices

A: cn.prepareStatement(sql, TYPE_SCROLL_INSENSITIVE, CONCUR_UPDATABLE);

B: cn.prepareStatement(sql, TYPE_FORWARD_ONLY, CONCUR_UPDATABLE);

C: cn.prepareStatement(sql, TYPE_SCROLL_INSENSITIVE, CONCUR_READ_ONLY);

D: cn.prepareStatement(sql, TYPE_SCROLLABLE, CONCUR_UPDATABLE);

Q. No. 5

Question:

In code below, cn – JDBC connection & add_me is already existing stored procedure on the DB , which accepts 2 integers as IN parameters & result of addition is stored in 3rd OUT parameter.

What will be the result of the following code?

```
CallableStatement cst = cn.prepareCall("{call add_me(?,?,?)}");
```

```
cst.setInt(1, num1);  
  
cst.registerOutParameter(3,Types.INTEGER);  
  
cst.execute();  
  
System.out.println("Result = "+cst.getInt(3));
```

Format Type 1 (If answer choices are lengthy, one or more than one line)

Answer Choices

A:Compiler error

B:Prints addition of numbers

C:Run time error as OUT parameter is not registered

D:Run time error as IN parameters are not set correctly.

Q. No. 6

Question:

Choose appropriate transaction isolation level to prevent dirty reads & non-repeatable reads.

Answer Choices

A: TRANSACTION_SERIALIZABLE

B: TRANSACTION_REPEATABLE_READ

C: TRANSACTION_READ_COMMITTED

D: TRANSACTION_READ_UNCOMMITTED

Q. No. 7

Question:

What method can be used to retrieve all the parameter values being sent as part of the request by the client?

Answer Choices

A: Use the method 'HttpServletRequest.getParameterNames()' which will return an enumeration of parameter names.

B: Use the method 'HttpServletRequest.getParameterValues()' which will return array of string values.

C: Use the method 'HttpServletResponse.getValues()' which will return an enumeration of parameter names.

D: There is no direct support in Servlet API

Q. No. 8

Question: Given the following code in a servlet,

```
@WebServlet(urlPatterns = { "/s1" }, initParams = {  
    @WebInitParam(name = "test", value = "test123")})  
  
public class AddCookie extends HttpServlet {  
    public void init() throws ServletException  
    {  
        ServletConfig config=getServletConfig();  
        System.out.println("test="+config.getInitParameter("test"));  
    }  
}
```

What will be output for above servlet, on server console?

Answer Choices

A: The Servlet will fail to load as the init param is not mentioned in the annotation.

B: Null Pointer Exception

C: test123

D: None of above

Q. No. 9

Question:

Consider Servlet1 & Servlet2 with code given below.

Servlet1 code

```
@WebServlet("/s1")

public class Servlet1 extends HttpServlet {

protected void doGet(HttpServletRequest request,HttpServletResponse response) throws
ServletException, IOException {

    response.setContentType("text/html");

    try (PrintWriter pw = response.getWriter()) {

        pw.print("from 1st page...");

        response.sendRedirect("s2");

    }

}
```

Servlet2 code

```
@WebServlet("/s2")

public class Servlet2 extends HttpServlet {

protected void doGet(HttpServletRequest request,HttpServletResponse response) throws
ServletException, IOException {

    response.setContentType("text/html");

    try (PrintWriter pw = response.getWriter()) {

        pw.print("from 2nd page...");

    }

}
```


}

What will be output on client browser & server console after giving URL of

http://host:8080/test/s1 (Assume that web server is running on localhost & servlets are deployed in test1 web application)

Answer Choices

A: Displays 'from 2nd page' on client browser.

B: Displays 'from 1st page' on client browser.

C: Displays 'from1st page' on client browser & IllegalStateException on server console

D:Displays blank on client browser & NullPointerException on server console.

Q. No. 10

Question:

Suppose you are developing online stock trading web application. Which is the most appropriate scope to choose , to store information for available stocks , common for all clients?

Answer Choices

A: Page

B:Session

C: Request

D:Application

Q. No. 11

Question:

Which of the following is inherently thread safe ?

Answer Choices

A:Session Scoped Attributes

B:Application scoped attributes

C:Servlet or JSP instance variables

D:Servlet or JSP method local variable

Q. No. 12

Question:

UserBean is created as java bean , with email property , suitable getter & setter.

Consider one.jsp

```
<jsp:useBean id="user" class="UserBean" scope="request"/>
```

```
<jsp:setProperty name="user" property="email" value="rama@gmail"/>
```

```
<a href="two.jsp">Next</a>
```

Consider two.jsp

Hello, \${user.email}

If Client clicks on Next link, what will be output on client browser?

Answer Choices

A: Hello

B: Hello, rama@gmail

C: Blank page will be displayed

D:Run time error .

Q. No. 13

Question:

What will be output on client browser , for following URL, provided web server is running on localhost , port number 8080 & deployed application is test.

`http://localhost:8080/test/check.jsp?event_id=1234`

check.jsp contains

`${param.event_id}`

Answer Choices

A: 1234

B: Blank page

C:JSP translation time error

D:None of above

Q. No. 14

Question:

Your JSP page(test.jsp) connects to the database and retrieves the data. It also formats the data and displays it to the client. Any of these operations can throw exceptions but you do not want to catch them all in this page and so you have written another JSP page that is meant to handle any kind of exceptions. How would you associate that error page named "error.jsp" with this page?

Answer Choices

A: Add `<%@page errorPage="error.jsp"%>` in test.jsp & Add `<%@page isErrorPage="true"%>` in error.jsp

B: Add `<%@page errorPage="error.jsp"%>` in test.jsp & modify web.xml

C: Add `<%@page isErrorPage="true"%>` in error.jsp

D: Add `<%@ page errorPage="error.jsp"%>` in test.jsp

Q. No. 15

Question:

Which form of the JSP element is used to insert the content generated by other dynamic resources at the request processing time?

Answer Choices

A:JSP Scripting elements

B:JSP Page Directive

C:JSP Include Directive

D:JSP Include Action

Q. No. 16

Question:

In JSP pages , how to directly access context parameters , specific to a particular web application?

Answer Choices

A:Using implicit object context

B: Using implicit object application

C:Using EL implicit object initParam

D:Using JSP implicit object page

Q. No. 17

Question:

Following is tag execution logic in custom tag handler class.(assume that remaining part of the class is specified correctly)

```
public void doTag() throws JspException, IOException {  
    getJspContext().getOut().write("Using Custom Tags");  
}
```

Below is tag definition from Tag Library Descriptor. Example.tld

```
<uri>/WEB-INF/tlds/example</uri>  
  
<tag>  
  
<name>hello</name>  
  
<tag-class>cust_tags.HelloTagHandler</tag-class>  
  
<body-content>empty</body-content>  
  
</tag>
```

Below is important part JSP code (assume that rest of page directive attributes are specified correctly)

```
<%@ taglib uri="/WEB-INF/tlds/example" prefix="test111" %>  
  
<test111:hello/><br/>  
  
<test111:hello/><br/>
```

Answer Choices

A: Translation time error.

B: Prints on client browser "Using Custom Tags" 1 time

C: Request processing time error

D: Prints on client browser "Using Custom Tags" 2 times.

Q. No. 18

Question:

What will be output on client browser for URL given as

`http://www.abc.com:8080/bank/one.jsp`

(Assume that web server is running on host `www.abc.com` & web application bank is deployed)

one.jsp (only relevant part is specified)

```
<h3> Hello </h3>
```

```
<jsp:forward page="two.jsp"/>
```

```
<h3> Hi </h3>
```

two.jsp (only relevant part is specified)

```
<h3>Hello again</h3>
```

Answer Choices

A: Hello Hello again Hi in proper format.

B:IllegalStateException

C:Hello Hi in proper format.

D:Hello again in proper format.

Q. No. 19

Question: What will be output for URL given as

`http://www.abc.com:8080/bank/one.jsp`

(Assume that web server is running on host `www.abc.com` & web application bank is deployed and client has disabled cookies)

Code in one.jsp

```
<jsp:useBean id="dt" class="java.util.Date"/>
```

```
<c:set var="test" value="${dt}" scope="session"/>
```

```
<c:redirect url="two.jsp" />
```

Code in two.jsp

```
<h3> From 2nd page : <c:out value="${dt}"/> </h3>
```

Format Type 1 (If answer choices are lengthy, one or more than one line)

Answer Choices

A: From 2nd page : Current date is printed

B: From 2nd page

C: Blank page

D: Run time error

Q. No. 20

Question:

Which is the best approach to ensure thread safety for context scoped attributes ?

Answer Choices

A: Access context scoped attributes from within the synchronized block , locked on application(ServletContext)

B: <%@ page isThreadSafe="false" %>

C: <%@ page isThreadSafe="true" %>

D: Nothing is required since context scoped attributes are inherently thread safe.

Q. No. 21

Question: In hibernate application, what is the effect of invoking evict method on hibernate session?

Answer Choices

A: Unpredictable results

B: Session level cache is cleared.

C: Removes specified POJO from session cache.

D: POJO becomes persistent

Q. No. 22

Question:

Specify mandatory annotations for creating Hibernate based POJO or Entity class.

Answer Choices

A: @Entity , @Table , @Id , @Column

B: @Serializable, @Table

C: @Entity , @Id

D: @Entity , @Id , @Table

Q. No. 23

Which of the following statements is false in hibernate based web application?

Question:

Answer Choices

A: Its mandatory to create Context listener , to initialize hibernate framework.

B: Hibernate does not support reverse engineer tools.

C : Hibernate POJOs may not be Serializable.

D : Hibernate POJO 's ID property may not be Serializable.

Q. No. 24

Question: Which of the following is true about load & get methods of hibernate session?

Answer Choices

A: Lazy Initialization exception is not raised in get method.

B: load method returns null if POJO is not found.

C: load uses eager fetching policy always.

D: get uses lazy fetching policy always.

Q. No. 25

Question:

Which of the following is NOT a role of the Hibernate session interface?

Answer Choices

A: Holds a mandatory (first-level) cache of persistent objects, used when navigating the object graph or looking up objects by identifier.

B: Holds optionally L2 cache.

C: Wraps a JDBC connection

D: Provides core API for create, retrieve, update & delete.

Q. No. 26

Question:

What will be result of following OGNL expression ?

<s:property value="#application.customer.id"/>

Answer Choices

A: Customer id will be evaluated from value stack

B: Customer id will be evaluated from context scoped attribute

C: Customer id will be evaluated from request parameter.

D: Invalid syntax

Q. No. 27

Question:

Specify thread safety regarding Struts 2 interceptors & actions.

Format Type 1 (If answer choices are lengthy, one or more than one line)

Answer Choices

A: Both are inherently thread safe.

B: Both are inherently thread unsafe.

C: Inherently interceptors are thread unsafe & actions are thread safe.

D: Inherently interceptors are thread safe & actions are thread unsafe.

Q. No. 28

Question:

What will happen if Struts 2 validator framework detects validation error?

Answer Choices

A: If result , name=input , is not specified, exception will be raised.

B: Business logic execution does not take place.

C: If result , name=input , is specified, workflow is diverted to specified input page.

D: All of above options are valid.

Q. No. 29

Question:

What are advantages of Struts 2 over Struts 1?

Answer Choices

A: Introduction of Interceptors

B: Addition of OGNL

C: Inherent thread safety of struts2 actions

D: All of above

Q. No. 30

Question:

What is the need of Model Driven Interceptor in Struts2?

Answer Choices

A: For supporting client side validation framework

B: For automatic conversion of request parameters to Model data.

C: For clean separation between domain object & business logic

D: All of above.

Q. No. 31

Question:

Which of the following is not a role of EJB container?

Answer Choices

A: Instance Pooling of Stateless Session beans

B: Managing Entity life cycle

C: Managing servlet life cycle

D: Providing cache management for Stateful session beans

Q. No. 32

Question:

What is NOT true regarding Stateless Session Beans of EJB 3.x specification?

Answer Choices

A: Stateless Session Beans being light weight , are highest performant.

B: Stateless Session Beans follow pool based life cycle

C: Stateless Session Beans do not use activation & passivation call backs.

D: When remote client invokes any method annotated with @Destroy on Stateless Session bean , EJB container immediately marks it for garbage collection.

Q. No. 33

Question:

If cache type for Stateful Session bean is chosen as NRU(Not recently used),

When will EJB container begin passivation?

Answer Choices

A: If any of Stateful session bean in active cache exceed idle timeout.

B: If number of client requests exceed max cache size.

C: A & B

D: None of above

Q. No. 34

Question:

For online banking based application, which type is best fit to represent a bank customer, whose details are stored in database?

Answer Choices

A: Stateless Session Bean

B: Stateful Session Bean

C: Message Driven Bean

D: JPA based entity.

Q. No. 35

Question:

What is mandatory requirement for implementing Stateful session bean?

Answer Choices

A: Stateful session bean class must implement Serializable interface.

B: Properties of Stateful bean , representing client's conversational state must be non transient & Serializable.

C: Must specify primary key as unique identifier & annotate it correctly.

D: A & B both.

Q. No. 36

Question:

What is NOT true regarding Message Driven Bean's life cycle & its configuration?

Answer Choices

A: It follows pool based life cycle.

B: Implements MessageListener interface to service incoming asynchronous messages.

C: @PostConstruct & @PreDestroy call backs are never called.

D: Must configure destination & its type either via XML or annotations.

Q. No. 37

Question:

In Spring AOP, which type of advice can prevent execution of business logic?

Answer Choices

A: Before

B: After

C: After Throwing

D: Around

Q. No. 38

Question:

Choose suitable class level annotation for web application request handler layer , while integrating spring with hibernate.

Answer Choices

A: @Singleton

B: @Controller

C: @Repository

D: @Service

Q. No. 39

Question:

What is the significance of BindingResult in Spring web MVC architecture?

Answer Choices

A: It stores client's conversational state.

B: Stores result of conversion & validations of the client's conversational state.

C: Stores session scoped attributes.

D: All of above.

Q. No. 40

Question:

Suggest suitable transaction propagation attribute in Spring framework ,that does not support a current transaction; throw an exception if a current transaction exists.

Answer Choices

A: MANDATORY

B: REQUIRED

C: SUPPORTS

D: NEVER

Q. No. 41

Question:

In JSF life-cycle , which phase is used for storing incoming form parameter values in server-side UI component objects?

Answer Choices

A: Apply Request Values

B: Restore View

C:Update Model Values

D:Process Validation

Q. No. 42

Question:

In JSF , which is the annotation used for dependency injection ?

Answer Choices

A: ManagedBean

B:ManagedProperty

C:ViewScoped

D:RequestScoped

1) In a multitiered application, which tier is the browser in?

- A. First tier.
- B. Second tier.
- C. Third tier.
- D. Fourth tier

Ans: A

2) What is the meaning of `ResultSet.TYPE_SCROLL_INSENSITIVE`

- A. This means that the `ResultSet` is insensitive to scrolling
- B. This means that the `ResultSet` is sensitive to scrolling, but insensitive to updates, i.e. not updateable
- C. This means that the `ResultSet` is sensitive to scrolling, but insensitive to changes made by others
- D. The meaning depends on the type of data source, and the type and version of the driver you use with this data source

Ans: C

3) What happens if you call the method `close()` on a `ResultSet` object?

- A. The method `close()` does not exist for a `ResultSet`. Only `Connections` can be closed.
- B. The database and `JDBC` resources are released
- C. You will get a `SQLException`, because only `Statement` objects can close `ResultSets`

D. The ResultSet, together with the Statement which created it and the Connection from which the Statement was retrieved, will be closed and release all database and JDBC resources

Ans: B

4) Which statement is static and synchronized in JDBC API?

- A. executeQuery()
- B. executeUpdate()
- C. getConnection()
- D. prepareCall()

Ans: C

5) To get the servlet environment information

- A. ServletConfig object is used
- B. ServletException object is used
- C. ServletContext object is used
- D. ServletContainer object is used

Ans: C

6) The life cycle of a servlet is managed by

- A. servlet context
- B. servlet container
- C. the supporting protocol (such as http or https)
- D. all of the above

Ans: B

7) Dynamic interception of requests and responses to transform the information is done by

- A. servlet container
- B. servlet config
- C. servlet context
- D. servlet filter

Ans: D

8) Which method is used to retrieve an attribute from ServletContext?

- A. String getAttribute(int index)
- B. String getObject(int index)
- C. Object getAttribute(String name)
- D. String getAttribute(String name)

Ans: C

9) How can a Servlet call a JSP error page ?

A. This capability is not supported.

B. When the servlet throws the exception, it will automatically be caught by the calling JSP page.

C. The servlet needs to forward the request to the specific error page URL. The exception is passed along as an attribute named "javax.servlet.jsp.jspException".

D. The servlet needs to redirect the response to the specific error page, saving the exception off in a cookie.

Ans: C.

10) JSP pages have access to implicit objects that are exposed automatically. One such object that is available is request. The request object is an instance of which class?

A. HttpRequest

B. ServletRequest

C. Request

D. HttpServletRequest

Ans: D

11) Implementations of the _____ interface are notified of changes to the list of active sessions in a web application.

- A. HttpSessionListener
- B. HttpSessionAttributeListener
- C. HttpRequestListener
- D. HttpContextListener

Ans: A

12) A JSP page needs to generate an XML file. Which attribute of page directive may be used to specify that the JSP page is generating an XML file.

- A. contentType
- B. generateXML
- C. type
- D. outputXML

Ans: A

13) What is the key difference between using forward and HttpServletResponse.sendRedirect()?

- A. forward executes on the client while sendRedirect() executes on the server.
- B. forward executes on the server while sendRedirect() executes on the client.
- C. forward and sendRedirect() executes on both client and server.
- D. The two methods perform identically.

ANS: B

14) What is legal about JSP scriptlets.

- A. A loop can begin in one Scriptlet and end in another
- B. Statements in Scriptlets should follow Java Syntax
- C. Semicolon is needed at the end of each statement in a Scriptlet
- D. All the above

ANS: D

15) Why DB connections are not written directly in JSPs ?

- A. Response is slow
- B. Not a standard J2EE architecture
- C. Load Balancing is not possible
- D. Both B. and C.

Ans: D

16) Why beans are used in J2EE architecture in stead of writing all the code in JSPs ?

- A. Allows separation of roles between web developers and application developers
- B. Allows integration with Content Management tools
- C. To simplify the code.
- D. Both A and B.

Ans: A

17) Which are JSP scripting elements and what are they?

- A. Declarations
- B. Scriptlets
- C. both A & B
- D. none of the above

Ans: C

18) You are asked to compare if myStrVariable is equal to 'Z' using struts if condition tag.Which of the following is correct?

```
<s:if test="myStrVariable == 'Z'">
```

Condition met!!

```
</s:if>
```

B.

```
<s:if test='myStrVariable == "Z"'>
```

Condition met!!

```
</s:if>
```

```
<s:if test='myStrVariable == "Z"'>
```

Condition met!!

```
</s:if>
```

All of the above

Ans: B

19) You have created a action class called TakeTestAction to dispatch to takeTest.jsp and have configured in struts.xml. The class has only one method named perform() and does not have execute() method.

Which of the following is true?

A. While building the application, compile error is thrown.

B. While accessing the action, an exception is thrown

C. takeTest.jsp is displayed

D. takeTest.jsp is displayed, if the struts.devMode is set to true in struts.properties.

Ans: B

20) Which of the following statement(s) is true about Struts 2?

A. Different custom RequestProcessor can be attached to per struts module.

B. HttpSession object can be accessed from Action class by invoking
`ActionContext.getContext().getSession()`

C. RequestProcessor is replaced with Interceptors in Struts 2.

D. Only one custom RequestProcessor can be attached per web application.

Ans: A

21) Which of the following is true about the code segment below?

```
<s:form action="ForgotPassword" validate="true">
```

```
  <s:textfield key="userid"/>
```

```
  <s:submit/>
```

```
</s:form>
```

A. Validation is enabled at the server side based on the configurations in <action class>-
validation.xml.

B. JavaScript client validation code is generated by the framework.

C. validate() method of the ActionForm class gets called when the form is submitted.

D. None of the above

Ans: B

22) A simple java application uses Hibernate core to access db. Which of the following statements are true?

- A. Hibernate gets initialized when the application starts.
- B. Hibernate gets initialized when one calls first db access Query object.
- C. Hibernate gets initialized when a SessionFactory is created.
- D. Hibernate gets initialized when first session gets created

Ans: C

23) Which of the following statements are true ?

- A. In Hibernate the persistent beans should implement Serializable interface
- B. Hibernate require a constructor with no arguments for every persistent class and the constructor should be public
- C. Hibernate require a constructor with no arguments for every persistent class and the constructor can be Private.

D. All the above

Ans: B

24) Which of the following identifier - generator modules are defined in Hibernate core?

A. Auto

B. Column

C. Sequence

D. Table

Ans: C

25) What are the different types of EJB?

A. Entity Bean

B. Session Bean

C. Message Driven Bean(MDB)

D. All of the above

Ans: D

26) _____ contain information which is required to both session and entity bean.

- A. JNDI context
- B. EjbContext
- C. Initial Context
- D. Session Context

Ans: B

27) Which are the parts of the message?

- A. A message header
- B. Message properties
- C. Optional message body
- D. All of the above

Ans: D

28) The JMS API are provided in the Java package _____ package.

- A. system.jms

- B. java.jms
- C. javax.jms
- D. jms.*

Ans: C

29) JMS supports messages that contain _____ Java objects

- A. nonserialized
- B. serialized
- C. dynamic
- D. A and C are true

Ans: B

30) What is a thin-client application?

- A. A browser that uses a plug-in to process user data.
- B. A distributed application where the client program does not process data but instead passes data for processing to an enterprise bean running on an application server.
- C. An application that cannot be stopped by a firewall.
- D. An application compiled with the -thin option of the javac command.

Ans: B

31) What advantage does an entity bean have over a session bean?

- A. Entity bean data survives crashes.
- B. An entity bean represents non-persistent data.
- C. It creates its own JAR file during deployment.
- D. You get authentication code without having to write any.

Ans: A

32) When do you use a session bean?

- A. When you want to be certain your application data persists between program invocations, even in the event of a crash.
- B. If you need to initiate a database transaction.
- C. To process transient data that can be re-created in the event of a crash.
- D. To keep people who do not know how to program from accidentally changing important logic code.

Ans: C

33) ejbCreate() method of CMP bean returns.

- A. null
- B. Primary Key class
- C. Home Object
- D. Remote Object

Ans: A

34) What could not return a Spring MVC controller?

- A. An absolute path to the view
- B. A logical view name
- C. A new JstlView
- D. void

Ans: A

35) What are the features of the XML context namespace?

- A. @Transactional annotation scanning
- B. @Aspect annotation detection enabling
- C. @Autowired annotation scanning
- D. @Component annotation scanning

Ans: D

36) Where do you cannot declare Spring MVC controller?

- A. In a Spring application context XML configuration file
- B. Into the web.xml file of the web application(ans)
- C. Into the java code by using annotations
- D. All of the above

Ans: B

37) What is the default rollback policy in transaction management?

- A. Rollback for any Exception
- B. Rollback for RuntimeException
- C. Rollback for checked exceptions
- D. Always commit

Ans: B

38) What is a pointcut?

- A. Code to execute at a join point
- B. An advice and a jointpoint
- C. An expression to identify joinpoints
- D. None of the above

Ans: C

39) What is correct statements about AOP proxy?

- A. AOP proxies are created by Spring in order to implement the aspect contracts
- B. AOP proxies are always created with a JDK dynamic proxy
- C. Only classes that implements a least one interface could be proxied
- D. All methods could be proxied

Ans: A

40) Which of the following is used to locate and describe web services?

- A. SOAP
- B. Web page
- C. WSDL
- D. UDDI

Ans: C