

Q1:

Which of the following is not true for servlet?

It is persistent

Platform independent

It is multi threaded

It is single threaded.

Answer: It is single threaded.

Description: Servlets are multi-threaded components by design.

Q2:

Which method of the servlet is/are called several times in its life?

init()

doPost()

destroy()

None of above

Answer: doPost()

Description: doPost() is called multiple times for handling HTTP requests.

Q3:

Which object is used to forward the request processing from one servlet to another?

ServletContext

ServletConfig

RequestDispatcher

ResponseDispatcher

Answer: RequestDispatcher

Description: RequestDispatcher forwards requests between servlets.

Q4:

The method `getWriter` returns an object of type `PrintWriter`. Which of these classes define the `getWriter` method?

`HttpServletRequest`

`HttpServletResponse`

`ServletConfig`

`ServletContext`

Answer: `HttpServletResponse`

Description: `getWriter()` is used in `HttpServletResponse` to write response data.

Q5:

In which file database table configuration is stored?

`.dbm`

`.hbm`

`.ora`

`.sql`

Answer: `.hbm`

Description: Hibernate uses `.hbm` files for mapping database tables.

Q6:

How can we get context init parameter and run some code before rest of the application can service a client?

`ServletContextAttributeListener`

`ServletContextListener`

`HttpSessionListener`

All of these

Answer: `ServletContextListener`

Description: `ServletContextListener` is used for initializing context parameters.

Q7:

Suppose you want to know each time request comes in, which listener is appropriate for that?

ServletContextAttributeListener

ServletContextListener

HttpSessionListener

All of these

Answer: All of these

Description: Various listeners can be used for different levels of request tracking.

Q8:

In which of these getAttribute() and setAttribute() method has defined?

HttpSession

ServletRequest

ServletContext

All of these

Answer: All of these

Description: getAttribute() and setAttribute() are defined in HttpSession, ServletRequest, and ServletContext.

Q9:

Which of the following are the valid scopes in JSP?

request, page, context, application

response, page, session, application

request, page, session, global

request, page, session, application

Answer: request, page, session, application

Description: These are the valid scopes in JSP: request, page, session, application.

Q10:

Which method can be used to instantiate a method?

static factory method

default-init method

destroy method

lazy-init method

Answer: static factory method

Description: A static factory method is commonly used for instantiating objects.

Q11:

What is the default scope of the beans?

Prototype

session

Request

Singleton

Answer: Singleton

Description: By default, Spring beans have a singleton scope.

Q12:

Which Standard tag is used to store data in the JavaBeans instance?

<jsp:useBean>

<jsp:setBean>

<jsp:set>

<jsp:setProperty>

Answer: <jsp:setProperty>

Description: The <jsp:setProperty> tag is used to store data in JavaBeans.

Q13:

Which driver converts JDBC calls directly into the vendor-specific database protocol?

Native-API driver

Network Protocol driver

Thin driver

None of the above

Answer: Native-API driver

Description: Native-API driver communicates with the database using a native protocol.

Q14:

Which interface provides methods to execute queries with the database?

Connection interface

Statement interface

ResultSet interface

None of the above

Answer: Statement interface

Description: The Statement interface provides methods to execute SQL queries.

Q15:

What are the method of Methods of PreparedStatement interface?

public void setInt()

public void setDouble()

public ResultSet executeQuery()

public void setFloat()

Answer: public void setInt()

Description: setInt() is a method of PreparedStatement for setting parameter values.

Q16:

Which of the following are tags of hibernate.cfg.xml?

SQL variant to generate

DTD

JDBC connection

All of the options

Answer: All of the options

Description: hibernate.cfg.xml contains settings like JDBC connection, SQL generation, and DTD.

Q17:

In the elements of Hibernate architecture is a factory of session and client of ConnectionProvider, the second level cache (optional) of data is

Session

ConnectionProvider

Transaction

SessionFactory

Answer: SessionFactory

Description: SessionFactory is responsible for managing sessions and handling caching in Hibernate.

Q18:

What is dirty checking in Hibernate?

object state changes in order to synchronize the updated state with the database

remove the dirty data from database

check the data when insert into database

None

Answer: object state changes in order to synchronize the updated state with the database

Description: Dirty checking in Hibernate tracks changes to an entity's state to synchronize it with the database.

Q19:

Which of the following element is used to represent one-to-one relationship in hibernate?

many-to-one

many-one

ManyToOne

None of the above

Answer: many-to-one

Description: Hibernate uses many-to-one for representing one-to-one relationships.

Q20:

Which ways are used by the Log4j and Logback frameworks in hibernate framework to support logging?

By log4j.xml file

By log4j.properties

Both of above

None of the above

Answer: Both of above

Description: Both log4j.xml and log4j.properties are supported by Hibernate for logging configuration.

Q21:

Which of these simplifies an Object Relational Mapping tool?

Data creation

Data manipulation

Data access

All mentioned above

Answer: All mentioned above

Description: ORM tools simplify data creation, manipulation, and access by mapping objects to database tables.

Q22:

org.hibernate.SessionFactory can manage contextual sessions and allows to retrieve them by:

getSession() method

getCurrent() method

getCurrentSession() method

None of the above

Answer: getCurrentSession() method

Description: getCurrentSession() is used to retrieve a contextual session in Hibernate.

Q23:

What is no mode of autowiring?

Autowiring by property name.

Similar to byType, but type applies to constructor arguments.

Default setting which means no autowiring and you should use explicit bean reference for wiring.

Spring first tries to wire using autowire by constructor, if it does not work, Spring tries to autowire by byType.

Answer: Default setting which means no autowiring and you should use explicit bean reference for wiring.

Description: The default autowire mode is no autowiring, requiring explicit bean references.

Q24:

Which is not DI?

Setter Based DI

Auto-wiring DI

Both of the above

None of the above.

Answer: None of the above.

Description: Setter-based DI and autowiring are both forms of Dependency Injection (DI).

Q25:

Which of the following is not a state of object in Hibernate?

Attached

Detached

Persistent

Transient

Answer: Attached

Description: The state 'Attached' is not recognized in Hibernate; the states are Detached, Persistent, and Transient.

Q26:

Which is not application context?

ClassPathXmlApplicationContext

AnnotationApplicationContext

WebApplicationContext

WebPathXmlApplicationContext

Answer: WebPathXmlApplicationContext

Description: WebPathXmlApplicationContext is not a valid Spring application context.

Q27:

Which is Stereo Type Annotations?

@Autowired

@Controller

@PreDestroy

@Qualifier

Answer: @Controller

Description: @Controller is a stereotype annotation for Spring MVC controllers.

Q28:

What is Spring MVC framework?

Spring MVC framework is Model-Value-Class architecture and used to bind model data with values.

The Spring web MVC framework provides model-view-controller architecture and ready components that can be used to develop flexible

Spring MVC framework is used for Transaction management for Web Applications.

Spring MVC framework is used for AOP for Web Applications.

Answer: The Spring web MVC framework provides model-view-controller architecture and ready components that can be used to develop flexible

Description: Spring MVC uses the MVC pattern to separate concerns in web applications.

Q29:

How to handle shut down of IoC container?

Using shutdownHook()

Using shutdownHandler()

Using registerHook()

Using registerShutdownHook()

Answer: Using registerShutdownHook()

Description: registerShutdownHook() allows the IoC container to be closed gracefully.

Q30:

What is @Controller annotation?

The @Controller annotation indicates that a particular class serves the role of a controller.

The @Controller annotation indicates how to control the transaction management.

The @Controller annotation indicates how to control the dependency injection.

The @Controller annotation indicates how to control the aspect programming.

Answer: The @Controller annotation indicates that a particular class serves the role of a controller.

Description: @Controller is used in Spring MVC to define a controller class.

Q31:

Which of the following is correct about messaging in RESTful web services?

A client sends a message in form of a HTTP Request and server responds in form of a HTTP Response.

These messages contain message data and metadata i.e. information about the message.

Both of the above

None of the above.

Answer: Both of the above

Description: RESTful web services use HTTP messages to exchange data and metadata between client and server.