

1. Which one of the following is not the input type in HTML5?

A: button

B: checkbox

C: email

 box

2. The _____ attribute specifies the HTTP method (GET or POST) to be used when submitting the form data:

 method

B: action

C: http

D: data

3. Which one of the following list type is not available in HTML5?

A: unordered list

 table list

C: ordered list

D: None of the above

4. Which one of the following HTML5 tag is used to embed video in webpage?

A: audio

 video

C: multimedia

D: media

5. Which one of the following is correct CSS syntax?

A: selector { property= value }

B: selector [property: value]

 selector { property: value }

D: selector (property: value)

6. Which one of the following CSS property is used to create the rounded border of any Div section?

 border-radius

B: border-round

C: border-tranform

D: border-type

7. Which one of the following is correct about javascript?

 A: All JavaScript code for a web page is executed by the web server.

B: All web pages must include JavaScript code in order to work.

C: Javascript is used to create static web page

D: JavaScript and Java are the same thing.

8. How many alert dialogs will be displayed by following javascript code?

```
var x = "10";
```

```
function f(){var x = "4";
```

```
    alert(this.x);
```

```
    function g(){alert(x);}
    g();}
```

```
f();
```

A: 6

B: 7

C: 3

 D: 2

9. _____ function is used to convert string value to integer value in Javascript?

A: Number()

 B: parseInt()

C: to String()

D: parseFloat()

10. Which one of the following denotes the value which is not a number in Javascript?

 A: NaN

B: infinity

C: -infinity

D: isNaN()

11. The special method placed inside a class having the name of the class itself as the function name is _____.

-  A: constructor
B: encapsulation
C: abstraction
D: polymorphism

12. Which one of the following property is used to get the length of array?

-  A: length
B: size
C: width
D: height

13. Which one of the following property is provided by HTML element in DOM?

- A: innerHTML
B: attribute
C: setAttribute(attrib,val)

 D: all of them

14. Which one of the following code is used to hide the p tag on click event using jquery?

-  A:

```
$(document).ready(function(){  
    $("p").click(function(){  
        $(this).hide();  
    });});
```


B:

```
$(document).ready(function(){  
    $("#p").click(function(){  
        $(p).hide();  
    });});
```


C:

```
$(document).ready(function(){  
    $(".p").click(function(){  
        $(this).hide();  
    });});
```


D:

```
$(document).ready(function(){  
    $(p).click(function(){
```

```
$(p).hide();  
});});
```

15. Which one of the following is correct about jquery callback functions?

A: A callback function must be called by user from code

☒ A callback function is executed after the current effect is 100% finished.

C: A callback can be used to only hide and show the HTML element

D: B: A callback function is executed before the current effect is finished.

16. Which one of the following is not the jquery event?

A: blur

B: change

C: click

☒ search

17. Which one of the following function returns all the direct children of the selected element?

A: child()

☒ children()

C: DirectChildren()

D: node()

18. Which one of the following is false about package.json?

A: package.json is present in the root directory of any Node application/module.

B: package.json is used to define the properties of a package.

C: package.json can be used to update dependencies of a Node application.

☒ None of the above.

19. Which one of the following is not the type of stream in Nodejs?

A: Readable

☒ Executable

C: Writable

D: Duplex

20. Which one of the following syntax is correct to open a file in asynchronous mode using fs module?

A: fs.open(callback)

 fs.open(path, flags[, mode], callback)

C: fs.open(path)

D: fs.open(path, flags[, mode])

21. _____ function is used to add a listener at the end of the listeners array for the specified event.

A: addListener(listener)

B: add(event, listener)

 addListener(event, listener)

D: addListener(event)

22. Which one of the following is the correct method to create event emitter object in nodejs?

 var events = require('events');
var EventEmitter = new events.EventEmitter();

B: var events = require('events');
var EventEmitter = generateEventEmitter();

C: var events = require('events');
var EventEmitter = new EventEmitter();

D: var events = require('events');
var EventEmitter = createEventEmitter(new MyEvent());

23. Which one of the following will load the middleware in ExpressJS?

A: app.add

 app.use

C: app.set

D: Any of the above

24. Which one of the following option is correct for the below code?

```
var http = require('http');
```

```
var server = http.createServer(function(req, res){
```

```
var path = req.url.replace(/\/?(?:\?\.*)?$/, '').toLowerCase();
```

```
switch(path) {  
  case " :  
    res.writeHead(200, {'Content-Type': 'text/html'});  
    res.end('<h1>Home Page</h1>');  
    break;  
  case '/about' :  
    res.writeHead(200, {'Content-Type': 'text/html'});  
    res.end('<h1>About us</h1>');  
    break;  
  default:  
    res.writeHead(404, { 'Content-Type': 'text/plain' });  
    res.end('Not Found');  
    break;  
}  
});  
server.listen(3000);
```

A: It will run the server on port number 3000

B: url <http://localhost:3000/about> will display About us

C: url <http://localhost:3000/> will display Home Page

☒ All of the above

25. What `url.parse()` does?

☒ A: This method, and it will return a URL object with each part of the address as properties.

B: This method, and it will return a URL in list form.

C: This method will print the URL

D: This method is invalid

26. Which one of the following method converts a JavaScript object or value to a JSON string?

A: `JSON.toString()`

☒ B: `JSON.stringify()`

C: `json.stringify()`

D: `Json.stringify()`

27. Http methods used in express.js are _____ to create Rest services.



A: Get, Post, Put, Delete

B: Get, Post, Update, Delete

C: Get, Post, Update, Remove

D: Get, Post, Update

28. Which among the following is not a built in module in Node Js?

A: OS

B: PATH

C: HTTP

D: EXPRESS



29 . Which of the following options best describe the markup given below?

```
<div class="row">
```

```
  <div class="col-md-1">.col-md-1</div>
```

```
  <div class="col-md-5">.col-md-5</div>
```

```
  <div class="col-md-6">.col-md-6</div>
```

```
</div>
```

A: generates three equal-width columns starting at tablets and scaling to large desktops.

Not supported in mobiles



B: generates three columns with 1,5,6-width respectively, starting at tablets and scaling to large desktops. On mobile phones, the columns will automatically stack

C: generates three columns with width 5,1,6 starting at mobiles and scaling to large desktops

D: generates three columns with 6,5,1-width respectively columns starting at desktops. On mobile phones, the columns will automatically stack

30. Which one of the following syntax can be used to access value of 'id'?

A: req.param[0]



B: req.params.id

C: req.body.id

D: req.id

31. _____ plugin is used to cycle through elements, like a slideshow.

A: SlideShow

B: Orbit

 Carousel

D: Scrollspy

32. _____ class is used to create a badge.

A: .label

B: .tag

 .badge

D: .flag

33. How many columns are in bootstrap grid system?

 12

B: 9

C: 3

D: 6

34. _____ error send by server in HTTP protocol when requested resource not found.

A: 503

 404

C: 545

D: 304

35. Which one is correct about HTTP?

 It is a stateless protocol

B: It is a statefull protocol

C: Both of the above

D: not a protocol

36. Which one of the following is correct about domain name?

A: A domain name is the address where Internet users can access your website

B: it is difficult for humans to remember ip address. Because of this, domain names were developed and used to identify entities on the Internet rather than using IP addresses.

C: A domain name can be any combination of letters and numbers, and it can be used in combination of the various domain name extensions, such as .com, .net and more.

 All of the above

37. Which one of the following is used to set state in react ?

A: this.state()

 this.setState()

C: this.getState()

D: this.showState()

38. Which one of the following function is used to perform rest api request?

A: api()

 fetch()

C: request()

D: rest()

39. In react component we can return only _____ element.

 1

B: 2

C: 3

D: 4

40. As soon as the state of react component is changed, component will

_____.

A: Does nothing , you have to call render method to render the component again

 e-renders the component

C: be created again from scratch

D: None of above

41. Which one of the following prevents any changes to an object?

 Object.freeze(object)

B: Object.froze(object)

C: froze(object)

D: Object.isfreeze(object)

42. Which one of the following selects the first element of the first ?

 \$("ul li:first")

- B: \$("li:first")
- C: \$("ul first")
- D: \$(":first")

43. Which one of the following selects all elements?

- A: \$("all")
- B: \$("*")



C: \$("*")

D: Not possible

44. Which one of the following is used to create HTTP module instance?



A: var http = require("http");

B: var http = new require("http");

C: var http = new http();

D: None of the above

45. How many number of callback functions can be attached to handle a request?

A: 1



B: unlimited

C: None

D: 255

46. _____ module is used to perform the file system related operation.

A: fileStream

B: file



C: fs

D: fileSystem

47. Which one of the following is the core features of the express.js?

A: Allows to set up middlewares to respond to HTTP Requests.

B: Defines a routing table which is used to perform different actions based on HTTP Method and URL.

C: Defines a routing table which is used to perform different actions based on HTTP Method and URL.

 All of the above

48. Which one of the following built-in middleware provided by express.js to serve static files, such as images, CSS, JavaScript, etc.?

 express.static

B: expressStatic

C: static

D: None of the above

49. Which one of the following is not true about react-redux?

A: It is state management library

B: It gives access to store through provider

 We can also pass data above provider using redux

D: All of the above

50. _____ is used to load the middleware in ExpressJS.

A: app.add

 app.use

C: app.set

D: Any of the above

51. The _____ attribute adds video controls, like play, pause, and volume.

 controls

B: control

C: option

D: attribute

52. Which one of the following value of type attribute of input tag is invalid?

A: text

B: url

 call

D: number

53. The _____ attribute provides an alternate text for an image.

 alt

- B: option
- C: controls
- D: placeholder

54. In CSS, _____ is the range of opacity property.

A: 0.0-10.0

B: 1-10

 0.0-1.0

D: 1-100

55. What are the two ways that data gets handled in React?

 state & props

B: services and component

C: state

D: props

56. ReactJS uses _____ to increase performance.

A: Original DOM

 Virtual DOM

C: Both A and B

D: None of the above

57. _____ used to pass data to a component from outside.

A: setState

B: render and arguments

 props

D: propTypes

58. Everything in react is a _____.

A: Module

 Component

C: Package

D: Class

59. What function allows you to render React content in an HTML page?

A: React.mount()

B: ReactDOM.start()

 ReactDOM.render()

D: React.render()

60. What is state in React?

A: A persistent storage

 An internal data store of a component

C: It's a data transfer mechanism

D: None of the above