

 LT POWER &
CONTROL CABLE





XLPE INSULATED CABLE

- Higher current rating and emergency overload rating
- Superior short circuit rating
- Low dielectric loss
- Much better insulation resistance
- Resistant to chemical & corrosive gases etc.
- Better resistance to surge currents
- Much longer life of the cables

INSULATED MATERIAL

- XLPE
- PVC


PVC INSULATED CABLE

- High dielectric strength & resistance to D.C. voltage effects
- High mechanical strength & resistance to abrasion, vibration & ageing
- Resistant to most acids, alkalies, to temporary contact with solvents, oils and liquid fluids
- Flame retardant, does not support combustion and self extinguishing

APPLICABLE STANDARD

- IEC 60502 Part-1/BS 5467
- BS 6746






XLPE Insulated Unarmoured Single Core Cable

(Copper/Al. Conductor, XLPE Insulated and PVC Sheathed)

Type of Cable	:	N2XY/NA2XY
Rated Voltage	:	0.6/1 kV
Size Range	:	6 to 1000 mm ²
Specification	:	IEC-60502-1
Application	:	For Electric Power Circuit
Identification of Core	:	Natural
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor	:	Annealed Copper/Aluminium
Insulation	:	XLPE
Sheath	:	Extruded PVC



XLPE Insulated Armoured Single Core Cable


(Copper/Al. Conductor, XLPE Insulated, Round Al. Wire

Armoured and PVC Sheathed)

Type of Cable	:	N2XRaY/NA2XRaY
Rated Voltage	:	0.6/1 kV
Size Range	:	6 to 1000 mm ²
Specification	:	IEC-60502-1
Application	:	Indoor and outdoor installation direct Bureal preferably use where considerable me chanical stress must be envisaged.
Identification of Core	:	Natural
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor	:	Annealed Copper/Aluminium
Insulation	:	XLPE
Armouring	:	Round Aluminium Wire
Outer Sheath	:	Extruded PVC




XLPE Insulated Unarmoured Two Core Cable

(Copper/Al. Conductor, XLPE Insulated and PVC Sheathed)

Type of Cable	:	N2XY/NA2XY
Rated Voltage	:	0.6/1 kV
Size Range	:	4 to 400 mm ²
Specification	:	IEC-60502-1
Application	:	For Electric Power Circuit
Identification of Core	:	Red & Black
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor	:	Annealed Copper/Aluminium
Insulation	:	XLPE
Inner Sheath	:	Extruded PVC
Outer Sheath	:	Extruded PVC




XLPE Insulated Armoured Two Core Cable

(Copper/Al. Conductor, XLPE Insulated, Round Al. Wire Armoured and PVC Sheathed)

Type of Cable	:	N2XRY/NA2XRY
Rated Voltage	:	0.6/1 kV
Size Range	:	6 to 400 mm ²
Specification	:	IEC-60502-1
Application	:	For Electric Power Circuit
Identification of Core	:	Red & Black
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor	:	Annealed Copper/Aluminium
Insulation	:	XLPE
Inner Sheath	:	Extruded PVC
Armouring	:	Galvanized Round Steel Wire
Outer Sheath	:	Extruded PVC




XLPE Insulated Unarmoured Three Core Cable

(Copper/Al. Conductor, XLPE Insulated and PVC Sheathed)

Type of Cable	:	N2XY/NA2XY
Rated Voltage	:	0.6/1 kV
Size Range	:	4 to 400 mm ²
Specification	:	IEC-60502-1
Application	:	For Electric Power Circuit
Identification of Core	:	Red, Yellow & Blue
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor	:	Annealed Copper/Aluminium
Insulation	:	XLPE
Inner Sheath	:	Extruded PVC
Outer Sheath	:	Extruded PVC




XLPE Insulated Armoured Three Core Cable

(Copper/Al. Conductor, XLPE Insulated Galvanized Round Steel Wire Armoured and PVC Sheathed)

Type of Cable	:	N2XRY/NA2XRY
Rated Voltage	:	0.6/1 kV
Size Range	:	4 to 400 mm ²
Specification	:	IEC-60502-1
Application	:	For Electric Power Circuit
Identification of Core	:	Red, Yellow & Blue
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor	:	Annealed Copper/Aluminium
Insulation	:	XLPE
Inner Sheath	:	Extruded PVC
Armouring	:	Galvanized Round Steel Wire
Outer Sheath	:	Extruded PVC




XLPE Insulated Unarmoured Three & half Core Cable

(Copper/Al. Conductor, XLPE Insulated and PVC Sheathed)

Type of Cable	:	N2XY/NA2XY
Rated Voltage	:	0.6/1 kV
Size Range	:	25 to 400 mm ²
Specification	:	IEC-60502-1
Application	:	For Electric Power Circuit
Identification of Core	:	Red, Yellow, Blue & Black
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor	:	Annealed Copper/Aluminium
Insulation	:	XLPE
Inner Sheath	:	Extruded PVC
Outer Sheath	:	Extruded PVC




XLPE Insulated Armoured Three & half Core Cable

(Copper/Al. Conductor, XLPE Insulated Galvanized Round Steel Wire Armoured and PVC Sheathed)

Type of Cable	:	N2XRY/NA2XRY
Rated Voltage	:	0.6/1 kV
Size Range	:	25 to 400 mm ²
Specification	:	IEC-60502-1
Application	:	For Electric Power Circuit
Identification of Core	:	Red, Yellow Blue & Black
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor	:	Annealed Copper/Aluminium
Insulation	:	XLPE
Inner Sheath	:	Extruded PVC
Armouring	:	Galvanized Round Steel Wire
Outer Sheath	:	Extruded PVC




XLPE Insulated Unarmoured Four Core Cable

(Copper/Al. Conductor, XLPE Insulated and PVC Sheathed)

Type of Cable	:	N2XY/NA2XY
Rated Voltage	:	0.6/1 kV
Size Range	:	4 to 400 mm ²
Specification	:	IEC-60502-1
Application	:	For Electric Power Circuit
Identification of Core	:	Red, Yellow, Blue & Black
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor	:	Annealed Copper/Aluminium
Insulation	:	XLPE
Inner Sheath	:	Extruded PVC
Outer Sheath	:	Extruded PVC




XLPE Insulated Armoured Four Core Cable

(Copper/Al. Conductor, XLPE Insulated Galvanized round steel Wire Armoured and PVC Sheathed)

Type of Cable	:	N2XRY/NA2XRY
Rated Voltage	:	0.6/1 kV
Size Range	:	4 to 400 mm ²
Specification	:	IEC-60502-1
Application	:	For Electric Power Circuit
Identification of Core	:	Red, Yellow, Blue & Black
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor	:	Annealed Copper/Aluminium
Insulation	:	XLPE
Inner Sheath	:	Extruded PVC
Armouring	:	Galvanized Round Steel Wire
Outer Sheath	:	Extruded PVC




XLPE Insulated Unarmoured Control Cable

(Copper Conductor, XLPE Insulated and PVC Sheathed)

Type of Cable	:	N2XY
Rated Voltage	:	0.6/1 kV
Size Range	:	2 to 61 x 1.5 mm ²
Specification	:	IEC-60502-1, BS:5467
Application	:	For Electric Power Circuit
Identification of Core	:	Black with white numbering
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor	:	Annealed Copper
Insulation	:	XLPE
Inner Sheath	:	Extruded PVC
Outer Sheath	:	Extruded PVC




XLPE Insulated Armoured Control Cable

(Copper Conductor, XLPE Insulated Round Steel Wire Armoured and PVC Sheathed)

Type of Cable	:	N2XRY
Rated Voltage	:	0.6/1 kV
Size Range	:	2 to 61 x 1.5 mm ²
Specification	:	IEC-60502-1, BS:5467
Application	:	For Electric Power Circuit
Identification of Core	:	Black with white numbering
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor	:	Annealed Copper
Insulation	:	XLPE
Inner Sheath	:	Extruded PVC
Armouring	:	Galvanized Steel Round Wire
Outer Sheath	:	Extruded PVC




XLPE Insulated Unarmoured Control Cable

(Copper Conductor, XLPE Insulated and PVC Sheathed)

Type of Cable	:	N2XY
Rated Voltage	:	0.6/1 kV
Size Range	:	2 to 61 x 2.5 mm ²
Specification	:	IEC-60502-1, BS:5467
Application	:	For Electric Power Circuit
Identification of Core	:	Black with white numbering
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor	:	Annealed Copper
Insulation	:	XLPE
Inner Sheath	:	Extruded PVC
Outer Sheath	:	Extruded PVC




XLPE Insulated Armoured Control Cable

(Copper Conductor, XLPE Insulated, Round Steel Wire Armoured and PVC Sheathed)

Type of Cable	:	N2XRY
Rated Voltage	:	0.6/1 kV
Size Range	:	2 to 61 x 2.5 mm ²
Specification	:	IEC-60502-1, BS:5467
Application	:	For Electric Power Circuit
Identification of Core	:	Black with white numbering
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor	:	Annealed Copper
Insulation	:	XLPE
Inner Sheath	:	Extruded PVC
Armouring	:	Galvanized Round Steel Wire
Outer Sheath	:	Extruded PVC




XLPE Insulated Armoured Single Core Cable

(Copper/Al. Conductor, XLPE Insulated, Round Al. Wire Armoured and PVC Sheathed)

Type of Cable	:	N2XRaY/NA2XRaY
Rated Voltage	:	1.8/3.0 (3.6) kV
Size Range	:	25 to 630 mm ²
Specification	:	IEC-60502-1
Application	:	Indoor and outdoor installations direct Bureal preferably use where considerable mechanical stress must be envisaged.
Identification of Core	:	Natural
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor	:	Annealed Copper/Aluminium
Insulation	:	XLPE
Armouring	:	Round Aluminium Wire
Outer Sheath	:	Extruded PVC



XLPE Insulated Armoured Three Core Cable

(Copper/Al. Conductor, XLPE Insulated, Galvanized Round Steel

Wire Armoured and PVC Sheathed)

Type of Cable	:	N2XRY/NA2XRY
Rated Voltage	:	1.8/3.0 (3.6) kV
Size Range	:	25 to 400 mm ²
Specification	:	IEC-60502-1
Application	:	For Electric Power Circuit
Identification of Core	:	Red, Yellow & Blue
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor	:	Copper/Aluminium
Insulation	:	XLPE
Inner Sheath	:	Extruded PVC
Armouring	:	Galvanized Round Steel Wire
Outer Sheath	:	Extruded PVC






HT POWER CABLE

- High continuous current rating
- Higher short circuit rating
- High emergency load capacity
- Low dielectric loss
- Longer charging currents
- Free from height limitation & maintenance
- Resistant to vibration, moisture, chemical & corrosive gases
- Much longer life of the cable

APPLICABLE STANDARD

- IEC 60502 Part-2/BS 6622






XLPE Insulated Armoured Single Core HT Cable

(Cu/Al. Conductor, Semi-conducting Screen, XLPE Insulated, Ins. Semi-conducting Screen Metallic Screen, Separation Sheath, Round Al. Wire, Armoured and PVC sheathed)

Type of Cable	:	N2XHSYRaY/NA2XHSYRaY
Rated Voltage	:	3.6/6.0 (7.2) kV
Size Range	:	25 to 1000 mm ²
Specification	:	IEC-60502-2
Application	:	For Electric Power Circuit
Identification of Core	:	Natural
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

- Conductor - Copper/Aluminium
- Semi Conducting Conductor Screen
- XLPE Insulation
- Semi-Conducting Insulation Screen
- Metallic Screen
- Separation Sheath - PVC
- Aluminium Round Wire Armour
- Outer Sheath - PVC




XLPE Insulated Armoured Three Core HT Cable

(Cu/Al. Conductor, Semi-conducting Screen, XLPE Insulated, Ins. Semi-conducting Screen Metallic Screen, Filler Inner, Covering, Galvanized Round Steel Wire Armoured and PVC sheathed)

Type of Cable	:	N2XXEYRY/NA2XSEYRY
Rated Voltage	:	3.6/6.0 (7.2) kV
Size Range	:	25 to 400 mm ²
Specification	:	IEC-60502-2
Application	:	For Electric Power Circuit
Identification of Core	:	Red, Yellow & Blue
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

- Conductor - Copper/Aluminium
- Semi Conducting Conductor Screen
- XLPE Insulation
- Semi-Conducting Insulation Screen
- Metallic Screen
- Filler
- Inner Covering
- Galvanized Steel Round Wire Armour
- Over Sheath - PVC




XLPE Insulated Armoured Single Core HT Cable

(Cu/Al. Conductor, Semi-conducting Screen, XLPE Insulated, Ins. Semi-conducting Screen, XLPE Insulated. Ins. Semi-conducting screen, Metallic Screen, Separation Sheath Round Al. Wire, armoured and PVC sheathed)

Type of Cable	:	N2XHSYRaY/NA2XHSYRaY
Rated Voltage	:	6/10 (12) kV
Size Range	:	25 to 1000 mm ²
Specification	:	IEC-60502-2
Application	:	For Electric Power Circuit
Identification of Core	:	Natural
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor - Copper/Aluminium
 Semi Conducting Conductor Screen
 XLPE Insulation
 Semi-Conducting Insulation Screen
 Metallic Screen
 Separation Sheath - PVC
 Round Aluminium Wire Armour
 Over Sheath - PVC




XLPE Insulated Armoured Three Core HT Cable

(Cu/Al. Conductor, Semi-conducting Screen, XLPE Insulated, Ins. Semi-conducting Screen, XLPE Insulated. Ins. Semi-conducting screen, Metallic Screen, Filler Inner Coering, Round Steel Wire, armoured and PVC sheathed)

Type of Cable	:	N2XSEYRY/NA2XSEYRY
Rated Voltage	:	6/10 (12) kV
Size Range	:	25 to 400 mm ²
Specification	:	IEC-60502-2
Application	:	For Electric Power Circuit
Identification of Core	:	Red, Yellow & Blue
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor - Copper/Aluminium
 Semi Conducting Conductor Screen
 XLPE Insulation
 Semi-Conducting Insulation Screen
 Metallic Screen
 Filler
 Inner Covering
 Galvanized Steel Round Wire Armour
 Over Sheath - PVC




XLPE Insulated Armoured Single Core HT Cable

(Cu/Al. Conductor, Semi-conducting Screen, XLPE Insulated, Ins. Semi-conducting Screen, Metallic Screen, Separation Sheath, Round Al. Wire armoured and PVC sheathed)

Type of Cable	:	N2XHSYRaY/NA2XHSYRaY
Rated Voltage	:	8.7/15 (17.5) kV
Size Range	:	25 to 1000 mm ²
Specification	:	IEC-60502-2
Application	:	For Electric Power Circuit
Identification of Core	:	Natural
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

- Conductor - Copper/Aluminium
- Semi Conducting Conductor Screen
- XLPE Insulation
- Semi-Conducting Insulation Screen
- Metallic Screen
- Separation Sheath - PVC
- Round Aluminium Wire Armour
- Over Sheath - PVC



XLPE Insulated Armoured Three Core HT Cable

(Cu/Al. Conductor, Semi-conducting Screen, XLPE Insulated, Ins. Semi-conducting Screen, Metallic Screen, Filler Inner Covering, Round Steel Wire armoured and PVC sheathed)

Type of Cable	:	N2XSEYRY/NA2XSEYRY
Rated Voltage	:	8.7/15 (17.5) kV
Size Range	:	25 to 300 mm ²
Specification	:	IEC-60502-2
Application	:	For Electric Power Circuit
Identification of Core	:	Red, Yellow & Blue
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor - Copper/Aluminium

Semi Conducting Conductor Screen

XLPE Insulation

Semi-Conducting Insulation Screen


Metallic Screen

Filler

Inner Covering

Galvanized Steel Round Wire Armour

Over Sheath - PVC




XLPE Insulated Armoured Single Core HT Cable

(Cu/Al. Conductor, Semi-conducting Screen, XLPE Insulated, Ins. Semi-conducting Screen, Metallic Screen, Separation Sheath, Round Al. Wire armoured and PVC sheathed)

Type of Cable	:	N2XHSYRaY/NA2XHSYRaY
Rated Voltage	:	12/20 (24) kV
Size Range	:	25 to 1000 mm ²
Specification	:	IEC-60502-2
Application	:	For Electric Power Circuit
Identification of Core	:	Natural
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

- Conductor - Copper/Aluminium
- Semi Conducting Conductor Screen
- XLPE Insulation
- Semi-Conducting Insulation Screen
- Metallic Screen
- Separation Sheath - PVC
- Round Aluminium Wire Armour
- Over Sheath - PVC



XLPE Insulated Armoured Three Core HT Cable

(Cu/Al. Conductor, Semi-conducting Screen, XLPE Insulated, Ins. Semi-conducting Screen, Metallic Screen, Filler Inner Covering, Round Steel Wire armoured and PVC sheathed)

Type of Cable	:	N2XSEYRY/NA2XSEYRY
Rated Voltage	:	12/20 (24) kV
Size Range	:	35 to 300 mm ²
Specification	:	IEC-60502-2
Application	:	For Electric Power Circuit
Identification of Core	:	Red, Yellow & Blue
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor - Copper/Aluminium

Semi Conducting Conductor Screen

XLPE Insulation

Semi-Conducting Insulation Screen


Metallic Screen

Filler

Inner Covering

Galvanized Steel Round Wire Armour

Over Sheath - PVC



XLPE Insulated Armoured Single Core HT Cable

(Cu/Al. Conductor, Semi-conducting Screen, XLPE Insulated, Ins. Semi-conducting Screen, Metallic Screen, Separation Sheath, Round Al. Wire armoured and PVC sheathed)

Type of Cable	:	N2XHSYRaY/NA2XHSYRaY
Rated Voltage	:	18/30 (36) kV
Size Range	:	50 to 1000 mm ²
Specification	:	IEC-60502-2
Application	:	For Electric Power Circuit
Identification of Core	:	Natural
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor - Copper/Aluminium

Semi Conducting Conductor Screen

XLPE Insulation


Semi-Conducting Insulation Screen

Metallic Screen

Separation Sheath - PVC

Round Aluminium Wire Armour

Over Sheath - PVC



XLPE Insulated Armoured Three Core HT Cable

(Cu/Al. Conductor, Semi-conducting Screen, XLPE Insulated, Ins. Semi-conducting Screen, Metallic Screen, Filler Inner Covering, Round Steel Wire armoured and PVC sheathed)

Type of Cable	:	N2XSEYRY/NA2XSEYRY
Rated Voltage	:	18/30 (36) kV
Size Range	:	50 to 300 mm ²
Specification	:	IEC-60502-2
Application	:	For Electric Power Circuit
Identification of Core	:	Red, Yellow & Blue
Type of Packing	:	Wooden Drum
Other specification and colour are available on request		

Construction

Conductor - Copper/Aluminium

Semi Conducting Conductor Screen

XLPE Insulation

Semi-Conducting Insulation Screen

Metallic Screen

Filler

Inner Covering

Galvanized Steel Round Wire Armour

Over Sheath - PVC