
Flexibility vs. Interpretability in High-Dimensional Cancer Classification

Regularized Regression, Tree Ensembles, and Neural Networks on TCGA RNA-Seq Data ($p \gg n$)

Rajveer Vora | **Amartya Amritanshu** | **P. Sanjith Reddy**

Why Is High-Dimensional Gene Expression Hard?

801 patients, 20,531 measured genes — a severely underdetermined system



Statistical bottlenecks in $p \gg n$:

- **Singular covariance:** $\mathrm{rank}(\mathbf{S}) \leq 800 \ll 20{,}531$; classical LDA fails.
- **Separability:** causes MLE divergence ($\|\mathbf{w}\|_2 \to \infty$).
- **Multicollinearity:** co-expressed genes ($|r| > 0.85$) destabilize selection.

▷ **Regularization is essential to prevent ill-posed estimation.**

SECTION 01

Dataset and Exploratory Analysis

TCGA RNA-Seq Dataset


Five primary tumour types — balanced, log-transformed, pre-screened by variance

801 samples
Total patients

1,000 genes
MAD pre-screen

5 classes
BRCA KIRC COAD
LUAD PRAD


20,531 genes
Raw transcriptome



Preprocessing: Log-transform $z_{ij} = \log_2(x_{ij} + 1)$ ▶ Top-1,000 by in-fold MAD (zero leakage)
▶ In-fold Z-standardization

Expression Heatmap: 50 Highest-Variance Genes

Unsupervised hierarchical clustering reveals tissue-specific expression blocks




Key observations:

- Colours show standardised expression per gene; columns are patients.
- Cancer cohorts form **distinct blocks** without any labels.
- Row clusters reflect shared **gene modules** and pathways.
- Strong visual separation motivates linear classification.

▷ **The dataset carries strong class-specific structure even in unsupervised clustering.**

PCA: Tumours Separate in Two Linear Dimensions

Spectral projection of 1,000 variance-filtered genes onto the leading principal components



- **PC1 (18.6%):** Separates BRCA from KIRC.
- **PC2 (12.3%):** Separates COAD and LUAD.
- **30.9%** of total variation visible in 2D.
- Five cohorts are almost fully linearly separable in this unsupervised projection.

▷ **Linear separability exists before any model fitting — non-linear methods gain little here.**

SECTION 02

Statistical Methodology

Three Regularized Multinomial Classifiers

Penalty geometries under collinearity

Ridge (L_2)

$\mathcal{L}_{\text{CE}} + \frac{\lambda}{2} \sum_k \|\mathbf{w}_k\|_2^2$

- Dense: **1,000 genes**.
- Best calibration (0.005).

Lasso (L_1)

$\mathcal{L}_{\text{CE}} + \lambda \sum_k \|\mathbf{w}_k\|_1$

- Sparse: **89 genes**.
- Drops collinear genes.

Elastic Net ($L_1 + L_2$)

$\mathcal{L}_{\text{CE}} + \lambda \sum_k [\alpha \|\mathbf{w}\|_1 + \frac{1-\alpha}{2} \|\mathbf{w}\|_2^2]$

- Grouping: **218 genes**.
- Stable feature selection.

Why Elastic Net Handles Collinearity Better

Theorem and non-linear baselines

Grouping Bound (Zou & Hastie)

For correlated genes (r):

$$\left|\hat{w}_i - \hat{w}_j\right| \leq \frac{\sqrt{2(1-r)}}{\lambda(1-\alpha)} \|\mathbf{y}\|_2$$

- $\hat{w}_i \to \hat{w}_j$ as $r \to 1$.
- Selects groups jointly.

Non-Linear Baselines

- **Random Forest:** 200 trees.
- **XGBoost:** depth 4.
- **PCA-MLP:** 434 PCs.
- **Sparse NN:** group-L_1.

▷ **Trees split arbitrarily; Elastic Net groups collinear genes.**

SECTION 03

Experimental Design

Zero-Leakage Evaluation Pipeline

10 repeated stratified splits with strictly within-fold feature prescreening



▷ **Strict zero-leakage: feature prescreening and standardization are isolated within training folds.**

Why Three Metrics?

Accuracy, probability calibration, and biomarker stability

Macro-F1 (Accuracy)

$$\frac{1}{5}\sum_{k=1}^{5}\frac{2P_kR_k}{P_k+R_k}$$

Harmonic mean across classes.

Ceiling: all models > 0.99.

Log-Loss (Calibration)

$$-\frac{1}{N}\sum_{i,k} y_{ik}\log\hat{p}_{ik}$$

Penalizes overconfidence.

Decisive metric for ranking.

Stability (Biomarkers)

$$J = \frac{|S_a \cap S_b|}{|S_a \cup S_b|}$$

Gene overlap across splits.


Key for clinical biomarkers.

SECTION 04

Results

All Models Achieve High Accuracy — Log-Loss Tells the Real Story

Performance distributions across 10 repeated train/test splits



F1 saturates above 0.993 for every model. Accuracy alone cannot distinguish architectures on this data.

Log-loss diverges sharply. Random Forest: 0.081. Linear models and PCA-MLP: $<$ 0.020 ($\approx 10\times$ difference).

Comprehensive Model Comparison


10-split cross-validated test results

Model	Macro-F1	Log-Loss	Genes	Jaccard
Softmax	0.998	0.005	1000	1.00
Ridge	0.998	0.005	1000	1.00
Lasso	0.995	0.030	**89**	0.44
Elastic Net	**0.998**	**0.020**	**218**	**0.57**
Random Forest	0.994	0.081	1000	0.16
XGBoost	0.995	0.028	1000	0.29
PCA-MLP	0.998	0.004	434	—
Sparse NN	0.997	0.063	1000	—

▷ **Elastic Net matches top F1 with 218 genes and leads sparse stability.**

Sparsity vs. Calibration: The Pareto Frontier

Elastic Net achieves optimal balance between features and calibration




- **Ridge / PCA-MLP:** Dense (1000 genes / 434 PCs), log-loss 0.004–0.005.
- **Lasso:** Highly sparse (89 genes), log-loss 0.030.
- **Elastic Net:** Optimal trade-off (218 genes, log-loss 0.020).
- **Tree models:** Off frontier (log-loss 0.081).

▷ **Elastic Net occupies the optimal sparse Pareto frontier.**

Feature Selection Stability

Selection consistency across 10 independent data splits




- **Elastic Net:** Jaccard 0.57 (Dice 0.73) — leads sparse models.
- **Lasso:** Jaccard 0.44 — collinear omission hurts stability.
- **XGBoost:** Jaccard 0.29 — greedy splits fluctuate.
- **Random Forest:** Jaccard **0.16** — lowest consistency.

▷ L_2 **grouping is essential for reproducible biomarker discovery.**

Sample Efficiency Under Data Scarcity

Macro-F1 as training size drops from 640 to 30



- **Ridge & Elastic Net:** Maintain $F_1 \geq 0.995$ down to $n_{\text{train}} = 30$.
- **XGBoost:** Drops to 0.976 under data scarcity.
- **Random Forest:** Degrades to 0.985 at $n = 30$.

Y-axis starts at 0.96 to highlight low-n divergence.

▷ **Regularized linear models remain sample-efficient; trees degrade sharply.**

SECTION 05

Interpretation and Conclusions

Three Main Findings

Q1 **Flexibility provides no advantage in RNA-Seq.**

Linear separability holds. Complex models yield no F1 gain and worse calibration.

Q2 **Collinearity destabilises Lasso and trees.**

Lasso drops genes arbitrarily; tree stability drops to 0.16. Elastic Net grouping ensures stability (0.57).

Q3 **Elastic Net achieves optimal balance.**

Ties best F1 (0.998), selects 218 genes (78% cut), and leads in sparse stability.

Limitations and Open Questions

Study Limitations:

- **Single cohort:** $n = 801$; batch effects unmeasured across centres.
- **Inter-tissue task:** intra-organ subtypes remain unstudied.
- **Predictive screen:** 218 genes form statistical candidates, not a diagnostic assay.

Non-Linear Roles:

- Subtle intra-tumour molecular subtyping.
- Higher-order epistatic gene interactions.
- Multi-modal data (genomics + pathology).

Takeaway:

Default to Elastic Net for high-dimensional transcriptomics.

In $p \gg n$ RNA-Seq classification,
regularized linear models are not a compromise —
they are the principled choice.

High accuracy, sharp calibration, 78% feature reduction,
and the most reproducible biomarker sets.

Indian Statistical Institute, Kolkata | November 2026

Thank You

Questions & Discussion