

Background:

Liminal is one of the top crypto wallet infrastructure companies in the world whose customers are mainly Crypto Exchanges.

Exchanges can leverage Liminal's API endpoints to create hot wallets and process customer withdrawals through these hot wallets.

In order to transfer funds to a single or multiple destination addresses Exchanges hit the following API -> <https://docs.lmnl.app/reference/sendmanytransaction>

As an exceptional technical writer, what changes would you make in the documentation for the below scenarios

- Q1. The Product and Development Team at Liminal is launching a new feature that screens any destination address for cyber, fraud and compliance related threats through the integration of a security partner [cube3](#).

Request Changes

A new screeningFlag will be added to the response object that can be either **true** or **false**.

The screening Flag indicates whether the destination address(s) passed in the body of the request must be screened through [cube3's inspector API](#) for threats or not.

Liminal has decided to block the transaction if any of the addresses in its body parameters has combined 'Risk Score' > 80, provided the screeningFlag is **true**.

Response Changes

1. If address screening does not block the transaction (Risk Score < 80)

"screeningResult": "passed"

"screeningID" : 14823 *//(14823 is an example integer)*

will be added to the **data** response object

2. If cube3 detects any of the addresses having a risk score > 80 , it should be handled via error **400**

Even if a single address is blocked, all the transactions should be blocked and the score for the first blocked address should be returned.

Sample 400 error

```
{
  "success": false,
  "data": {
    "error": [
      {
        "value": "",
        "destinationAddress": "0xB9dF6D174d6f1f3A61484762E7131F46Ec85b0d1",
        "screeningResult": "blocked"
        "screeningID" : 14825
        "riskScore": "89"
        "msg": "This transaction has been blocked because the
        destination addresses in the set of addresses is tagged as a sanctioned
        address or has participated in malicious activities such as hacks and
        scams in the past"
        "param": "recepipients.destinationAddress[2]",
        "location": "body"
      },
    ]
  }
}
```

Note in case screeningFlag is **false, the transaction will not be screened and there will be no change in the response.

Document each and every change that you will have to make to the API endpoint page ->

<https://docs.lmnl.app/reference/sendmanytransaction>

Include (not limited to) changes in the response object, body params and the description of the API.

You are encouraged to make assumptions and state them wherever required

Q2. Exchanges can use Liminal's dashboard to stake tokens in the cold wallets such as cardano, solana and ethereum and earn rewards.

Liminal has already compiled a guide on staking on Solana and Ethereum via their dashboard that can be found at -> <https://docs.lmnl.app/docs/staking>

Solana Staking Guide -> <https://docs.lmnl.app/docs/stake-solana-assets-in-liminal-vaults>

Go through the guides in depth and suggest as many points of improvement for the above Solana Staking Guide. We encourage you to think from how the end user using the Liminal dashboard will be able to stake solana smoothly by following the guide step by step.

Q3. The below 3 APIs are not following the best practices of the REST standard. Redesign these APIs according to REST standards.

1. <https://docs.lmnl.app/reference/gettransfers>
2. <https://docs.lmnl.app/reference/sendmanytransaction>
3. <https://docs.lmnl.app/reference/getwalletbalance>

Q4. Share a few samples of your previous work. If it's a public link, please highlight your scope of work clearly.