

Programming Paradigms Fall 2022 — Problem Sets

by Nikolai Kudasov

October 13, 2022

1 Problem set №7

1. What is the type of `guess` in the following program? Justify your answer.

```
guess p g = do
  s <- getLine
  x <- g s
  case p x of
    True  -> return x
    False -> guess p g
```

2. Implement a program `echo :: IO ()` that goes through an infinite loop of reading user input and printing it back in CAPS. Use `toUpper :: Char -> Char` to convert a single character to upper case. Remember that `type String = [Char]`.

```
import Data.Char (toUpper)

echo :: IO ()
```

3. Implement the following functions over `IO`:

- (a) `foreverIO :: IO a -> IO b` — run a given program forever in an infinite loop:

```
>>> foreverIO (putStrLn "Hello!")

Hello!
Hello!
Hello!
...
```

- (b) `whenIO :: Bool -> IO () -> IO ()` — run a given program if a condition is satisfied;
- (c) `maybeIO :: Maybe (IO a) -> IO (Maybe a)` — run a given program if there is one;
- (d) `sequenceMaybeIO :: [IO (Maybe a)] -> IO [a]` — run a sequence of programs and collect all results of type `a`;
- (e) `whileJustIO :: (a -> IO (Maybe a)) -> a -> IO ()` — starting with an initial value of type `a`, apply a given function to run a program and either get `Nothing` and stop or get the next value and repeat;

- (f) `forStateIO_ :: s -> [a] -> (a -> s -> IO s) -> IO s` — starting with an initial state of type `s`, go over values in the list of type `[a]` from left to right, applying a step function `a -> s -> IO s` to update intermediate state on every element; return the final state of type `s`:

```
verboseCons :: Int -> [Int] -> IO [Int]
verboseCons x xs = do
  putStrLn ("prepending " ++ show x ++ " to " ++ show xs)
  return (x:xs)

>>> forStateIO_ [] [1, 2, 3] verboseCons
prepending 1 to []
prepending 2 to [1]
prepending 3 to [2,1]
[3,2,1]
```

4. Implement a **polymorphic** higher-order function `iforIO_` that runs a program for each element and its index in a given list (using given function). Provide an explicit type signature for `iforIO_`.

```
example = do
  iforIO_ [1, 2] (\i n ->
    iforIO_ "ab" (\j c ->
      print ((i, j), replicate n c)))

>>> example

((0,0),"a")
((0,1),"b")
((1,0),"aa")
((1,1),"bb")
```