PRIVATE BETA / TESTER HANDBOOK

SMC LLM
Trade Setup Validator

How it works. What to watch. What not to assume.

Handbook 1.0 | 13 November 2026
Backend package 0.3.0 | Policy strict_v1 | Detector timing_sessions_v2

Ready for controlled testing - not a finished commercial product

The core chart-to-backend workflow is implemented, deployed and tested. Not every original PRD item is complete. There is no established trading edge, calibrated win probability, customer account system or paid-product readiness.

This guide is for a friend testing the interface, signal explanations, delivery and paper outcomes. It is not a trading strategy recommendation. Do not place trades as part of this test.

Read first	Then use as a reference
2 Safe handoff and quick start 3 System and dependencies 4 Chart installation	5-8 Chart legend, rules, settings and timing
9 Read the dashboard 10 News and notifications 11 Automatic paper outcomes	12 Test routine and feedback 13 Troubleshooting
14 Owner-only alert operations 15 Market-closed local preview	16 Completion boundaries and sources

In plain English: SMC means Smart Money Concepts; LLM means large language model. ES is the E-mini S&P 500 future; NQ is the E-mini Nasdaq-100 future. This tool combines programmed chart-pattern checks with an AI review, not a trained price-prediction model.

The three distinctions that prevent most mistakes

A chart **CANDIDATE** is not a final approval. A backend **APPROVED** decision is not an order. A paper **WIN** is not realized profit.

Evidence snapshot: 321 backend tests passed; real price-feed delivery and private Telegram transport were verified on 13 November. This handbook does not certify future uptime or future market results.

Share this PDF without credentials. The service address, passwords, API keys, webhook secret and private chat identifiers are deliberately omitted.

01 / START HERE

Safe handoff and quick start

Do not share the owner's operator login

The MVP has shared HTTP Basic authentication, not individual read-only tester accounts. Those credentials also authorize management/review APIs. Use supervised viewing, a local demo, or a separately configured tester instance. A PDF alone does not provision safe customer access.

Testing mode	What your friend needs
Chart only	Their own TradingView account, the owner-provided Pine file, and access to the agreed ES/NQ feed. No backend keys, webhook secret or OpenAI account required. Leave JSON alerts off in this personal chart copy.
Hosted workflow review	Owner-supervised dashboard access, or an isolated instance with its own credentials and data. The existing Telegram bot sends only to the owner's configured private chat.
Local UI demo	Repository, Python 3.11+, installed backend dependencies and the isolated preview command on page 15. No market session or paid API call is needed.

Your first 10 minutes

1. Agree that this is observation-only testing. Choose chart-only, supervised or isolated mode before receiving access.

2. For comparison with the live cohort, open the exact delayed NQ continuous contract and a standard 4h candlestick chart. The current source is CME_MINI_DL:NQ1!; do not substitute a CFD, micro contract or a different data entitlement.

3. Add the detector and keep its default rules. Use Compact panel, candidate price labels on, debug zones/markers off, test mode off.

4. Read Gate, Candle and HTF. WAIT / No setup is a valid state. A historical label is not a current instruction.

5. In the supervised dashboard, check current readiness, news status and timestamps before reading the latest decision. Open Forward testing to see eligibility, delivery timings and paper outcome evidence.

6. Record questions with the exact symbol, timeframe, UTC time and a redacted screenshot. Do not create or change a production alert.

Before handoff, the owner supplies the approved script version, access method, test start/end date and where to send feedback. Credentials must be exchanged separately through an appropriate private channel.

02 / ARCHITECTURE

What the system actually does

1 TradingView / Pine
Confirmed chart conditions create a provisional candidate.

2 Authenticated webhook
Backend validates and stores the receipt and durable job.

3 Safety checks + structured LLM review
Fresh news and deterministic gates can reject before reasoning.

4 Final validation + storage
BUY / SELL / NO_TRADE; invalid model output cannot bypass rules.

5 Dashboard + approved private notification
A decision-support record, never an order or a broker fill.

A second, data-only path follows the prices

The separate SMC Paper Price Feed sends completed 1m NQ bars in 5m batches. The backend stores these bars and compares eligible final decisions with later prices. This path does not call the LLM or produce trading signals.

Component	Current role / dependency
TradingView + Pine v6	Live chart detection and server-side alerts. Current candidate alert: NQ 4h. Separate price-feed alert: NQ 5m. A webhook-capable plan, enabled 2FA and available alert slots are needed to operate alerts [S1-S2].
Render + Neon	Hosted FastAPI worker/dashboard plus persistent PostgreSQL. Local development uses SQLite. Free hosting/database wake-up and quotas remain operational risks [S3-S4].
OpenAI	Live structured reviewer: gpt-4o-mini. Owner-managed API credentials and credits. Failure provenance is stored; fallback cannot become a live approved push.
ShowMyTrades calendar	Live scheduled USD-event coverage, refreshed every 15 minutes while the backend runs. Not a comprehensive breaking-news or headline service.
Telegram	Live outgoing final-approved notification transport. Incoming sentiment/summary context remains mocked.
Uptime monitor	Optional health checks. A green /health check proves neither alert delivery nor signal accuracy.

The Mac can be closed once hosted alerts are configured. TradingView, Render, Neon and external services must remain available. This is not entirely free: TradingView entitlements and live OpenAI usage can cost money; quotas/pricing may change.

03 / CHART SETUP

Install and open the detector

For a personal chart-only copy; do not alter the live owner layout or its alerts.

1. Get the owner-approved file pine/smc_llm_candidate_detector.pine. In TradingView, open Pine Editor, create a new indicator, paste the complete source, save it with a distinct personal name, and Add to chart. Report any compiler error rather than patching rules ad hoc.

2. Use standard time-based candles. Validated detector combinations are ES and NQ on 5m, 15m, 1h and 4h. For the current live test, use NQ 4h. Charts validated elsewhere do not have active backend alerts automatically.

3. Check the exact feed and delayed-data badge with the owner. ES pairs with NQ and NQ with ES. Leave Companion symbol override blank unless a coordinated feed change is explicitly agreed.

4. In indicator settings, use Panel mode = Compact; Show diagnostic table = on; Show candidate price labels = on. Keep Show FVG zones and Show proof markers off initially.

5. Keep Enable test webhook alert = off. For your chart-only copy, turn Enable alert() JSON payloads off. The owner's production copy keeps JSON enabled. A Pine toggle alone does not create a TradingView alert [S1].

6. Allow data to load. If Gate says 1m data incomplete or Companion data, capture it with the symbol and time. Do not lower data-quality checks to remove the message.

A chart change is not an alert update

TradingView alerts run a saved snapshot of code, inputs, symbol and timeframe. Changing the visible chart does not update an existing server-side alert. Only the owner should perform an approved replacement [S1].

Use	Do not substitute
ES / NQ futures, agreed exact data feed	MES/MNQ, broker CFDs, SPY/QQQ, gold, crypto or arbitrary correlated symbols
Standard candles; supported interval	Heikin Ashi, Renko or other synthetic prices for evaluation
Agreed price adjustments / session settings	Unannounced back-adjustment or settlement-price changes

XAUUSD is not supported. A gold chart is not a valid way to make this ES/NQ workflow generate weekend signals. Use the isolated preview for market-closed UI tests.

04 / CHART LEGEND

Read the panel, not just the color

Compact panel row	Meaning / what to do
SMC strict_v1	WAIT means no current eligible candidate; BULLISH/BEARISH identifies a provisional candidate direction.
Gate	The first blocking reason, or PASS. Read the reason before treating the score as meaningful. PASS is a Pine rule result, not backend/news approval.
Candle	OPEN / PREVIEW may change before close. CLOSED means the chart candle is confirmed. Only confirmed realtime closing bars can emit new natural alerts.
Score	X/100 with a separate minimum of 75. No setup means no active directional FVG; it is not a frozen score.
HTF	Completed higher-timeframe bias. A 4h chart normally uses D (daily), not the unfinished daily candle.
Session (1m)	Session of the latest completed minute used in this chart bar. It is not necessarily the wall-clock session at delivery.
Setups / 100 bars	Recent qualifying setup count in loaded chart history. Not delivered webhooks, filled trades, wins or a complete backtest.
News / final decision	Backend only. Pine cannot see live news approval, final LLM results, Telegram success or backend readiness.

Chart visuals

Visual	Interpretation
BUY CANDIDATE / SELL CANDIDATE	Provisional direction with Entry, SL, TP and RR. Not a fill or final approval. Old labels remain historical even if the current panel is WAIT.
Gray background	Consolidation pause. Two confirmed clear bars are required before release.
FVG box (optional)	Gap zone. Retired boxes may say MITIGATED, INVALIDATED, EXPIRED or SUPERSEDED. Only one active zone is tracked; not every historical zone remains eligible.
BOS / SWEEP / SMT labels (optional)	Debug evidence markers, not separate entry signals. Older drawings are pruned. Obstructive entry/SL/TP line trails were intentionally removed.

In Diagnostics mode, ages such as 3b mean three chart bars. READY means eligible for that feature; EXPIRED means too old. The current label ORDER BLOCK means event-order/sequence blocked, **not** an order-block zone. That wording is a known clarity limitation.

05 / DETECTION POLICY

What must line up for a candidate

The rules are an explicit approximation of SMC concepts, not a claim that every discretionary trader would label the same pattern. A high score cannot override a hard block.

Feature	Implemented definition
BOS	Break of Structure: a confirmed close crosses a buffered last confirmed swing high/low. Default pivots need three bars on either side.
FVG + retest	Fair Value Gap: a three-candle gap at least two ticks wide. A later candle overlaps the still-valid zone. A close beyond the far edge invalidates it; midpoint mitigation retires it after candidate evaluation.
Liquidity sweep	Wick beyond a watched pool, then close back inside. Pools use prior-day, completed-session or equal-pivot levels; the current priority is equal-pivot, then session, then prior-day.
SMT	ES/NQ rolling 20-bar high/low non-confirmation with aligned companion timestamps. This is not full pivot-matched SMT.
Relative volume	Volume / 50-bar average. Below 0.70 is THIN and blocks; 1.50 or higher is STRONG.
Consolidation	20-bar range compression AND low directional efficiency, with two confirmed clear bars before release.
HTF / displacement	HTF close and EMA 50/200 alignment use completed HTF bars. Displacement adds score for a large directional body with a close near that candle's extreme.

Required sequence

Aligned sweep **or** SMT must occur no later than BOS. FVG forms on the BOS bar or within two bars after it; retest occurs later. BOS/liquidity evidence must remain within the configured six-bar limit. The companion and completed 1m session data must be available; HTF must agree; consolidation and thin volume must be absent.

Confirmation	Points	Confirmation	Points
Aligned active FVG	25	Aligned recent BOS	20
Aligned sweep	10	Aligned SMT	10
Aligned HTF	15	Strong RVOL	10
Aligned displacement	10	Maximum / minimum	100 / 75

Valid risk geometry and at least 1.5 RR are also required. One candidate is emitted per tracked FVG. Strict NQ 4h filtering can be quiet for days; low frequency alone proves neither quality nor failure.

Other terms: HTF = higher timeframe; EMA = exponential moving average; ATR = average true range; RVOL = relative volume; tick = the instrument's minimum price increment. SMT here means paired-market non-confirmation.

06 / SETTINGS REFERENCE

Keep the baseline fixed during testing

Changing settings changes the experiment. Record any owner-approved variant separately; do not compare mixed settings as if they were one performance sample. These are baseline values, not optimized recommendations.

Input group	Baseline	Why it matters
Companion / pivots	Auto pair; left 3 / right 3	Controls structure confirmation and associated delay.
BOS / FVG minimum	2 / 2 ticks	Requires a buffered break and a minimum gap size.
Sweep / equal-level tolerance	1 / 4 ticks	Sets wick clearance and equal-pivot matching.
SMT lookback	20 bars	Rolling-window comparison, not pivot matching.
RVOL	50 bars; 0.70 thin; 1.50 strong	Thin volume blocks; strong volume adds score.
ATR / displacement	ATR 14; body 1.0 ATR	Measures movement magnitude; directional close is also required.
Consolidation	20 bars; range 2.0 ATR; efficiency < 0.30	Both compression and low efficiency trigger the pause.
HTF input / EMA	60; EMA 50 / 200	Auto-escalates when 60m is not above the chart. See page 8.
Zone expiry	30 chart bars	Maximum FVG age, not the LLM decision's entry expiry.
Rule score / confirmation age	75 minimum / 6 bars	Hard gates still apply even above the score threshold.
Risk levels	Minimum RR 1.50; target 2.0R; stop buffer 2 ticks	Entry is FVG midpoint; stop uses zone/sweep extreme plus buffer. Target is algebraic, not proof of reachable liquidity.
Display	Compact; labels on; zones/proof markers off	Switch Diagnostics on temporarily when reporting a blocker.
Alert inputs	Owner JSON on; test mode off	Friend's chart-only copy: JSON off. Never enable production test mode to force activity.

Rule score and model confidence are different

The rule score counts deterministic confirmations. The LLM's setup-quality score is a model assessment. Neither is a measured probability of winning. Backend baseline confidence threshold is 70; it does not waive news, freshness, direction or risk checks.

Levels and RR: Entry = proposed observation price; SL = stop-loss level; TP1 = first take-profit level. RR is reward distance / risk distance. Synthetic BUY example: entry 100, SL 95, TP1 110 gives 10/5 = 2.0 RR. It is arithmetic, not a forecast or an instruction to trade.

07 / TIME AND SESSIONS

Why signals arrive later than a wick

Source of delay	What to expect
Market-data entitlement	The current NQ source is delayed. First price-feed verification showed a ten-minute difference between market bar close and emission. Check the actual timestamp; do not assume every delay is ten minutes.
Pivot confirmation	Three right bars must finish before a pivot is confirmed. On 4h this is three chart bars, not three minutes; market breaks can lengthen wall-clock time.
Confirmed chart / HTF	Candidates wait for the chart close; HTF bias uses a completed HTF candle. These are intentional information delays, not rendering bugs.
Network, hosting, model	Webhook transport, database/worker scheduling and LLM processing add separate delay. A green health check does not prove a timely decision.

Effective higher timeframe with the default 60m input

Chart	5m	15m	1h	4h
HTF used	1h	1h	4h	Daily

Session labels use America/New_York

Label	New York local-time window
ASIA	18:00 to 00:00
LONDON	02:00 to 05:00
NY_AM	08:30 to 11:30
NY_PM	13:30 to 16:00
OFF_HOURS	All other minutes; not by itself a news blackout or a closed-market declaration.

These are implementation-defined context windows, not exchange opening hours or universal session definitions. Daylight saving is handled with New York timestamps; do not hard-code a London/UTC offset. A 4h candle can span multiple windows. Session (1m) follows the latest completed included minute.

The backend uses the **actual candle-close time**, including shortened final candles, and normally rejects setup age over 15 minutes. Its stored timestamps use UTC. News and delivery times should be compared in one timezone.

No zero-lag claim

Confirmed bars reduce known timing/repainting problems. They do not make historical markings equivalent to tradable realtime opportunities, or establish complete historical/live equivalence.

08 / DASHBOARD

Read current status before the latest decision

Open the owner-provided HTTPS dashboard in a browser. Do not open backend/templates/index.html directly: it is a server template, not a running dashboard. Refresh the page to get a new snapshot.

Area / field	What it tells you
Armed (operator-verified)	Combined readiness based partly on an operator's TradingView observation. Not a live poll or a promise that the next webhook will arrive.
Worker / failed jobs / oldest pending	Processing health. A stuck queue or STOPPED worker needs owner investigation even when /health is green.
TradingView alert / last checked	ACTIVE, expired/inactive or UNKNOWN observation. Observations become stale after the configured age (normally 24h); UNKNOWN is not proof the alert was deleted.
News coverage / calendar refresh	Current ES/NQ safety state, source publication time, last fetch, failures and next attempt. Compare freshness, not just a recent download.
Latest Setup / Source	Symbol, interval, received/open/close times, SMC facts and CHART CANDIDATE or DELIVERY TEST. The dashboard is a received-setup ledger, not a continuously streaming chart.
Latest Decision	Model, time, raw LLM Action and **Final Action**. Final action plus validator result is authoritative. PENDING means unfinished processing, not approval.
Entry (unfilled), SL, TP1, RR	Proposed levels, not an executed position. Use the final stored decision for paper evaluation, not older provisional Pine levels.
Historical warning	The newest stored decision may be old. It must not be read as a new entry signal merely because it is displayed first.
Recorded News Context	Snapshot associated with that setup, not necessarily today's live news. It can legitimately differ from current coverage at the top.
Setup History / raw payloads	Open a row for context, validation and delivery evidence. Raw data is for auditing, not another recommendation.

Navigation

Health: public process liveness. **Processing Status**: authenticated operational JSON. **Forward testing**: eligible/excluded receipts, timing, automatic outcomes and manual annotations. Main history shows 25 recent setups; it is not the entire database.

For example: LLM Action BUY with Final Action NO_TRADE / REJECTED means the validator blocked the model. Do not ignore the final result because the raw response looked positive.

09 / SAFETY AND NOTIFICATIONS

News and the LLM are separate gates

Current news state	Meaning
CLEAR	A source-validated, in-window calendar is fresh and no configured blackout is active. This does not mean all possible market risks are absent.
BLACKOUT	A configured scheduled event window blocks final approval. The current adapter blocks HIGH/MEDIUM events and Fed-labelled appearances, normally 30 minutes before and after.
UNKNOWN / unavailable / stale	Required coverage cannot be trusted. Approvals remain blocked. Never turn off the gate or renew an old timestamp to manufacture CLEAR.

What the news feed does and does not cover

The free ShowMyTrades scheduled USD calendar refreshes every 15 minutes while the service runs. Publication freshness is capped at two hours. A failed fetch retains the old snapshot but does not renew it. The backend checks news before/after reasoning and again before notification.

Source validation checks format, time and declared coverage; it is not independent verification of every event. Unscheduled headlines, incomplete publisher data and broader systemic risk are not comprehensively covered.

How the LLM is constrained

The live reviewer receives structured chart facts and supplied context, not vague chart screenshots. It returns strict JSON: BUY, SELL or NO_TRADE, quality score, explanation and proposed levels. Schema checks and deterministic rules can override it. OpenAI failure or mock fallback is held as NO_TRADE in the live OpenAI-requested workflow; it cannot become a live final push.

Notification you see	Interpretation
TradingView app / toast	Provisional Pine candidate. Backend news or validation may still reject it.
Private Telegram BUY / SELL	Final approved, fresh, non-test, non-fallback decision passed send-time news checks. Still unfilled decision support, not a trade instruction.
SMC NOTIFICATION DELIVERY TEST	Transport diagnostic only. No setup, approval, order or performance observation.
SENT / UNKNOWN / FAILED	SENT is API acceptance, not phone reading. UNKNOWN requires reconciliation; do not blindly resend. Failure does not erase the stored decision.

Telegram sentiment context is still mock data, even though outgoing bot delivery is live. The bot is configured for one private recipient; starting it from your friend's account does not subscribe them automatically.

10 / OUTCOMES

Automatic tracking without invented wins

The live NQ feed batches the latest 20 completed 1m bars at each 5m close. The repair buffer can fill some short delivery gaps. It is delayed market evidence, not broker execution data. No LLM call is used to decide a paper outcome.

Result	Evidence required
WIN	Eligible final decision; post-decision preferred-entry price touch; then TP1 before SL with unambiguous minute evidence.
LOSS	Post-decision entry touch; then SL before TP1 with unambiguous minute evidence.
EXPIRED	Continuous evidence of no entry touch before a known decision expiry. Missing data cannot prove expiry.
UNKNOWN	Missing/ambiguous prices, both exits touched in one bar, uncertain entry sequence, unmatched price anchor, contract change, invalid/missing timing, conflicting bars or an unresolved path.

Conservative rules worth knowing

1. Only current-cohort, current-revision, approved live-provider BUY/SELL decisions qualify. Tests, rejected decisions and mock/fallback records are excluded. The cohort began 13 November 2026 at 17:10:12 UTC.

2. The exact setup-close minute and price must match the feed. Continuous same-contract data is required through the relevant path. Session breaks and outages may leave UNKNOWN rather than a guessed result.

3. A minute's low/high must span the final preferred entry price, not just any part of its zone. Entry is considered only after the recorded decision time and before decision expiry. Earlier price movement is not credited as an achievable entry. Boundary-straddling minutes that touch relevant levels remain ambiguous.

4. Entry and exit within one minute are UNKNOWN unless entry is exactly that complete post-decision bar's open. If both SL and TP1 are touched, sequence is still UNKNOWN.

5. An entered observation is followed for at most 24 hours from the decision. The evaluator considers the newest 500 decisions created within 72 hours; it does not reconstruct older weeks without price evidence.

Where to see it

Forward testing shows Automatic paper outcome, Automatic evidence and a separate Manual annotation. Manual corrections append evidence; they do not overwrite the automatic audit. UNRECORDED in the manual field does not mean automatic tracking has failed.

Paper result is not realized P&L

OHLC range touches do not prove fills, tick ordering, fees, spread, slippage or profitability. Keep UNKNOWN results visible; do not exclude them to inflate performance. NQ is the only active price feed.

11 / TEST ROUTINE

What your friend should actually test

Before each session

1. Confirm the agreed exact chart/feed, timeframe and baseline settings. Note delayed data and the timezone used in screenshots.

2. Check worker, queue, news publication/freshness and alert observation/expiry. The owner checks actual TradingView alert logs when needed.

3. Check automatic feed status. RECEIVING means recent stored bars; STALE_OR_MARKET_CLOSED needs context, not an automatic conclusion that the market or server is broken.

When a candidate appears

1. Capture the candidate label and Compact/Diagnostics state with the symbol, interval and candle-close time. Note whether you saw it live or only in history.

2. Match its setup ID/time to the dashboard receipt and TradingView alert log. Compare LLM action, final action and rejection reason. A chart label alone does not prove a webhook was sent.

3. For an approved result, check the private notification and automatic outcome evidence. Record missing or late delivery, but do not place an order or mark a historical pre-decision touch as a fill.

Weekly review

Review all receipts, exclusions, rejections, delivery failures, delay distributions and UNKNOWN outcomes. Keep test records separate. Compare like-for-like settings and data feeds. Do not optimize the rules after each isolated win/loss.

Feedback record	Fill in
Observed at (UTC)	Date/time; live observation or historical review
Environment	Exact symbol/feed, interval, device/browser, script/policy version
Reference	Setup ID or relevant candle close; no credentials or webhook URL
Expected / actual	What you expected, what the panel/dashboard/log actually showed
Evidence	Redacted chart + dashboard screenshots; timing and reproduction steps
Impact	Visual confusion, missing candidate, delivery failure, unsafe approval, or uncertain outcome

Stop using a result for evaluation and notify the owner immediately if stale news permits approval, a test/fallback is pushed as live, prices appear future-dated or the same setup produces duplicate notifications.

12 / TROUBLESHOOTING

Quiet is not the same as broken

Symptom	Check first	Safe response
No candidate for days	Gate reason, 100-bar count, confirmed bars, active alert and expiry	Strict NQ 4h can be sparse. Investigate evidence; do not lower thresholds just to get alerts.
No setup / score empty	Active FVG lifecycle	Expected without a directional active zone. It is not automatically a calculation freeze.
1m data incomplete	Loaded intrabar history and gaps	Wait/reload ordinary chart data or report it. Do not synthesize missing minutes.
Companion data	Exact companion, entitlement and timestamps	Owner checks alignment. Do not substitute another symbol without validation.
Chart candidate, no final BUY/SELL	Webhook log, processing job, news, validator	Read the final reason. Pine does not know backend news and may remain bullish after rejection.
Webhook failed / timed out	TradingView delivery status and matching stored setup	Report promptly. A timeout can occur even after storage. Owner reconciles before any retry; no duplicate alert.
Couldn't find domain	Saved alert destination	Owner checks for a stale tunnel/domain. Use the approved stable HTTPS host, not an old quick-tunnel URL.
401 or 503 dashboard	Credentials / server auth configuration	Ask owner privately. Do not disable production authentication or use raw template files.
News UNKNOWN or HTTP 429	Publication age, refresh error, next retry	Leave approvals blocked. Do not change freshness dates or hammer the publisher.
PENDING / failed job	Worker, database, oldest pending	Owner investigates status/logs; never replay old setups as fresh signals.
No Telegram message	Final eligibility, outbox, expiry, news and recipient	Only approved fresh decisions are pushed. SENT is not proof of phone receipt; UNKNOWN needs review.
Paper outcome UNKNOWN	Automatic evidence reason, coverage and contract	This is often the correct conservative result. Provide evidence, not a guessed WIN/LOSS.
Latest decision is old	Received and decided times, historical banner	Expected when no new receipt exists. Refresh; do not treat the old result as current.

Escalate with redacted evidence and UTC timestamps. Never send passwords, API keys, tokens, query secrets or full private webhook URLs in screenshots, chat, support tickets or Git commits.

13 / OWNER OPERATIONS

Two alerts, with different jobs

Reference configuration only. Reading this manual is not permission to create, replace or duplicate live alerts. A friend should not attach new alerts to the owner's endpoint.

Setting	Candidate alert	Data-only price alert
Name	SMC LLM Candidate Detector webhook	SMC Paper Price Feed NQ
Symbol / interval	CME_MINI_DL:NQ1! / 4h	CME_MINI_DL:NQ1! / 5m
Indicator	SMC LLM Candidate Detector	SMC Paper Price Feed
Condition	Any alert() function call	Any alert() function call
Inputs	JSON on; test off; score 75	Feed on; ID nq-paper-v1
Message	Script-generated JSON	Script-generated JSON; last 20 completed 1m bars
Webhook path	/webhooks/tradingview	/webhooks/tradingview/prices
Notifications	App + toast + webhook	Webhook only
Expiry	7 Jan 2027, 18:00 UTC	7 Jan 2027, 18:00 UTC

Both use the existing HTTPS backend and a privately configured secret. No static JSON, password or API key belongs in Pine. TradingView requires 2FA for webhooks; plan/alert limits must be checked in the account [S2].

Owner checks after an approved change

1. Verify the actual editor/script identity, compiled source, inputs, symbol and interval. A prior MCP tab-routing issue targeted the wrong editor; it was restored. Do not assume a tab-switch response proves the write target.

2. Inspect saved alert snapshots, expiry and destination privately. Keep one candidate alert plus one data-only feed. The live candidate snapshot remains revision 19; the restored editor revision number is not a rule change.

3. Confirm real delivery in the TradingView log and corresponding stored receipt or price-bar timestamp. A manual HTTP probe is not proof of TradingView-origin delivery.

Public /health checks only liveness. Authenticated /status, /decisions/latest, /notifications and /dashboard/forward-testing give different evidence. The price feed does not increment the candidate receipt count. Arrange alert renewal before expiry; no automatic renewal is implemented.

14 / SAFE OFFLINE PRACTICE

Test the interface when markets are closed

Use the isolated preview. It creates synthetic fixtures in disposable SQLite, ignores .env files, uses mock reasoning, keeps verified-news test gates enabled and disables outbound workers/notifications. It does not change production, send TradingView alerts or use an OpenAI key.

Dependencies for local testers

Get the owner-approved repository, Python 3.11 or newer and a terminal. The backend installs FastAPI, Uvicorn, Pydantic, SQLAlchemy, Jinja2, JSON Schema validation, psycopg, HTTP clients and the OpenAI SDK. The SDK being installed does not mean the preview calls OpenAI. No Node.js, broker or tunnel is needed.

One-time setup (macOS/Linux; from the repository root)

```
python3 -m venv backend/.venv
backend/.venv/bin/python -m pip install -e './backend[dev]'
```

Start an approved-looking synthetic UI case

```
backend/.venv/bin/python backend/scripts/preview_mvp.py \
  --port 8012 --scenario approved
```

Open **http://127.0.0.1:8012/dashboard**. Stop with Ctrl-C. If the port is occupied, choose another unused local port. On Windows, use the corresponding backend\.venv\Scripts\python.exe path.

Scenario	Expected demonstration
approved	Synthetic approved BUY display; explicitly a DELIVERY TEST, not a market result.
blackout	NO_TRADE with blackout refusal.
stale	NO_TRADE / unknown news, not confirmed ready.
gold	Unsupported XAUUSD rejected; not gold signal support.

Repeat the command with another --scenario value. History includes all four fixtures. The local preview is intentionally not armed and is unauthenticated on loopback only. Never publish it through a tunnel or deploy it as a public dashboard.

Optional developer regression check

```
cd backend
.venv/bin/python -m pytest -q
```

What this proves

UI, schema and rule behavior can be exercised with markets closed. A chart reload, historical drawing or local demo does not prove real webhook delivery, notification delivery or profitability.

15 / RELEASE BOUNDARIES

What is complete, and what is not

Status	Honest assessment
Implemented and exercised	Pine detection/diagnostics on ES/NQ 5m, 15m, 1h, 4h; authenticated webhook and durable jobs; live structured OpenAI review; deterministic validation; persistent storage; protected dashboard; scheduled-news fail-closed gates; private Telegram transport; mobile checks; automatic NQ paper-outcome infrastructure.
Live operational evidence	321 tests pass. Real price-feed webhook delivered on 13 Nov at 19:40 UTC; backend stored it at 19:40:02. Private Telegram diagnostic was received on the phone. These are delivery/code checks, not market-performance proof.
Partial or not implemented	Order-block fallback is NONE; no IFVG detector or manual final-decision Pine overlay. SMT is rolling-window, not pivot-aligned. Telegram sentiment is mocked; no normalized summary ingestion workflow is connected. No comprehensive live headline feed. Gold and broad asset support are absent.
Not finished as a product	No independent tester accounts/read-only roles, multi-tenant isolation, customer billing/licensing or self-service onboarding. Dashboard is basic, without the full original PRD filtering interface. Hosting reliability and recovery still need production hardening.
Not proven	A representative forward sample, complete natural candidate-to-final-push cycle for the current cohort, real eligible paper WIN/LOSS behavior over time, calibrated confidence, realistic execution costs or profitability.

Release decision

Yes: a usable, controlled private-testing MVP. **No:** every original PRD requirement completed, a validated signal service, or a finished product ready for paying customers. Before wider release, finish safe tester access, run representative forward evaluation, harden monitoring/backups/availability, reconcile remaining scope and review provider data rights and applicable distribution requirements.

References and evidence

Implementation: pine/smc_llm_candidate_detector.pine; backend/app/eligibility.py, validators.py, outcome_engine.py; docs/automatic_paper_outcomes.md, automatic_outcome_activation.md, private_telegram_activation_2026_11_13.md, forward_testing.md, automatic_news_calendar.md, closed_market_testing.md. The July PRD is the baseline; the dated rollout documents explain subsequent scope changes.

[S1] TradingView: alerts and saved snapshots
[S2] TradingView: webhooks, 2FA, delivery status and timeouts
[S3] Render: free-service limits and idle behavior
[S4] Neon: compute suspension and activation

External documentation checked 13 November 2026. Operating status is a dated snapshot, not continuous certification. No service address or credential is embedded in this handbook.