# Premier League Analytics API (1.0.0)

Download OpenAPI specification: Download

Rakan Rouchdi: sc23r2r@leeds.ac.uk

A REST API for exploring Premier League data including players, teams, matches, and advanced analytics such as top scorers and league tables.

Features:

- Player CRUD operations
- Team and match retrieval
- Analytical insights
- Season league table generation

## Players

## Get all players

Retrieve all players in the database with optional filters.

QUERY PARAMETERS

| | |
|---|---|
| `team_id` > | Team Id (integer) or Team Id (null) (Team Id)<br>Filter players by team ID |
| `position` > | Position (string) or Position (null) (Position)<br>Filter players by position (FWD, MID, DEF, GKP) |

### Responses

> **200** Successful Response

> **422** Validation Error

GET /players/

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "name": "string",
      "team_id": 0,
      "position": "string",
      "appearances": 0,
      "minutes": 0,
      "goals": 0,
      "assists": 0,
      "id": 0
   }
]
```


## Create a player

Create a new player record linked to an existing team.

REQUEST BODY SCHEMA: application/json
required

| | |
|---|---|
| name<br>required | string (Name) |
| team_id<br>required | integer (Team Id) |
| position > | Position (string) or Position (null) (Position) |

| | |
|---|---|
| `appearances` | integer (Appearances)<br>Default: 0 |
| `minutes` | integer (Minutes)<br>Default: 0 |
| `goals` | integer (Goals)<br>Default: 0 |
| `assists` | integer (Assists)<br>Default: 0 |

## Responses

> **201** Successful Response

> **422** Validation Error

POST `/players/`

### Request samples

**Payload**

**Content type**
application/json

Copy

```
{
    "name": "string",
    "team_id": 0,
    "position": "string",
    "appearances": 0,
    "minutes": 0,
    "goals": 0,
    "assists": 0
}
```

### Response samples

201 422

Content type
application/json

Copy

```
{
    "name": "string",
    "team_id": 0,
    "position": "string",
    "appearances": 0,
    "minutes": 0,
    "goals": 0,
    "assists": 0,
    "id": 0
}
```

---

## Get player by ID

Retrieve a single player using their unique ID.

PATH PARAMETERS

| | |
|---|---|
| player_id<br>required | integer (Player Id) |

## Responses

> 200 Successful Response

— 404 Player not found

> 422 Validation Error

GET /players/{player_id}

### Response samples

200 422

Content type
application/json

Copy

```
{
    "name": "string",
    "team_id": 0,
    "position": "string",
    "appearances": 0,
    "minutes": 0,
    "goals": 0,
    "assists": 0,
    "id": 0
}
```

---

## Update player

Update an existing player's information.

PATH PARAMETERS

| | |
|---|---|
| player_id<br>required | integer (Player Id) |

REQUEST BODY SCHEMA: application/json
required

| | |
|---|---|
| name<br>required | string (Name) |
| team_id<br>required | integer (Team Id) |
| position > | Position (string) or Position (null) (Position) |
| appearances | integer (Appearances)<br>Default: 0 |
| minutes | integer (Minutes)<br>Default: 0 |

| | |
|---|---|
| `goals` | integer (Goals)<br>Default: 0 |
| `assists` | integer (Assists)<br>Default: 0 |

## Responses

> **200** Successful Response

— **404** Player not found

> **422** Validation Error

PUT `/players/{player_id}`

### Request samples

**Payload**

Content type
application/json

Copy

```
{
    "name": "string",
    "team_id": 0,
    "position": "string",
    "appearances": 0,
    "minutes": 0,
    "goals": 0,
    "assists": 0
}
```

### Response samples

**200** **422**

**Content type**
application/json

Copy

```
{
    "name": "string",
    "team_id": 0,
    "position": "string",
    "appearances": 0,
    "minutes": 0,
    "goals": 0,
    "assists": 0,
    "id": 0
}
```

---

# Delete player

Remove a player from the database.

PATH PARAMETERS

| | |
|---|---|
| `player_id`<br>required | integer (Player Id) |

## Responses

— **204** Successful Response

— **404** Player not found

> **422** Validation Error

DELETE `/players/{player_id}`

### Response samples

422

Content type
application/json

Copy Expand all Collapse all

```
{
  - "detail": [
      + { … }
    ]
}
```

---

# Teams

## Get all teams

Retrieve all Premier League teams stored in the database.

### Responses

> **200** Successful Response

GET /teams/

### Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
[
 - {
      "name": "string",
      "id": 0
   }
]
```


---

# Get team by ID

Retrieve a single team using its unique team ID.

PATH PARAMETERS

| | |
|---|---|
| team_id<br>required | integer (Team Id) |

## Responses

> **200** Successful Response

— **404** Team not found

> **422** Validation Error

GET /teams/{team_id}

### Response samples

200 422

Content type
application/json

Copy


```
{
   "name": "string",
   "id": 0
```

```
}
```

# Matches

## Get matches

Retrieve all matches with optional filters.

QUERY PARAMETERS

| | |
|---|---|
| `season` > | Season (string) or Season (null) (Season)<br>Filter matches by season (example: 2024/25) |
| `team_id` > | Team Id (integer) or Team Id (null) (Team Id)<br>Filter matches where a specific team participated |

### Responses

> **200** Successful Response

> **422** Validation Error

GET `/matches/`

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all

```
[
 - {
      "id": 0,
      "match_date": "2019-08-24",
      "season": "string",
      "home_team_id": 0,
      "away_team_id": 0,
      "home_goals": 0,
      "away_goals": 0,
      "home_shots": 0,
      "away_shots": 0,
      "home_corners": 0,
      "away_corners": 0,
      "home_yellow": 0,
      "away_yellow": 0,
      "home_red": 0,
      "away_red": 0
   }
]
```


---

## Get match by ID

Retrieve details for a specific match.

PATH PARAMETERS

| | |
|---|---|
| `match_id`<br>required | integer (Match Id) |

## Responses

> **200** Successful Response

— **404** Match not found

> **422** Validation Error

GET /matches/{match_id}

### Response samples

200 422

Content type
application/json

Copy


```
{
    "id": 0,
    "match_date": "2019-08-24",
    "season": "string",
    "home_team_id": 0,
    "away_team_id": 0,
    "home_goals": 0,
    "away_goals": 0,
    "home_shots": 0,
    "away_shots": 0,
    "home_corners": 0,
    "away_corners": 0,
    "home_yellow": 0,
    "away_yellow": 0,
    "home_red": 0,
    "away_red": 0
}
```


---

# Analytics

## Top goal scorers

Return the players with the highest number of goals.

QUERY PARAMETERS

`limit` integer (Limit) [ 1 .. 50 ]
Default: `10`
Maximum number of players to return

## Responses

> **200** Successful Response

> **422** Validation Error

GET /analytics/top-scorers

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "id": 0,
      "name": "string",
      "team_id": 0,
      "goals": 0,
      "assists": 0
   }
]
```


# Top assist providers

Return the players with the highest number of assists.

QUERY PARAMETERS

`limit` integer (Limit) [ 1 .. 50 ]
Default: `10`
Maximum number of players to return

## Responses

> **200** Successful Response

> **422** Validation Error

GET /analytics/top-assists

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all

```
[
 - {
      "id": 0,
      "name": "string",
      "team_id": 0,
      "goals": 0,
      "assists": 0
   }
]
```

# Highest scoring matches

Return matches with the highest combined goal totals.

QUERY PARAMETERS

`limit` integer (Limit) [ 1 .. 50 ]
Default: `10`
Maximum number of matches to return

## Responses

> **200** Successful Response

> **422** Validation Error

GET `/analytics/highest-scoring-matches`

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "match_id": 0,
      "match_date": "2019-08-24",
      "season": "string",
      "home_team_id": 0,
      "away_team_id": 0,
      "home_goals": 0,
      "away_goals": 0,
      "total_goals": 0
   }
]
```


# Season league table

Generate a league table based on match results for a specific season.

QUERY PARAMETERS

| | |
|---|---|
| season<br>required | string (Season)<br>Season format example: 2024/25 |

## Responses

> **200** Successful Response

> **422** Validation Error

GET /analytics/league-table

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "team_id": 0,
      "team_name": "string",
      "played": 0,
      "wins": 0,
      "draws": 0,
      "losses": 0,
      "goals_for": 0,
      "goals_against": 0,
      "goal_difference": 0,
      "points": 0
   }
]
```

# Team performance summary

Return an overview of a team's performance across all matches.

PATH PARAMETERS

| | |
|---|---|
| team_id<br>required | integer (Team Id) |

## Responses

> **200** Successful Response

— **404** Team not found

> **422** Validation Error

GET /analytics/team-summary/{team_id}

### Response samples

200 422

Content type
application/json

Copy

```
{
    "team_id": 0,
    "team_name": "string",
    "matches_played": 0,
    "wins": 0,
    "draws": 0,
    "losses": 0,
    "goals_for": 0,
    "goals_against": 0,
    "points": 0
}
```


---

# Root

# Root

## Responses

> **200** Successful Response

GET /

### Response samples

**200**

**Content type**
application/json

Copy

```
null
```

---

# Api Root

## Responses

> **200** Successful Response

GET /api

### Response samples

200

Content type
application/json

Copy

```
null
```