RAJALAKSHMI ENGINEERING COLLEGE

Rakchena C 250701576-2025-CSE

R2

Started on	Wednesday, 16 September 2026, 3:35 PM
State	Finished
Completed on	Wednesday, 16 September 2026, 3:38 PM
Time taken	2 mins 42 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>
int compare_asc(const void *a, const void *b) {
    long long num1 = *(const long long *)a;
    long long num2 = *(const long long *)b;
    if (num1 < num2) return -1;
    if (num1 > num2) return 1;
    return 0;
}
int compare_desc(const void *a, const void *b) {
    long long num1 = *(const long long *)a;
    long long num2 = *(const long long *)b;
    if (num1 < num2) return 1;
    if (num1 > num2) return -1;
    return 0;
}
int main() {
    int n;
    if (scanf("%d", &n) != 1) return 0;
    long long array_One[n];
    for (int i = 0; i < n; i++) {
        if (scanf("%lld", &array_One[i]) != 1) return 0;
    }
    long long array_Two[n];
    for (int i = 0; i < n; i++) {
        if (scanf("%lld", &array_Two[i]) != 1) return 0;
    }
    qsort(array_One, n, sizeof(long long), compare_asc);
    qsort(array_Two, n, sizeof(long long), compare_desc);
    long long min_sum = 0;
    for (int i = 0; i < n; i++) {
        min_sum += array_One[i] * array_Two[i];
    }
    printf("%lld\n", min_sum);
    return 0;
}
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course