

"Y" Flow Path, Hamaflon, HV, PSD Valve

Specification Sheet (Part/REF # 99891-01)



Product Specifications

Valve Model	3-2	
Valve Model Description	"Y" Valve	
Fluid Path	CTFE/Hamaflon	
Valve Size	HV	
Nominal Port Diameter	0.059 inch (1.5 mm)	
Housing Material	CTFE	
Actuated	PSD/4, PSD/6, PSD/8	
Break Away Torque	25 oz-in (176 mNm)	
Panel Mounting	No	
Panel Thickness	N/A	
Thread Depth	0.250 (6.35 mm)	
Threaded Connection	1/4-28	
Operating Temp High	40 °C (104 °F)	
Operating Temp Low	15 °C (59 °F)	
Operating Pressure	0 to 100 psig (0 to 6.9 bar)	
Storage Temp High	65 °C (149 °F)	
Storage Temp Low	-29 °C (-20 °F)	
Specifications are subject to change without notice		Spec. Version B



US: +1-800-648-5950 EU: +40-356-635-055



https://www.hamiltoncompany.com/laboratory-products/valves/99891-01



Visit <u>www.hamiltoncompany.com/support</u> to find a representative in your area or call us:

US: +1-800-648-5950 EU: +40-356-635-055