

## SPECIFICATIONS

Insulation Resistance:	1,000MΩ min. at 500V DC
Withstanding Voltage:	500V ACrms for 1 minute
Contact Resistance:	100mΩ at 1mA / 20mV max.
Voltage Rating:	50Vrms AC
Current Rating:	0.5A
Operating Temp. Range:	-25°C to +85°C
Coplanarity:	≤ 0.1mm
Reflow Temp.:	220°C for max. 60 secs., 260° peak / 10 secs.
Mating Cycles:	10,000 (office environment)

## MATERIALS AND FINISH


Insulator:	LCP
Shielding Plate:	Stainless
Contacts:	Copper Alloy, Ni-Au

## FEATURES

- Card lock mechanism
- Smooth extraction function by Push-in /Push-out of card
- Reversed type
- RoHS2011/65/EU


## PART NUMBER

PJS	008	-	2003	-	1
Series No.					
Number of Contacts					
Design No.					
1= with Positioning Pins					




- Card detector
  - Tape & Reel packaging
- (PJS008-2003-0 = 1,000 / PJS008-2003-1 = 800 pcs/reel)

## OUTLINE DIMENSIONS FOR PJS008-2003-1



## CARD INSERTION DETAILS



## RECOMMENDED PCB LAYOUT

