

Problem C. Sets-STL

OS Linux

Sets are a part of the C++ STL. Sets are containers that store unique elements following a specific order. Here are some of the frequently used member functions of sets:

- *Declaration:*

```
1 | set<int>s; //Creates a set of integers.
```

- *Size:*

```
1 | int length=s.size(); //Gives the size of the set.
```

- *Insert:*

```
1 | s.insert(x); //Inserts an integer x into the set s.
```

- *Erasing an element:*

```
1 | s.erase(val); //Erases an integer val from the set s.
```

- *Finding an element:*

```
1 | set<int>::iterator itr=s.find(val); //Gives the iterator to the element
2 | Ex: set<int>::iterator itr=s.find(100); //If 100 is not present t
```

To know more about sets [click Here](#). Coming to the problem, you will be given Q queries. Each query is of one of the following three types:

1 x : Add an element x to the set.

2 x : Delete an element x from the set. (If the number x is not present in the set, then do nothing).

3 x : If the number x is present in the set, then print "Yes"(without quotes) else print "No"(without quotes).

Input Format

The first line of the input contains Q where Q is the number of queries. The next Q lines contain 1 query each. Each query consists of two integers y and x where y is the type of the query and x is an integer.

Constraints

$$1 \leq Q \leq 10^5$$

$$1 \leq y \leq 3$$

$$1 \leq x \leq 10^9$$

Output Format

For queries of type 3 print "Yes"(without quotes) if the number x is present in the set and if the number is not present, then print "No"(without quotes).

Each query of type 3 should be printed in a new line.

Input	Output
8	Yes
1 9	No
1 6	No
1 10	
1 4	
3 6	
3 14	
2 6	
3 6	