

```
#include <stdio.h>
#include <stdlib.h>

int main()
{
    int *a, *b;

    // Allocate array of 5 integers using malloc
    a = (int*)malloc(5 * sizeof(int));

    // Allocate array of 5 integers using calloc (initialized to zero)
    b = (int*)calloc(5, sizeof(int));

    // Reallocate memory to resize array 'a' to 10 integers
    a = (int*)realloc(a, 10 * sizeof(int));

    // Free memory blocks to avoid memory leaks
    free(a);
    free(b);

    return 0;
}
```

⌘G

Get Help

⌘X

Exit

⌘Q

WriteOut

⌘J

Justify

⌘R

Read File

⌘W

Where is

⌘Y

Prev Pg

⌘V

Next Pg

⌘K

Cut Text

⌘U

UnCut Text

⌘C

Cur Pos

⌘T

To Spell

```
medikondarakesh@Medikondas-MacBook-Air ~ % gcc -g program.c -o program
medikondarakesh@Medikondas-MacBook-Air ~ % leaks --atExit -- ./program
program(5381) MallocStackLogging: could not tag MSL-related memory as no_footprint, so those pages will be included in process footprint - No such file or directory (2)
program(5381) MallocStackLogging: recording malloc (and VM allocation) stacks using lite mode
Process 5381 is not debuggable. Due to security restrictions, leaks can only show or save contents of readonly memory of restricted processes.

Process:      program [5381]
Path:         /Users/USER/program
Load Address: 0x100610000
Identifier:   program
Version:      0
Code Type:   ARM64
Platform:    macOS
Parent Process: leaks [5380]
Target Type:  live task

Date/Time:    2026-10-02 17:17:05.662 +0530
Launch Time:  2026-10-02 17:17:05.188 +0530
OS Version:   macOS 27.0.1 (26A434)
Report Version: 7
Analysis Tool: /usr/bin/leaks

Physical footprint:      2256K
Physical footprint (peak): 2272K
Idle exit:               untracked
-----

leaks Report Version: 4.0, multi-line stacks
Process 5381: 187 nodes malloced for 10 KB
Process 5381: 0 leaks for 0 total leaked bytes.

medikondarakesh@Medikondas-MacBook-Air ~ %
```