



SQL Queries

1. Customers in Delhi

```
SQLSELECT*  
FROM customers  
WHERE city ='Delhi';
```

2. Average restaurant rating in Mumbai

```
SQLSELECT AVG(rating) AS avg_rating  
FROM restaurants  
WHERE city ='Mumbai';
```

3. Customers who placed at least one order

```
SQLSELECTDISTINCT c.*  
FROM customers c  
JOIN orders o ON c.customer_id = o.customer_id;
```

4. Total orders by each customer

```
SQLSELECT customer_id, COUNT(order_id) AS total_orders  
FROM orders  
GROUPBY customer_id;
```

5. Total revenue by each restaurant

```
SQLSELECT restaurant_id, SUM(amount) AS total_revenue  
FROM orders  
GROUPBY restaurant_id;
```

6. Top 5 restaurants by average rating

```
SQLSELECT*
```

```
FROM restaurants
ORDERBY rating DESC
LIMIT5;
```

7. Customers who never placed an order

```
SQLSELECT*
FROM customers
WHERE customer_id NOTIN (
SELECT customer_id FROM orders
);
```

8. Orders count by customers in Mumbai

```
SQLSELECT c.customer_id, COUNT(o.order_id) AS total_orders
FROM customers c
JOIN orders o ON c.customer_id = o.customer_id
WHERE c.city ='Mumbai' GROUPBY
c.customer_id;
```

9. Orders in last 30 days

```
SQLSELECT*
FROM orders
WHERE order_date >=CURRENT_DATE-INTERVAL30DAY;
```

10. Delivery partners with more than 1 delivery

```
SQLSELECT partner_id, COUNT(delivery_id) AS deliveries
FROM deliveries
GROUPBY partner_id
HAVINGCOUNT(delivery_id) >1;
```

11. Customers ordering on exactly 3 different days

```
SQLSELECT customer_id
FROM orders
GROUPBY customer_id
HAVINGCOUNT(DISTINCT order_date) =3;
```

12. Delivery partner with most unique customers

```
SQLSELECT d.partner_id,  
COUNT(DISTINCT o.customer_id) AS unique_customers  
FROM deliveries d  
JOIN orders o ON d.order_id = o.order_id  
GROUPBY d.partner_id  
ORDERBY unique_customers DESC  
LIMIT1;
```

13. Customers same city, same restaurant, different dates

```
SQLSELECTDISTINCT c1.customer_id, c2.customer_id  
FROM customers c1  
JOIN customers c2 ON c1.city = c2.city AND c1.customer_id < c2.customer_id  
JOIN orders o1 ON c1.customer_id = o1.customer_id  
JOIN orders o2 ON c2.customer_id = o2.customer_id  
WHERE o1.restaurant_id = o2.restaurant_id AND  
o1.order_date <> o2.order_date;
```
