



CSE408

Matrix Chain

Multiplication

Lecture # 24

Matrix-chain Multiplication



- Suppose we have a sequence or chain A_1, A_2, \dots, A_n of n matrices to be multiplied
 - That is, we want to compute the product $A_1 A_2 \dots A_n$
- There are many possible ways (parenthesizations) to compute the product

Matrix-chain Multiplication ...contd



- Example: consider the chain A_1, A_2, A_3, A_4 of 4 matrices
 - Let us compute the product $A_1A_2A_3A_4$
- There are 5 possible ways:
 1. $(A_1(A_2(A_3A_4)))$
 2. $(A_1((A_2A_3)A_4))$
 3. $((A_1A_2)(A_3A_4))$
 4. $((A_1(A_2A_3))A_4)$
 5. $((((A_1A_2)A_3)A_4))$

Matrix-chain Multiplication ...contd



- To compute the number of scalar multiplications necessary, we must know:
 - Algorithm to multiply two matrices
 - Matrix dimensions
- Can you write the algorithm to multiply two matrices?

Algorithm to Multiply 2 Matrices



Input: Matrices $A_{p \times q}$ and $B_{q \times r}$ (with dimensions $p \times q$ and $q \times r$)

Result: Matrix $C_{p \times r}$ resulting from the product $A \cdot B$

MATRIX-MULTIPLY($A_{p \times q}, B_{q \times r}$)

1. **for** $i \leftarrow 1$ **to** p
2. **for** $j \leftarrow 1$ **to** r
3. $C[i, j] \leftarrow 0$
4. **for** $k \leftarrow 1$ **to** q
5. $C[i, j] \leftarrow C[i, j] + A[i, k] \cdot B[k, j]$
6. **return** C

Scalar multiplication in line 5 dominates time to compute C
Number of scalar multiplications = pqr

Matrix-chain Multiplication ...contd



- Example: Consider three matrices $A_{10 \times 100}$, $B_{100 \times 5}$, and $C_{5 \times 50}$
- There are 2 ways to parenthesize

– $((AB)C) = D_{10 \times 5} \cdot C_{5 \times 50}$

- $AB \Rightarrow 10 \cdot 100 \cdot 5 = 5,000$ scalar multiplications
- $DC \Rightarrow 10 \cdot 5 \cdot 50 = 2,500$ scalar multiplications

Total:
7,500

– $(A(BC)) = A_{10 \times 100} \cdot E_{100 \times 50}$

- $BC \Rightarrow 100 \cdot 5 \cdot 50 = 25,000$ scalar multiplications
- $AE \Rightarrow 10 \cdot 100 \cdot 50 = 50,000$ scalar multiplications

Total:
75,000



Matrix-chain Multiplication ...contd



- Matrix-chain multiplication problem
 - Given a chain A_1, A_2, \dots, A_n of n matrices, where for $i=1, 2, \dots, n$, matrix A_i has dimension $p_{i-1} \times p_i$
 - Parenthesize the product $A_1 A_2 \dots A_n$ such that the total number of scalar multiplications is minimized
- Brute force method of exhaustive search takes time exponential in n



- The structure of an optimal solution
 - Let us use the notation $A_{i..j}$ for the matrix that results from the product $A_i A_{i+1} \dots A_j$
 - An optimal parenthesization of the product $A_1 A_2 \dots A_n$ splits the product between A_k and A_{k+1} for some integer k where $1 \leq k < n$
 - First compute matrices $A_{1..k}$ and $A_{k+1..n}$; then multiply them to get the final matrix $A_{1..n}$

- **Key observation:** parenthesizations of the subchains $A_1A_2...A_k$ and $A_{k+1}A_{k+2}...A_n$ must also be optimal if the parenthesization of the chain $A_1A_2...A_n$ is optimal (why?)
- That is, the optimal solution to the problem contains within it the optimal solution to subproblems



- Recursive definition of the value of an optimal solution
 - Let $m[i, j]$ be the minimum number of scalar multiplications necessary to compute $A_{i..j}$
 - Minimum cost to compute $A_{1..n}$ is $m[1, n]$
 - Suppose the optimal parenthesization of $A_{i..j}$ splits the product between A_k and A_{k+1} for some integer k where $i \leq k < j$

Dynamic Programming Approach ...contd



- $A_{i..j} = (A_i A_{i+1} \dots A_k) \cdot (A_{k+1} A_{k+2} \dots A_j) = A_{i..k} \cdot A_{k+1..j}$
- Cost of computing $A_{i..j}$ = cost of computing $A_{i..k}$ + cost of computing $A_{k+1..j}$ + cost of multiplying $A_{i..k}$ and $A_{k+1..j}$
- Cost of multiplying $A_{i..k}$ and $A_{k+1..j}$ is $p_{i-1} p_k p_j$
- $m[i, j] = m[i, k] + m[k+1, j] + p_{i-1} p_k p_j$ for $i \leq k < j$
- $m[i, i] = 0$ for $i=1, 2, \dots, n$

Dynamic Programming Approach ...contd



- But... optimal parenthesization occurs at one value of k among all possible $i \leq k < j$
- Check all these and select the best one

$$m[i, j] = \begin{cases} 0 & \text{if } i=j \\ \min_{i \leq k < j} \{m[i, k] + m[k+1, j] + p_{i-1} p_k p_j\} & \text{if } i < j \end{cases}$$



- To keep track of how to construct an optimal solution, we use a table s
- $s[i, j]$ = value of k at which $A_i A_{i+1} \dots A_j$ is split for optimal parenthesization
- Algorithm: next slide
 - First computes costs for chains of length $l=1$
 - Then for chains of length $l=2,3, \dots$ and so on
 - Computes the optimal cost bottom-up

Algorithm to Compute Optimal Cost



Input: Array $p[0 \dots n]$ containing matrix dimensions and n

Result: Minimum-cost table m and split table s

MATRIX-CHAIN-ORDER($p[\], n$)

for $i \leftarrow 1$ **to** n

$m[i, i] \leftarrow 0$

for $l \leftarrow 2$ **to** n

for $i \leftarrow 1$ **to** $n-l+1$

$j \leftarrow i+l-1$

$m[i, j] \leftarrow \infty$

for $k \leftarrow i$ **to** $j-1$

$q \leftarrow m[i, k] + m[k+1, j] + p[i-1] p[k] p[j]$

if $q < m[i, j]$

$m[i, j] \leftarrow q$

$s[i, j] \leftarrow k$

return m and s

Takes $O(n^3)$ time

Requires $O(n^2)$ space

Constructing Optimal Solution



- Our algorithm computes the minimum-cost table m and the split table s
- The optimal solution can be constructed from the split table s
 - Each entry $s[i, j] = k$ shows where to split the product $A_i A_{i+1} \dots A_j$ for the minimum cost

Example

- Show how to multiply this matrix chain optimally

- Solution on the board
 - Minimum cost 15,125
 - Optimal parenthesization $((A_1(A_2A_3))((A_4A_5)A_6))$

Matrix	Dimension
A_1	30×35
A_2	35×15
A_3	15×5
A_4	5×10
A_5	10×20
A_6	20×25



Thank You !!!