

Global-e SFCC Metadata

Site PreferenceTable of Contents

- [Site PreferenceTable of Contents](#)
- [Custom Objects](#)
 - [GLOBALE_APP_SETTINGS](#)
 - [GLOBALE_COUNTRIES](#)
 - [GLOBALE_COUNTRY_COEFFICIENTS](#)
 - [GLOBALE_PRODUCT_CLASS_COEFFICIENTS](#)
 - [GLOBALE_CULTURES](#)
 - [GLOBALE_CURRENCIES](#)
 - [GLOBALE_CURRENCY_RATES](#)
 - [GLOBALE_ROUNDING_RULES](#)
 - [GLOBALE_HUB_DETAILS](#)
 - [DEMO_GLOBALE_GIFT_CARDS](#)
 - [DEMO_GLOBALE_LOYALTY_CARDS](#)
 - [GLOBALE_RESTRICTED_ITEMS](#)
 - [GLOBALE_ORDER_NOTIFICATION](#)
 - [GLOBALE_INVENTORY_NOTIFICATION](#)
- [System Objects](#)
 - [Product](#)
 - [Site Preferences](#)
 - [Organization Preferences](#)
 - [Promotion](#)
 - [Price Adjustment](#)
 - [Basket](#)
 - [Order](#)
 - [Order Address](#)
 - [Customer Address](#)
 - [Product Line Item](#)
 - [Shipping Method](#)
 - [Price book](#)
 - [Payment Transaction](#)
 - [Gift Certificate](#)
 - [Gift Certificate Line Item](#)
 - [Organization Preferences](#)
 - [Profile](#)
- [Shipping Methods](#)
- [Payment Method](#)
- [Services](#)
- [Scheduled Jobs](#)

Custom Objects

Global-e cartridge uses the following Custom Objects, which needs to be imported once on the Salesforce B2C Commerce Digital (can be found in the metadata folder as globale.custom.xml file).

For all Global-e Custom Objects: Data Replication: Not Replicable. Storage Scope: Site.

GLOBALE_APP_SETTINGS

Used to hold cached data from Global-e API /Browsing/AppSettings and /Browsing/AppVersion.

SFCC Attribute ID	SFCC Key Attribute	Type	SFCC Attribute Name	Global-e API Attribute ID	Description
name	Yes	String	Name	-	Name of App Setting on Global-e side
apiVersion	No	String	APIVersion	APIVersion	Version identifier of Global-e API
clientSettings	No	Text	ClientSettings	ClientSettings	Dictionary of client-side settings
serverSettings	No	Text	ServerSettings	ServerSettings	Dictionary of server-side settings
webClientVersion	No	String	WebClientVersion	WebClientVersion	Version identifier of Global-e client-side (JS) code
sfccSendCartSendHubId	No	String	Send HubId in SendCart	sfccUseGEShippingPrice	Send HubId in SendCart Payload
sfccUseGEShippingPrice	No	String	Use Global-e Shipping Price (B2B)	sfccUseGEShippingPrice	Use Global-e Shipping Price (B2B)
sfccWhitelistedServerIps	No	String	Whitelisted Global-e Server IP's	sfccWhitelistedServerIps	A list of IP addresses of Global-e servers separated by a semicolon (;) that should be whitelisted.
sfccLanguagesConfiguration	No	Text	Languages Switcher Configuration	sfccLanguagesConfiguration	Language Switcher Configuration
sfccCartHashValidation	No	Text	SFCC Cart Hash Validation	sfccCartHashValidation	Enable SFCC Cart Hash Validation
sfccPlaceOrderOnPaymentUpdate	No	String	Place Order On Payment Update	sfccPlaceOrderOnPaymentUpdate	The preference allows turn on/off the placing of SFCC order when is seng Global-e PaymentUpdate request. If the preference is set to false then order is placed during SOTM request(when are updated order attributes). If the preference is set to 'false' the order is placed during PaymentUpdate request(when

					is changed order payment and export statuses).
sfccUseFixedPricesOnly	No	String	Use Only Fixed Prices	sfccUseFixedPricesOnly	The preference is used only for fixed price countries. It specifies that for fixed price countries should be used the prices only from fixed price books .
sfccCreateNewAddressesFromCheckout	No	String	Save GE Address	sfccCreateNewAddressesFromCheckout	Allows to create and save new addresses from GE checkout
sfccCultureMapping	No	Text	Culture Mapping	sfccCultureMapping	The preference allows to override default culture code for Global-e popups/templates. Culture code is used for setting right language.
sfccCheckoutCultureMapping	No	Text	Checkout Culture Mapping	sfccCheckoutCultureMapping	The preference allows to override default culture code for Global-e checkout templates. Culture code is used for setting right language.
sfccDynamicCountryCurrencyMapping	No	Text	Dynamic Country/Currency Mapping	sfccDynamicCountryCurrencyMapping	The preference allows to override default currency code for dynamic price countries
sfccAllowedCurrencies	No	Text	Allowed country currencies	sfccAllowedCurrencies	Allowed country currencies (price book caching approach)
sfccShippingSwitcherConfiguration	No	Text	Shipping Switcher Configuration	sfccShippingSwitcherConfiguration	Shipping Switcher Configuration
sfccDefaultCountryCodeMapping	No	Text	Default Country Code Mapping	sfccDefaultCountryCodeMapping	Default Country Code Mapping
sfccMerchantBaseCurrencyCode	No	String	Merchant Base Currency Code	sfccMerchantBaseCurrencyCode	Merchant Base Currency Code(Site default currency is used if empty)
sfccCachePriceBooksConfig	No	Text	Cache Price Books Configuration	sfccCachePriceBooksConfig	Cache Price Books Configuration
sfccParseCountryCodeFromRequestLocale	No	String	Parse CountryCode from RequestLocale	sfccParseCountryCodeFromRequestLocale	Use SFCC locale country code to define shipping country
sfccJWTAuthConfiguration	No	Text	JWT Authentication Configuration	sfccJWTAuthConfiguration	JWT Authentication Configuration (GE to SFCC)
sfccJWTApiAuthConfiguration	No	Text	JWT API Authentication Configuration	sfccJWTApiAuthConfiguration	JWT API Authentication Configuration (SFCC to GE)
sfccLocalizationConfiguration	No	Text	SendCartV2 Localization Configuration	sfccLocalizationConfiguration	Allows to configure localized product data (SendCartV2 API).

sfccUseProductCodeSecondaryInFulfillmentEnabled	No	String	SFCC Use ProductCodeSecondary In Fulfillment Enabled	sfccUseProductCodeSecondaryInFulfillmentEnabled	Allows to use ProductCodeSecondary In Fulfillment instead of ProductCode
sfccKlarnaConfigurations	No	Text	SFCC Klarna Configurations	sfccKlarnaConfigurations	SFCC Klarna OSM Configurations
sfccDoWebStoreValidation	No	String	Do WebStore Validation	sfccDoWebStoreValidation	Do WebStore Validation
sfccPayByLinkConfigurations	No	Text	Pay By Link Configurations	sfccPayByLinkConfigurations	Pay By Link Configurations
sfccReconciliationCurrency	No	Text	Reconciliation Currency	sfccReconciliationCurrency	Uses if a merchant has more than 1 reconciliation currency

GLOBALE_COUNTRIES

Used to hold cached data from Global-e API /Browsing/Countries.

SFCC Attribute ID	SFC C Key Attribute	Type	SFCC Attribute Name	Global-e API Attribute ID	Description
code	Yes	String	Code	Code	2-char ISO country code
defaultCurrencyCode	No	String	DefaultCurrencyCode	DefaultCurrencyCode	3-char ISO currency code
isStateMandatory	No	Boolean	IsStateMandatory	IsStateMandatory	TRUE if State or province (region) is mandatory for addresses in this country
isOperatedByGlobalE	No	Boolean	IsOperatedByGlobalE	IsOperatedByGlobalE	TRUE if Country is operated by Global-e. Countries that are not operated by Global-e can still be available for selection as a shipping destination on the merchant's site. However Global-e functionality must be disabled for such countries
name	No	String	Name	Name	Country name
siteUrl	No	String	SiteURL	SiteURL	URL of a country-specific site owned by the merchant. Used to allow redirection to the merchant's country-specific domain for a selected country. Can be either a static URL, like "https://merchantsite.com" or a special format to be parsed on SFCC backend, like "en_US SiteGenesis merchantsite.com param1 value1".
useCountryVAT	No	Boolean	UseCountryVAT	UseCountryVAT	TRUE if VAT rate specific to this shipping country must be applied to the product prices. Otherwise, VAT rates defined for the products on the merchant's site must be used. This setting is used to support trade agreements between the countries

					such as EEA, when end customer must pay VAT for the shipping country in certain cases
defaultVATRateType	No	String	DefaultVATRateType	DefaultVATRateType	Default (most widely used) VAT rate type or class for this country
supportsFixedPrices	No	Boolean	SupportsFixedPrices	SupportsFixedPrices	TRUE if fixed product prices are allowed for this country. Product prices may be fixed only in the Default Currency for this Country
vatExemptionDisabled	No	Boolean	VATExemptionDisabled	VATExemptionDisabled	Used in order to identify, if no VAT case is supported

GLOBALE_COUNTRY_COEFFICIENTS

Used to hold cached data from Global-e API /Browsing/CountryCoefficients.

SFCC Attribute ID	SFCC Key Attribute	Type	SFCC Attribute Name	Global-e API Attribute ID	Description
countryCode	Yes	String	CountryCode	CountryCode	2-char ISO country code
includeVAT	No	Integer	IncludeVAT	IncludeVAT	This attribute is applicable only to Country level (i.e. not applicable to ProductClass level). One of the possible values of IncludeVATOptions enumeration designated to control the way VAT is handled in browsing on the Merchant's site and in checkout on Global-e
rate	No	Double	Rate	Rate	Country Coefficient rate decimal value. All the prices displayed to the end customer shipping to the country involved must be multiplied by this value

GLOBALE_PRODUCT_CLASS_COEFFICIENTS

Used to hold cached data from Global-e API /Browsing/CountryCoefficients.

SFCC Attribute ID	SFCC Key Attribute	Type	SFCC Attribute Name	Global-e API Attribute ID	Description
key	Yes	String	Key	ProductClassCode + '-' + Country Code	The unique key value for the instance

rate	No	Double	Rate	Rate	Country Coefficient rate decimal value. All the prices displayed to the end customer shipping to the country involved must be multiplied by this value
country Code	No	String	Country Code	CountryCode	2-char ISO country code
product ClassCode	No	String	Product ClassCode	ProductClassCode	Product class code used by the merchant to classify products for using different country coefficient rates per classes of products instead of the single country level default (when no rate is defined for a certain product class, the country level default rate should be used by the merchant for the respective product)

GLOBALE_CULTURES

Used to hold cached data from Global-e API /Browsing/LocationsDefaultCulturesList.

SFCC Attribute ID	SFCC Key Attribute	Type	SFCC Attribute Name	Global-e API Attribute ID	Description
code	Yes	String	Country code	CountryCode	2-char ISO country code
regionCode	No	String	Region Code	RegionCode	Region code (unique in the respective Country)
cityCode	No	String	City Code	CityCode	City code (unique in the respective Region)
isRTL	No	Boolean	IsRTL	Culture.IsRTL	TRUE for "right-to-left" languages such as Hebrew and Arabic
localizedName	No	String	Localized Name	Culture.LocalizedName	Culture name in the respective language, such as "עברית" for he-IL (Hebrew-Israel) culture
name	No	String	Name	Culture.Name	Culture name
culture	No	String	Culture Code	Culture.Code	ISO culture code

GLOBALE_CURRENCIES

Used to hold cached data from Global-e API /Browsing/Currencies.

SFCC Attribute ID	SFCC Key Attribute	Type	SFCC Attribute Name	Global-e API Attribute ID	Description
code	Yes	String	Code	Code	3-char ISO currency code

maxDecimalPlaces	No	Integer	MaxDecimalPlaces	MaxDecimalPlaces	Number of decimal places indicating the fractional ("cents") part of the price. For example Bahraini Dinar "cents" has 3 decimal places, US Dollar has 2, and Japanese Yen has 0
name	No	String	Name	Name	Currency name
symbol	No	String	Symbol	Symbol	Currency symbol (e.g. \$ for USD)

GLOBALE_CURRENCY_RATES

Used to hold cached data from Global-e API /Browsing/CurrencyRates.

SFCC Attribute ID	SFCC Key Attribute	Type	SFCC Attribute Name	Global-e API Attribute ID	Description
key	Yes	String	Key	SourceCurrencyCode + '_' + TargetCurrencyCode	The unique key value for the instance
rate	No	String	Rate	Rate	Currency rate decimal value
sourceCurrencyCode	No	String	SourceCurrencyCode	SourceCurrencyCode	3-char ISO currency cod
targetCurrencyCode	No	String	TargetCurrencyCode	TargetCurrencyCode	3-char ISO currency code
rateData	No	String	Rate Data	RateData	Currency data used by global-e to verify the rate

GLOBALE_ROUNDING_RULES

Used to hold cached data from Global-e API /Browsing/RoundingRules.

SFCC Attribute ID	SFCC Key Attribute	Type	SFCC Attribute Name	Global-e API Attribute ID	Description
key	Yes	String	Key	CurrencyCode [+ '_' + CountryCode]	The unique key value for the instance
countryCode	No	String	Country Code	CurrencyCode	2-char ISO country code
currencyCode	No	String	CurrencyCode	CurrencyCode	3-char ISO currency code

roundingRanges	No	Text	RoundingRanges	RoundingRanges	List of decimal ranges and their respective rounding behaviors
roundingRuleId	No	String	RoundingRuleId	RoundingRuleId	Rule identifier denoting the respective Rounding Rule on Global-e side. This value must be further specified when calling SaveProductsList and SendCart methods

GLOBALE_HUB_DETAILS

Used to hold cached data from Global-e API /Browsing/ActiveHubDetails.

SFCC Attribute ID	SFCC Key Attribute	Type	SFCC Attribute Name	Global-e API Attribute ID	Description
key	Yes	String	Key	-	The unique key value for the instance
address1	No	String	Address1	Address1	Address line 1
address2	No	String	Address2	Address2	Address line 2
city	No	String	City	City	City name
countryCode	No	String	CountryCode	CountryCode	2-char ISO country code
countryName	No	String	CountryName	CountryName	Country name
email	No	String	Email	Email	E-mail address
fax	No	String	Fax	Fax	Fax
hubID	No	Integer	HubID	HubId	Hub identifier on Global-e system
hubName	No	String	HubName	HubName	Name of the Hub
phone1	No	String	Phone1	Phone1	Phone #1
phone2	No	String	Phone2	Phone2	Phone #2
stateCode	No	String	StateCode	StateCode	State or province ISO code such as AZ for Arizona (if applicable)

stateOrProvince	No	String	StateOrProvince	StateOrProvince	State or province name
zip	No	String	Zip	Zip	Zip or postal code

DEMO_GLOBALE_GIFT_CARDS

Used for demo implementation of the 'Gift Cards' feature

SFCC Attribute ID	SFC C Key Attribute	Type	SFCC Attribute Name	Description
cardID	Yes	String	Card ID	Card ID(card number)
currentBalance	No	Integer	Current Balance	Current balance of the card
initialBalance	No	Integer	Initial Balance	Initial balance of the card
originalCurrencyCode	No	String	Currency Code	Currency code of the card
redeemRequestJSON	No	Text	Redeem Request JSON	Used as a storage and contains information about redeem requests(between Global-e and SFCC) of the card
redeemResponseJSON	No	Text	Redeem Response JSON	Used as a storage and contains information about redeem responses(between Global-e and SFCC) of the card
refundRequestJSON	No	Text	Refund Request JSON	Used as a storage and contains information about refund requests(between Global-e and SFCC) of the card
refundResponseJSON	No	Text	Refund Response JSON	Used as a storage and contains information about refund responses(between Global-e and SFCC) of the card

DEMO_GLOBALE_LOYALTY_CARDS

Used for demo implementation of the 'Loyalty Cards' feature

SFCC Attribute ID	SFC C Key Attribute	Type	SFCC Attribute Name	Description
cardID	Yes	String	Card ID	Card ID(card number)

currentBalance	No	Integer	Current Balance	Current balance of the card
initialBalance	No	Integer	Initial Balance	Initial balance of the card
originalCurrencyCode	No	String	Currency Code	Currency code of the card
redeemRequestJSON	No	Text	Redeem Request JSON	Used as a storage and contains information about redeem requests(between Global-e and SFCC) of the card
redeemResponseJSON	No	Text	Redeem Response JSON	Used as a storage and contains information about redeem responses(between Global-e and SFCC) of the card
refundRequestJSON	No	Text	Refund Request JSON	Used as a storage and contains information about refund requests(between Global-e and SFCC) of the card
refundResponseJSON	No	Text	Refund Response JSON	Used as a storage and contains information about refund responses(between Global-e and SFCC) of the card

GLOBALE_RESTRICTED_ITEMS

Used for SFCC job 'GlobleRestrictedItemsFeed'. More details are described here: [Global-e_SFCC_Cartridge_GlobleRestrictedItemsFeed](#)

SFCC Attribute ID	SFC C Key Attribute	Type	SFCC Attribute Name	Description
name	Yes	String	name	Name of entity which is used restrictions. There are possible values: 'brands', 'categories', 'products'
countriesExclusions	No	Text	Countries Exclusions	Used for storing Countries Exclusions of entities: 'brands', 'categories'
sourceHandler	No	Text	Source Handler	Used as source handler for extracting the current values products restrictions

GLOBALE_ORDER_NOTIFICATION

Used for GE->SFCC and SFCC->GE notifications.

The Custom Object Retention is 7 days.

SFCC Attribute ID	SFCC Key Attribute	Type	SFCC Attribute Name	Description
ID	Yes	string	ID	Notification ID
geOrderId	No	string	Order Id	SFCC or Global-e order ID

geNotificationType	No	enum-of-string	Notification Type	Possible values are: OrderStatusUpdate, OrderDispatchUpdate, OrderRefundUpdate, OrderRMAUpdate, OrderRMACreate
geNotificationPayload	No	Text	Notification Payload	The notification payload (JSON stringified object)

GLOBALE_INVENTORY_NOTIFICATION

The custom objects are used for storing inventory update notifications.

The Custom Object Retention is 7 days.

SFCC Attribute ID	SFCC Key Attribute	Type	SFCC Attribute Name	Description
ID	Yes	string	ID	Notification ID
geOrderId	No	string	Order Id	SFCC or Global-e order ID
geNotificationType	No	enum-of-string	Notification Type	Possible values are: VoidReservation
geNotificationPayload	No	Text	Notification Payload	The notification payload (JSON stringified object)

System Objects

Product

Used for demo implementation of the 'Loyalty Cards' feature

ID	Type	Name	Attributes Group Name	Description
geCountriesExclusions	string	Countries Exclusions	not assigned	Specifies the list of countries codes for which the product is restricted(blocked)
gelsForbidden	boolean	Global-e Is Forbidden	Global-e Attributes	Specifies that the product is globally forbidden(for all countries) for selling
geRestrictedCountries	string	Global-e RestrictedCountries	Global-e Attributes	Specifies the list of Global-e Restricted Countries for the product. Contains the list of countries codes. Example value: AU,UA,IT
geVatRates	text	Global-e Vat Rates	Global-e Attributes	Specifies the list of Global-e Vat Rates for the product in json format. JSON format provides different vat rates depends on country code. Example value: {'AU': {}, 'UA': {}}
gelsGiftCard	boolean	Is Globale Gift Card	Global-e Attributes	Specifies that the product is selling as 'gift card' product

Site Preferences

ID	Type	Name	Preference Group Name	Description		Default Value
				Purpose	Configuration	
geEnabled	boolean	Global-e Enabled	Global-e Settings	The preference allows turn on/off Global-e integration	- No (false) - Yes (true)	No (false)
geCookieLifetime	int	Cookie lifetime	not assigned	The preference specifies the lifetime of the 'GlobalE_Data' - main Global-e cookie(in seconds) default is one week(7 days).	By default is not required any configuration. The default value should not be changed without good reason.	604 800
geCookieDomain	text	Cookie domain	not assigned	The preference specifies the domain for which the Global-e cookies are registered in browser.	Not required any configuration. By default is taken 'httpHost' from SFCC Request	-

					(class: dw.system.Request). Exceptions: If for different locales of one site are used different domains then can be added configuration which will handle this case. The configuration example: <pre> 1 { 2 "defaultDomain": "www.example.com", 3 "en_GB": "www.example.uk" 4 }</pre>	
geClientJsMerchantId	int	Client JS Merchant ID	Global-e Settings	The preference specifies the Global-e Merchant ID. The Global-e Merchant ID is used to load Global-e Client SDK.	Must be set Global-e Merchant ID (which is provided by the Global-e team to the Merchant team)	-
geClientJsBaseUrl	enum-of-string	Global-e Client JS SDK Base URL	Global-e Settings	The preference specifies the Base URL for Global-e Client SDK. The Global-e Base URL is used to load Global-e Client SDK.	- Global-e Staging (https://www2.bgl-obale.com) Must be selected on SFCC sandboxes/Development/Staging instances - Global-e Production (https://web.global-e.com) Must be selected on SFCC Production instance	Global-e Staging (https://www2.bglobal-e.com)
geClientJsSource	string	Client JS SDK Source	Global-e Settings	The preference specifies the Source of Global-e Client JS SDK.	By default is not required any configuration. The default value	/scripts/merchants/global-e.merchant.client.js

		(/SOURCE)		The Global-e Source is used to load Global-e Client SDK.	should not be changed without good reason.	
geMerchantGuid	string	Merchant GUID	Global-e Settings	The preference specifies the Global-e Merchant GUID. The Global-e Merchant GUID is used for validation requests: - from Global-e to SFCC (SOTM, PaymentUpdate, etc.) - from SFCC to Global-e (service calls which are sent to Global-e)	Must be set Global-e Merchant GUID (which is provided by the Global-e team to the Merchant team)	-
geApiUrl	enum-of-string	Global-e API URL	Global-e Settings	The preference specifies the Global-e API URL. The Global-e API URL is used for generating SFCC service URL when is sent a request from SFCC to Global-e.	- Global-e Staging (https://connect2.bglobale.com) Must be selected on SFCC sandboxes/Development/Staging instances - Global-e Production (https://api.global-e.com) Must be selected on SFCC Production instance	Global-e Staging (https://connect2.bglobale.com)
geDefaultShippingMethod	string	Global-e Default Shipping Method ID	Global-e Settings	The preference specifies Default Shipping Method ID for operated by Global-e countries. This shipping method is selected and assigned to shipment by default.	By default is not required any configuration. The default value should not be changed without good reason.	GLOBALE
geEnableStockReservation	boolean	Enable Stock	Global-e Settings	The preference allows turn on/off reservation of basket inventory	- No (false) - Yes (true)	No (false)

		Reserv ation		before Global-e checkout is displayed (before Send Cart request)		
geStockReservationTime	int	Stock reservat ion time	Global- e Settings	The preference specifies the amount of time in minutes for stock to be reserved in Global-e checkout	By default is not required any configuration. The default value should not be changed without good reason.	30
geEnableCartValidationCAPIBasket	boolean	Enable CartVali dation SFCC CAPI	Global- e Settings	Enable CartValidation SFCC CAPI (SCAPI/OCAPI) basket	- No (false) - Yes (true)	No (false)
geEnableCartValidationErrors	boolean	Enable CartVali dation Errors	Global- e Settings	Enables CartValidation Error popup (in case of non-expected error)	- No (false) - Yes (true)	No (false)
geAddNotes	boolean	Add Global- e Notes	Global- e Settings	The preference allows turn on/off adding of Notes to SFCC Order when are processed any requests to/from Global-e that are related to the order.	- No (false) - Yes (true)	Yes (true)
geCatalogFeedConfig	text	Global- e Catalog Feed Config	Global- e Catalog Jobs	The preference specifies Global-e Catalog Feed configuration.	More details are described here: Global- e_SFCC_Cartridge_ GlobaleCatalogFeed .pdf	-
geCatalogFeedLastRun	datetime	Global- e Catalog Feed last run	not assigne d	This preference contains information about last time run of Global-e Catalog Feed.	Not required any configuration.	-
geCatalogFeedStartPosition	number	Catalog Feed Start Position	not assigne d	This preference specifies of products iterator start position for Global-e Catalog Feed.	By default is used 0.	
geRestrictedItemsFeedConfig	text	Restrict ed Items Feed	Global- e Catalog Jobs	The preference specifies Global-e Restricted Items Feed configuration.	More details are described here: Global- e_SFCC_Cartridge_	-

		Configuration			Global-e Restricted Items Feed	
geRestrictedItemsFeedLastRun	datetime	Restricted Items Last Run	not assigned	This preference contains information about last time run of Global-e Restricted Items Feed.	Not required any configuration.	-
geProductClassCodePropName	string	Product Class Code Custom Property Name	Global-e Product Settings	The preference specifies the product custom attribute that is used to check against ProductClassCode for coefficient rate. Product class code used by the merchant to classify products for using different country coefficient rates per classes of products instead of the single country level default (when no rate is defined for a certain product class, the country level default rate should be used by the merchant for the respective product).	By default is not required any configuration. If is needed to use product class code for calculation of coefficient rate then should be set product attribute in format - custom[attribute id] For example: custom.geProductClassCode	-
geProductGroupCodePropName	string	Product Group Code Property Name	Global-e Product Settings	The preference specifies the product custom attribute that is used for setting ProductGroupCode(in SendCart request) if exists (optional). Product's group code on the Merchant's site (to be mapped on Global-e side). Usually this value is a part of product SKU code denoting a group of similar products (such as "the same product in different colors").	By default is not required any configuration. If is needed to use the attribute then should be set product attribute in format - custom[attribute id] For example: custom.geProductGroupCode	-

geProductCodeSecondaryPattern	string	Product Code Secondary Pattern	Global-Product Settings	The preference specifies the product custom attribute that is used for setting ProductCodeSecondary(in SendCart request) if exists (optional). Secondary code that may be used to refer to the product on the Merchant's site. This code may be used in addition to the ProductCode and is not guaranteed to be unique (may be reused for other products as long as the old product is not available on the merchant's site anymore).	By default is not required any configuration. If is needed to use the attribute then should be set product attribute in format - custom[attribute id] For example: custom.geProductCodeSecondary	-
geProductGroupCodeSecondaryPattern	string	Product Group Code Secondary Pattern	Global-Product Settings	The preference specifies the product custom attribute that is used for setting ProductGroupCodeSecondary(in SendCart request) if exists (optional). Secondary code that may be used to refer to the group of products on the Merchant's site. This code may be used in addition to the ProductGroupCode and is not guaranteed to be unique (may be reused for other groups as long as the old group is not available on the merchant's site anymore).	By default is not required any configuration. If is needed to use the attribute then should be set product attribute in format - custom[attribute id] For example: custom.geProductGroupCodeSecondary	-
geWeightAttributeKey	string	Weight attribute key	Global-Product Settings	The preference specifies the product custom attribute that is used for setting product's weight(in SendCart request) if exists (optional).	By default is not required any configuration. If is needed to use the attribute then should be set product attribute in	-

				Product's weight in Merchant's default unit of weight measure (will be converted to grams). Merchant's default product weight will be used if not specified.	format - custom[attribute id] For example: custom.geWeight	
geHeightAttributeKey	string	Height attribute key	Global-e Product Settings	The preference specifies the product custom attribute that is used for setting product's height(in SendCart request) if exists (optional). Product's height in Merchant's default unit of length measure (will be converted to CM).	By default is not required any configuration. If is needed to use the attribute then should be set product attribute in format - custom[attribute id] For example: custom.geHeight	-
geWidthAttributeKey	string	Width attribute key	Global-e Product Settings	The preference specifies the product custom attribute that is used for setting product's width(in SendCart request) if exists (optional). Product's width in Merchant's default unit of length measure (will be converted to CM).	By default is not required any configuration. If is needed to use the attribute then should be set product attribute in format - custom[attribute id] For example: custom.geWidth	-
geLengthAttributeKey	string	Length attribute key	Global-e Product Settings	The preference specifies the product custom attribute that is used for setting product's length(in SendCart request) if exists (optional). Product's length in Merchant's default unit of length measure (will be converted to CM).	By default is not required any configuration. If is needed to use the attribute then should be set product attribute in format - custom[attribute id] For example: custom.geLength	-
geVolumeAttributeKey	string	Volume attribute key	Global-e Product Settings	The preference specifies the product custom attribute that is used for setting product's volume(in SendCart request) if exists (optional).	By default is not required any configuration. If is needed to use the attribute then should be set product attribute in format -	-

				Alternative for specifying all 3 dimensions above(height, width, length). Product's volume in Merchant's default unit of volume measure (will be converted to cubic CM).	custom[attribute id] For example: custom.geVolume	
geProductImageViewType	string	Product Image ViewType	Global-e Product Settings	The preference specifies the ViewType of the product's image that will be sent to Global-e(in SendCart request) and used on Global-e page (checkout, confirmation page, emails, etc.)	By default is not required any configuration. The default value should not be changed without good reason.	large
geResetCurrencyCodeOnCountryChange	boolean	Reset Global-e Currency Code on Country change	Global-e Settings	The preference allows turn on/off resetting currency code on Country change. The preference is used only for dynamic price countries and allows to reset currency code to the country's default value for every SFCC request.	- No (false) - Yes (true)	No (false)
geSearchableProductsPromotionId	string	Searchable Products Promotion ID	Global-e Settings	The preference specifies the SFCC Promotion ID that is used filter out the restricted / forbidden products on CLP/PLP or any other search result page. More details are described here: Global-e_SFCC_Cartridge_Restricted_Forbidden_Products.pdf	By default is not required any configuration. If is used SFCC Promotion for hiding some products then should be set SFCC Promotion ID. For example: GLOBALE-RESTRICTED-PRODUCTS	-
geLoyaltyPromotionSpentPointsFactor	double	Global-e Loyalty Promotion Spent	not assigned	The preference specifies Global-e Loyalty Promotion Spent Points Factor. Can be any Number like 0.001, 0.01, 0.1, 1, 10, 100, 1000, etc.	By default is not required any configuration.	-

		Points Factor		For example: 100, which means each really spent dollar will be represented on Global-e Checkout page as 100 Global-e Loyalty points.		
geLoyaltyPromotionEarnedPointsFactor	double	Global-e Loyalty Promotion Earned Points Factor	not assigned	The preference specifies Global-e Loyalty Promotion Earned Points Factor. Can be any Number like 0.001, 0.01, 0.1, 1, 10, 100, 1000, etc. For example: 100, which means each really earned dollar will be represented on Global-e Checkout page as 100 Global-e Loyalty points.	By default is not required any configuration.	-
geReturnPortalUrl	enum-of-string	Return Portal URL	Global-e Settings	The preference specifies the URL for Global-e return portal. Out of the box the value of this preference is not used in code. If project requires to use Return Portal URL then development team can use the preference and implement custom logic according to requirements.	- Global-e Staging (Returns/Portal/{returnPortalId}?OrderID={orderNo}&Email={email}">https://www2.bgl-obale.com>Returns/Portal/{returnPortalId}?OrderID={orderNo}&Email={email}) Must be selected on SFCC sandboxes/Development/Staging instances - Global-e Production (https://web.global-e.com/Returns/Portal/{returnPortalId}?OrderID={orderNo}&Email={email}) Must be selected on SFCC Production instance	Global-e Staging (Returns/Portal/{returnPortalId}?OrderID={orderNo}&Email={email}">https://www2.bgl-obale.com>Returns/Portal/{returnPortalId}?OrderID={orderNo}&Email={email})

geCustomObjectsCacheSettings	text	Custom Object's cache settings	not assigned	The preference specifies the SFCC Custom Cache settings for cached entities.	By default is not required any configuration and are used next settings: <pre>1 { 2 "countries" 3 : 86400, 4 "appSettings": 86400, 5 "hubDetails" 6 : 86400, 7 "countryCoefficients": 8 86400, 9 "productClassCoefficients": 10 86400, 11 "cultures": 12 86400, 13 "currencies" 14 : 86400, 15 "currencyRates": 16 86400, 17 "roundingRules": 18 86400, 19 "fixedPriceBooks": 60, 20 "priceDisplayFormat": 21 60 22 }</pre> where is: 'countries' - ID of entity 86400 - cache time in seconds If is needed to change cache time then should be added configuration	-
------------------------------	------	--------------------------------	--------------	--	--	---

					according to format above	
geCAPIType	enum-of-string	Used SFCC CAPI Type	Global-e Settings	The preference determines the SFCC CAPI (SCAPI/OCAPI) used with the Global-e integration	- OCAPI (OCAPI) - SCAPI (SCAPI)	OCAPI (OCAPI)
geOCAPIDomain	string	OCAPI Domain	Global-e OCAPI Settings	The preference specifies OCAPI domain and is used for Global-e features that work with SFCC OCAPI	By default is not required any configuration.	-
geOCAPIVersion	string	OCAPI Version	Global-e OCAPI Settings	The preference specifies OCAPI Version and is used for Global-e features that work with SFCC OCAPI	Must be set SFCC OCAPI Version	-
geOCAPIClientId	password	OCAPI ClientId	Global-e OCAPI Settings	The preference specifies OCAPI Client Id and is used for Global-e features that work with SFCC OCAPI	Must be set SFCC OCAPI Client Id	-
geSCAPIOrganizationId	string	SCAPI Organization Id	Global-e SCAPI Settings	The preference specifies SCAPI Organization Id and is used for Global-e features that work with SFCC SCAPI	By default is not required any configuration.	-
geSCAPIShortCode	string	SCAPI Short Code	Global-e SCAPI Settings	The preference specifies SCAPI Short Code and is used for Global-e features that work with SFCC SCAPI	By default is not required any configuration.	-
geSCAPIVersion	string	SCAPI Version	Global-e SCAPI Settings	The preference specifies SCAPI Version and is used for Global-e features that work with SFCC SCAPI	By default is not required any configuration.	-
geSCAPIRedirectURI	string	SCAPI Redirect URI	Global-e SCAPI Settings	The preference specifies SCAPI Redirect URI and is used for Global-e features that work with SFCC SCAPI	By default is not required any configuration.	-
geSCAPIAuthType	enum-of-string	SCAPI Authority	Global-e	The preference specifies SCAPI Auth Type and is used for	By default is not required any configuration.	-

		zation Type	SCAPI Settings	Global-e features that work with SFCC SCAPI	• Public Client (PublicClient) • Private Client (PrivateClient)	
geSCAPIClientId	passw ord	SCAPI ClientId	Global- e SCAPI Settings	The preference specifies SCAPI Client Id and is used for Global-e features that work with SFCC SCAPI	By default is not required any configuration.	-
geSCAPIClientSecret	passw ord	SCAPI ClientS ecret	Global- e SCAPI Settings	The preference specifies SCAPI Client Secret and is used for Global-e features that work with SFCC SCAPI	By default is not required any configuration.	-
geRSAPublicKey	text	RSA Public Key	Global- e Crypto Settings	The preference specifies RSA Public Key and is used to Global-e features that work with RSA encryption/decryption	By default is not required any configuration.	-
geRSAPrivateKey	text	RSA Private Key	Global- e Crypto Settings	The preference specifies RSA Private Key and is used to Global-e features that work with RSA encryption/decryption	By default is not required any configuration.	-
geAESPrivateKey	text	AES Private Key	Global- e Crypto Settings	The preference specifies AES Private Key and is used to Global-e features that work with AES encryption/decryption	By default is not required any configuration.	-

Organization Preferences

geMetadataCustomAttributes	set-of-string	Meta Data Custom Attributes	Global-e Product Settings	The preference specifies attributes of product line items or product that should be set in the 'metadata' array(which is sent in SendCart request). For example: if is needed to add one more product custom attribute for displaying on Global-e checkout.	Format of configuration: - attrID - or - metadataAttrKey: attrID Example of configuration: - custom.productVolume - or	-
----------------------------	---------------	-----------------------------	---------------------------	---	---	---

Promotion

ID	Type	Name	Description	Default Value
geLanguagesConfiguration	text	Global-e Languages Selector Configuration	product's variation attributes) The preference specifies the configuration of language selector in Global-e Country	-
geTaxJurisdictionId		string	Tax Jurisdiction ID Global-e Settings Switcher More details are here: Global-e_SFCC_Country_Switcher.pdf	By default is not required any configuration.
geEnableNativeGiftCertificates	boolean	Enable Native SFCC Gift Certific	Global-e Settings Enables Creating And Using Native SFCC Gift Certificates	- No (false) - Yes (true)
ID	Type	Name	Description	Default Value
geUseCustomProductDiscountType	enum-of-string	Inventory Lists boolean Promotion Discount Type	Use Custom Product Inventory Lists Please help Global-e to identify product inventory properly. It helps to calculate Promotional Price properly on Storefront.	- No (false) - Yes (true)
geWebStoreUUID geDoNotConvert	boolean	string Do not Convert Promotional Discount	Global-e not assign UUID For example: "get -10 off" - will do -10 off on end-customer Price. Applicable only for the following	-
			Promotion Discount Types: AMOUNT, FIXED_PRICE, PRICE_BOOK_PRICE, TOTAL_FIXED_PRICE.	
geFreeShippingMethod	enum-of-string	Global-e Free Shipping Method	Allows Global-e to identify the Free Shipping Method in the checkout.	-
geLoyaltyPromotion	boolean	Global-e Loyalty Promotion	If it is Global-e Loyalty Promotion - then Global-e cartridge will treat this Promotion as special promotion in SendCart API.	-

geDiscountPrice	double	Discount Price	Applicable only for the following Promotion Discount Types: AMOUNT	
-----------------	--------	----------------	---	--

Price Adjustment

ID	Type	Name	Description
geName	string	Discount Name	Discount textual description
geDescription	string	Discount Description	Discount Description
gePrice	double	Price	Discount value in currency defined in CurrencyCode property of the respective Merchant.Order object for the order being submitted to the Merchant.
geVatRate	double	VAT Rate	VAT rate applied to this discount
geLocalVatRate	double	Local VAT Rate	VAT rate that would be applied to this discount if the order was placed by the local customer. This value must be specified if UseCountryVAT for the current Country is TRUE and therefore VATRate property actually denotes the VAT for the target country.
geInternationalPrice	double	International Price	Discount value in end customer's currency (specified in InternationalDetails.CurrencyCode property for the respective Merchant.Order), after applying country coefficient, FX conversion and IncludeVAT handling.
geCouponCode	string	Coupon Code	Merchant's coupon code used for this discount (applicable to coupon-based discounts only)
geDiscountCode	string	Discount Code	Discount code originally specified in Discount.DiscountCode property of the respective discount in SendCart method for the cart converted to this order on Global-e.
geLoyaltyVoucherCode	string	Loyalty Voucher Code	Loyalty Voucher code originally specified in Discount.LoyaltyVoucherCode property of the respective discount in SendCart method for the cart converted to this order on Global-e.
geDiscountType	int	Discount Type	Discount type ("Cart", "Shipping", etc.), as defined in DiscountTypeOptions enumeration described in Discount class in this document.
geOriginalPriceAdjustmentPrice	double	Original Price Adjustment Price	Original Price Adjustment Price

Basket

ID	Type	Name	Description
----	------	------	-------------

geCartToken	string	Global-e Cart Token	The token exchanged within the SendCart API call to display the Global-e checkout iframe.
geCartId	string	Cart ID	Identifier of the cart on the Merchant's site originally specified in geMerchantCartToken argument for SendCart method for the cart converted to this order on Global-e.
geMerchantOrderId	string	Global-e Merchant Order ID	Reserved SFCC merchant order ID.
gelsOrderCreatedFallbackScenario	boolean	Is Order Created Fallback Scenario	SFCC order is created from a fallback scenario(when a new SFCC basket is generated from the SOTM payload)

Order

ID	Type	Name	Description
geCartToken	string	Global-e Cart Token	The token exchanged within the SendCart API call to display the Global-e checkout iframe.
geOrderNumber	string	Global-e Order Number	Global-e Order Number
geReceivedOrderStatusUpdates	set-of-string	Order Status Updates received from Global-e	The set of strings of the statuses received from Global-e
geOrderCancellationReasonCode	string	Global-e Order Cancellation Reason Code	Global-e order cancellation reason code received from Global-e
geStatusCode	string	Order Status Code	Code denoting the order status on the Merchant's site (to be mapped on Global-e side)
gelsSplitOrder	boolean	Is Split Order	Indicates if the order should be handled as split order (i.e. without consolidation)
geOtVoucherCode	string	OT Voucher Code	Onetime voucher code used to place the order
geOtCurrencyCode	string	OT Currency Code	Currency of the onetime voucher code used to place the order
geOtVoucherAmount	double	OT Voucher Amount	Amount taken off the voucher when applicable
geLoyaltyPointsSpent	double	Loyalty Points Spent	Number of loyalty points spent for this purchase. The existing loyalty points handling procedure must be applied to the end customer's user account. Therefore, "Loyalty points" type discount must not be applied to the order directly, but can be used for the display purposes elsewhere in the system (i.e in end user's My Account page)
geLoyaltyPointsEarned	double	Loyalty Points Earned	Number of loyalty points to be earned for this purchase by the end customer on the Merchant's site, as specified in loyaltyPointsEarned argument for SendCart method for the cart converted to this order on Global-e
geLoyaltyCode	string	Loyalty Code	Loyalty code applicable to the Merchant's site entered by the end customer in Global-e checkout
geCustomerComments	text	Customer Comments	Comments text entered by the end customer in Global-e checkout

geDeliveryStoreId	string	Delivery Store ID	Delivery Store ID
geBarCode	string	Global-e Bar Code	Global-e Bar Code. The attribute contains - Global-e Order Number.
geCurrencyCode	string	Global-e Currency Code	3-char ISO currency code for the order being posted. By default this is set to the original Merchant's currency
geIsFreeShipping	boolean	Is Free Shipping	Indicates if the Merchant offers free international shipping to the end customer, as specified in IsFreeShipping argument for SendCart method for the cart converted to this order on Global-e
geFreeShippingCouponCode	string	Free Shipping Coupon Code	Merchant's free shipping coupon code applied by the end customer, as specified in FreeShippingCouponCode argument for SendCart method for the cart converted to this order on Global-e
geShippingMethodCode	string	Shipping Method Code	Code denoting the selected international shipping method as defined on the Merchant's site (to be mapped on Global-e side). If this international shipping method doesn't exist on the Merchant's site, the internal Global-e shipping method code will be specified instead
gePriceCoefficientRate	double	Price Coefficient Rate	CountryCoefficient rate applied to the prices in this order
geAllowEmailsFromMerchant	boolean	Allow Emails from Merchant	Indicates if the end customer has opted on Global-e checkout to receive emails from the Merchant.
geAllowDirectCommunicationFromMerchant	boolean	Allow Direct Communication from Merchant	Indicates if the end customer has opted on Global-e checkout to receive direct communication from the Merchant.
geCartId	string	Cart ID	Identifier of the cart on the Merchant's site originally specified in geMerchantCartToken argument for SendCart method for the cart converted to this order on Global-e.
geRoundingRate	string	Global-e Rounding Rate	Average conversion rate applied to the prices paid by the end customer, when calculating the prices paid by Global-e to the Merchant in the original Merchant's currency. This rate includes "FX conversion" and "marketing rounding" factors
geTotalCustomerDiscounts	double	Total Customer Discounts	Total customer discounts for Cart and Loyalty type discounts
geTotalDutiesPaidByCustomerPrice	double	Total Duties Paid By Customer	The Duties paid by customer (in merchant currency) for Duties as they were shown in checkout
geOrderTrackingNumber	string	Order Tracking Number	Tracking number used by the selected international shipping method for this order.

geOrderTrackingUrl	string	Order Tracking URL	Full tracking URL including OrderTrackingNumber used by the selected international shipping method for this order.
geShippingMethodName	string	Shipping Method Name	Name of the selected international shipping method.
geShippingMethodTypeCode	string	Shipping Method Type Code	Code denoting the selected international shipping method type as defined on the Merchant's site (to be mapped on Global-e side). If this international shipping method type doesn't exist on the Merchant's site, the internal Global-e shipping method type code will be specified instead.
geShippingMethodTypeName	string	Shipping Method Type Name	Name of the selected international shipping method type.
geOrderDeliveryDate	string	Global-e Order Delivery Date	Global-e Order Delivery Date
geDeliveryDaysFrom	int	Delivery Days From	Minimum number of days for delivery to the end customer for the selected shipping method.
geDeliveryDaysTo	int	Delivery Days To	Maximum number of days for delivery to the end customer for the selected shipping method.
geConsignmentFee	double	Consignment Fee	Consignment fee paid by the end customer in the currency denoted by CurrencyCode. This value is included in TotalShippingPrice.
geSizeOverchargeValue	double	Size Overcharge Value	Oversized items charge paid by the end customer in the currency denoted by CurrencyCode. This value is included in TotalShippingPrice.
geRemoteAreaSurcharge	double	Remote Area Surcharge	Remote area surcharge paid by the end customer in the currency denoted by CurrencyCode. This value is included in TotalShippingPrice.
geCustomerCurrencyCode	string	Customer Currency Code	3-char ISO code for the currency selected by the end customer for the order payment
geTotalPrice	double	Total Price	Total order price in the currency denoted by CurrencyCode
geTransactionCurrencyCode	string	Transaction Currency Code	3-char ISO code for the currency actually used for the current order payment. TransactionCurrencyCode may differ from CurrencyCode if the currency selected by the end customer could not be used with the selected payment method
geTransactionTotalPrice	double	Transaction Total Price	Total order price actually paid by the end customer in the currency denoted by TransactionCurrencyCode
geTotalShippingPrice	double	Total Shipping Price	Total shipping price in the currency denoted by CurrencyCode

geSameDayDispatch	boolean	Same Day Dispatch	Indicates if the end customer has requested "Same Day Dispatch" on Global-e checkout
geSameDayDispatchCost	double	Same Day Dispatch Cost	Cost of 'Same Day Dispatch' option (if selected by the end customer on Global-E checkout), in the currency denoted by CurrencyCode. This value is NOT included in TotalShippingPrice
geDoNotChargeVat	boolean	Do Not Charge VAT	Indicates if the end customer hasn't been charged VAT in Global-e checkout, as specified in doNotChargeVAT argument for SendCart method for the cart converted to this order on Global-e
gePrePayOffered	boolean	PrePay Offered	Indicates if the prepayment option for duties and taxes was offered to the customer
geIsReplacementOrder	boolean	Is Replacement Order	Indicates if the order is replacement
geOriginalOrderNumber	string	Original Order Global-e Order Number	Global-e order unique identifier for the Original order
geOriginalMerchantOrderNumber	string	Original Order Merchant Order Number	OrderId returned from SendOrderToMerchant call for the Original order
geOriginalMerchantInternalOrderNumber	string	Original Order Merchant Internal Order Number	InternalOrderId returned from SendOrderToMerchant call for the Original order
geTotalDutiesPrice	double	Total Duties Price	Total Duties and Taxes value including Customs Clearance Fees, in the currency denoted by Customer Currency Code
geTotalDutiesAndTaxesPrice	double	Total Duties and Taxes Price in Merchant Currency	Total Duties & Taxes value including Customs Clearance Fees, in the merchant currency. This amount is the total amount, regardless whether customer or the merchant paid it.
geDutiesAndTaxesSubsidy	double	Duties And Taxes Subsidy	Value of Duties and Taxes subsidized as part of product price in Merchant's Currency
geTotalProductsNetPrice	double	Total Products Net Price	Value of products after deduction of duties and taxes subsidies in Merchant's Currency
geCcfPrice	double	CCF Price	Customs Clearance Fees (CCF), in the merchant currency
geTotalCcfPrice	double	Total CCF Price	Total Customs Clearance Fees value in the currency denoted by CurrencyCode. This value is included in TotalDutiesPrice
geDutiesGuaranteed	boolean	Is Duties Guaranteed	Indicates if the end customer has selected the 'guaranteed duties and taxes' option.
geOrderWaybillNumber	string	Order Waybill Number	Waybill number used by the selected international shipping method for this order
geCashOnDeliveryFee	double	CashOnDeliveryFee	Additional charge paid by the end customer when "Cash on Delivery" payment method has been selected.

geTotalVatAmount	double	Total VAT Amount	Amount of VAT paid by the customer to Global-e
geShippingMethodStatusCode	string	Shipping Method Status Code	Code denoting the selected shipping status as defined on the Merchant's site (to be mapped on Global-e side). If this shipping status doesn't exist on the Merchant's site, the internal Global-e shipping status code will be specified instead
geShippingMethodStatusName	string	Shipping Method Status Name	Name of the shipping status
geTotalDiscountedShippingPrice	double	Total Discounted Shipping Price	The price paid by customer in local currency. Total Shipping price reducing Order Discounts International price.
geDiscountedShippingPriceMerchantCurrency	double	Discounted Shipping Price In Merchant Currency	The shipping price paid by the customer converted to the merchant's currency. Total Shipping price reducing Order Discounts (InternationalDetails.DiscountedShippingPrice price converted to the merchant currency)
geShippingSubsidy	double	Shipping Subsidy	Shipping Subsidy
geShippingVATRate	double	Shipping VAT Rate	Shipping VAT rate for customer. This rate is applied on the shipping cost.
geMerchantShippingVATRate	double	Merchant Shipping VAT Rate	Merchant Shipping VAT rate. This rate is applied on the shipping cost between Global-e and a Merchant.
gePaymentMethodName	string	Payment method name	Name of the selected payment method.
gePaymentMethodCode	string	Payment method code	Code denoting the selected payment method as defined on the Merchant's site (to be mapped on Global-e side). If this payment method doesn't exist on the Merchant's site, the internal Global-e payment method code will be specified instead.
geShippingAddress1	string	Shipping Address 1	Shipping Address line 1
geShippingAddress2	string	Shipping Address 2	Shipping Address line 2
geShippingCity	string	Shipping City	Shipping City name
geShippingCityRegion	string	City Region	Shipping City Region
geShippingCompany	string	Shipping Company	Shipping Company name
geShippingCountryCode	string	Shipping Country code	Shipping Country code
geShippingCountryName	string	Shipping Country name	Shipping Country name
geShippingEmail	string	Shipping Email	Shipping Email address
geShippingFax	string	Shipping Fax	Shipping Fax
geShippingFirstName	string	Shipping First name	Shipping First nam
geShippingLastName	string	Shipping Last nam	Shipping Last name

geShippingMiddleName	string	Shipping Middle name	Shipping Middle name
geShippingPhone1	string	Shipping Phone 1	Shipping Phone 1
geShippingPhone2	string	Shipping Phone 2	Shipping Phone 2
geShippingSalutation	string	Shipping Salutation	Shipping Salutation
geShippingStateCode	string	Shipping State code	Shipping State code
geShippingStateOrProvince	string	Shipping State or province	Shipping State or province
geShippingZip	string	Shipping Zip	Shipping Zip code
geBillingAddress1	string	address 1	Address line 1
geBillingAddress2	string	address 2	Address line 2
geBillingCity	string	city	City name
geBillingCityRegion	string	City Region	Billing City Region
geBillingCompany	string	company	Company name
geBillingCountryCode	string	country code	2-char ISO country code
geBillingCountryName	string	country name	Country name
geBillingEmail	string	email	E-mail address
geBillingFax	string	fax	Fax
geBillingFirstName	string	first name	First name
geBillingLastName	string	Last name	Last name
geBillingMiddleName	string	middle name	Middle name
geBillingPhone1	string	phone 1	Phone 1
geBillingPhone2	string	phone 2	Phone 2
geBillingSalutation	string	salutation	Salutation
geBillingStateCode	string	state code	State code
geBillingStateOrProvince	string	state or province	State or province
geBillingZip	string	Zip	Zip code
geCustomerShippingAddress1	string	Address1	Address1
geCustomerShippingAddress2	string	Address2	Address2
geCustomerShippingCity	string	City	City
geCustomerShippingCityRegion	string	City Region	City Region
geCustomerShippingCompany	string	Company	Company
geCustomerShippingCountryCode	string	Country code	Country code
geCustomerShippingCountryName	string	Country name	Country name

geCustomerShippingEmail	string	Email	Email
geCustomerShippingFax	string	Fax	Fax
geCustomerShippingFirstName	string	First name	First name
geCustomerShippingLastName	string	Last name	Last name
geCustomerShippingMiddleName	string	Middle name	Middle name
geCustomerShippingPhone1	string	Phone1	Phone1
geCustomerShippingPhone2	string	Phone2	Phone2
geCustomerShippingSalutation	string	Salutation	Salutation
geCustomerShippingStateCode	string	State code	State code
geCustomerShippingStateOrProvince	string	State or province	State or province
geCustomerShippingZip	string	Zip	Zip
geCustomerBillingAddress1	string	Address1	Address1
geCustomerBillingAddress2	string	Address2	Address2
geCustomerBillingCity	string	City	City
geCustomerBillingCityRegion	string	City Region	City Region
geCustomerBillingCompany	string	Company	Company
geCustomerBillingCountryCode	string	Country code	Country code
geCustomerBillingCountryName	string	Country name	Country name
geCustomerBillingEmail	string	Email	Email
geCustomerBillingFax	string	Fax	Fax
geCustomerBillingFirstName	string	First name	First name
geCustomerBillingLastName	string	Last name	Last name
geCustomerBillingMiddleName	string	Middle name	Middle name
geCustomerBillingPhone1	string	Phone1	Phone1
geCustomerBillingPhone2	string	Phone2	Phone2
geCustomerBillingSalutation	string	Salutation	Salutation
geCustomerBillingStateCode	string	State code	State code
geCustomerBillingStateOrProvince	string	State or province	State or province
geCustomerBillingZip	string	Zip	Zip
gePdOwnerFirstName	string	PD Owner first name	PD Owner first name
gePdOwnerLastName	string	PD Owner last name	PD Owner last name
gePdOwnerName	string	PD Owner name	PD Owner name

gePdPaymentMethodCode	string	PD Payment method code	PD Payment method code
gePdPaymentMethodName	string	PD Payment method name	PD Payment method name
gePdCountryCode	string	PD Country code	PD Country code
gePdCountryName	string	PD Country name	PD Country name
gePdEmail	string	PD Email	PD Email
gePdExpirationDate	password	PD Expiration Date	PD Expiration Date
gePdFax	string	PD Fax	PD Fax
gePdStateCode	string	PD State code	PD State code
gePdStateOrProvince	string	PD State or province	PD State or province
gePdCity	string	PD City	PD City
gePdZip	string	PD Zip	PD Zip
gePdAddress1	string	PD Address1	PD Address1
gePdAddress2	string	PD Address2	PD Address2
gePdPhone1	string	PD Phone1	PD Phone1
gePdPhone2	string	PD Phone2	PD Phone2
gePdPaymentMethodTypeCode	string	PD Payment method type code	PD Payment method type code
gePdCardNumber	password	PD Card Number	PD Card Number
gePdCvvNumber	password	PD CVV Number	PD CVV Number
geSuppressPersonalInformation	boolean	Is Suppress Personal Information (GDPR)	Is Suppress Personal Information (GDPR)
geOrderDocuments	text	Order Documents	The list of possible order documents. There possible values In format(DocumentTypeName = DocumentTypeCode): • CommercialInvoice = 1 • PackingList = 2 • ShipperManifest = 3 • Label = 4 • VATInvoice = 5 • DangerousGoodDeclarationLink = 6 • GELabel = 7 • CustomerReceiptInvoice = 8
geUSSalesTax	double	Sales tax value for USA	Sales tax value for USA in the merchant currency. This value is included in

			TotalDutiesAndTaxesPrice.
geCashOnDeliveryFeeMc	double	CashOnDeliveryFee (Merchant currency)	Additional charge paid by the end customer when "Cash on Delivery" payment method has been selected.
geCustomerUSSalesTax	double	Sales tax value for USA	Sales tax value for USA in the currency denoted by CurrencyCode. This value is included in TotalDutiesPrice.
geNonProductTotalSubsidy	double	Order DTSubsidy in Merch ant currency	Order DTSubsidy in Merchant currency
geInternationalNonProductTotalSubsidy	double	Order DTSubsidy in Custo mer currency	Order DTSubsidy in Customer currency
geOrderCreationSource	number	Order Creation Source	Order Creation Source The possible values: • 0 - Global-e checkout • 1 - Marketplace
geOrderCreationSourceInfo	string	Order Creation Source Info	Contains the extended information about the order source
gelsTaxExemption	boolean	Is Tax Exemption	Indication if the order has tax exemption
geCookieConsent	string	Customer Cookie Consent	The possible values: • 0 - No consent • 1 - Consent to all cookies • 2 - Consent to the essential cookies only
gelsOrderCreatedFallbackScenario	boolean	Is Order Created Fallback Scenario	SFCC order is created from a fallback scenario(when a new SFCC basket is generated from the SOTM payload)
gelsGiftWrappingRequired	boolean	Is Gift Wrapping Required	Indication if the order has Gift Wrapping
geOrderType	enum- of-string	Global-e Order Type	Indication if the SFCC order type created via Global-e checkout
geMixedOrdersMainOrderID	string	Main Order ID	Used/filled only with "Mixed Orders" feature. Contains the Global-e order number of main order.
geMixedOrdersSubOrdersIDs	string	Sub Orders IDs	Used/filled only with "Mixed Orders" feature. Contains the Global-e order numbers of sub orders.
geMixedOrdersSuccessfullyUpdated	boolean	All Mixed Orders Successfully Updated	Used/filled only with "Mixed Orders" feature. The value is set to TRUE only if all main and sub order were succesfully updated on SOTM request from the Global-e
gelsOrderCreatedPayByLinkScenario	boolean	Is Order Created	SFCC order is created by an agent user from the
ID	Type	Name	Description
	pe		

Order Address

geDeliveryStoreId	string	Delivery Store ID	Code denoting the Merchant's store specified by the customer for "ship to shop" shipping destination (to be mapped on Global-e side)
geVATRegistrationNumber	string	Customer VAT registration Number	Customer VAT registration Number if provided in cart / checkout or Global-e importer entity registration number for relevant markets (eg. Switzerland)
geCustomerTaxId	string	Customer Tax number	Customer Tax number provided at checkout as required for clearance into certain markets
geCityRegion	string	City Region	City Region

Customer Address

ID	Type	Name	Description
geCityRegion	string	City Region	City Region

Product Line Item

ID	Type	Name	Description
geCartItemOptionId	string	Cart item option ID	Identifier of the child cart item "option" on the Merchant's site originally specified in Product.CartItemOptionId property of the respective product in SendCart method for the cart converted to this order on Global-e.
geInternationalPrice	double	International Price	Single product final sale price in end customer's currency (specified in InternationalDetails.CurrencyCode property for the respective Merchant.Order), after applying country coefficient, FX conversion, rounding rule (if applicable) and IncludeVAT handling
geDiscountedPrice	double	Discounted Price	The product value in merchant currency after deducting all product and cart level discounts from the price. Product level discounts will be fully deducted from the respective product's price and cart discounts will be prorated over all products according to the remaining value. This value can be used as pre-calculated value for returned product's refund.
geInternationalDiscountedPrice	double	International Discounted Price	The product value in customer currency after deducting all product and cart level discounts from the price. Product level discounts will be fully deducted from the respective product's price and cart discounts will be prorated over all products according to the remaining value. This value can be used as pre-calculated value for returned product's refund.
geInternationalDiscountedPriceInMerchantCurrency	double	International Discounted Price in merchant currency	International Discounted Price in merchant currency
geParentCartItemId	string	Parent cart item ID	Identifier of the current item's parent cart item on the Merchant's site originally specified in Product.ParentCartItem property of the respective product in SendCart method for the cart converted to this order on Global-e.

gePrice	double	Price	Single product final sale price in currency defined in geCurrencyCode property of the respective Merchant.Order object for the order being submitted to the Merchant
gePriceBeforeGlobalDiscount	double	Price Before Global-e Discount (DEPRECATED)	Single product price in currency defined in CurrencyCode property of the respective Merchant.Order object for the order being submitted to the Merchant, before applying any per-product Global-e discounts (such as per-product Shipping discounts). If no Global-e discount was applied, PriceBeforeGlobalEDiscount is equal to Price.
gePriceBeforeRoundingRate	double	Price Before Rounding Rate	Price Before Rounding Rate
geVatRate	double	VAT Rate	VAT rate applied to this product (decimal point rate eg. "0.2" for 20%)
geCustomerVATRate	double	Customer VAT Rate	Customer VAT Rate applied to this product (raw rate eg. "20" for 20%)
geRoundingRate	string	Global-e Rounding Rate	Conversion rate applied to this product's price paid by the end customer, when calculating the prices paid by Global-e to the Merchant in the original Merchant's currency. This rate includes "FX conversion" and "marketing rounding" factors.
geOriginalPriceBookTotalPrice	double	Original Price Book Total Price	Original Price Book Total Price
geDiscountedPriceForCustoms	double	Original Discounted Price for Customs	Product price in merchant currency reflects the price after Reverse D&T calculation
geInternationalDiscountedPriceForCustoms	double	International Discounted Price for Customs	Product price in customer currency reflects the price after Reverse D&T calculation
geListPrice	double	Original List Price	Single product List price in currency defined in geCurrencyCode property of the respective Merchant.Order object for the order being submitted to the Merchant
geInternationalListPrice	double	International List Price	Single product list price in end customer's currency (specified in InternationalDetails.CurrencyCode property for the respective Merchant.Order), after applying country coefficient, FX conversion, rounding rule (if applicable) and IncludeVAT handling
geLineItemInternationalPrice	double	Line Item International Price	Line item (product in ordered quantity) price in end customer's currency (specified in InternationalDetails.CurrencyCode property for the respective Merchant.Order), after applying country coefficient, FX conversion, rounding rule (if applicable) and IncludeVAT handling. If not specified, should be deemed equal to "InternationalPrice * Quantity". If specified, should take preference over InternationalPrice.
geIsBackOrdered	boolean	Is Back Ordered	Boolean specifying if the product was ordered as a backed ordered item
geBackOrderDate	string	Back Order Date	Estimated date for the backordered item to be in stock

gelsGiftCard	boolean	Is Globale Gift Card	Specifies that the product line items is a 'gift card'
geProductSubsidy	double	Product DTSubsidy in Merchant currency	Product DTSubsidy in Merchant currency
geInternationalProductSubsidy	double	Product DTSubsidy in customer currency	Product DTSubsidy in customer currency

Shipping Method

ID	Type	Name	Description
isGeShippingMethod	boolean	Is Global-e Shipping Method	Specifies that shipping method is used for Global-e integration
geCarrier	string	Carrier	Carrier's short name
geCarrierName	string	Carrier Name	Carrier's full name
geCarrierTitle	string	Carrier Title	Carrier's title

Price book

ID	Type	Name	Description
geNotApplicableForDynamic	boolean	Global-e Not Applicable for Dynamic Countries	Global-e Not Applicable for Dynamic Countries
geBasePricebook	boolean	Global-e Base Price Book	Global-e Base Price Book
geFixedPricebook	boolean	Global-e Fixed Price Book	Global-e Fixed Price Book
geApplicableToCountries	set-of-string	Applicable To Countries	Global-E operated countries to which the price book is applicable
geApplicableToCurrencies	set-of-string	Applicable To Currencies	Global-E operated country currencies to which the price book is applicable
geApplicableToMerchantId	string	Applicable to Merchant ID	Allows to apply the price book to some specific merchant ID (should be used only if multiple GE accounts are used in the same SFCC instance).
geCachePriceBook	boolean	Global-e Cache Price Book	Identifies if a price book is used for caching purposes
geCachePriceBookCombinations	string	Global-e Cache Price Book Combinations	Global-E country/currency combinations to which the price book is applicable

Payment Transaction

ID	Type	Name	Description
----	------	------	-------------

gePaymentAmountInCustomerCurrency	double	Payment Amount In Customer Currency	Global-e Payment Amount In Customer Currency
gePaymentMethodType	enum-of-string	Payment Method Type	Global-e Payment Method Type Possible values: • GlobalePayment • GlobaleGiftCard • GlobaleLoyaltyCard
gePaymentMethodName	string	Payment method name	Name of the selected payment method
gePaymentDetails	text	Payment Details	Global-e Payment Details
geAlternativePaymentDetails	text	Alternative Payment Details	Global-e Alternative Payment Details

Gift Certificate

ID	Type	Name	Description
currentBalance	double	Current Balance	Current balance of the card
geCurrencyCode	string	International Currency Code	Customer currency code of the card
geInternationalPrice	double	International Price	Price in end customer's currency, after applying country coefficient, FX conversion, and rounding rule (if applicable)
initialBalance	double	Initial Balance	Initial balance of the card
redeemRequestJSON	text	Redeem Request JSON	Used as a storage and contains information about redeem requests(between Global-e and SFCC) of the card
redeemResponseJSON	text	Redeem Response JSON	Used as a storage and contains information about redeem responses(between Global-e and SFCC) of the card
refundRequestJSON	text	Refund Request JSON	Used as a storage and contains information about refund requests(between Global-e and SFCC) of the card
refundResponseJSON	text	Refund Response JSON	Used as a storage and contains information about refund responses(between Global-e and SFCC) of the card
originalCurrencyCode	string	Currency Code	Currency code of the card (should be the same as GC's currency code in "General" tab)

Gift Certificate Line Item

ID	Type	Name	Description
geCartItemId	string	Cart item ID	Identifier of the cart item on the Merchant's site originally specified in Product.CartItemId property of the respective product in SendCart method for the cart converted to this order on Global-e.geCartItemOptionId
geCartItemOptionId	string	Cart item option ID	Identifier of the child cart item "option" on the Merchant's site originally specified in Product.CartItemOptionId property of the respective product in SendCart method for the cart converted to this order on Global-e.
geInternationalPrice	double	International Price	Single gift cart final sale price in end customer's currency (specified in InternationalDetails.CurrencyCode property for the respective Merchant.Order).
geDiscountedPrice	double	Discounted Price	The product value in merchant currency after deducting all product and cart level discounts from the price. Product level discounts will be fully deducted from the respective product's price and cart discounts will be prorated over all products according to the remaining value. This value can be used as pre-calculated value for returned product's refund.
geInternationalDiscountedPrice	double	International Discounted Price	The product value in customer currency after deducting all product and cart level discounts from the price. Product level discounts will be fully deducted from the respective product's price and cart discounts will be prorated over all products according to the remaining value. This value can be used as pre-calculated value for returned product's refund.
geParentCartItemId	string	Parent cart item ID	Identifier of the current item's parent cart item on the Merchant's site originally specified in Product.ParentCartItemId property of the respective product in SendCart method for the cart converted to this order on Global-e.
gePrice	double	Price	Used as a storage and contains information about refund requests(between Global-e and SFCC) of the card
gePriceBeforeGlobalDiscount	double	Price Before Global-e Discount (DEPRECATED)	Single product price in currency defined in CurrencyCode property of the respective Merchant.Order object for the order being submitted to the Merchant, before applying any per-product Global-e discounts (such as per-product Shipping discounts). If no Global-e discount was applied, PriceBeforeGlobalEDiscount is equal to Price.
gePriceBeforeRoundingRate	double	Price BeforeRounding Rate	Price BeforeRounding Rate

geVatRate	double	VAT Rate	VAT rate applied to this product (decimal point rate eg. "0.2" for 20%)
geCustomerVATRate	double	Customer VAT Rate	Customer VAT Rate applied to this product (raw rate eg. "20" for 20%)
geRoundingRate	string	Global-e Rounding Rate	Conversion rate applied to this product's price paid by the end customer, when calculating the prices paid by Global-e to the Merchant in the original Merchant's currency. This rate includes "FX conversion" and "marketing rounding" factors.
geOriginalPriceBookTotal Price	double	Original Price Book Total Price	Original Price Book Total Price
geDiscountedPriceForCustoms	double	Original Discounted Price for Customs	Product price in merchant currency reflects the price after Reverse D&T calculation
geInternationalDiscountedPriceForCustoms	double	International Discounted Price for Customs	Product price in customer currency reflects the price after Reverse D&T calculation
geListPrice	double	Original List Price	Single product List price in currency defined in geCurrencyCode property of the respective Merchant.Order object for the order being submitted to the Merchant
geInternationalListPrice	double	International List Price	Single product list price in end customer's currency (specified in InternationalDetails.CurrencyCode property for the respective Merchant.Order), after applying country coefficient, FX conversion, rounding rule (if applicable) and IncludeVAT handling
geLineItemInternationalPrice	double	Line Item International Price	Line item (product in ordered quantity) price in end customer's currency (specified in InternationalDetails.CurrencyCode property for the respective Merchant.Order), after applying country coefficient, FX conversion, rounding rule (if applicable) and IncludeVAT handling. If not specified, should be deemed equal to "InternationalPrice * Quantity". If specified, should take preference over InternationalPrice.
gelsBackOrdered	boolean	Is Back Ordered	Boolean specifying if the product was ordered as a backed ordered item
geBackOrderDate	string	Back Order Date	Estimated date for the backordered item to be in stock
gelsGiftCard	boolean	Is Globale Gift Card	Specifies that the product line items is a 'gift card'
geProductSubsidy	double	Product DTSubsidy in Merchant currency	Product DTSubsidy in Merchant currency
geInternationalProductSubsidy	double	Product DTSubsidy in customer currency	Product DTSubsidy in customer currency

Organization Preferences

ID	Type	Name	Description	Default Value
geLanguagesConfiguration	text	Global-e Languages Selector Configuration	The preference specifies the configuration of language selector in Global-e Country Switcher. More details are here: Global-e_SFCC_Country_Switcher.pdf	-

Profile

ID	Type	Name	Description	Default Value
geSalutation	enum-of-int	Salutation	Salutation	0 (None)

Shipping Methods

i Please note that the following list of Shipping Methods is not the real Global-e Shipping Methods, it is needed only for Salesforce B2C Commerce Digital as a placeholder to be able to Create/Place SFCC Order.

Despite some Shipping Method filtering logic in Global-e cartridge, by default, any of Global-e Shipping Method is not configured to be restricted to your local/domestic Checkout. Global-e Shipping Methods should not be shown anywhere on your storefront, but we recommend to make additional configurations to all of the following Shipping Methods and add to exclusion of your domestic/local (not operated by Global-e) country(ies).

ID	Name	Description
GLOBALE	GLOBALE	Global-e Generic Shipping (default)
GLOBALE_STANDARD	GLOBALE STANDARD	Global-e Standard Shipping
GLOBALE_EXPRESS	GLOBALE EXPRESS	Global-e Express Shipping
GLOBALE_STORE_COLLECTION	GLOBALE STORE COLLECTION	Global-e Store Collection
GLOBALE_HUB	GLOBALE HUB	Global-e Shipping via GE Hub
GLOBALE_DIRECT	GLOBALE DIRECT	Global-e Shipping Direct from Brand Hub
GLOBALE_WYOL	GLOBALE WYOL	Brand own carrier service

Payment Method

 Please note that the following Payment Method/Processor is not real Global-e Payment Method/Processor, it is needed only for Salesforce B2C Commerce Digital as a placeholder to be able to Create/Place SFCC Order.
The real data about shipping and payment methods will be stored in custom attributes of the Order.

ID	Name	Payment Processor
GLOBALE	Globale General	GLOBALE

Services

Global-e cartridge uses the following Services, which needs to be imported once on Salesforce B2C Commerce Digital (can be also found in metadata folder as globale.services.xml file):

Service	Profile	Credential	Description
Globale-AppSettings	GLOBALE-JOB.LC.T	Globale-AppSettings	To retrieve Global-e App Settings and store in GLOBALE_APP_SETTINGS Custom Object
Globale-AppVersion	GLOBALE-JOB.LC.T	Globale-AppVersion	To retrieve Global-e App Version and store in GLOBALE_APP_VERSION Custom Object
Globale-Countries	GLOBALE-JOB.LC.T	Globale-Countries	To retrieve Global-e Countries and store in GLOBALE_COUNTRIES Custom Object
Globale-CountryCoefficients	GLOBALE-JOB.LC.T	Globale-CountryCoefficients	To retrieve Global-e Country Coefficients and store in GLOBALE_COUNTRY_COEFFICIENTS Custom Object
Globale-Currencies	GLOBALE-JOB.LC.T	Globale-Currencies	To retrieve Global-e Currencies and store in GLOBALE_CURRENCIES Custom Object
Globale-CurrencyRates	GLOBALE-JOB.LC.T	Globale-CurrencyRates	To retrieve Global-e Currency Rates and store in GLOBALE_CURRENCY_RATES Custom Object
Globale-ActiveHubDetails	GLOBALE-JOB	Globale-ActiveHubDetails	To retrieve Global-e Hub Details and store in GLOBALE_HUB_DETAILS Custom Object

	.LC T		
Globale- LocationsDefaultCul turesList	GLO BAL E- JOB .LC T	Globale- LocationsDefaultC ulturesList	To retrieve Global-e Cultures and store in GLOBALE_CULTURES Custom Object
Globale- RecentProductCoun tryS	GLO BAL E- JOB .HC T	Globale- RecentProductCo untryS	To retrieve Global-e Product Restrictions and store them on SFCC Product's level
Globale- RoundingRules	GLO BAL E- JOB .LC T	Globale- RoundingRules	To retrieve Global-e Rounding Rules and store in GLOBALE_ROUNDING_RULES Custom Object
Globale- SendCartV2	GLO BAL E- SEN DCA RT	Globale- SendCartV2	Used to send SendCartData data to Global-e, for Global-e Checkout
Globale- CreateOrderRefund	GLO BAL E- JOB .LC T	Globale- CreateOrderRefun d	Used to send OrderRefundDetails data to Global-e, in case of Refund should be created
Globale- UpdateOrderDispat chV2	GLO BAL E- JOB .LC T	Globale- UpdateOrderDispa tchV2	Used to send UpdateOrderDispatchRequest data to Global-e, to update Order status and Delivery Quantities for the products on Global-e side
Globale- UpdateOrderStatus	GLO BAL E- JOB .LC T	Globale- UpdateOrderStatu s	Used to send OrderStatusDetails data to Global-e, to update Order status on Global-e side
Globale-JWT	GLO BAL E-	Globale-JWT	Used to get Global-e JWT token

	JOB .LC T		
Globale-ShippingDetails	GLOBALE-JOB.LC T	Globale-ShippingDetails	Used to get ShippingDetails data
Globale-OCAPI	GLOBALE-JOB.LC T	Globale-OCAPI	Used for Order's creation, applying of coupons on the Global-e checkout page
Globale-SCAPI	LOB-ALE-JOB.LC T	Globale-SCAPI	Used for Order's creation, applying of coupons on the Global-e checkout page

Scheduled Jobs

i Please note that all Jobs except 'GlobaleSettings' are just a samples, so you might have to extend/customize it according to your business logic/requirements.

Job ID	Description	Step ID	Step Description
GlobaleSettings	Loads the Global-e Settings in respective SFCC Custom Objects	AppSettings	Loads Global-e AppSettings
		Countries	Loads Global-e Countries
		CountryCoefficients	Loads Global-e Country Coefficients
		Cultures	Loads Global-e Cultures
		Currencies	Loads Global-e Currencies
		CurrencyRates	Loads Global-e Currency Rates
		RoundingRules	Loads Global-e Rounding Rules
		ActiveHubDetails	Loads Global-e Active Hub Details
		LoadRecentProductCountryS	Loads Recent Product Country S data
		GlobaleGenerateCachePriceBooksXML	Generates cache price books XML
		GlobaleImportPriceBook	Imports cache price books XML
		InvalidatePageCache	Invalidates page cache
GlobaleOrderNotifications	This job sends the UpdateOrderDispatchV2 , GlobaleUpdateRMA, CreateOrderRefund request and the Order status update to Global-e.	UpdateOrderDispatch	Sends the UpdateOrderDispatchV2 request to Global-e
		UpdateOrderStatus	Sends the Order status update to Global-e
		CreateOrderRefund	Sends the CreateOrderRefund request to Global-e
		UpdateRMA	Sends update RMA number from SFCC to Global-e
GlobaleCatalogFeed	Generates Catalog Feed and sends it to Global-e SFTP folder	GenerateCatalogFeed	Generates Product Catalog Feed for Global-e and stores it in IMPEX/globale/catalog/ folder
		UploadCatalogFeed	Uploads the generated catalog feed(s) stored in IMPEX/globale/catalog/ folder to SFTP folder configured in GLOBALE Site Preferences
GlobaleRestrictedItemsFeed	Generates Restricted Items Feed and sends it to Global-e SFTP folder	GenerateRestrictedItemsFeed	Generates Restricted Items file and stores it in IMPEX/* folder

		UploadRestrictedItemsFeed	Uploads generated Restricted Items file from IMPEX/* to Global-e SFTP folder
GlobaleCancelOrdersPayByLink	Cancels old orders, created by "PayByLink" scenario	CancelOrders	Cancels old orders, created by "PayByLink" scenario, in status "OPEN/NEW" and "NOT PAID" based on the expiration date (autoCancelOrdersTime) from MAS "sfccPayByLinkConfigurations"