

Screenplay Project Setup Guide

This guide provides the necessary steps to set up and run the Screenplay project on your local machine. Follow these steps carefully to ensure a smooth setup.

Prerequisites

Make sure you have the following installed:

- Node.js (v18+ recommended)
- npm (v9+ recommended)
- MongoDB Atlas cluster or a local MongoDB instance

Project Structure

The project is organized into the following packages:

1. **Editor** - Located in `packages/screenplay-editor`
 2. **Frontend Dashboard** - Located in `apps/script-writer`
 3. **Backend Server** - Located in `apps/server`
-

Step 1: Setting Up the Editor

1. Navigate to the editor directory:
2. `cd packages/screenplay-editor`
3. Install the dependencies:
4. `npm install`
5. Build the editor:
6. `npm run build`

Step 2: Setting Up the Frontend Dashboard

1. Navigate to the frontend directory:
2. `cd apps/script-writer`
3. Install the dependencies:
4. `npm install`
5. Start the frontend server:
6. `npm run dev`

Step 3: Setting Up the Backend Server

1. Navigate to the backend directory:
2. `cd apps/server`

3. Install the dependencies:
4. `npm install`
5. Start the backend server:
6. `npm run dev`

Environment Variables

Ensure you have the following environment files in place:

Backend `.env.development`

```
PORT=6001
NODE_ENV=development
MONGO_DB_URI=mongodb+srv://script-
server:PIVgLQlnTaVXnagJ@cluster0.1j0zftv.mongodb.net
JWT_SALT=DF5AAC0D4082CD2A65FC48D5A5C4B74729FF4DDC4C6849B85C05181EE747075E
GOOGLE_OAUTH_CLIENT_ID=24644104762-
0r7aillvth4ivolsmlmnd4ndd7ilr97h.apps.googleusercontent.com
GOOGLE_OAUTH_1CLIENT_SECRET=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
RAZERPAY_API_KEY=rzp_test_dhUy62KpTI3MWl
RAZERPAY_SECRET=i5WJLvYR8G1LbEwGW980Jmr0
FRONTEND_BASEURL=http://localhost:3000
BACKEND_BASEURL=http://localhost:6001
SESSION_SECRET=appie
AWS_S3_BUCKET=pdf-bucket-for-pdf-to-json-storage
AWS_S3_PROFILE_BUCKET=screenplay-profiles-screenplay
AWS_S3_COMMON_BUCKET=screenplay-common-screenplay
AWS_S3_FEEDBACK_BUCKET=screeplay-feedback-screenplay
AWS_S3_ACCESS_KEY_ID=AKIA5FTZDOUKZG4RR4GR
AWS_S3_SECRET_ACCESS_KEY=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
AWS_REGION=ap-south-1
AWS_SES_ACCESS_KEY_ID=AKIASOEUCWFJBAG6UFG7
AWS_SES_SECRET_ACCESS_KEY=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
OPENAI_API_KEY=sk-proj-qlztp7djF5UM-
6ylODlNhnOECWe8QEKjFAiIi9wvS_6qsr86O8Khln8QPPfchfPI0HeKG-VYTUT3BlbkFJH-
H1td0OZY9UAjs7jblBlejfoH4FBo5bj-vsOpClbIze5uHtQ6bAsrKvp-hPwSnfDQMQEgSUgA
OWNER_EMAILID=hello@screenplay.ink
SMTP_PASSWORD=dfumqgbhzumkbejmk
PHONEPE_API_URL=https://api-preprod.phonepe.com/apis/pg-sandbox
PHONEPE_SECRET_KEY=e51ac498-b100-42be-a945-bb8d9d80d811
PHONEPE_MERCHANT_ID=UATM22N4LSNB788Z
STREAM_API_KEY=3m449czrbp6c
STREAM_API_SECRET=vm4c7dwyec8mg8a6jc37y47egcs52yfrdzr8w79zzmx7tutu3r25b4zjuc
yw5qq
TOKEN_EXPIRY_COOKIE=1d
```

Frontend `.env`

```
VITE_APP_ENABLE_API MOCKING=true
VITE_APP_API_URL=http://localhost:6001
VITE_APP_COLLAB_URL=ws://localhost:8080/collaboration
```

Both `.env` files should be placed in their respective directories (backend and frontend).

Final Steps

- Make sure MongoDB Atlas is properly configured and accessible.
- Test the frontend at <http://localhost:3000> and backend at <http://localhost:6001>.

If you encounter any issues during setup, make sure to check the console for errors and confirm that all environment variables are correctly set.