Zero Trust Network Access (ZTNA) with Zscaler: Protecting Application Access in a Zero Trust Environment.

S.No	NAME	COLLEGE NAME	CONTACT
1.	RAKSHANA K	SRI KRISHNA ADITHYA COLLEGE OF ARTS AND SCIENCE	23bscs143rakshanak@skacas.ac.in
2.	RIYA D	SRI KRISHNA ADITHYA COLLEGE OF ARTS AND SCIENCE	23bscs144riyad@skacas.ac.in
3.	SABARI RAJAN R	SRI KRISHNA ADITHYA COLLEGE OF ARTS AND SCIENCE	23bscs146sabarirajanr@skacas.ac.in
4.	HARINI NETRAA R K	SRI KRISHNA ADITHYA COLLEGE OF ARTS AND SCIENCE	23bscs118harininetraark@skacas.ac.in
5.	MEENAGAYATHRI A G	SRI KRISHNA ADITHYA COLLEGE OF ARTS AND SCIENCE	23bscs130meenagayathriag@skacas.ac.in

Project details

Title: Zero Trust Network Access (ZTNA) with Zscaler: Protecting Application Access in a Zero Trust Environment

AI-Enhanced User Protection (AIUP)

AI-Enhanced User Protection (AIUP) is an advanced security capability integrated into the **Zero Trust Network Access (ZTNA)** framework to strengthen protection for users accessing enterprise applications. In a Zero Trust environment, application access must be continuously verified to ensure that only authorized users can connect to sensitive resources. Traditional security systems often rely on fixed rules and signature-based detection methods, which may not be effective against modern and evolving cyber threats. AIUP addresses these limitations by using **Artificial Intelligence (AI)** and **Machine Learning (ML)** to analyze user behavior, detect anomalies, and protect application access in real time.

Within a **Zscaler-based ZTNA architecture**, AIUP continuously monitors user activity, device posture, and application access patterns. The system collects and analyzes large volumes of security data from multiple sources such as authentication logs, device information, and application usage records. AI algorithms process this information to identify unusual or suspicious behaviors that may indicate potential security threats targeting enterprise applications.

One of the key benefits of AI-Enhanced User Protection is its ability to detect **compromised accounts and insider threats**. For example, if a user suddenly attempts to access a critical application from an unfamiliar location, device, or network, the AI system can recognize the anomaly. Based on the risk level, the system may trigger security responses such as requesting **multi-factor authentication (MFA)**, restricting access to the application, or terminating the session to prevent unauthorized activity.

AIUP also strengthens threat detection by continuously learning from historical user behavior and previous attack patterns. Over time, the system becomes more effective at identifying malicious activities such as credential theft, unusual login attempts, and abnormal data access patterns. This adaptive learning capability allows organizations to proactively respond to new and evolving cyber threats.

In the **Zscaler Zero Trust architecture**, AIUP works alongside identity-based access policies to enhance application security. Every user request is evaluated based on identity, device health, location, and contextual security factors before granting access to an application. AI further enhances this process by providing **risk-based access decisions**, ensuring that only legitimate and trusted users can connect to enterprise resources.

Additionally, AI-Enhanced User Protection helps reduce the workload on security administrators by automating threat detection and response processes. Instead of manually analyzing large volumes of logs and alerts, administrators can rely on AI-driven insights to quickly identify suspicious activities and take appropriate action.

Overall, AIUP plays a significant role in protecting application access within a **Zero Trust environment**. By combining AI-driven analytics with **Zscaler's cloud-based security platform**, organizations can ensure secure and reliable user-to-application connectivity while minimizing the risk of unauthorized access and cyber attacks.

Abstract:

With the increasing adoption of cloud services, remote work, and distributed enterprise environments, traditional network security models based on perimeter defenses are no longer sufficient to protect organizational resources. Zero Trust Network Access (ZTNA) has emerged as a modern security approach that follows the principle of **"never trust, always verify,"** ensuring that every user and device requesting access to an application is continuously authenticated and authorized.

This study focuses on the implementation of **Zero Trust Network Access (ZTNA) using Zscaler** to protect application access in a Zero Trust environment. Instead of providing broad network-level access like traditional VPN solutions, ZTNA establishes secure, identity-based connections between users and specific applications. By leveraging Zscaler's cloud-native security architecture, organizations can ensure that internal applications remain hidden from the public internet while allowing authorized users to access them securely from any location.

The system enforces strict access policies based on user identity, device posture, location, and contextual security information. Additionally, advanced security capabilities such as AI-driven monitoring and continuous verification help detect abnormal behavior and prevent unauthorized access to sensitive resources.

Overall, implementing ZTNA with Zscaler enhances enterprise security by reducing the attack surface, preventing lateral movement within networks, and ensuring secure user-to-application connectivity. This approach provides a scalable and efficient security model that supports modern digital workplaces while maintaining strong protection against evolving cyber threats.

Use Case Scenarios:

Scenario 1: Secure Remote Employee Access to Enterprise Application

A remote employee needs to access an internal enterprise application from a home network. Using **Zscaler Zero Trust Network Access (ZTNA)**, the employee must first authenticate through the organization's identity provider. The system verifies the user identity, device security posture, and access policies before establishing a secure connection directly to the required application.

Output:

- Secure authentication of the remote employee completed
- Direct and encrypted connection established only to the required application
- Internal corporate network remains hidden from the internet
- Unauthorized access attempts automatically blocked by ZTNA policies

Scenario 2: Controlled Third-Party Vendor Access

A third-party vendor requires temporary access to a specific internal application for system maintenance. With ZTNA implemented through Zscaler, the vendor is authenticated and granted limited access only to the designated application. Other internal resources and systems remain completely invisible and inaccessible.

Output:
- Vendor authenticated using secure identity verification
- Access limited strictly to the authorized maintenance application
- Other enterprise systems remain hidden and inaccessible
- All vendor activities logged for monitoring and auditing purposes

Scenario 3: Detection of Suspicious Login Activity

A user account attempts to access an internal application from an unfamiliar device or geographic location. The **AI-Enhanced User Protection (AIUP)** system analyzes user behavior and detects abnormal login activity compared to the user's normal access patterns.

Output:
- AI system identifies abnormal login behavior
- Additional security verification such as multi-factor authentication triggered
- Application access temporarily restricted until verification is completed
- Security alert generated for administrators

Scenario 4: Secure Access to Cloud-Hosted Applications

Employees need to access enterprise cloud applications such as internal dashboards, project management platforms, or development tools. Zscaler ZTNA verifies the user identity, device posture, and security policies before granting access to the required cloud application.

Output:
• Identity-based authentication successfully completed
• Access granted only to authorized cloud applications
• All communication encrypted during the session
• Unauthorized access attempts automatically blocked

Scenario 5 Prevention of Unauthorized Application Access

An employee attempts to access a restricted internal database or application that is not assigned to their role. The **ZTNA policy engine in Zscaler** verifies the user's role and access permissions before allowing the connection.

Output:
• User identity and role verified by the ZTNA policy engine
• Access to the restricted application denied
• Attempt logged in the security monitoring system
• Organization's sensitive data remains protected

Stage-1

Title Of the Project:

Zero Trust Network Access (ZTNA) with Zscaler: Protecting Application Access in a Zero Trust Environment

Overview:

The project focuses on implementing a secure access framework using **Zero Trust Network Access (ZTNA) with Zscaler** to protect enterprise applications from unauthorized access and modern cyber threats. Traditional network security models rely on perimeter-based defenses that assume users inside the network can be trusted. However, with the rapid growth of remote work, cloud-based services, and mobile devices, this approach is no longer effective in protecting sensitive applications and data. ZTNA addresses these challenges by following the principle of **"never trust, always verify,"** ensuring that every user and device must be verified before accessing any application.

The main objective of this project is to strengthen **application access security** by implementing identity-based access control through the Zscaler platform. Instead of granting users full network access like traditional VPN solutions, the system provides **direct and secure connectivity only to the specific applications that users are authorized to access**. This approach significantly reduces the risk of unauthorized access, data breaches, and lateral movement across internal systems.

The system verifies several security parameters before granting application access, including **user identity, device posture, location, and predefined security policies**. Zscaler's cloud-native architecture ensures that enterprise applications remain hidden from the public internet while still allowing secure connectivity for authorized users. By establishing **application-level access rather than network-level access**, the system improves security while maintaining a seamless user experience.

To further enhance security, **AI-Enhanced User Protection (AIUP)** is integrated into the framework. Artificial intelligence and machine learning techniques analyze user behavior patterns, detect anomalies, and

identify suspicious activities such as unusual login attempts or abnormal application access patterns. Real-time monitoring allows the system to quickly detect potential threats and automatically trigger additional security measures such as **multi-factor authentication (MFA)** or temporary access restrictions.

Secure authentication and continuous monitoring play an important role in protecting application access. When abnormal behavior is detected, additional verification mechanisms are activated to confirm the legitimacy of the user. Security alerts and notifications help administrators respond quickly to potential threats and maintain the integrity of the system.

Data security is also ensured through **encrypted communication between users and enterprise applications**. Logging and monitoring mechanisms record user activities and security events, which help organizations track access patterns, analyze security incidents, and maintain compliance with security regulations.

The system also supports integration with **enterprise identity providers, cloud services, and internal applications**, allowing organizations to implement a unified security framework. Monitoring and reporting tools provide administrators with visibility into application access, system performance, and potential security risks.

Scalability and reliability are achieved through Zscaler's **cloud-based infrastructure**, which is designed to support a large number of users and applications without affecting performance. Distributed security nodes and load balancing mechanisms ensure high availability and efficient application access across multiple locations.

Overall, this project demonstrates how implementing **Zero Trust Network Access with Zscaler** can effectively protect enterprise applications by enforcing identity-based authentication, minimizing the attack surface, and ensuring secure user-to-application connectivity. The approach provides a **secure, scalable, and efficient solution** for protecting application access in modern digital environments.

List of Vulnerability Table:

Practice Website:

S.no	Vulnerability Name	CWE - No
1	Improper Ownership Management	CWE- 282
2	Cleartext Storage of Sensitive Information in a Cookie	CWE-315
3	Use of Unmaintained Third Party Components	CWE-1104
4	Insufficient Entropy	CWE -331
5	Unchecked Error Condition	CWE-391
6	Embedded Malicious Code	CWE-506
7	Missing Encryption of Sensitive Data	CWE-331
8	Missing XML Validation	CWE -112
9	Missing Critical Step in Authentication	CWE-304
10	Insufficient Logging	CWE-778

-

REPORT:

1) Vulnerability Name: Improper Ownership Management

CWE/CVE: CWE-282

OWASP/SANS Category: A01:2025 – Broken Access Control

Description:

Improper Ownership Management occurs when a system fails to correctly assign or enforce ownership permissions for resources such as files, applications, or data. In such situations, unauthorized users may gain the ability to access, modify, or delete resources that should be restricted to specific owners or administrators. This vulnerability often arises due to incorrect configuration of access controls, weak permission management, or improper handling of user roles and privileges. Attackers may exploit this weakness to manipulate ownership settings, leading to unauthorized control over critical system resources.

Business Impact:

If ownership management is not properly enforced, attackers or unauthorized users may gain access to sensitive resources and perform actions that compromise system integrity. This can result in unauthorized modification or deletion of important data, disruption of business operations, and potential data breaches. Additionally, organizations may face financial losses, legal consequences, and reputational damage if sensitive information or critical systems are compromised due to improper access control mechanisms.

Zero Trust Network Access (ZTN | CWE - CWE-282: Improper Own | (5) WhatsApp

cwe.mitre.org/data/definitions/282.html

School | All Bookmarks

Common Weakness Enumeration

A community-developed list of SW & HW weaknesses that can become vulnerabilities

Top 25 | Top HW CWE | New to CWE? Start here!

Home > CWE List > CWE-282: Improper Ownership Management (4.19.1) | ID Lookup: Go

Home | About ▼ | Learn ▼ | Access Content ▼ | Community ▼ | Search ▼

CWE-282: Improper Ownership Management

Weakness ID: 282
Vulnerability Mapping: ALLOWED (with careful review of mapping notes)
Abstraction: Class

View customized information: Conceptual | Operational | Mapping Friendly | Complete | Custom

Description

The product assigns the wrong ownership, or does not properly verify the ownership, of an object or resource.

Common Consequences

Impact	Details
Gain Privileges or Assume Identity	**Scope: Access Control**

Potential Mitigations

Phase(s)	Mitigation
Architecture and Design; Operation	Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust

2) Vulnerability Name: Cleartext Storage of Sensitive Information in a Cookie

CWE/CVE: CWE-315

OWASP/SANS Category: A02:2025-Security Misconfiguration

Description:

Cleartext Storage of Sensitive Information in a Cookie occurs when an application stores confidential data such as user credentials, session identifiers, or personal information in browser cookies without encryption. Since cookies are stored on the client side, they can be accessed by attackers through browser vulnerabilities, cross-site scripting (XSS) attacks, or by intercepting network traffic. If sensitive information is stored in plain text, attackers can easily read and misuse the data to gain unauthorized access to user accounts or application resources.

Business Impact:

Storing sensitive information in cleartext cookies can lead to serious security risks such as session hijacking, unauthorized account access, and data breaches. Attackers may impersonate legitimate users and gain access to confidential information or internal systems. This can result in financial loss, legal liabilities, and damage to the organization's reputation, especially if customer or employee data is exposed.



3) Vulnerability Name: Use of Unmaintained Third Party Components

CWE/CVE: CWE-1104

OWASP/SANS Category: A03:2025-Software Supply Chain Failures

Description:

Use of Unmaintained Third Party Components occurs when an application depends on external libraries, frameworks, or software components that are no longer actively maintained or updated by their developers. These outdated components may contain known security vulnerabilities that remain unpatched, making the application susceptible to exploitation. Attackers often scan systems for such components and exploit their weaknesses to gain unauthorized access, execute malicious code, or compromise the system.

Business Impact:

Using unmaintained third-party components can expose an organization to significant security risks. Attackers may exploit known vulnerabilities to compromise applications, leading to data breaches, service disruptions, or unauthorized system access. This can result in financial losses, regulatory compliance issues, and damage to the organization's reputation. Maintaining updated and supported software components is therefore essential for ensuring long-term system security.



4) Vulnerability Name: Insufficient Entropy

CWE/CVE: CWE-331

OWASP/SANS Category: A04:2025-Cryptographic Failures

Description:

Insufficient Entropy occurs when a system generates random values, such as cryptographic keys, session IDs, or tokens, using weak or predictable sources of randomness. Entropy refers to the level of unpredictability in generated values. When entropy is insufficient, attackers may be able to predict or reproduce these values, allowing them to bypass security mechanisms. This vulnerability often appears in authentication systems, encryption processes, or session management where strong randomness is required to maintain security.

Business Impact:

If attackers can predict security tokens, session identifiers, or cryptographic keys, they may gain unauthorized access to user accounts or sensitive systems.This can lead to session hijacking, data breaches, and unauthorized transactions. For organizations, such incidents may result in financial losses, legal consequences, and damage to customer trust and reputation. Ensuring strong random number generation is essential to maintain system security.



5) Vulnerability Name: Unchecked Error Condition

CWE/CVE: CWE-391

OWASP/SANS Category: A10:2025-Mishandling of Exceptional Conditions

Description:
Unchecked Error Condition occurs when a system or application fails to properly handle errors that occur during program execution. Instead of detecting and responding to these errors appropriately, the system may ignore them or continue processing without taking corrective action. This can lead to unexpected system behavior, incorrect outputs, or security weaknesses. Attackers may exploit such situations to trigger abnormal conditions, potentially bypassing security controls or causing the application to behave in unintended ways.

Business Impact:
Failure to properly handle errors can result in system instability, data corruption, or unauthorized system behavior. Attackers may exploit these weaknesses to disrupt services, manipulate application functionality, or gain access to sensitive information. For organizations, this can lead to operational downtime, financial losses, and damage to reputation due to unreliable or insecure systems. Proper error handling and monitoring mechanisms are essential to maintain application reliability and security.



6) Vulnerability Name: Embedded Malicious Code

CWE/CVE: CWE-506

OWASP/SANS Category: A08:2025-Software or Data Integrity Failures

Description:
Embedded Malicious Code refers to the presence of intentionally harmful code hidden within an application or software component. This malicious code may be inserted by attackers, compromised third-party libraries, or during insecure development practices. Such code can perform unauthorized actions such as stealing sensitive information, creating backdoors, or executing harmful operations without the user's knowledge. Because the code is embedded within legitimate software, it may remain undetected for long periods and can be triggered under specific conditions.

Business Impact:
The presence of embedded malicious code can severely compromise the security and reliability of an organization's systems.Attackers may use it to steal confidential data, gain unauthorized access, or disrupt system operations. This can lead to data breaches, financial losses, operational downtime, and reputational damage. In critical environments, malicious code may also affect the integrity of applications and undermine trust in the organization's software systems.



7) Vulnerability Name: Missing Encryption of Sensitive Data

CWE/CVE: CWE-311

OWASP/SANS Category: A06:2025-Insecure Design

Description:

Missing Encryption of Sensitive Data occurs when an application or system transmits or stores confidential information without using proper encryption mechanisms. Sensitive data such as user credentials, financial records, personal information, or internal system details may be exposed in plain text. If this data is intercepted during transmission or accessed by unauthorized users, attackers can easily read and misuse the information. This vulnerability often arises due to poor security configuration or failure to implement secure communication protocols.

Business Impact:

The absence of encryption can lead to unauthorized disclosure of sensitive information, resulting in data breaches and identity theft.Attackers may intercept or access confidential data and use it for malicious purposes such as fraud or unauthorized system access. For organizations, this may result in financial losses, regulatory penalties, and serious damage to their reputation and customer trust. Implementing strong encryption mechanisms is essential to protect sensitive data from unauthorized access.



8) Vulnerability Name: Missing XML Validation

CWE/CVE: CWE-112

OWASP/SANS Category: A05:2025-Injection

Description:
Missing XML Validation occurs when an application processes XML input without properly validating its structure or content. XML is widely used for data exchange between systems, and if proper validation mechanisms are not implemented, attackers may send specially crafted XML data to manipulate application behavior. Without validation, the system may accept malicious or malformed XML input that can lead to security vulnerabilities such as XML injection, data manipulation, or unauthorized access to system resources.

Business Impact:
If XML inputs are not properly validated, attackers may exploit this weakness to alter application data, bypass security checks, or disrupt normal system operations. This can lead to data integrity issues, service interruptions, and potential exposure of sensitive information.For organizations, such incidents may result in operational disruptions, financial losses, and reduced trust from customers or partners due to compromised system security.



9) Vulnerability Name: Missing Critical Step in Authentication

CWE/CVE: CWE-304

OWASP/SANS Category: A07:2025-Authentication Failures

Description:
Missing Critical Step in Authentication occurs when an application fails to enforce an essential step in the authentication process required to verify a user's identity. This may happen when security mechanisms such as multi-factor authentication, verification tokens, or session validation are skipped or improperly implemented. As a result, attackers may bypass authentication controls and gain unauthorized access to protected resources or user accounts. Such vulnerabilities often arise due to poor authentication logic or incomplete implementation of security checks.

Business Impact:
If critical authentication steps are missing, attackers may successfully bypass login protections and gain unauthorized access to sensitive systems or user accounts.This can lead to data breaches, unauthorized transactions, and compromise of confidential information. For organizations, the impact may include financial losses, legal consequences, and damage to their reputation due to the failure to properly protect user authentication processes.



10) Vulnerability Name: Insufficient Logging

CWE/CVE: CWE-778

OWASP/SANS Category: A09:2025-Security Logging and Alerting Failures

Description:
Insufficient Logging occurs when an application or system fails to properly record security-related events such as login attempts, access requests, system errors, or configuration changes. Without adequate logging mechanisms, it becomes difficult to detect suspicious activities, unauthorized access attempts, or potential security breaches. Attackers may exploit this weakness to perform malicious actions without leaving sufficient evidence for administrators to identify or investigate the incident.

Business Impact:
Lack of proper logging can significantly delay the detection of security incidents and make it difficult for organizations to respond effectively to cyber threats. Without accurate logs, identifying the source and impact of an attack becomes challenging, which may result in prolonged system compromise or data breaches. This can lead to operational disruptions, financial losses, regulatory compliance issues, and damage to the organization's reputation.



This is stage 1 in the context of web application testing and security
we take help from

OWASP top 10 to understand them. The OWASP Top 10 is a widely recognized list of the most critical web application security risks. Understanding these risks is essential for ensuring the security of web applications.

Stage 2

Overview :-

Nessus is a vulnerability scanner developed by Tenable, Inc. It is a remote scanner, meaning that it does not need to be installed on the target host to scan it. Nessus works by sending a variety of probes to the target host in order to identify vulnerabilities. These probes can include network traffic, operating system commands, and application requests.

Nessus uses a plugin-based architecture. Plugins are small pieces of code that are designed to identify specific vulnerabilities. There are over 1200 plugins available for Nessus, covering a wide range of vulnerabilities in operating systems, applications, and network devices.

When Nessus scans a host, it first uses a discovery plugin to identify the operating system and services running on the host. Once the host has been discovered, Nessus runs a series of plugins to test for vulnerabilities. For each vulnerability that Nessus finds, it provides a detailed report that includes the severity of the vulnerability, the steps to reproduce the vulnerability, and the steps to remediate the vulnerability.

Nessus can be used to scan a variety of targets, including single hosts, networks, and web applications. It can also be used to scan specific ports and services. Nessus can be configured to run scans on a schedule or manually.

Here is a step-by-step explanation of how Nessus works:

1. Nessus connects to the target host using a variety of protocols, including TCP, UDP, and ICMP.
2. Nessus sends a series of probes to the target host in order to identify its operating system and services.
3. Nessus runs a series of plugins to test for vulnerabilities.
4. Nessus generates a report that includes the severity of each vulnerability, the steps to reproduce the vulnerability, and the steps to remediate the vulnerability.

Nessus is a valuable tool for security professionals who need to identify and remediate vulnerabilities in their networks. It is easy to use and provides comprehensive reports that can be used to prioritise remediation efforts.

Here are some of the benefits of using Nessus:

- Comprehensive vulnerability coverage: Nessus has over 1200 plugins available, covering a wide range of vulnerabilities in operating systems, applications, and network devices.
- Easy to use: Nessus has a user-friendly interface that makes it easy to configure and run scans.
- Comprehensive reporting: Nessus provides detailed reports that include the severity of each vulnerability,the steps to reproduce the vulnerability, and the steps to remediate the vulnerability.
- Scalability: Nessus can be used to scan a variety of targets, including single hosts, networks, and web applications.
- Flexibility: Nessus can be configured to run scans on a schedule or manually.

Nessus is a powerful tool that can be used to improve the security of any network. It is a valuable asset for any security professional.

Target website :- http://testfire.net/
Target ip address:- 65.61.137.117

List of vulnerability:-

s.no	Vulnerability name	Severity	plugins
1	TCP/IP Timestamps Supported	INFO	25220
2	Service Detection	INFO	22964
3	SSL / TLS Versions Supported	INFO	56984
4	TLS Version 1.3 Protocol Detection	INFO	138330
5	Additional DNS Hostnames	INFO	46180
6	TLS ALPN Supported Protocol Enumeration	INFO	84821
7	Common Platform Enumeration (CPE)	INFO	45590
8	Device Type	INFO	54615
9	OS Fingerprints Detected	INFO	209654
10	TLS Version 1.2 Protocol Detection	INFO	136318

REPORT: -

1.Vulnerability Name : - 25220 - TCP/IP Timestamps Supported

Severity: INFO

Plugin: - 25220

Port: - N/A

Description: - The remote host supports TCP timestamps as defined in RFC1323. This feature is used to improve network performance and reliability by helping with round-trip time calculations and protection against wrapped sequence numbers. However, a side effect of TCP timestamps is that an attacker may be able to estimate the uptime of the remote system. By analyzing timestamp values in TCP packets, it may be possible to determine how long the system has been running since its last reboot.

Solution: -

If the exposure of system uptime information is a concern, administrators can disable TCP timestamps in the operating system's network configuration. This can typically be done by modifying system network settings or kernel parameters depending on the operating system in use. Disabling this feature may slightly affect certain TCP performance optimizations

Business Impact:

This issue does not directly compromise the system or expose sensitive data. However, it can reveal system uptime information, which may provide useful insights to attackers when performing reconnaissance on the network. Understanding system uptime could help attackers plan targeted attacks or identify systems that have not been recently restarted or updated. Proper configuration and monitoring can help minimize such information exposure.

2.Vulnerability Name : - Service Detection

Plugin: - 22964

Port: - 80 / tcp / www

Description: - The scan detected the service running on the remote host by analyzing the service banner or by examining the response returned when an HTTP request was sent. Banner information or error messages from services may reveal details about the software, web server, or application running on the target system. This information helps identify the type and version of services operating on the host.

Solution: - Administrators can reduce information exposure by configuring services to hide or limit banner information and detailed error messages. Web servers and applications should be configured to suppress version details and unnecessary system information. Regular updates and proper service configuration also help minimize unnecessary information disclosure**.**

Business Impact: - This issue does not directly pose a security threat. However, exposed service details can assist attackers during the reconnaissance phase by revealing information about the technologies used in the system. Such information may help attackers identify potential vulnerabilities associated with specific services or software versions. Proper configuration helps reduce this information exposure and strengthens overall security posture.

3.Vulnerability Name : - SSL / TLS Versions Supported

Severity: - INFO

Plugin: - 56984

Port: - 443 / tcp / www

Description: - The scan identified the Secure Sockets Layer (SSL) and Transport Layer Security (TLS) protocol versions supported by the remote service for encrypting communications. These protocols are used to secure data transmitted between the client and the server. Detecting supported SSL/TLS versions helps administrators understand which encryption protocols are enabled on the server and whether they meet current security standards.

Solution: - Administrators should review the enabled SSL/TLS versions on the server and ensure that only secure and up-to-date protocols are allowed. Older and insecure versions should be disabled to maintain strong encryption standards. Regularly updating the server configuration and security settings will help ensure that secure communication protocols are used.

Business Impact: - This information does not directly represent a vulnerability but reveals which encryption protocols the server supports. Attackers could use this information during reconnaissance to identify outdated or weak SSL/TLS versions if they are enabled. Ensuring that only modern and secure protocols are supported helps maintain strong protection for data transmitted over the network**.**

4.Vulnerability Name: - TLS Version 1.2 Protocol Detection

Severity: - INFO

Plugin: - 136318

Port: - 443 / tcp / www

Description: - The scan detected that the remote service supports Transport Layer Security (TLS) version 1.2 for encrypting communications. TLS 1.2 is a widely used cryptographic protocol that helps secure data transmitted between clients and servers over the internet. This detection simply confirms that the service can establish encrypted connections using TLS 1.2.

Solution: - Ensure that the server continues to support secure and up-to-date encryption protocols. Administrators should verify that insecure protocols such as older SSL or TLS versions are disabled if they are not required. Regular updates and proper configuration of SSL/TLS settings help maintain strong communication security.

Business Impact: - This finding is informational and does not indicate a direct vulnerability. The presence of TLS 1.2 support confirms that the server is capable of providing secure encrypted communication. Proper management of supported protocols ensures that data transmitted between users and the server remains protected from interception.

5.Vulnerability Name: - 46180 - Additional DNS Hostnames

Severity: - INFO

Plugin: - 46180

Port: - 0

Description: - Hostnames different from the current hostname have been collected by miscellaneous plugins. Nessus has generated a list of hostnames that point to the remote host. Note that these are only the alternate hostnames for hosts discovered on a web server.
Different web servers may be hosted on name-based virtual hosts.

Solution: - If you want to test them, re-scan using the special vhost syntax, such as : www.example.com [192.0.32.10]

Business Impact: -This does not pose an immediate threat to business operations or data security. It indicates the discovery of hostnames that are associated with the remote host, particularly in cases of web servers utilizing name-based virtual hosts. While not a security risk on its own, it could be useful for understanding the server's configuration and infrastructure.
Organizations should consider this information as part of their network documentation but do not need to take immediate action to mitigate it as a security threat.

6.Vulnerability Name:-TLS ALPN Supported Protocol Enumeration
Severity: - INFO

Plugin: - 84821

Port: - 443 / tcp / www
Description: The scan detected that the remote host supports the Application-Layer Protocol Negotiation (ALPN) extension in TLS. ALPN allows the client and server to negotiate which application-layer protocol should be used during the TLS connection, such as HTTP/1.1 or HTTP/2. This plugin enumerates the protocols supported by the ALPN extension on the remote service.
Solution: - Administrators should review the protocols supported by the ALPN extension and ensure that only necessary and secure protocols are enabled. Disabling unused or outdated protocols can help reduce unnecessary information exposure and improve the security configuration of the server. Regular updates and proper server configuration are also recommended.
Business Impact: - This finding is informational and does not indicate a direct security risk. However, the disclosure of supported protocols may provide useful information to attackers during the reconnaissance phase. Understanding which protocols are enabled on a server could help attackers identify potential weaknesses if outdated or insecure protocols are present. Proper configuration and monitoring can help reduce this exposure.

7.Vulnerability Name: - 45590 - Common Platform Enumeration (CPE)

Severity: - INFO

Plugin:-45

Port: - 0

Description: - By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

Solution: - n/a

Business Impact: - This provides insights into hardware and software products identified on a host through a Nessus scan. It reports CPE matches, which are standardized identifiers for these products. This information is valuable for asset management and inventory purposes. While it doesn't signify a security threat, it aids administrators in understanding the components within their network, contributing to effective resource management and facilitating future system maintenance.

8.VulnerabilityName: - Device Type

Severity: - INFO

Plugin: - 54615

Port: - 0

Description: - Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution: -

Business Impact: - It allows for the identification of the remote system type, such as a printer, router, or general-purpose computer, based on the remote operating system. While this doesn't pose a direct security threat, it offers valuable insights for network administrators to better understand and classify the devices in their network. This information aids in network management, optimization, and ensures that the right security measures are in place for each device type.

9.Vulnerability Name: - OS Fingerprints Detected

Severity: - INFO

Plugin: - 209654

Port: - N/A

Description: - The scan detected operating system fingerprints from the remote host using multiple remote probing techniques such as TCP/IP, SMB, HTTP, NTP, and SNMP. These probes analyze how the system responds to network requests in order to identify characteristics of the underlying operating system. While the most accurate result is reported in the OS Identification plugin, this plugin lists all fingerprints that were detected during the scanning process.

Solution: - Administrators can reduce the exposure of system fingerprint information by limiting unnecessary network services and filtering external requests using firewalls or intrusion prevention systems. Proper network configuration and regular system updates can also help reduce information disclosure about the operating system.

Business Impact: - This finding is informational and does not represent a direct security vulnerability. However, information about the operating system can assist attackers during reconnaissance activities. Knowing the type of operating system may help attackers search for known vulnerabilities related to that system. Limiting unnecessary information exposure can improve the overall security posture of the network**.**

10.Vulnerability Name: - TLS Version 1.3 Protocol Detection

Severity: - INFO

Plugin: - 138330

Port: - 443 / tcp / www

Description: The scan detected that the remote service supports Transport Layer Security (TLS) version 1.3 for encrypting network communications. TLS 1.3 is the latest and more secure version of the TLS protocol, designed to provide stronger encryption, improved performance, and better protection against modern security threats. This detection confirms that the server is capable of establishing secure encrypted connections using TLS 1.3.

Solution: - Administrators should ensure that TLS 1.3 remains enabled and properly configured on the server. It is also recommended to disable older and less secure protocols such as SSL and outdated TLS versions if they are not required. Regular updates and proper configuration of encryption settings help maintain strong communication security.

Business Impact: - This finding is informational and does not represent a security vulnerability. Supporting TLS 1.3 is considered a good security practice because it provides stronger encryption and better protection for data transmitted over the network. Proper management of encryption protocols ensures secure communication between users and the server.

Stage-3

Title: - Implementing Zero Trust Network Access (ZTNA) with Zscaler: Protecting Application Access in a Zero Trust Environment

• Zero Trust Network Access (ZTNA)

Zero Trust Network Access (ZTNA) is an IT security framework that provides secure remote access to an organization's internal applications and data based on clearly defined access control policies. Unlike traditional Virtual Private Networks (VPNs), which grant users broad access to the entire network, ZTNA operates on a "never trust, always verify" principle. It grants users access only to the specific applications they need, and only after their identity and device have been verified.

ZTNA is a critical component of modern security architecture. It helps organizations move away from the concept of a trusted internal network and an untrusted external network (the "castle-and-moat" model). By hiding the internal network from the internet and establishing one-to-one, encrypted connections between users and applications, ZTNA drastically reduces the attack surface and stops common threats like lateral movement by attackers.

• The ZTNA Access Cycle

The ZTNA cycle is a continuous process of verifying identity, establishing secure connections, and enforcing policy for every access request. It typically consists of the following steps:

1. User Request: A user, from any location (office, home, coffee shop), requests access to a specific internal application (e.g., an HR portal, a finance server, or an internal code repository).

2. Identity and Device Verification: Before any connection is established, the ZTNA solution verifies who the user is (via multi-factor authentication, or MFA) and checks the security posture of their device. This includes ensuring the device has up-to-date antivirus, a healthy firewall, and is not compromised.
3. Policy Enforcement: The ZTNA solution checks the access policy. Does this specific user, with this specific device, have permission to access the requested application at this specific time?
4. Establish Secure Connection: If the policy allows access, the ZTNA solution creates a highly secure, encrypted micro-tunnel between the user's device and the target application. Crucially, the user never gains access to the underlying network, only to the application itself.
5. Continuous Monitoring: The ZTNA solution continues to monitor the connection for anomalies. If the user's behavior becomes suspicious or their device posture changes, the connection can be terminated in real-time.
6. Logging and Analytics: All access attempts, successful and failed, are logged and analyzed. This data is used for auditing, threat hunting, and refining access policies.

• Zscaler (Zscaler Internet Access / Zscaler Private Access)

Zscaler is a cloud-native security platform that delivers its services entirely from the cloud, eliminating the need for on-premises hardware like VPN concentrators. For ZTNA, Zscaler offers Zscaler Private Access (ZPA) . ZPA is a service that provides seamless, identity-based access to private applications without ever placing users on the network.

Zscaler ZPA operates on a simple principle: the application is "inside" the Zscaler cloud, and the user connects to it there. It collects data from a variety of sources, including:

1. Identity Providers (IdP): Such as Azure AD, Okra, or Ping Identity, to verify user identities.
2. Device Posture Partners: Such as CrowdStrike, Tanium, or Microsoft Defender for Endpoint, to check the health of the endpoint.
3. Business Applications: The internal web apps, file servers, and legacy applications hosted in data centers or public clouds (e.g., AWS, Azure).
4. Zscaler App Connectors: Lightweight software components deployed in the data center or cloud that initiate outbound connections to the Zscaler cloud, making internal servers invisible to the internet

.

Zscaler then enforces policies based on this data, including:

1. Identity-Based Access: Policies are built around user and group identities, not IP addresses.
2. Application Segmentation: Users are granted access to specific applications, not entire subnets.
3. Least Privilege Access: Ensures users have the minimum level of access required to perform their jobs.

• The Zscaler ZTNA Cycle

The Zscaler ZTNA cycle is the practical application of the ZTNA principles using the Zscaler cloud. The cycle typically consists of the following steps:

1. User Login and Authentication: A user attempts to access an internal application. They are redirected to their organization's Identity Provider (IdP) for authentication and MFA.
2. Device Posture Check (Integration): Zscaler checks with integrated endpoint protection tools to ensure the device is compliant with security policies.
3. Policy Lookup and Decision: The Zscaler cloud evaluates the request against the defined access policies. It verifies that the user, device, and context (time, location) are authorized for that specific application.
4. Establishing the Micro-tunnel: Once authorized, the Zscaler cloud instructs the user's Zscaler Client Connector and the appropriate Zscaler App Connector in the data center to establish an encrypted connection. The user is now connected to the application.
5. Traffic Inspection (Optional): For sanctioned applications, Zscaler can optionally inspect the traffic for data loss prevention (DLP) or to detect malware.
6. Logging and Analytics: All activity is logged in the Zscaler cloud portal for reporting, threat hunting, and compliance.

• MISP (Malware Information Sharing Platform) Integration

While Zscaler is a primary access control tool, it can be enhanced by integrating with threat intelligence platforms like MISP.

1. Threat Intelligence Feed: MISP can aggregate and share threat intelligence about malicious domains, IPs, and URLs. This list of indicators of compromise (IOCs) can be fed into Zscaler's cloud.
2. Proactive Blocking: If a user, even one authorized by ZPA, attempts to access a known malicious site that has been flagged by the MISP feed, Zscaler Internet Access (ZIA) can block the request, preventing a potential infection.
3. Enhanced Visibility: Security teams can use MISP to cross-reference Zscaler logs. If a user's behavior is anomalous, the team can check MISP to see if the destination IP or domain is associated with a known threat actor or campaign.

• Your College Network Information

This infrastructure presents a large attack surface, especially with the need for remote learning and

administrative access. The network includes:

- Core routers and switches
- Distribution routers and switches
- Wireless access points
- Firewalls and Intrusion Detection Systems (IDS)
- Internal Application Servers: Hosting the student information system, library resources, research data repositories, and administrative portals.
- Legacy VPN Concentrator: Currently providing broad network-level access for faculty and staff working remotely.

The need for ZTNA arises from the limitations of the current VPN model:

- Over-permissioned Access: Once on the VPN, a faculty member's compromised laptop could potentially scan and attack the entire internal network (lateral movement).
- Hidden Applications: Some research applications need to be accessed by external collaborators without granting them full network access.
- User Experience: The legacy VPN can be slow and cumbersome, often requiring users to route all their internet traffic through the university.

• How you think you deploy ZTNA using Zscaler in your college

To deploy Zscaler ZTNA (ZPA) in your college, you would start by identifying the specific applications that need to be secured and the user groups that need access to them. This is a shift from securing the network to securing access to applications.

The plan would need to include the following:

1. Application Discovery: Catalog all internal applications (e.g., ERP, library system, research servers, file shares) and identify which ones are currently exposed via the VPN.
2. User Segmentation: Define user groups (e.g., Students, Faculty - Research, Faculty - Admin, IT Staff, External Collaborators) and the specific applications each group needs.
3. Deploying Zscaler App Connectors: Install lightweight App Connector VMs in the university's data center. These connectors will establish outbound connections to the Zscaler cloud, making the application servers invisible to the public internet.
4. Integrating Identity Provider: Connect Zscaler to the university's existing Identity Provider (e.g., Microsoft Azure AD) to leverage current usernames, passwords, and MFA policies.
5. Configuring Access Policies: Create granular policies in the Zscaler admin portal. For example: "The 'Faculty' group can access the 'ERP Application' from any device that has antivirus enabled, after MFA."

6. Deploying Zscaler Client Connector: Students, faculty, and staff will install the Zscaler Client Connector on their laptops and mobile devices. This small client intelligently routes traffic for private applications through ZPA and public traffic through ZIA.

Threat Intelligence

In the context of Zscaler and ZTNA, threat intelligence is used to understand who is trying to access what, and from where. It helps move beyond simple identity checks to a more contextual understanding of risk.

Sources include:

1. Zscaler Cloud Logs: Internal logs provide real-time data on who is accessing which applications, from which locations, and on what devices.
2. External Threat Feeds (MISP): Information about new malware campaigns, phishing kits, or command-and-control servers being used by attackers.
3. Identity Provider Logs: Anomalies in login attempts, such as a user logging in from two geographically impossible locations in a short time, can signal a compromised account.

This intelligence is used for:

1. Adaptive Access Control: If threat intelligence suggests a user's location is high-risk, Zscaler can step-up authentication requirements or block access entirely.
2. Hunting for Compromised Accounts: Analysts can use Zscaler logs to see if a user is suddenly accessing applications they never have before, which could be a sign of credential theft.
3. Blocking Malicious Communication: Threat intelligence feeds can be used by Zscaler Internet Access (ZIA) to block outbound connections to known malicious sites, even if they originate from a user inside the university.

- Incident Response (Adapted for ZTNA)

Incident response in a ZTNA model is faster and more targeted because the environment is inherently more controlled.

1. Detection: The SOC team detects an anomaly. For example, a faculty account is downloading an unusually high volume of data from a research server at 3 AM. Zscaler logs provide the exact details: the user, the device, the application, and the amount of data transferred.
2. Containment: The SOC team can instantly isolate the user. In the Zscaler portal, they can simply deactivate that user's access or block their specific device. Because there is no network-level access, this action immediately severs all connections to every application, preventing lateral movement.
3. Eradication: The compromised device is taken offline for malware scanning and cleaning by the IT helpdesk.
4. Recovery: Once the device is clean and the user's password is reset, the Zscaler policy is re-enabled, granting the user access again.
5. Post-incident review: The security team analyzes the logs to understand how the account was compromised (e.g., a phishing email) and updates Zscaler policies, perhaps by adding a block for similar malicious domains or tightening access rules for that specific research application.

Benefits of this incident response approach:

1. Near-Instant Containment: Actions take seconds in a cloud dashboard, not minutes or hours configuring firewall rules.
2. No Lateral Movement: The attacker is contained to the single compromised application, protecting the rest of the university's network.

3. Granular Forensics: Zscaler provides a detailed audit trail of every connection, making investigations faster and more accurate.
4. Compliance: This model helps demonstrate compliance with data protection regulations by proving that access to sensitive student or research data is tightly controlled and audited.

• Understanding about the tool (Zscaler ZPA)

Zscaler Private Access (ZPA) is a cloud service that embodies the ZTNA principle of "connect a user to an app, not the network." Here are the key things to understand:

1. It is "Application-Centric," Not "Network-Centric": You define policies based on applications (e.g., "SAP Server 01"), not network constructs like IP subnets. This aligns security with how businesses actually operate.
2. It Hides the Network: ZPA uses App Connectors inside your data center that only make *outbound* connections to the Zscaler cloud. Your internal servers never need to open inbound firewall ports, making them invisible to port scanners and attackers on the internet.
3. It uses a "Dark Cloud" Approach: To an external scanner, the organization's applications simply don't exist. They only become visible to authorized users after a multi-step verification process.
4. It Provides a Superior User Experience: Users don't have to mess with clunky VPN clients. The Zscaler Client Connector works silently in the background. For web apps, access can even be agentless, requiring only a modern browser.
5. It is Inherently Scalable: Because it's a cloud service, ZPA scales instantly to handle thousands of concurrent users, unlike a legacy VPN appliance that needs to be manually upgraded.

Conclusion: -

In conclusion, exploring the realm of AI for web security using IBM QRadar has been an insightful journey through various stages.

In **Stage 1**, understanding web application testing unveiled the critical importance of assessing vulnerabilities and ensuring the security of web-based systems. This foundational knowledge served as a cornerstone for comprehending the subsequent stages.

Stage 2 delved into the intricacies of Nessus reports, emphasising the significance of detailed vulnerability assessments. Analysing these reports provided valuable insights into potential threats, enabling informed decision-making for robust security measures.

Stage 3 introduced the pivotal concept of Zero Trust Network Access (ZTNA) and its implementation using Zscaler Private Access (ZPA). It demonstrated a paradigm shift from traditional VPN-based network access to secure, identity-based user-to-application connectivity. The solution showcased the power of hiding internal applications from the internet, enforcing granular access policies, and eliminating lateral movement. This underscores the need for modern, proactive cybersecurity strategies in an era of remote work and cloud adoption

Considering the future scope, **Stage 1** illuminated the evolving landscape of web application testing. With advancements in AI, there is a promising avenue for more sophisticated testing methodologies, ensuring even higher levels of security for web applications.

Stage 2 highlighted the future trajectory of the testing process, indicating a shift towards more automation and integration of AI-driven tools. This evolution promises quicker, more accurate vulnerability assessments, enhancing overall cybersecurity postures.

Stage 3 illuminated the future potential of Zero Trust Network Access (ZTNA) and Zscaler technologies. With AI integration and machine learning, these systems are poised to become more intelligent and adaptive, enabling real-time risk assessment based on user behavior and device posture. Enhanced automation in policy enforcement, predictive analytics for threat detection, and improved scalability are anticipated, empowering organizations to stay ahead of sophisticated cyber threats in an increasingly distributed world.

In essence, the project not only provided a deep understanding of the current state zero trust using ZSCALER but also offered a glimpse into the exciting future of cybersecurity. Embracing these advancements will be crucial for organisations aiming to fortify their digital landscapes in the face of ever-evolving cyber threats.

Future Scope: -

Future of web application testing

The future of WAT is bright, as web applications become increasingly complex and sophisticated. Organizations are increasingly reliant on web applications to conduct business, and they need to be confident that their web applications are secure and reliable.

Here are some of the key trends that are expected to shape the future of WAT:

- Increased focus on security: Security is a top priority for all organizations, and WAT is essential for identifying and mitigating security vulnerabilities. In the future, we can expect to see even more emphasis on security testing, as web applications become increasingly targeted by cyberattacks.
- Rise of artificial intelligence (AI) and machine learning (ML): AI and ML are already being used in WAT, and their role is expected to grow in the future. AI and ML can be used to automate repetitive tasks, such as test case generation and execution. They can also be used to identify complex patterns and anomalies that may be difficult to detect with traditional testing methods.
- Shift to cloud-based testing: More and more organizations are moving their web applications to the cloud. This trend is driving the growth of cloud-based WAT platforms. Cloud-based testing platforms offer a number of advantages, such as scalability, flexibility, and cost-effectiveness.
- Increased focus on user experience (UX) testing: UX testing is essential for ensuring that web applications are easy to use and meet the needs of users. In the future, we can expect to see more focus on UX testing, as organizations increasingly recognize the importance of providing a positive user experience.

Future scope of the testing process

The future scope of the testing process is bright, as software becomes increasingly complex and sophisticated. Organisations are increasingly reliant on software to conduct business, and they need to be confident that their software is high-quality and reliable.

Here are some of the key trends that are expected to shape the future of the testing process:

- Increased focus on continuous testing: Continuous testing is a methodology that involves testing software throughout the SDLC, from development to deployment. This helps to identify defects early and prevent them from causing problems later in the development process.
- Rise of AI and ML: AI and ML are already being used in the testing process, and their role is expected to grow in the future. AI and ML can be used to automate repetitive tasks, such as test case generation and execution. They can also be used to identify complex patterns and anomalies that may be difficult to detect with traditional testing methods.
- Shift to cloud-based testing: Cloud-based testing platforms offer a number of advantages, such as scalability, flexibility, and cost-effectiveness. This is driving the growth of cloud-based testing platforms.
- Increased focus on testing automation: Testing automation is the use of software to execute test cases without human intervention. Testing automation can help to save time and resources, and it can also help to improve the quality and efficiency of testing.

Future scope of SOC / SEIM:-

The future scope of Zero Trust Network Access (ZTNA) and the broader Zero Trust framework is poised for significant evolution, driven by emerging technologies and changing threat landscapes:

1. **AI-Driven Zero Trust (AI-ZTA):** Future Zero Trust implementations will leverage advanced AI and deep learning to move beyond static policies. Systems will continuously learn user behavior, predict anomalous activities before they occur, and dynamically adjust access privileges in real-time based on contextual risk, creating a truly "adaptive" security posture.
2. **Integration with Edge Computing and IoT:** As organizations deploy more IoT devices and edge computing nodes, Zero Trust principles will extend to these resource-constrained environments. Expect the development of lightweight Zero Trust agents and protocols that can authenticate and secure machine-to-machine (M2M) communication at the edge, preventing large-scale botnet attacks.
3. **Identity-Centric Everything:** The future will see identity become the ultimate security perimeter. Zero Trust will evolve to incorporate advanced identity verification methods, including **continuous behavioral biometrics** (keystroke dynamics, gait analysis) and **decentralized identity** solutions using blockchain, ensuring that the user behind the session is verified at all times.
4. **Convergence with SASE Architecture:** Zero Trust will be a core component of the Secure Access Service Edge (SASE) framework. This convergence will provide organizations with a unified, cloud-delivered stack that combines ZTNA, Secure Web Gateways (SWG), Cloud Access Security Brokers (CASB), and Firewall-as-a-Service (FWaaS), simplifying management and ensuring consistent security for all users, regardless of location.

5. **Zero Trust for Operational Technology (OT) and Critical Infrastructure:** Sectors like energy, manufacturing, and healthcare will increasingly adopt Zero Trust to protect critical infrastructure. Future scope includes air-gapped Zero Trust solutions and specialized protocols designed to secure legacy industrial control systems (ICS) and SCADA environments from nation-state attacks.
6. **Automated Threat Hunting and Response:** Future Zero Trust platforms will integrate with Security Orchestration, Automation, and Response (SOAR) tools to enable automated threat hunting. Upon detecting a compromised identity or device, the system will not just block access but automatically initiate investigation playbooks, isolate affected systems, and even roll back malicious changes.

Topics explored: -

Data Collection and Aggregation, Standardization and Normalisation, Enrichment and Analysis, Sharing and Distribution, Integration with Security Tools, Customization and Flexibility, Automation and Orchestration, Community Involvement, Incident Response Support, Threat Intelligence Feeds, Soc and Siem

Tools explored: -

Nmap, Metasploit, Nessus, Kali Linux, OWASP ZAP, Burp Suite

THE END