

Practical Session 2

Task 1

```
j_rakshitha@RAKSHITHA:~/ossp_project$ nano src/file_copy.c
j_rakshitha@RAKSHITHA:~/ossp_project$ gcc -Wall -Wextra -g src/file_copy.c -o build/file_copy
j_rakshitha@RAKSHITHA:~/ossp_project$ echo "This is a sample file for the OSSP file copy task." > sample.txt
j_rakshitha@RAKSHITHA:~/ossp_project$ cat sample.txt
This is a sample file for the OSSP file copy task.
j_rakshitha@RAKSHITHA:~/ossp_project$ ./build/file_copy sample.txt copied.txt
File copied successfully.
Source      : sample.txt
Destination : copied.txt
j_rakshitha@RAKSHITHA:~/ossp_project$ cat copied.txt
This is a sample file for the OSSP file copy task.
j_rakshitha@RAKSHITHA:~/ossp_project$ cmp sample.txt copied.txt
j_rakshitha@RAKSHITHA:~/ossp_project$ |
```

```
GNU nano 8.7.1 src/file_copy.c *
#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>
#include <stdlib.h>

#define BUFFER_SIZE 1024

int main(int argc, char *argv[]) {

    if (argc != 3) {
        printf("Usage: %s <source_file> <destination_file>\n", argv[0]);
        return 1;
    }

    int source_fd = open(argv[1], O_RDONLY);

    if (source_fd < 0) {
        perror("Error opening source file");
        return 1;
    }

    int destination_fd = open(
        argv[2],
        O_WRONLY | O_CREAT | O_TRUNC,
        0644
    );

    if (destination_fd < 0) {
        perror("Error opening destination file");
        close(source_fd);
        return 1;
    }

    char buffer[BUFFER_SIZE];
    ssize_t bytes_read;

    while ((bytes_read = read(source_fd, buffer, BUFFER_SIZE)) > 0) {

        ssize_t bytes_written = write(
            destination_fd,
            buffer
```

```

GNU nano 8.7.1 src/file_copy.c *
);

if (destination_fd < 0) {
    perror("Error opening destination file");
    close(source_fd);
    return 1;
}

char buffer[BUFFER_SIZE];
ssize_t bytes_read;

while ((bytes_read = read(source_fd, buffer, BUFFER_SIZE)) > 0) {

    ssize_t bytes_written = write(
        destination_fd,
        buffer,
        bytes_read
    );

    if (bytes_written != bytes_read) {
        perror("Error writing to destination file");
        close(source_fd);
        close(destination_fd);
        return 1;
    }

    if (bytes_read < 0) {
        perror("Error reading source file");
    }

    close(source_fd);
    close(destination_fd);

    printf("File copied successfully.\n");
    printf("Source      : %s\n", argv[1]);
    printf("Destination : %s\n", argv[2]);

    return 0;
}

```

Practice Tasks

```

Processing triggers for libc-bin (2.43-2ubuntu2.3)
j_rakshitha@RAKSHITHA:~$ gcc command_executor.c -o command_executor
j_rakshitha@RAKSHITHA:~$ ./command_executor
Enter a Linux command: ls

Parent Process
Parent PID : 2387
Child PID : 2388

Child Process
Child PID : 2388
Parent PID : 2387
Executing command: ls
OSSP command_executor command_executor.c
Child process completed.
j_rakshitha@RAKSHITHA:~$ |

```

```
j_rakshitha@RAKSHITHA:~$ ps
  PID TTY          TIME CMD
   374 pts/0    00:00:00 bash
   940 pts/0    00:00:00 ps
j_rakshitha@RAKSHITHA:~$ top
top - 05:39:05 up 52 min,  1 user,  load average: 0.05, 0.03, 0.00
Tasks:  24 total,   1 running, 23 sleeping,   0 stopped,   0 zombie
%Cpu(s):  0.0 us,   0.0 sy,   0.0 ni,100.0 id,   0.0 wa,   0.0 hi,   0.0 si,   0.0 st
MiB Mem :  7794.6 total,  7194.5 free,   539.3 used,   211.8 buff/cache
MiB Swap: 2048.0 total,  2048.0 free,    0.0 used.  7255.3 avail Mem
```

PID	USER	PR	NI	VIRT	RES	SHR	S	%CPU	%MEM	TIME+	COMMAND
1	root	20	0	24140	15412	11604	S	0.0	0.2	0:00.84	systemd
2	root	20	0	3180	2204	2072	S	0.0	0.0	0:00.01	init-systemd(Ub
7	root	20	0	3180	2040	1940	S	0.0	0.0	0:00.00	init
47	root	19	-1	50420	16668	15392	S	0.0	0.2	0:00.24	systemd-journal
82	systemd+	20	0	22540	14624	12004	S	0.0	0.2	0:00.09	systemd-resolve
89	root	20	0	35376	12364	9252	S	0.0	0.2	0:01.35	systemd-udev
108	root	20	0	2888	1952	1820	S	0.0	0.0	0:00.05	chronyd-starter
116	root	20	0	4472	3132	2884	S	0.0	0.0	0:00.01	cron
121	message+	20	0	8816	5412	4724	S	0.0	0.1	0:00.07	dbus-daemon
156	root	20	0	44092	29708	14564	S	0.0	0.4	0:00.26	networkd-dispat
162	root	20	0	18436	9404	8156	S	0.0	0.1	0:00.10	systemd-logind
187	syslog	20	0	220548	5920	4632	S	0.0	0.1	0:00.09	rsyslogd
211	root	20	0	5492	2764	2576	S	0.0	0.0	0:00.00	agetty
232	_chrony	20	0	24248	11684	7112	S	0.0	0.1	0:00.10	chronyd
252	_chrony	20	0	12092	2456	1816	S	0.0	0.0	0:00.01	chronyd
275	root	20	0	123456	32624	18016	S	0.0	0.4	0:00.20	unattended-upgr
367	root	20	0	3184	1108	980	S	0.0	0.0	0:00.00	SessionLeader
368	root	20	0	3200	1248	1108	S	0.0	0.0	0:00.01	Relay(374)
374	j_raksh+	20	0	6268	5536	3864	S	0.0	0.1	0:00.09	bash
375	root	20	0	8644	5524	4684	S	0.0	0.1	0:00.01	login
421	j_raksh+	20	0	22508	13444	10984	S	0.0	0.2	0:00.17	systemd
423	j_raksh+	20	0	22908	4120	2120	S	0.0	0.1	0:00.00	(sd-pam)
451	j_raksh+	20	0	6136	5464	3912	S	0.0	0.1	0:00.04	bash
952	j_raksh+	20	0	8172	6012	3900	R	0.0	0.1	0:00.02	top

```
j_rakshitha@RAKSHITHA:~$ uname -a
Linux RAKSHITHA 6.18.33.2-microsoft-standard-WSL2 #1 SMP PREEMPT_DYNAMIC Thu Jun 18 21:54:43 UTC 2026 x86_64 GNU/Linux
j_rakshitha@RAKSHITHA:~$ lscpu
Architecture:            x86_64
CPU op-mode(s):          32-bit, 64-bit
Address sizes:            39 bits physical, 48 bits virtual
Byte Order:              Little Endian
CPU(s):                  12
On-line CPU(s) list:     0-11
Vendor ID:               GenuineIntel
Model name:              12th Gen Intel(R) Core(TM) i5-12450HX
CPU family:              6
Model:                  151
Thread(s) per core:      2
Core(s) per socket:      6
Socket(s):               1
Stepping:                2
BogoMIPS:                5376.00
Flags:                   fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat pse36 clflush mmx fxsr sse sse2 ss ht syscall nx pdpe1gb rdtsc
cp ln constant_tsc rep_good nopl xtopology tsc_reliable nonstop_tsc cpuid tsc_known_freq pni pclmulqdq vmx ssse3 fma cx16 pcid
sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer aes xsave avx f16c rdrand hypervisor lahf_lm abm 3dnowprefetch srbdt ibrs i
bpb stibp lbrs_enhanced tpr_shadow ept vpid ept_ad fsgsbase tsc_adjust bmi1 avx2 smep bmi2 erms invpcid rdseed adx smap clflush
opt clwb sha_ni xsaveopt xsavec xgetbv1 xsaves avx_vnni vnni umip waitpkg gfni vaes vpclmulqdq rdpid movdiri movdir64b fsrm md_
clear serialize ibt flush_lld arch_capabilities

Virtualization features:
Virtualization:          VT-x
Hypervisor vendor:       Microsoft
Virtualization type:     full
Caches (sum of all):
L1d:                     288 KiB (6 instances)
L1i:                     192 KiB (6 instances)
L2:                       7.5 MiB (6 instances)
L3:                      12 MiB (1 instance)
NUMA:
NUMA node(s):            1
NUMA node0 CPU(s):       0-11
Vulnerabilities:
Gather data sampling:    Not affected
Ghostwrite:             Not affected
Indirect target selection: Not affected
ITlb multihit:          Not affected
L1tf:                   Not affected
Mds:                    Not affected
Meltdown:               Not affected
Mmio stale data:        Not affected
Old microcode:          Not affected
Reg file data sampling:  Mitigation; Clear Register File
Retbleed:               Mitigation; Enhanced IBRS
Spec rstack overflow:   Not affected
Spec store bypass:      Mitigation; Speculative Store Bypass disabled via prctl
Spectre v1:             Mitigation; usercopy/swapgs barriers and __user pointer sanitization
Spectre v2:             Mitigation; Enhanced / Automatic IBRS; IBPB conditional; PBRSP-eIBRS SW sequence; BHI BHI_DIS_S
Srbds:                  Not affected
Tsx:                    Not affected
Tsx async abort:        Not affected
```

Task 2

```
j_rakshitha@RAKSHITHA:~/ossp_project$ strace -V
Command 'strace' not found, but can be installed with:
sudo apt install strace
j_rakshitha@RAKSHITHA:~/ossp_project$ sudo apt install strace
Installing:
  strace

Installing dependencies:
  libunwind8

Summary:
  Upgrading: 0, Installing: 2, Removing: 0, Not Upgrading: 40
  Download size: 737 kB
  Space needed: 2660 kB / 1024 GB available

Continue? [Y/n] Y
Get:1 http://archive.ubuntu.com/ubuntu resolute/main amd64 libunwind8 amd64 1.8.3-0ubuntu1 [59.6 kB]
Get:2 http://archive.ubuntu.com/ubuntu resolute/main amd64 strace amd64 6.19+ds-0ubuntu5 [678 kB]
Fetched 737 kB in 1s (514 kB/s)
Selecting previously unselected package libunwind8:amd64.
(Reading database ... 43151 files and directories currently installed.)
Preparing to unpack .../libunwind8_1.8.3-0ubuntu1_amd64.deb ...
Unpacking libunwind8:amd64 (1.8.3-0ubuntu1) ...
Selecting previously unselected package strace.
Preparing to unpack .../strace_6.19+ds-0ubuntu5_amd64.deb ...
Unpacking strace (6.19+ds-0ubuntu5) ...
Setting up libunwind8:amd64 (1.8.3-0ubuntu1) ...
Setting up strace (6.19+ds-0ubuntu5) ...
Processing triggers for man-db (2.13.1-1build1) ...
Processing triggers for libc-bin (2.43-2ubuntu2.3) ...
j_rakshitha@RAKSHITHA:~/ossp_project$ strace -V
strace -- version 6.19
Copyright (c) 1991-2026 The strace developers <https://strace.io>.
This is free software; see the source for copying conditions.  There is NO
warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

Optional features enabled: stack-trace=libunwind stack-demangle m32-mpers mx32-mper
s
```

```

j_rakshitha@RAKSHITHA:~/ossp_project$ strace cat sample.txt
execve("/usr/bin/cat", ["cat", "sample.txt"], 0x7ffdc60887a8 /* 27 vars */) = 0
brk(NULL)                               = 0x58b52e244000
mmap(NULL, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) = 0x738b371af000
access("/etc/ld.so.preload", R_OK)      = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/etc/ld.so.cache", O_RDONLY|O_CLOEXEC) = 3
fstat(3, {st_mode=S_IFREG|0644, st_size=21555, ...}) = 0
mmap(NULL, 21555, PROT_READ, MAP_PRIVATE, 3, 0) = 0x738b371a9000
close(3)                                = 0
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libselinux.so.1", O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\0\0\0\0\0\0\0"..., 832) = 832
fstat(3, {st_mode=S_IFREG|0644, st_size=199120, ...}) = 0
mmap(NULL, 206288, PROT_READ, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x738b37176000
mmap(0x738b3717d000, 135168, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x7000) = 0x738b3717d000
mmap(0x738b3719e000, 28672, PROT_READ, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x28000) = 0x738b3719e000
mmap(0x738b371a5000, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2f000) = 0x738b371a5000
mmap(0x738b371a7000, 5584, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x738b371a7000
close(3)                                = 0
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libgcc_s.so.1", O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\0\0\0\0\0\0\0"..., 832) = 832
fstat(3, {st_mode=S_IFREG|0644, st_size=187120, ...}) = 0
mmap(NULL, 185256, PROT_READ, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x738b37148000
mmap(0x738b3714c000, 147456, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4000) = 0x738b3714c000
mmap(0x738b37170000, 16384, PROT_READ, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x28000) = 0x738b37170000
mmap(0x738b37174000, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2c000) = 0x738b37174000
close(3)                                = 0
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libm.so.6", O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\3\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\0\0\0\0\0\0\0"..., 832) = 832
fstat(3, {st_mode=S_IFREG|0644, st_size=1198376, ...}) = 0
mmap(NULL, 1200152, PROT_READ, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x738b37022000

```

```

TE, 3, 0x12000) = 0x738b37034000
mmap(0x738b370d4000, 466944, PROT_READ, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xb2000) = 0x738b370d4000
mmap(0x738b37146000, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x123000) = 0x738b37146000
close(3) = 0
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libc.so.6", O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\3\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0 \250\2\0\0\0\0"... , 832) = 832
pread64(3, "\6\0\0\0\4\0\0\0@\0\0\0\0\0\0\0@\0\0\0\0\0\0\0@\0\0\0\0\0\0\0"... , 840, 64) = 840
fstat(3, {st_mode=S_IFREG|0755, st_size=2186512, ...}) = 0
pread64(3, "\6\0\0\0\4\0\0\0@\0\0\0\0\0\0\0@\0\0\0\0\0\0\0@\0\0\0\0\0\0\0"... , 840, 64) = 840
mmap(NULL, 2231696, PROT_READ, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x738b36e00000
mmap(0x738b36e28000, 1671168, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x28000) = 0x738b36e28000
mmap(0x738b36fc0000, 319488, PROT_READ, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xc0000) = 0x738b36fc0000
mmap(0x738b3700e000, 24576, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x20d000) = 0x738b3700e000
mmap(0x738b37014000, 52624, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x738b37014000
close(3) = 0
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libpcr2-8.so.0", O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\0\0\0\0\0\0\0"... , 832) = 832
fstat(3, {st_mode=S_IFREG|0644, st_size=699056, ...}) = 0
mmap(NULL, 701112, PROT_READ, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x738b36d54000
mmap(0x738b36d57000, 507904, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3000) = 0x738b36d57000
mmap(0x738b36dd3000, 176128, PROT_READ, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x7f000) = 0x738b36dd3000
mmap(0x738b36dfe000, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xa9000) = 0x738b36dfe000
close(3) = 0
mmap(NULL, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) = 0x738b36d52000
mmap(NULL, 12288, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) = 0x738b36d4f000
arch_prctl(ARCH_SET_FS, 0x738b36d4fb00) = 0
set_tid_address(0x738b36d50128) = 4171
set_robust_list(0x738b36d4fde0, 24) = 0

```

```

mprotect(0x738b37146000, 4096, PROT_READ) = 0
mprotect(0x738b37174000, 4096, PROT_READ) = 0
mprotect(0x738b371a5000, 4096, PROT_READ) = 0
mprotect(0x58b4ef51c000, 1462272, PROT_READ) = 0
mprotect(0x738b371f4000, 8192, PROT_READ) = 0
prlimit64(0, RLIMIT_STACK, NULL, {rlim_cur=8192*1024, rlim_max=RLIM64_INFINITY}) =
0
getrandom("\xcd\xe3\xb2\x79\xa0\x1b\x8b\x6a", 8, GRND_NONBLOCK) = 8
munmap(0x738b371a9000, 21555) = 0
statfs("/sys/fs/selinux", {f_type=SYSFS_MAGIC, f_bsize=4096, f_blocks=0, f_bfree=0,
f_bavail=0, f_files=0, f_ffree=0, f_fsid={val=[0xe4dd8142, 0xec3f5a0e]}, f_namelen
=255, f_frsize=4096, f_flags=ST_VALID|ST_NOSUID|ST_NODEV|ST_NOEXEC|ST_NOATIME}) = 0
statfs("/selinux", 0x7ffc84c46ca0) = -1 ENOENT (No such file or directory)
brk(NULL) = 0x58b52e244000
brk(0x58b52e265000) = 0x58b52e265000
openat(AT_FDCWD, "/proc/filesystems", O_RDONLY|O_CLOEXEC) = 3
fstat(3, {st_mode=S_IFREG|0444, st_size=0, ...}) = 0
read(3, "nodev\tsysfs\nnodev\ttmpfs\nnodev\tbd"... , 1024) = 442
lseek(3, 0, SEEK_CUR) = 442
lseek(3, 416, SEEK_SET) = 416
close(3) = 0
openat(AT_FDCWD, "/proc/mounts", O_RDONLY|O_CLOEXEC) = 3
fstat(3, {st_mode=S_IFREG|0444, st_size=0, ...}) = 0
read(3, "none /usr/lib/modules/6.18.33.2-"... , 1024) = 1024
read(3, "e 0 0\ndevpts /dev/pts devpts rw,"... , 1024) = 1024
read(3, ",access=client,msize=65536,trans"... , 1024) = 1024
read(3, "700,noswap 0 0\ntmpfs /run/user/1"... , 1024) = 250
read(3, "", 1024) = 0
close(3) = 0
access("/etc/selinux/config", F_OK) = -1 ENOENT (No such file or directory)
fcntl(0, F_GETFD) = 0
fcntl(1, F_GETFD) = 0
fcntl(2, F_GETFD) = 0
rt_sigaction(SIGPIPE, NULL, {sa_handler=SIG_DFL, sa_mask=[], sa_flags=0}, 8) = 0
poll([{fd=0, events=0}, {fd=1, events=0}, {fd=2, events=0}], 3, 0) = 0 (Timeout)
rt_sigaction(SIGPIPE, {sa_handler=SIG_IGN, sa_mask=[PIPE], sa_flags=SA_RESTORER|SA_
RESTART, sa_restorer=0x738b36e45cb0}, {sa_handler=SIG_DFL, sa_mask=[], sa_flags=0},
8) = 0
openat(AT_FDCWD, "/proc/self/maps", O_RDONLY|O_CLOEXEC) = 3
prlimit64(0, RLIMIT_STACK, NULL, {rlim_cur=8192*1024, rlim_max=RLIM64_INFINITY}) =
0
fstat(3, {st_mode=S_IFREG|0444, st_size=0, ...}) = 0
read(3, "58b4eebb3000-58b4eeca5000 r--p 0"... , 1024) = 1024
read(3, "r/lib/x86_64-linux-gnu/libpcr2-"... , 1024) = 1024

```



```

openat(AT_FDCWD, "/usr/share/coreutils/locales/uucore/en-US.ftl", O_RDONLY|O_CLOEXEC) = 3
statx(3, "", AT_STATX_SYNC_AS_STAT|AT_EMPTY_PATH, STATX_ALL, {stx_mask=STATX_ALL|STATX_MNT_ID, stx_attributes=0, stx_mode=S_IFREG|0644, stx_size=4080, ...}) = 0
read(3, "# Common strings shared across a...", 4080) = 4080
read(3, "", 32) = 0
close(3) = 0
statx(AT_FDCWD, "/usr/share/coreutils/locales/cat", AT_STATX_SYNC_AS_STAT, STATX_ALL, {stx_mask=STATX_ALL|STATX_MNT_ID, stx_attributes=0, stx_mode=S_IFDIR|0755, stx_size=4096, ...}) = 0
openat(AT_FDCWD, "/usr/share/coreutils/locales/cat/en-US.ftl", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
rt_sigaction(SIGPIPE, {sa_handler=SIG_DFL, sa_mask=[PIPE], sa_flags=SA_RESTORER|SA_RESTART, sa_restorer=0x738b36e45cb0}, {sa_handler=SIG_IGN, sa_mask=[PIPE], sa_flags=SA_RESTORER|SA_RESTART, sa_restorer=0x738b36e45cb0}, 8) = 0
rt_sigaction(SIGSEGV, {sa_handler=SIG_DFL, sa_mask=~[RTMIN RT_1], sa_flags=SA_RESTORER, sa_restorer=0x738b36e45cb0}, {sa_handler=0x58b4eed80c0, sa_mask=[], sa_flags=SA_RESTORER|SA_ONSTACK|SA_SIGINFO, sa_restorer=0x738b36e45cb0}, 8) = 0
rt_sigaction(SIGBUS, {sa_handler=SIG_DFL, sa_mask=~[RTMIN RT_1], sa_flags=SA_RESTORER, sa_restorer=0x738b36e45cb0}, {sa_handler=0x58b4eed80c0, sa_mask=[], sa_flags=SA_RESTORER|SA_ONSTACK|SA_SIGINFO, sa_restorer=0x738b36e45cb0}, 8) = 0
ioctl(1, TCGETS2, {c_iflag=ICRNL|IXON, c_oflag=NL0|CR0|TAB0|BS0|VT0|FF0|OPOST|ONLCR, c_cflag=B38400|CS8|CREAD, c_lflag=ISIG|ICANON|ECHO|ECHOE|ECHOK|IEXTEN|ECHOCTL|ECHO, ...}) = 0
brk(0x58b52e286000) = 0x58b52e286000
statx(AT_FDCWD, "sample.txt", AT_STATX_SYNC_AS_STAT, STATX_ALL, {stx_mask=STATX_ALL|STATX_MNT_ID, stx_attributes=0, stx_mode=S_IFREG|0644, stx_size=51, ...}) = 0
openat(AT_FDCWD, "sample.txt", O_RDONLY|O_CLOEXEC) = 3
fstat(3, {st_mode=S_IFREG|0644, st_size=51, ...}) = 0
fstat(1, {st_mode=S_IFCHR|0620, st_rdev=makedev(0x88, 0x2), ...}) = 0
splice(3, NULL, 1, NULL, 1048576, 0) = -1 EINVAL (Invalid argument)
pipe([4, 5]) = 0
fcntl(4, F_SETPIPE_SZ, 1048576) = 1048576
splice(3, NULL, 5, NULL, 1048576, 0) = 51
splice(4, NULL, 1, NULL, 51, 0This is a sample file for the OSSP file copy task.
) = 51
splice(3, NULL, 5, NULL, 1048576, 0) = 0
close(5) = 0
close(4) = 0
close(3) = 0
sigaltstack({ss_sp=NULL, ss_flags=SS_DISABLE, ss_size=8192}, NULL) = 0
munmap(0x738b371ac000, 12288) = 0
exit_group(0) = ?
+++ exited with 0 +++
j_rakshitha@RAKSHITHA:~/ossp_project$

```