

Rajalakshmi Engineering College

Name: RAKSHITHA R
Email: 240701418@rajalakshmi.edu.in
Roll no: 240701418
Phone: 7305274265
Branch: REC
Department: CSE - Section 8
Batch: 2028
Degree: B.E - CSE

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 5_PAH

Attempt : 1
Total Mark : 50
Marks Obtained : 50

Section 1 : Coding

1. Problem Statement

Each customer at the bank has an Account Number, Customer Name, and an Initial Balance. The bank allows two types of transactions:

Deposit – Increases the balance. Withdrawal – Decreases the balance, but only if enough funds are available. If the withdrawal amount exceeds the available balance, the transaction should be skipped, and the balance should remain unchanged.

You are required to implement this banking system by:

Creating a class with the necessary attributes to store account details.

Using a constructor to initialize the account details when a new account is created. Providing setter methods to update the details if required. Providing getter methods to retrieve account details. Creating

objects of this class to represent different customers, where each customer can perform deposits and withdrawals.

Instructions:

Implement the class to store account details. Implement the logic for performing deposit and withdrawal transactions. Ensure that withdrawals don't exceed the available balance. After performing the transactions, print the account number, customer name, and final balance.

Input Format

The first line of input contains an integer N, representing the number of customers.

For each customer:

- The next line contains the account number (integer).
- The following line contains the customer name (string).
- The next line contains the initial balance (double).
- The next line contains the deposit amount (double).
- The next line contains the withdrawal amount (double).

Output Format

For each customer, print the details in the following format:

1. Account Number: <account_number>
2. Customer Name: <customer_name>
3. Final Balance: <final_balance> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

1234

Rahul Sharma

5000

2000

3000

Output: Account Number: 1234

Customer Name: Rahul Sharma
Final Balance: 4000.0

Answer

```
import java.util.Scanner;

class Account {
    int accountNumber;
    String customerName;
    double balance;

    Account(int accountNumber, String customerName, double balance) {
        this.accountNumber = accountNumber;
        this.customerName = customerName;
        this.balance = balance;
    }

    void deposit(double amount) {
        balance += amount;
    }

    void withdraw(double amount) {
        if (amount <= balance) {
            balance -= amount;
        }
    }

    void display() {
        System.out.println("Account Number: " + accountNumber);
        System.out.println("Customer Name: " + customerName);
        System.out.printf("Final Balance: %.1f%n", balance);
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int n = sc.nextInt();
        sc.nextLine();

        for (int i = 0; i < n; i++) {
            int accNo = sc.nextInt();
```

```

        sc.nextLine();
        String name = sc.nextLine();
        double initial = sc.nextDouble();
        double deposit = sc.nextDouble();
        double withdraw = sc.nextDouble();

        Account acc = new Account(accNo, name, initial);
        acc.deposit(deposit);
        acc.withdraw(withdraw);
        acc.display();
    }
}

```

Status : Correct

Marks : 10/10

2. Problem Statement

Neha is working as a developer for CityMovie Theatre, which wants to build a system to calculate total ticket cost for movie-goers based on the number of tickets and type of seats booked.

Each customer's booking has:

Booking ID (integer) Customer Name (string) Number of Tickets (integer) Seat Type (string: "Standard", "Premium", "VIP")

The ticket prices are:

Standard – 250 units per ticket Premium – 400 units per ticket VIP – 600 units per ticket

The calculation rules:

Total Amount = Number of Tickets × Seat Price

If a customer books more than 4 tickets, they get a 10% discount on the total amount.

If the booking is for VIP seats and the total amount exceeds 3000 units, a

5% luxury tax is added after any discount.

Neha has been asked to implement this system using:

A class with attributes for booking details. A constructor to initialize booking details. Getter and Setter methods to retrieve and update booking details if required. A method to calculate the final ticket cost. Objects of the class to represent bookings.

Finally, display each customer's details and final ticket amount.

Input Format

The first line contains an integer N, representing the number of bookings.

For each booking:

- The next line contains the Booking ID (integer).
- The next line contains the Customer Name (string).
- The next line contains Number of Tickets (integer).
- The next line contains Seat Type ("Standard", "Premium", or "VIP").

Output Format

For each booking, print:

- Booking ID: <booking_id>
- Customer Name: <customer_name>
- Final Ticket Amount: <final_amount> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

1001

Ravi Kumar

3

Standard

Output: Booking ID: 1001

Customer Name: Ravi Kumar

Final Ticket Amount: 750.0

Answer

```
import java.util.Scanner;
```

```
class Booking {  
    int bookingId;  
    String customerName;  
    int numTickets;  
    String seatType;
```

```
    Booking(int bookingId, String customerName, int numTickets, String seatType)  
    {  
        this.bookingId = bookingId;  
        this.customerName = customerName;  
        this.numTickets = numTickets;  
        this.seatType = seatType;  
    }
```

```
    double calculateFinalAmount() {  
        double price = 0;  
        if (seatType.equals("Standard")) price = 250;  
        else if (seatType.equals("Premium")) price = 400;  
        else if (seatType.equals("VIP")) price = 600;  
  
        double total = numTickets * price;  
  
        if (numTickets > 4) {  
            total = total * 0.9;  
        }  
  
        if (seatType.equals("VIP") && total > 3000) {  
            total = total * 1.05;  
        }  
  
        return Math.round(total * 10.0) / 10.0;  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);
```

```

int n = sc.nextInt();
sc.nextLine();

for (int i = 0; i < n; i++) {
    int id = sc.nextInt();
    sc.nextLine();
    String name = sc.nextLine();
    int tickets = sc.nextInt();
    sc.nextLine();
    String type = sc.nextLine();

    Booking b = new Booking(id, name, tickets, type);

    System.out.println("Booking ID: " + b.bookingId);
    System.out.println("Customer Name: " + b.customerName);
    System.out.println("Final Ticket Amount: " + b.calculateFinalAmount());
}
}
}

```

Status : Correct

Marks : 10/10

3. Problem Statement

Ravi is working as a developer for SecureLogin Systems, which wants to build a system to evaluate the strength of user passwords.

Each user record has:

User ID (integer) User Name (string) Password (string)

The system must calculate whether a password is strong or weak.

A password is considered strong if it meets all of the following conditions:

At least 8 characters long. Contains at least one uppercase letter. Contains at least one lowercase letter. Contains at least one digit. Contains at least one special character (from !@#\$%^&*).

Ravi has been asked to implement this system using:

A class with attributes for user details. A constructor to initialize user details. Getter and setter methods to retrieve or update user details. A method to check whether the password is strong. Objects of the class to represent users.

Finally, display each user's details and indicate whether their password is Strong or Weak.

Input Format

The first line contains an integer N, representing the number of users.

For each user:

The next line contains the User ID (integer).

The next line contains the User Name (string).

The next line contains the Password (string).

Output Format

For each user, print the details in the following format:

User ID: <user_id>

User Name: <user_name>

Password: <password>

Password Strength: <Strong/Weak>

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

1001

Ravi Kumar

Abc@1234

Output: User ID: 1001

User Name: Ravi Kumar
Password: Abc@1234
Password Strength: Strong

Answer

```
// You are using Java  
import java.util.Scanner;
```

```
class User {  
    int userId;  
    String userName;  
    String password;
```

```
    User(int userId, String userName, String password) {  
        this.userId = userId;  
        this.userName = userName;  
        this.password = password;  
    }
```

```
    String checkPasswordStrength() {  
        if (password.length() < 8) return "Weak";
```

```
        boolean hasUpper = false, hasLower = false, hasDigit = false, hasSpecial =  
false;
```

```
        String specialChars = "!@#$%^&*";
```

```
        for (int i = 0; i < password.length(); i++) {  
            char c = password.charAt(i);  
            if (Character.isUpperCase(c)) hasUpper = true;  
            else if (Character.isLowerCase(c)) hasLower = true;  
            else if (Character.isDigit(c)) hasDigit = true;  
            else if (specialChars.indexOf(c) >= 0) hasSpecial = true;  
        }
```

```
        if (hasUpper && hasLower && hasDigit && hasSpecial) return "Strong";  
        else return "Weak";  
    }
```

```
    void display() {  
        System.out.println("User ID: " + userId);  
        System.out.println("User Name: " + userName);  
        System.out.println("Password: " + password);
```

```

        System.out.println("Password Strength: " + checkPasswordStrength());
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int n = sc.nextInt();
        sc.nextLine();

        for (int i = 0; i < n; i++) {
            int id = sc.nextInt();
            sc.nextLine();
            String name = sc.nextLine();
            String pass = sc.nextLine();

            User u = new User(id, name, pass);
            u.display();
        }
    }
}

```

Status : Correct

Marks : 10/10

4. Problem Statement

Neha is working as a developer for CityQuiz Platform, which wants to build a system to calculate quiz scores and identify top scorers among participants.

Each participant's record has:

Participant ID (integer) Participant Name (string) An array of scores in 5 quiz rounds (integers, each between 0 and 100)

The system must calculate:

Total Score = sum of scores in all 5 rounds. Average Score = Total Score ÷

5.If a participant scores above 80 in all rounds, a bonus of 10 points is added to the total score. Identify the Top Scorer among all participants. If two participants have the same total score, the one with the lower Participant ID is considered the top scorer.

Neha has been asked to implement this system using:

A class with attributes for participant details. A constructor to initialize participant details. Getter and setter methods to retrieve or update participant details. A method to calculate total score and average score (including bonus if applicable). Objects of the class to represent participants.

Finally, display each participant's details and announce the Top Scorer.

Input Format

The first line of input contains an integer N, representing the number of participants.

For each participant:

- Next line: Participant ID (integer)
- Next line: Participant Name (string)
- Next line: 5 integers separated by spaces (scores for 5 quiz rounds)

Output Format

For each participant:

- Participant ID: <participant_id>
- Participant Name: <participant_name>
- Total Score: <total_score>
- Average Score: <average_score>

Finally, print "Top Scorer: <participant_name> with <total_score> points"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

1001

Ravi Kumar

85 90 88 92 87

Output: Participant ID: 1001

Participant Name: Ravi Kumar

Total Score: 452

Average Score: 90

Top Scorer: Ravi Kumar with 452 points

Answer

```
import java.util.Scanner;
```

```
class Participant {  
    int participantId;  
    String participantName;  
    int[] scores = new int[5];  
    int totalScore;  
    int averageScore;
```

```
    Participant(int participantId, String participantName, int[] scores) {  
        this.participantId = participantId;  
        this.participantName = participantName;  
        this.scores = scores;  
        calculateScores();  
    }
```

```
    void calculateScores() {  
        totalScore = 0;  
        boolean allAbove80 = true;  
        for (int s : scores) {  
            totalScore += s;  
            if (s <= 80) allAbove80 = false;  
        }  
        if (allAbove80) totalScore += 10;  
        averageScore = totalScore / 5;  
    }
```

```
    void display() {
```

```

        System.out.println("Participant ID: " + participantId);
        System.out.println("Participant Name: " + participantName);
        System.out.println("Total Score: " + totalScore);
        System.out.println("Average Score: " + averageScore);
    }
}

```

```

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        sc.nextLine();

        Participant topScorer = null;

        for (int i = 0; i < n; i++) {
            int id = sc.nextInt();
            String firstName = sc.next();
            String lastName = sc.next();
            String name = firstName + " " + lastName;

```

```

            int[] scores = new int[5];
            for (int j = 0; j < 5; j++) {
                scores[j] = sc.nextInt();
            }

            Participant p = new Participant(id, name, scores);

            p.display();

            if (topScorer == null || p.totalScore > topScorer.totalScore
                || (p.totalScore == topScorer.totalScore && p.participantId <
                    topScorer.participantId)) {
                topScorer = p;
            }
        }
    }
}

```

```

        System.out.println("Top Scorer: " + topScorer.participantName + " with " +
            topScorer.totalScore + " points");
    }
}

```

Status : Correct

Marks : 10/10

5. Problem Statement

Anjali is working as a developer for CityFitness Gym, which wants to build a system to calculate monthly membership fees for gym members based on the type of membership and the number of personal training sessions booked.

Each member's record has:

Member ID (integer) Member Name (string) Membership Type (string: "Basic", "Premium", "Elite") Number of Personal Training Sessions (integer)

The monthly fees are:

Basic – 1000 units Premium – 1500 units Elite – 2000 units

The cost of personal training sessions is 500 units per session.

The calculation rules:

Total Amount = Membership Fee + (Number of Personal Training Sessions × 500) If the number of sessions is more than 5, a 10% discount is applied on the total amount. If the member has Elite membership and the total amount exceeds 4000, an additional 5% service tax is added after discount.

Anjali has been asked to implement this system using:

A class with attributes for member details. A constructor to initialize member details. Getter and Setter methods to retrieve and update member details if required. A method to calculate the final monthly fee. Objects of the class to represent members.

Finally, display each member's details and the final monthly fee.

Input Format

The first line contains an integer N, representing the number of members.

For each member:

- Next line contains Member ID (integer)
- Next line contains Member Name (string)
- Next line contains Membership Type ("Basic", "Premium", "Elite")
- Next line contains Number of Personal Training Sessions (integer)

Output Format

For each member, print:

- Member ID: <member_id>
- Member Name: <member_name>
- Final Monthly Fee: <final_fee> (The final fee must be rounded to one decimal place)

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

1001

Ravi Kumar

Basic

3

Output: Member ID: 1001

Member Name: Ravi Kumar

Final Monthly Fee: 2500.0

Answer

```
// You are using Java
import java.util.Scanner;
```

```
class Member {
    int memberId;
    String memberName;
    String membershipType;
    int personalSessions;
```

```
    Member(int memberId, String memberName, String membershipType, int
personalSessions) {
        this.memberId = memberId;
```

```
this.memberName = memberName;  
this.membershipType = membershipType;  
this.personalSessions = personalSessions;  
}
```

```
double calculateFinalFee() {  
    double membershipFee = 0;  
    switch (membershipType) {  
        case "Basic": membershipFee = 1000; break;  
        case "Premium": membershipFee = 1500; break;  
        case "Elite": membershipFee = 2000; break;  
    }  
}
```

```
double total = membershipFee + (personalSessions * 500);  
if (personalSessions > 5) total *= 0.9;  
if (membershipType.equals("Elite") && total > 4000) total *= 1.05;  
  
return Math.round(total * 10.0) / 10.0;  
}
```

```
void display() {  
    System.out.println("Member ID: " + memberId);  
    System.out.println("Member Name: " + memberName);  
    System.out.println("Final Monthly Fee: " + calculateFinalFee());  
}  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);  
        int n = sc.nextInt();  
        sc.nextLine();  
  
        for (int i = 0; i < n; i++) {  
            int id = sc.nextInt();  
            String firstName = sc.next();  
            String lastName = sc.next();  
            String name = firstName + " " + lastName;  
  
            String membershipType = sc.next();  
            int sessions = sc.nextInt();  
        }  
    }  
}
```



```
Member m = new Member(id, name, membershipType, sessions);  
m.display();
```

```
}
```

```
}
```

```
}
```

Status : Correct

Marks : 10/10