

1.Pod file

```
apiVersion: v1
kind: Pod
metadata:
  name: pod1
  namespace: dev
spec:
  containers:
    - name:
      image:
      ports:
        - containerPort:
```

Service files

2. Pod file for Service file

```
apiVersion: v1
kind: Pod
metadata:
  name: pod1
  namespace: dev
  labels:
    app: web
spec:
  containers:
    - name:
      image:
      ports:
        - containerPort:
```

3. Service file for ClusterIP

```
apiVersion: v1
kind: Service
metadata:
  name: s1
spec:
  type: ClusterIP
  ports:
    - port:
      targetPort:
  selector:
    app: web
```

4. Service file for Nodeport

```
apiVersion: v1
kind: Service
metadata:
  name: s1
spec:
  type: NodePort
  ports:
    - port:
      targetPort:
      nodePort: 30000-32767
  selector:
    app: web
```

5. Service file for Loadbalancer

```
apiVersion: v1
```

```
kind: Service
metadata:
  name: s1
spec:
  type: LoadBalancer
  ports:
    - port:
      targetPort:
  selector:
    app: web
```

6. Replication controller

```
apiVersion: v1
kind: ReplicationController
metadata:
  name: rc
spec:
  replicas: 3
  selector:
    app: web
  template:
    metadata:
      labels:
        app: web
    spec:
      containers:
        - name:
          image:
          ports:
            - containerPort:
```

7. ReplicaSet

```
apiVersion: apps/v1
kind: ReplicaSet
metadata:
  name: rs
spec:
  replicas: 3
  selector:
    matchLabels:
      app: web
  template:
    metadata:
      labels:
        app: web
    spec:
      containers:
        - name:
          image:
          ports:
            - containerPort:
```

8. Deployment file for Replicaset

```
apiVersion: apps/v1
kind: Deployment
metadata:
  name: d1
spec:
  replicas: 3
  selector:
    matchLabels:
```

```

        app: web
template:
  metadata:
    labels:
      app: web
  spec:
    containers:
      - name:
        image:
        ports:
          - containerPort:

```

9. NameSpace file

```

apiVersion: v1
kind: Namespace
metadata:
  name: dev

```

10. Deployment file for Namespace

```

apiVersion: apps/v1
kind: Deployment
metadata:
  name: d1
  namespace: dev
spec:
  replicas: 3
  selector:
    matchLabels:
      app: web
  template:
    metadata:
      labels:
        app: web
    spec:
      containers:
        - name:
          image:
          ports:
            - containerPort:

```

11. ConfigMap file

```

apiVersion: v1
kind: ConfigMap
metadata:
  name: cmname
data:
  key1: "value1"
  key2: "value2"

```

12. To Inject variables to pods [complete config file]

```

apiVersion: apps/v1
kind: Deployment
metadata:
  name: d1
spec:
  replicas: 3
  selector:
    matchLabels:
      app: web
  template:

```

```

metadata:
  labels:
    app: web
spec:
  containers:
    - name:
      image:
      ports:
        - containerPort:
      envFrom:
        - configMapRef:
            name: cmname

```

13. To Inject particular variables to pods

```

apiVersion: apps/v1
kind: Deployment
metadata:
  name: d1
spec:
  replicas: 3
  selector:
    matchLabels:
      app: web
  template:
    metadata:
      labels:
        app: web
    spec:
      containers:
        - name:
          image:
          ports:
            - containerPort:
          env:
            - name: keyname
              valueFrom:
                configMapKeyRef:
                  name: cmname
                  key: keyname

```

14. Secret file

```

apiVersion: v1
kind: Secret
metadata:
  name: s1
type: Opaque
stringData:
  key: value

```

15. To Inject variables to pods [complete secret file]

```

apiVersion: apps/v1
kind: Deployment
metadata:
  name: d1
spec:
  replicas: 3
  selector:
    matchLabels:
      app: web
  template:
    metadata:

```

```

    labels:
      app: web
  spec:
    containers:
      - name:
        image:
        ports:
          - containerPort:
        envFrom:
          - secretRef:
              name: secretname

```

16. To Inject particular variables to pods [secret file]

```

apiVersion: apps/v1
kind: Deployment
metadata:
  name: d1
spec:
  replicas: 3
  selector:
    matchLabels:
      app: web
  template:
    metadata:
      labels:
        app: web
    spec:
      containers:
        - name:
          image:
          ports:
            - containerPort:
          env:
            - name: keyname
              valueFrom:
                secretKeyRef:
                  name: secretname
                  key: keyname

```

VOLUMES

17. Deployment file for emptyDir

```

apiVersion: apps/v1
kind: Deployment
metadata:
  name: d1
spec:
  replicas: 3
  selector:
    matchLabels:
      app: web
  template:
    metadata:
      labels:
        app: web
    spec:
      containers:
        - name: c1
          image: ubuntu
          command: ["/bin/bash", '-c', "while true; do echo hello;sleep 300;
done"]

```

```

        volumeMounts:
          - name: vname
            mountPath: /data/path
      - name: c2
        image: amazonlinux
        command: ["/bin/bash", '-c', "while true; do echo hello;sleep 300;
done"]
        volumeMounts:
          - name: vname
            mountPath: /data/path
    volumes:
      - name: vname
        emptyDir: {}

```

18. Deployment file for hostPath

```

apiVersion: apps/v1
kind: Deployment
metadata:
  name: d1
spec:
  replicas: 3
  selector:
    matchLabels:
      app: web
  template:
    metadata:
      labels:
        app: web
    spec:
      containers:
        - name: c1
          image: ubuntu
          command: ["/bin/bash", '-c', "while true; do echo hello;sleep 300;
done"]
          volumeMounts:
            - name: vname
              mountPath: /data/path
        - name: c2
          image: amazonlinux
          command: ["/bin/bash", '-c', "while true; do echo hello;sleep 300;
done"]
          volumeMounts:
            - name: vname
              mountPath: /data/path
      volumes:
        - name: vname
          hostPath:
            path: /data/vol

```

19. Persistent volume

```

apiVersion: v1
kind: PersistentVolume
metadata:
  name: pv1
spec:
  capacity:
    storage: 10Gi
  accessModes:
    - ReadWriteOnce
  awsElasticBlockStore:

```

```
    volumeID:
    fsType: ext4
persistentVolumeReclaimPolicy: Recycle
```

20. Persistent volume claim

```
apiVersion: v1
kind: PersistentVolumeClaim
metadata:
  name: pvc1
spec:
  accessModes:
    - ReadWriteOnce
  resources:
    requests:
      storage: 5Gi
```

21. Deployment file for Persistent volume claim

```
apiVersion: apps/v1
kind: Deployment
metadata:
  name: d1
spec:
  replicas: 3
  selector:
    matchLabels:
      app: web
  template:
    metadata:
      labels:
        app: web
    spec:
      containers:
        - name: c1
          image: ubuntu
          command: ["/bin/bash", '-c', "while true; do echo hello;sleep 300;
done"]
          volumeMounts:
            - name: vname
              mountPath: /data/path
        - name: c2
          image: amazonlinux
          command: ["/bin/bash", '-c', "while true; do echo hello;sleep 300;
done"]
          volumeMounts:
            - name: vname
              mountPath: /data/path
      volumes:
        - name: vname
          persistentVolumeClaim:
            claimName: pvc1
```

