

# Dash Framework

In this chapter, we will discuss about the Dash framework in detail.

Dash is an open-source Python framework used for building analytical web applications. It is a powerful library that simplifies the development of data-driven applications. Its especially useful for Python data scientists who arent very familiar with web development. Users can create amazing dashboards in their browser using dash.

Built on top of Plotly.js, React, and Flask, Dash ties modern UI elements like dropdowns, sliders and graphs directly to your analytical python code.

Dash apps consist of a Flask server that communicates with front-end React components using JSON packets over HTTP requests.

Dash applications are written purely in python, so NO HTML or JavaScript is necessary.

## Dash Setup

If Dash is not already installed in your terminal, then install the below mentioned Dash libraries. As these libraries are under active development, install and upgrade then frequently. Python 2 and 3 are also supported.

```
■ pip install dash==0.23.1 # The core dash backend
■ pip install dash-renderer==0.13.0 # The dash front-end
■ pip install dash-html-components==0.11.0 # HTML components
■ pip install dash-core-components==0.26.0 # Supercharged components
■ pip install dash-bootstrap-components==0.12.0 # Bootstrap styling library
```

In the next section, we will see how to create a simple Dash application properly, here, we created a simple

Dash is an open-source Python framework used for building analytical web applications. It is a powerful library that simplifies the development of data-driven applications. Its especially useful for Python data scientists who arent very familiar with web development. Users can create amazing dashboards in their browser using dash.

Dash apps consist of a Flask server that communicates with front-end React components using JSON packets over HTTP requests.

## Dash Setup

```

■ pip install dash==0.23.1 # The core dash backend
■ pip install dash-renderer==0.13.0 # The dash front-end
■ pip install dash-html-components==0.11.0 # HTML components
■ pip install dash-table-components==0.26.0 # Supercharged components
■ pip install dash-bootstrap-components==1.4.0 # Bootstrap styling library

```

1/14

## Dash or App Layout

Dash apps are composed of two parts. The first part is the layout of the app which basically describes how the application looks like. The second part describes the interactivity of the application.

## Core Components

We can build the layout with the **dash\_html\_components** and the **dash\_core\_components** library. Dash provides python classes for all the visual components of the application. We can also customize our own components with JavaScript and React.js.

```
import dash_core_components as dcc
```

```
import dash_html_components as html
```

The dash\_html\_components is for all HTML tags where the dash\_core\_components is for interactivity built with React.js.

Using above two libraries, let us write a code as given below –



```
<div>
  <h1> Hello Dash </h1>
  <div> Dash Framework: A web application framework for Python. </div>
</div>
```


## Writing Simple Dash app

We will learn how to write a simple example on dash using above mentioned library in a file **dashApp.py**.

```
# -*- coding: utf-8 -*-
import dash
import dash_core_components as dcc
import dash_html_components as html

app = dash.Dash()
app.layout = html.Div(children=[
    html.H1(children='Hello Dash'),
    html.Div(children='''Dash Framework: A web application framework for
Python.'''),

    dcc.Graph(
        id='example-graph',
        figure={
            'data': [
                {'x': [1, 2, 3], 'y': [4, 1, 2], 'type': 'bar', 'name': 'Delhi'},
                {'x': [1, 2, 3], 'y': [2, 4, 5], 'type': 'bar', 'name':
u'Mumbai'}],
            'layout': {
                'title': 'Dash Data Visualization'
            }
        })
])
```




Note the following points while running the Dash app.

(MyDjangoEnv) C:\Users\rajesh\Desktop\MyDjango\dash>python dashApp1.py

- Serving Flask app "dashApp1" (lazy loading)
- Environment: production  
WARNING: Do not use the development server in a production environment.  
Use a production WSGI server instead.
- Debug mode: on
- Restarting with stat
- Debugger is active!
- Debugger PIN: 130-303-947
- Running on **http://127.0.0.1:8050/** (Press CTRL+C to quit)

```
127.0.0.1 - - [12/Aug/2018 09:32:39] "GET / HTTP/1.1" 200 -
127.0.0.1 - - [12/Aug/2018 09:32:42] "GET /_dash-layout HTTP/1.1" 200 -
127.0.0.1 - - [12/Aug/2018 09:32:42] "GET /_dash-dependencies HTTP/1.1" 200 -
127.0.0.1 - - [12/Aug/2018 09:32:42] "GET /favicon.ico HTTP/1.1" 200 -
127.0.0.1 - - [12/Aug/2018 09:39:52] "GET /favicon.ico HTTP/1.1" 200 -
```

Visit **http:127.0.0.1:8050/** in your web browser. You should see an app that looks like this.



In the following code, the components to be noted are as follows –

of components like `html.Div` and `dcc.Graph`.  
Dash has a component for every HTML tag. The component generates a `<h1> Hello Dash </h1>`

- Not all components are pure HTML. The `dash_core_components` describe higher-level components that are interactive and are generated with JavaScript, HTML, and CSS through the React.js library.
- Each component is described entirely through keyword attributes. Dash is declarative: you will primarily describe your application through these attributes.
- The `children` property is special. By convention, it's always the first attribute which means that you can omit it.
- `Html.H1 (children=Hello Dash)` is the same as `html.H1 (Hello Dash)`.
- The fonts in your application will look a little bit different than what is displayed here. This application is using a custom CSS stylesheet to modify the default styles of the elements. Custom font style is permissible, but as of now, we can add the below URL or any URL of your choice –  
`app.css.append_css`  
`({external_url:https://codepen.io/chriddyp/pen/bwLwgP.css})` to get your file to get the same look and feel of these examples.

## More about HTML

The `dash_html_components` library contains a component class for every HTML tag as well as keyword arguments for all of the HTML arguments.

Let us add the inline style of the components in our previous app text –

```
# -*- coding: utf-8 -*-
import dash
import dash_core_components as dcc
import dash_html_components as html

app = dash.Dash()
colors = {
    'background': '#87D653',
    'text': '#ff0033'
}

# ... (code partially obscured by advertisement) ...
background_color': colors['background']],
```

```

),

html.Div(children='Dash: A web application framework for Python.', style={
    'textAlign': 'center',
    'color': colors['text']
})),


dcc.Graph(
    id='example-graph-2',

    figure={
        'data': [
            {'x': [1, 2, 3], 'y': [4, 1, 2], 'type': 'bar', 'name': 'Delhi'},
            {'x': [1, 2, 3], 'y': [2, 4, 5], 'type': 'bar', 'name':
u'Mumbai'}],
        'layout': {
            'plot_bgcolor': colors['background'],
            'paper_bgcolor': colors['background'],
            'font': {
                'color': colors['text']
            }
        }
    }
)

if __name__ == '__main__':
    app.run_server(debug=True)

```

In the above example, we modified the inline styles of the `html.Div` and `html.H1` components with the `style` property.



- For style property in Dash, you can just supply a dictionary, whereas in HTML, it is semicolon-separated string.
- Style dictionary keys are **camelCased**, so text-align changes to **textalign**.
- ClassName in Dash is similar to HTML class attribute.
- The first argument is the children of the HTML tag which is specified through the children keyword argument.

## Reusable Components

By writing our markup in Python, we can create complex reusable components like tables without switching contexts or languages –

Below is a quick example that generates a Table from pandas dataframe.

```
import dash
import dash_core_components as dcc
import dash_html_components as html
import pandas as pd

df = pd.read_csv(
    'https://gist.githubusercontent.com/chriddyp/'
    'c78bf172206ce24f77d6363a2d754b59/raw/'
    'c353e8ef842413cae56ae3920b8fd78468aa4cb2/'
    'usa-agricultural-exports-2011.csv')

def generate_table(dataframe, max_rows=10):
    return html.Table(
        # Header
        [html.Tr([html.Th(col) for col in dataframe.columns])] +
        # Body
        [html.Tr([
            html.Td(dataframe.iloc[i][col]) for col in dataframe.columns
        ]) for i in range(min(len(dataframe), max_rows))])

generate_table(df, 'usa-agricultural-exports (2011)'),
```

```
if __name__ == '__main__':
    app.run_server(debug=True)
```

Our output will be something like –

Unnamed: 0	state	total exports	beef	pork	poultry	dairy	fruits	fresh fruits	proc total	fruits	veggies	fresh	veggies	proc total	veggies	corn	wheat	cotton
0	Alabama	1390.63	34.4	10.6	481	4.06	8	17.1	25.11	5.5	8.9	14.33	34.9	70	317.61			
1	Alaska	13.31	0.2	0.1	0	0.19	0	0	0	0.6	1	1.56	0	0	0			
2	Arizona	1463.17	71.3	17.9	0	105.48	19.3	41	60.27	147.5	239.4	386.91	7.3	48.7	423.95			
3	Arkansas	3586.02	53.2	29.4	562.9	3.53	2.2	4.7	6.88	4.4	7.1	11.45	69.5	114.5	665.44			
4	California	16472.88	228.7	11.1	225.4	929.95	2791.8	5944.6	8736.4	803.2	1303.5	2106.79	34.6	249.3	1064.95			
5	Colorado	1851.33	261.4	66	14	71.94	5.7	12.2	17.99	45.1	73.2	118.27	183.2	400.5	0			
6	Connecticut	259.62	1.1	0.1	6.9	9.49	4.2	8.9	13.1	4.3	6.9	11.16	0	0	0			
7	Delaware	282.19	0.4	0.6	114.7	2.3	0.5	1	1.53	7.6	12.4	20.03	26.9	22.9	0			
8	Florida	3764.09	42.6	0.9	56.9	66.31	438.2	933.1	1371.36	171.9	279	450.86	3.5	1.8	78.24			
9	Georgia	2860.84	31	18.9	630.4	38.38	74.6	158.9	233.51	59	95.8	154.77	57.8	65.4	1154.07			

## More about Visualization

The `dash_core_components` library includes a component called **Graph**.


Graph renders interactive data visualizations using the open source `plotly.js` JavaScript graphing library. Plotly.js support around 35 chart types and renders charts in both vector-quality SVG and high-performance WebGL.

Below is an example that creates a scatter plot from a Pandas dataframe –

```
import dash
import dash_core_components as dcc
import dash_html_components as html
import pandas as pd
import plotly.graph_objs as go

app = dash.Dash()

df = pd.read_csv(
    'https://gist.githubusercontent.com/chriddyp/' +
    '5d1ea79569ed194d432e56108a04d188/raw/' +
    'a9f9e8076b837d541398e999dcbac2b2826a81f8/' +
```



```
= i]['gdp per capita'],
```




```

y=df[df['continent'] == i]['life expectancy'],
text=df[df['continent'] == i]['country'],
mode='markers',
opacity=0.7,
marker={
    'size': 15,
    'line': {'width': 0.5, 'color': 'white'}
},
name=i
) for i in df.continent.unique()
],
'layout': go.Layout(
    xaxis={'type': 'log', 'title': 'GDP Per Capita'},
    yaxis={'title': 'Life Expectancy'},
    margin={'l': 40, 'b': 40, 't': 10, 'r': 10},
    legend={'x': 0, 'y': 1},
    hovermode='closest'
)
}
)
])

if __name__ == '__main__':
    app.run_server()

```

The output of the above code is as follows –



The above plot shows the relationship between GDP Per Capita and Life Expectancy. You can hover over points to see their values, click and drag to zoom, hold down shift, and click to pan.

M

While dash exposes HTML flavours through the `dash_html_components` library, it can be tedious to write your copy in HTML. For writing blocks of texts, you can use the Markdown component in the `dash_core_components` library.

## Core Components

The `dash_core_components` includes a set of higher-level components like dropdowns, graphs, markdown, blocks and many more.

Like all other Dash components, they are described entirely declaratively. Every option that is configurable is available as a keyword argument of the component.

Below is the example, using some of the available components –

```
# -*- coding: utf-8 -*-
import dash
import dash_core_components as dcc
import dash_html_components as html

app = dash.Dash()

app.layout = html.Div([
    html.Label('Dropdown'),
    dcc.Dropdown(
        options=[
            {'label': 'New York City', 'value': 'NYC'},
            {'label': u'Montral', 'value': 'MTL'},
            {'label': 'San Francisco', 'value': 'SF'}
        ],
        value='MTL'
    ),

    html.Label('Multi-Select Dropdown'),
    dcc.Dropdown(
        options=[
            {'label': 'New York City', 'value': 'NYC'},
            {'label': 'Montral', 'value': 'MTL'},
            {'label': 'San Francisco', 'value': 'SF'}
        ],
        value='NYC'
    )
])
```



```

html.Label('Radio Items'),
dcc.RadioItems(
    options=[
        {'label': 'New York City', 'value': 'NYC'},
        {'label': u'Montral', 'value': 'MTL'},
        {'label': 'San Francisco', 'value': 'SF'}
    ],
    value='MTL'
),

html.Label('Checkboxes'),
dcc.Checklist(
    options=[
        {'label': 'New York City', 'value': 'NYC'},
        {'label': u'Montral', 'value': 'MTL'},
        {'label': 'San Francisco', 'value': 'SF'}
    ],
    values=['MTL', 'SF']
),

html.Label('Text Input'),
dcc.Input(value='MTL', type='text'),

```



Chapters ▾

Categories ≡

```

dcc.Slider(
    min=0,
    max=9,
    marks={i: 'Label {}'.format(i) if i == 1 else str(i) for i in range(1,
6)},
    value=5,
),
], style={'columnCount': 2})


```

```
if name == 'main':
```



Advertisement

Output WS —



## Calling Help

Dash components are declarative. Every configurable aspect of these components is set during installation as a keyword argument. You can call help in your python console on any of the components to learn more about a component and its available arguments. Some of them are given below –

```
>>> help(dcc.DropDown)
Help on class Dropdown in module builtins:
class Dropdown(dash.development.base_component.Component)
| A Dropdown component.
| Dropdown is an interactive dropdown element for selecting one or more
|
| items.
| The values and labels of the dropdown items are specified in the `options`
| property and the selected item(s) are specified with the `value` property.
|
| Use a dropdown when you have many options (more than 5) or when you are
| constrained for space. Otherwise, you can use RadioItems or a Checklist,
| which have the benefit of showing the users all of the items at once.
|
| Keyword arguments:
| - id (string; optional)
| - options (list; optional): An array of options
| - value (string | list; optional): The value of the input. If `multi` is false
-- More --
```

To summarize, the layout of a Dash app describes what the app looks like. The layout is a hierarchical tree of components. The `dash_html_components` library provides classes for all the HTML tags and the keyword arguments, and describes the HTML attributes like `style`, `className`, and `id`. The `dash_core_components` library generates higher-level components like controls and graphs.



Advertisement

T  
P  
J  
C  
C

C# Tutorial  
PHP Tutorial  
R Tutorial  
HTML Tutorial  
CSS Tutorial  
JavaScript Tutorial  
SQL Tutorial


## TRENDING TECHNOLOGIES


Cloud Computing Tutorial  
Amazon Web Services Tutorial  
Microsoft Azure Tutorial  
Git Tutorial  
Ethical Hacking Tutorial  
Docker Tutorial  
Kubernetes Tutorial  
DSA Tutorial  
Spring Boot Tutorial  
SDLC Tutorial  
Unix Tutorial

## CERTIFICATIONS

Business Analytics Certification  
Java & Spring Boot Advanced Certification  
Data Science Advanced Certification  
Cloud Computing And DevOps  
Advanced Certification In Business Analytics  
Artificial Intelligence And Machine Learning

Dash Framework Certification

 Advertisement



[Online Python Compiler](#)  
[Online Go Compiler](#)  
[Online C Compiler](#)  
[Online C++ Compiler](#)  
[Online C# Compiler](#)  
[Online PHP Compiler](#)  
[Online MATLAB Compiler](#)  
[Online Bash Terminal](#)  
[Online SQL Compiler](#)  
[Online Html Editor](#)

[ABOUT US](#) | [OUR TEAM](#) | [CAREERS](#) | [JOBS](#) | [CONTACT US](#) | [TERMS OF USE](#) |  
[PRIVACY POLICY](#) | [REFUND POLICY](#) | [COOKIES POLICY](#) | [FAQ'S](#)



Tutorials Point is a leading Ed Tech company striving to provide the best learning material on technical and non-technical subjects.

© Copyright 2025. All Rights Reserved.

