

[Home](#) > [Tutorials](#) > [Python](#)

Dash for Beginners

Learn how to build dashboards in Python using Dash.

[Contents](#)

Aug 16, 2018 · 12 min read



Derrick Mwiti

TOPICS

[Python](#)[Data Science](#)**EXPLORE DATACAMP'S PYTHON
COURSE LIBRARY**[Explore Now](#)

Dash is Python framework for building web applications. It built on top of Flask, Plotly.js, React and React Js. It enables you to build dashboards using pure Python. Dash is open source, and its apps run on the web browser. In this tutorial, we introduce the reader to Dash fundamentals and assume that they have prior experience with Plotly.

Dash Installation

In order to start using Dash, we have to install several packages.

1. The core dash backend.
2. Dash front-end
3. Dash HTML components
4. Dash core components
5. Plotly

```
pip install dash==0.21.1
pip install dash-renderer==0.13.0
pip install dash-html-components==0.11.0
pip install dash-core-components==0.23.0
pip install plotly --upgrade
```

[🔗 Explain code](#)

POWERED BY datalab

Dash App Layout

A Dash application is usually composed of two parts. The first part is the layout and describes how the app will look like and the second part describes the interactivity of the application. Dash provides HTML classes that enable us to generate HTML content with Python. To use these classes, we need to import `dash_core_components` and `dash_html_components`. You can also create your own custom components using Javascript and React Js.

To kick us off we shall create a file called `app.py` using our favorite text editor then import these packages.

```
import dash
import dash_core_components as dcc
import dash_html_components as html
```

[🔗 Explain code](#)

POWERED BY datalab

Just like in Flask we initialize Dash by calling the Dash class of dash. Once that is done we can create the layout for our application. We use the Div class from the dash_html_components to create an HTML Div. We then use the HTML components to generate HTML components such as H1, H2 etc. dash_html_components has all HTML tags. In order to create a graph on our layout, we use the Graph class from dash_core_components. Graph renders interactive data visualizations using plotly.js. The Graph class expects a figure object with the data to be plotted and the layout details. Dash also allows you to do stylings such as changing the background color and text color. You can change the background by using the style attribute and passing an object with your specific color. In our case, we have defined a color dictionary with the background and text color we would like. Similarly, we can change the layout background using the plot_bgcolor attribute.

In HTML the style property is specified using a semicolon, but in Dash, a dictionary is supplied. The keys in the dictionary are camelCased e.g text-align is textAlign. Instead of using classes like in HTML, className is used in Dash.

```
app = dash.Dash()
colors = {
    'background': '#111111',
    'text': '#7FDBFF'
}
app.layout = html.Div(style={'backgroundColor': colors['background']}, children=[
    html.H1(
        children='Hello Dash',
        style={
            'textAlign': 'center',
            'color': colors['text']
        }
    ),
    html.Div(children='Dash: A web application framework for Python.', style={
        'textAlign': 'center',
        'color': colors['text']
    }),
    dcc.Graph(
        id='Graph1',
        figure={
            'data': [
                {'x': [1, 2, 3], 'y': [4, 1, 2], 'type': 'bar', 'name': 'SF'},
                {'x': [1, 2, 3], 'y': [2, 4, 5], 'type': 'bar', 'name': 'u'Montréal'}
            ],
            'layout': {
                'plot_bgcolor': colors['background'],
                'paper_bgcolor': colors['background'],
                'font': {
                    'color': colors['text']
                }
            }
        }
    )
])
```

POWERED BY  datalab


In order to view our visualization, we need to run our web server just like in Flask. Remember Dash is built on top of Flask. We also set debug to true to ensure we don't have to keep refreshing the server every time we make some changes

```
if __name__ == '__main__':
    app.run_server(debug=True)
```

 [Explain code](#)
POWERED BY  datalab

Next, move to the terminal and start the server by typing the code below: python app.py

This will start a new web server at <http://127.0.0.1:8050/>. Head over there and see your newly created dashboard.



Generating Scatter Plots

In order to plot a scatter plot, we import the normal dash components as previously done. We also need to import `Plotly graph_objs` in order to plot the scatter plot. As mentioned previously we use the `Div` class and `Graph` components from Dash in order to accomplish this. The `Graph` component takes a figure object which has the data and the layout description. We plot the scatter plot using `graph_objs` `scatter` property. In order to make sure the plot is a scatter plot we pass a `mode` attribute and set it as `markers`. Otherwise, we would have lines on the graph.

```
import dash
import dash_core_components as dcc
import dash_html_components as html
import pandas as pd
import plotly.graph_objs as go

app = dash.Dash()


df = pd.read_csv(
    'https://gist.githubusercontent.com/chriddyp/' +
    '5d1ea79569ed194d432e56108a04d188/raw/' +
    'a9f9e8076b837d541398e999dcba2b2826a81f8/' +
    'gdp-life-exp-2007.csv')

app.layout = html.Div([
    dcc.Graph(
        id='life-exp-vs-gdp',
        figure={
            'data': [
                go.Scatter(
                    x=df[df['continent'] == i]['gdp per capita'],
                    y=df[df['continent'] == i]['life expectancy'],
                    text=df[df['continent'] == i]['country'],
                    mode='markers',
                    opacity=0.8,
                    marker={
                        'size': 15,
                        'line': {'width': 0.5, 'color': 'white'}
                    },
                    name=i
                ) for i in df.continent.unique()
            ],
            'layout': go.Layout(
                xaxis={'type': 'log', 'title': 'GDP Per Capita'},
                yaxis={'title': 'Life Expectancy'},
                margin={'l': 40, 'b': 40, 't': 10, 'r': 10},
                legend={'x': 0, 'y': 1},
                hovermode='closest'
            )
        }
    )
])

if __name__ == '__main__':
    app.run_server()
```

 Explain code

POWERED BY  datalab



Markdown

Sometimes you may need to include a lot of text in your dashboards. You can do this using `dash_core_components` `Markdown` attribute as shown below.

```
import dash
import dash_core_components as dcc
import dash_html_components as html

app = dash.Dash()

markdown_text = '''
### Dash and Markdown
A lot of text
'''

app.layout = html.Div([
    dcc.Markdown(children=markdown_text)
])

if __name__ == '__main__':
    app.run_server()
```

[Explain code](#)

POWERED BY datalab

Core Components

Next, let's look at some `dash_core_components` that you will encounter when using Dash. You can generate a drop down as shown below. You do by calling `Dropdown` off `dash_core_components` and passing the options as a list of dictionaries. You can set the default value using the `value` attribute and passing in the default option.

```
dcc.Dropdown(
    options=[
        {'label': 'New York City', 'value': 'NYC'},
        {'label': 'u'Montréal', 'value': 'MTL'},
        {'label': 'San Francisco', 'value': 'SF'}
    ],
    value='MTL'
)
```

POWERED BY datalab

Generating a multi-select drop down is similar to above. The only changes are that you set the `multi` attribute to `True` since it is `False` by default. You can then specify the items you would like to be multi-selected by default by specifying the `value` attribute.

```
html.Label('Multi-Select Dropdown'),
dcc.Dropdown(
    options=[
        {'label': 'New York City', 'value': 'NYC'},
        {'label': 'u'Montréal', 'value': 'MTL'},
        {'label': 'San Francisco', 'value': 'SF'}
    ],
    value=['MTL', 'SF'],
    multi=True
)
```

POWERED BY datalab

Radio buttons can be generated using the `RadioItems` attribute. You then pass the options as a list of dictionaries. You can also set a default value by specifying the `value` attribute.

```
html.Label('Radio Items'),
dcc.RadioItems(
    options=[
        {'label': 'New York City', 'value': 'NYC'},
        {'label': 'Montréal', 'value': 'MTL'},
        {'label': 'San Francisco', 'value': 'SF'}
    ],
    value='MTL'
)
```

POWERED BY  datalab


To generate checkboxes, you call the `Checklist` attribute off `dash_core_components`. The options and default values are passed as above

```
html.Label('Checkboxes'),
dcc.Checklist(
    options=[
        {'label': 'New York City', 'value': 'NYC'},
        {'label': 'Montréal', 'value': 'MTL'},
        {'label': 'San Francisco', 'value': 'SF'}
    ],
    values=['MTL', 'SF']
)
```

POWERED BY  datalab

You will most certainly need input texts in your application. To generate them you will use the `Input` attribute. Using the `Html Label` tag, you can create a label for the Input field. Using the `values` attribute you can specify some text in the field and to specify the type of use `type` and indicate whether its a text field, number, etc.

```
html.Label('Text Box'),
dcc.Input(value='MTL', type='text')
```

 Explain codePOWERED BY  datalab

Calling help

Since Dash components are declarative, calling the help command on any of them will generate the help for that component.

```
help(dcc.Input)
```

Interactivity

Now let's cover how we can make our Dash apps interactive. In order to do this, we need to import `Input` and `Output` from `dash.dependencies`. Don't confuse these with the HTML `Input` because they are different. The HTML `Input` is imported from the dash core components. Below we create an input text and bind it a callback such that whenever you type something into that box, it updates `my-div` in real time. In order to enable this Dash provides a decorator `@app` which makes it possible to bind a callback function to `my-div` and the HTML input field. Notice that we use the decorator before we declare the `update_output_div` function.

```
import dash
import dash_core_components as dcc
import dash_html_components as html
from dash.dependencies import Input, Output

app = dash.Dash()

app.layout = html.Div([
    dcc.Input(id='my-id', value='Dash App', type='text'),
    html.Div(id='my-div')
])
```

```
@app.callback(
    Output(component_id='my-div', component_property='children'),
    [Input(component_id='my-id', component_property='value')]
)
def update_output_div(input_value):
    return 'You\'ve entered {}'.format(input_value)

if __name__ == '__main__':
    app.run_server()
```

[🔗 Explain code](#)
POWERED BY  datalab

Authentication

Dash provides authentication through a separate package called `dash-auth`. It provides two modes of authentication HTTP Basic Auth and Plotly OAuth. In Basic Auth, you hardcode a set of usernames and passwords in your application. This method has some challenges such as users cannot log out of your application, users cannot create accounts or change passwords, and you are responsible for safely storing the usernames and passwords in your code. Plotly OAuth provides authentication through your online Plotly account, and it's not free.

To set up the Basic Auth proceed as follows. First, install the necessary packages.

```
pip install dash==0.21.1
pip install dash-auth==1.0.0
```


[🔗 Explain code](#)
POWERED BY  datalab


After this set the username and password pairs you would like to have in your application.

```
VALID_USERNAME_PASSWORD_PAIRS = [
    ['hello', 'world']
]
```


[🔗 Explain code](#)
POWERED BY  datalab

The `dash_auth.BasicAuth` utility from Dash will take care of authentication for you once the password pairs have been set. All you have to do is pass the password pairs and your application name to `dash_auth.BasicAuth`.

```
app = dash.Dash('auth')
auth = dash_auth.BasicAuth(
    app,
    VALID_USERNAME_PASSWORD_PAIRS
)
```


[🔗 Explain code](#)
POWERED BY  datalab

Hosting Dashboards on Heroku

Hosting your dashboard on Heroku is fairly easy but will take a couple of steps.

First, create a directory that will hold all your projects files. You can do this on Ubuntu using the `mkdir` command.

```
$ mkdir my_dash_app
$ cd my_dash_app
```


[🔗 Explain code](#)
POWERED BY  datalab

Next, initialize the folder with git and virtualenv. Git is for version control, and virtualenv will enable us to create a virtual environment to hold all our Python dependencies. After creating the environment, we activate it using the `source` command.

```
$ git init
$ virtualenv venv
$ source venv/bin/activate
```


[✎ Explain code](#)

POWERED BY datalab

Next, we install all the packages we need for our Dash application:

```
$ pip install dash
$ pip install dash-renderer
$ pip install dash-core-components
$ pip install dash-html-components
$ pip install plotly
```


[✎ Explain code](#)

POWERED BY datalab

In order to serve our Dash application, we need a Python web server. We never use Flask's development server in production. We use Gunicorn web server for this function. Install it as shown below:

```
$ pip install gunicorn
```


[✎ Explain code](#)

POWERED BY datalab

Next, we need to create a few files in our folder:

1. app.py where we will code our dash application.
2. A .gitignore to make sure that unnecessary files are not pushed to production
3. A requirements.txt file that will contain all the Python dependencies and their versions.
4. A Procfile for deployment.

Add the following to app.py. This is just an example so you can use your own Dash dashboard.

```
import os
import dash
import dash_core_components as dcc
import dash_html_components as html
app = dash.Dash(__name__)
server = app.server
app.layout = html.Div([
    html.H2('Hello World'),
    dcc.Dropdown(
        id='dropdown',
        options=[{'label': i, 'value': i} for i in ['LA', 'NYC', 'MTL']],
        value='LA'
    ),
    html.Div(id='display-value')
])
@app.callback(dash.dependencies.Output('display-value', 'children'),
              [dash.dependencies.Input('dropdown', 'value')])
def display_value(value):
    return 'You have selected {}'.format(value)
if __name__ == '__main__':
    app.run_server(debug=True)
```


[✎ Explain code](#)

POWERED BY datalab

It is important to remind ourselves that at its core a Dash application is also a Flask application. For purposes of deployment, we need to access the Flask application instance. Dash enables us to do this using

```
app.server
```


[✎ Explain code](#)

POWERED BY datalab

```
app = dash.Dash(__name__)
server = app.server
```


[✎ Explain code](#)

POWERED BY datalab

Add the files you would not like to be pushed to production in the .gitignore file. A good Python .gitignore file is available at Github

Now let's specify our deployment information in the Procfile. We use the web variable to specify our server as gunicorn. We also specify our app details utilizing the app variable. app refers to the filename app.py and server refers to the server variable inside that file.

```
web: gunicorn app:server
```

[✚ Explain code](#)

POWERED BY datalab

We also need to write our Python dependencies to the requirements file. Heroku will install them during deployment.

```
pip freeze > requirements.txt
```

[✚ Explain code](#)

POWERED BY datalab

The next steps assume that you have an Heroku account and have installed the Heroku CLI. In case you do not have those in place head over to <https://www.heroku.com> and set them up.

The next step is to create a Heroku app on the terminal and add all our application packages. Once you have committed the changes; push your application to heroku master. The output of this command will have a link to your live Dash application on Heroku.

```
$ heroku create your-app-name
$ git add .
$ git commit -m 'Your-commit-message'
$ git push heroku master
```

[✚ Explain code](#)

POWERED BY datalab

This serves as an introduction to building a dashboard in pure Python using Dash by Plotly. To learn more about Dash visit the official [docs](#).

If you are interested in learning more about python, check out our [Python Tutorial for Beginners](#) and [Intermediate Python for Data Science](#) course.

TOPICS

[Python](#) [Data Science](#)



Training more people?

Get your team access to the full DataCamp for business platform.

[For Business](#)

For a bespoke solution [book a demo](#).

Learn more about Python and Plotly

COURSE

Introduction to Data Science in Python

🕒 4 hr 👤 489.8K

Dive into data science using Python and learn how to effectively analyze and visualize your data. No coding experience or skills needed.

[See Details](#) →

[Start Course](#)

[See More](#) →

Related



CHEAT-SHEET
Python For Data Science Cheat
Sheet For Beginners