Assignment 4: Word Embeddings

Welcome to the fourth (and last) programming assignment of Course 2!

In this assignment, you will practice how to compute word embeddings and use them for sentiment analysis.

- To implement sentiment analysis, you can go beyond counting the number of positive words and negative words.
- You can find a way to represent each word numerically, by a vector.
- The vector could then represent syntactic (i.e. parts of speech) and semantic (i.e. meaning) structures.

In this assignment, you will explore a classic way of generating word embeddings or representations.

- You will implement a famous model called the continuous bag of words (CBOW) model.

By completing this assignment you will:

- Train word vectors from scratch.
- Learn how to create batches of data.
- Understand how backpropagation works.
- Plot and visualize your learned word vectors.

Knowing how to train these models will give you a better understanding of word vectors, which are building blocks to many applications in natural language processing.

Important Note on Submission to the AutoGrader

Before submitting your assignment to the AutoGrader, please make sure you are not doing the following:

1. You have not added any *extra* `print` statement(s) in the assignment.
2. You have not added any *extra* code cell(s) in the assignment.
3. You have not changed any of the function parameters.
4. You are not using any global variables inside your graded exercises. Unless specifically instructed to do so, please refrain from it and use the local variables instead.
5. You are not changing the assignment code where it is not required, like creating *extra* variables.

If you do any of the following, you will get something like, `Grader Error: Grader feedback not found` (or similarly unexpected) error upon submitting your assignment. Before asking for help/debugging the errors in your assignment, check for these first. If this is the case, and you don't remember the changes you have made, you can get a fresh copy of the assignment by following these instructions.

Table of Contents

- 1 - The Continuous Bag of Words Model
- 2 - Training the Model
  - 2.1 - Initializing the Model
    - Exercise 1 - initialize_model (UNQ_C1)
  - 2.2 - Softmax
    - Exercise 2 - softmax (UNQ_C2)
  - 2.3 - Forward Propagation
    - Exercise 3 - forward_prop (UNQ_C3)
  - 2.4 - Cost Function
  - 2.5 - Training the Model - Backpropagation
    - Exercise 4 - back_prop (UNQ_C4)
  - 2.6 - Gradient Descent
    - Exercise 5 - gradient_descent (UNQ_C5)

- 3 - Visualizing the Word Vectors

1 - The Continuous Bag of Words Model

Let's take a look at the following sentence:

> **'I am happy because I am learning'**.

- In continuous bag of words (CBOW) modeling, we try to predict the center word given a few context words (the words around the center word).
- For example, if you were to choose a context half-size of say $C = 2$, then you would try to predict the word **happy** given the context that includes 2 words before and 2 words after the center word:

> C words before: [I, am]

> C words after: [because, I]

- In other words:

$$context = [I, am, because, I]$$
$$target = happy$$

The structure of your model will look like this:

alternate text

Figure 1

Where $\overline{x}$ is the average of all the one hot vectors of the context words.

alternate text

```
# Import Python libraries and helper functions (in utils2)
import nltk
from nltk.tokenize import word_tokenize
import numpy as np
from collections import Counter
from utils2 import sigmoid, get_batches, compute_pca, get_dict
import w4_unittest
```

```
[nltk_data] Downloading package punkt to /home/jovyan/nltk_data...
[nltk_data]   Unzipping tokenizers/punkt.zip.
```

```
True
```

```
# Download sentence tokenizer
```

```
# Load, tokenize and process the data
import re                                                          #  Load the Regex-modul
with open('./data/shakespeare.txt') as f:
    data = f.read()                                                #  Read in the data
data = re.sub(r'[,!?;-]', '.',data)                                #  Punktuations are repl
data = nltk.word_tokenize(data)                                    #  Tokenize string to wo
data = [ ch.lower() for ch in data if ch.isalpha() or ch == '.']   #  Lower case and drop n
```

```
Number of tokens: 60996
 ['o', 'for', 'a', 'muse', 'of', 'fire', '.', 'that', 'would', 'ascend', 'th
e', 'brightest', 'heaven', 'of', 'invention']
```

```
# Compute the frequency distribution of the words in the dataset (vocabulary)
fdist = nltk.FreqDist(word for word in data)
print("Size of vocabulary: ",len(fdist) )
```

```
Size of vocabulary:  5778
Most frequent tokens:  [('.', 9630), ('the', 1521), ('and', 1394), ('i', 125
7), ('to', 1159), ('of', 1093), ('my', 857), ('that', 781), ('in', 770),
('a', 752), ('you', 748), ('is', 630), ('not', 559), ('for', 467), ('it', 46
0), ('with', 441), ('his', 434), ('but', 417), ('me', 417), ('your', 397)]
```

Mapping words to indices and indices to words

We provide a helper function to create a dictionary that maps words to indices and indices to words.

```
# get_dict creates two dictionaries, converting words to indices and viceversa.
word2Ind, Ind2word = get_dict(data)
V = len(word2Ind)
```

```
Size of vocabulary:  5778
```

```
# example of word to index mapping
print("Index of the word 'king' :  ",word2Ind['king'] )
```

```
Index of the word 'king' :   2745
Word which has index 2743:   kindness
```

2 - Training the Model

2.1 - Initializing the Model

You will now initialize two matrices and two vectors.

- The first matrix (W_1) is of dimension $N \times V$, where V is the number of words in your vocabulary and N is the dimension of your word vector.
- The second matrix (W_2) is of dimension $V \times N$.
- Vector b_1 has dimensions $N \times 1$
- Vector b_2 has dimensions $V \times 1$.
- b_1 and b_2 are the bias vectors of the linear layers from matrices W_1 and W_2.

The overall structure of the model will look as in Figure 1, but at this stage we are just initializing the parameters.

Exercise 1 - initialize_model

Please use numpy.random.rand to generate matrices that are initialized with random values from a uniform distribution, ranging between 0 and 1.

Note: In the next cell you will encounter a random seed. Please **DO NOT** modify this seed so your solution can be tested correctly.

```python
# UNIT TEST COMMENT: Candidate for Table Driven Tests
# UNQ_C1 GRADED FUNCTION: initialize_model
def initialize_model(N,V, random_seed=1):
    '''
    Inputs:
        N:  dimension of hidden vector
        V:  dimension of vocabulary
        random_seed: random seed for consistent results in the unit tests
     Outputs:
        W1, W2, b1, b2: initialized weights and biases
    '''

    ### START CODE HERE (Replace instances of 'None' with your code) ###
    np.random.seed(random_seed)
    # W1 has shape (N,V)
    W1 = np.random.rand(N, V)

    # W2 has shape (V,N)
    W2 = np.random.rand(V, N)

    # b1 has shape (N,1)
    b1 = np.random.rand(N, 1)

    # b2 has shape (V,1)
    b2 = np.random.rand(V, 1)

    ### END CODE HERE ###
```

```python
# Test your function example.
tmp_N = 4
tmp_V = 10
tmp_W1, tmp_W2, tmp_b1, tmp_b2 = initialize_model(tmp_N,tmp_V)
assert tmp_W1.shape == ((tmp_N,tmp_V))
assert tmp_W2.shape == ((tmp_V,tmp_N))
print(f"tmp_W1.shape: {tmp_W1.shape}")
print(f"tmp_W2.shape: {tmp_W2.shape}")
print(f"tmp_b1.shape: {tmp_b1.shape}")
```

```
tmp_W1.shape: (4, 10)
tmp_W2.shape: (10, 4)
tmp_b1.shape: (4, 1)
tmp_b2.shape: (10, 1)
```

Expected Output

```
tmp_W1.shape: (4, 10)
tmp_W2.shape: (10, 4)
tmp_b1.shape: (4, 1)
tmp_b2.shape: (10, 1)
```

```python
# Test your function
```

```
All tests passed
```

2.2 - Softmax

Before we can start training the model, we need to implement the softmax function as defined in equation 5:

$$\text{softmax}(z_i) = \frac{e^{z_i}}{\sum_{i=0}^{V-1} e^{z_i}} \tag{5}$$

- Array indexing in code starts at 0.
- V is the number of words in the vocabulary (which is also the number of rows of z).
- i goes from 0 to |V| - 1.

Exercise 2 - softmax

Instructions: Implement the softmax function below.

- Assume that the input z to `softmax` is a 2D array
- Each training example is represented by a vector of shape (V, 1) in this 2D array.
- There may be more than one column, in the 2D array, because you can put in a batch of examples to increase efficiency. Let's call the batch size lowercase m, so the z array has shape (V, m)
- When taking the sum from $i = 1 \cdots V - 1$, take the sum for each column (each example) separately.

Please use

- numpy.exp
- numpy.sum (set the axis so that you take the sum of each column in z)

```
# UNQ_C2 GRADED FUNCTION: softmax
def softmax(z):
    '''
    Inputs:
        z: output scores from the hidden layer, shape (V, m)
    Outputs:
        yhat: prediction (estimate of y), shape (V, m)
    '''
    ### START CODE HERE ###
    # To prevent overflow, subtract max of each column
    z_exp = np.exp(z - np.max(z, axis=0, keepdims=True))
    # Sum of exponentials for each column
    z_sum = np.sum(z_exp, axis=0, keepdims=True)
    # Softmax output
    yhat = z_exp / z_sum
    ### END CODE HERE ###
```

```
# Test the function
tmp = np.array([[1,2,3],
                [1,1,1]
               ])
tmp_sm = softmax(tmp)
```

```
array([[0.5       , 0.73105858, 0.88079708],
       [0.5       , 0.26894142, 0.11920292]])
```

Expected Ouput

```
array([[0.5       , 0.73105858, 0.88079708],
       [0.5       , 0.26894142, 0.11920292]])
```

```
# Test your function
```

```
All tests passed
```

2.3 - Forward Propagation

Exercise 3 - forward_prop

Implement the forward propagation z according to equations (1) to (3).

$$h = W_1 \ X + b_1 \tag{1}$$
$$h = ReLU(h) \tag{2}$$
$$z = W_2 \ h + b_2 \tag{3}$$

For that, you will use as activation the Rectified Linear Unit (ReLU) given by:

$$f(h) = \max(0, h) \tag{6}$$

Hints

```
# UNQ_C3 GRADED FUNCTION: forward_prop
def forward_prop(x, W1, W2, b1, b2):
    '''
    Inputs:
        x:  average one-hot vector for the context, shape (V, m)
        W1, W2, b1, b2:  matrices and biases to be learned
    Outputs:
        z:  output score vector, shape (V, m)
        h:  hidden layer after ReLU, shape (N, m)
    '''

    ### START CODE HERE ###
    # Calculate hidden layer pre-activation
    h = np.dot(W1, x) + b1  # shape (N, m)

    # Apply ReLU activation
    h = np.maximum(0, h)    # shape (N, m)

    # Calculate output layer z
    z = np.dot(W2, h) + b2  # shape (V, m)
    ### END CODE HERE ###
```

```python
# Test the function

# Create some inputs
tmp_N = 2
tmp_V = 3
tmp_x = np.array([[0,1,0]]).T
#print(tmp_x)
tmp_W1, tmp_W2, tmp_b1, tmp_b2 = initialize_model(N=tmp_N,V=tmp_V, random_seed=1)

print(f"x has shape {tmp_x.shape}")
print(f"N is {tmp_N} and vocabulary size V is {tmp_V}")

# call function
tmp_z, tmp_h = forward_prop(tmp_x, tmp_W1, tmp_W2, tmp_b1, tmp_b2)
print("call forward_prop")
print()
# Look at output
print(f"z has shape {tmp_z.shape}")
print("z has values:")
print(tmp_z)

print()

print(f"h has shape {tmp_h.shape}")
print("h has values:")
```

```
x has shape (3, 1)
N is 2 and vocabulary size V is 3
call forward_prop

z has shape (3, 1)
z has values:
[[0.55379268]
 [1.58960774]
 [1.50722933]]

h has shape (2, 1)
h has values:
[[0.92477674]
 [1.02487333]]
```

Expected output

```
    x has shape (3, 1)
    N is 2 and vocabulary size V is 3
```

```
# Test your function
```

```
All tests passed
```

2.4 - Cost Function

- We have implemented the *cross-entropy* cost function for you.

```
# compute_cost: cross-entropy cost function
def compute_cost(y, yhat, batch_size):

    # cost function
    logprobs = np.multiply(np.log(yhat),y)
    cost = - 1/batch_size * np.sum(logprobs)
    cost = np.squeeze(cost)
```

```python
# Test the function
tmp_C = 2
tmp_N = 50
tmp_batch_size = 4
tmp_word2Ind, tmp_Ind2word = get_dict(data)
tmp_V = len(word2Ind)

tmp_x, tmp_y = next(get_batches(data, tmp_word2Ind, tmp_V,tmp_C, tmp_batch_size))

print(f"tmp_x.shape {tmp_x.shape}")
print(f"tmp_y.shape {tmp_y.shape}")

tmp_W1, tmp_W2, tmp_b1, tmp_b2 = initialize_model(tmp_N,tmp_V)

print(f"tmp_W1.shape {tmp_W1.shape}")
print(f"tmp_W2.shape {tmp_W2.shape}")
print(f"tmp_b1.shape {tmp_b1.shape}")
print(f"tmp_b2.shape {tmp_b2.shape}")

tmp_z, tmp_h = forward_prop(tmp_x, tmp_W1, tmp_W2, tmp_b1, tmp_b2)
print(f"tmp_z.shape: {tmp_z.shape}")
print(f"tmp_h.shape: {tmp_h.shape}")

tmp_yhat = softmax(tmp_z)
print(f"tmp_yhat.shape: {tmp_yhat.shape}")

tmp_cost = compute_cost(tmp_y, tmp_yhat, tmp_batch_size)
print("call compute_cost")
```

```
tmp_x.shape (5778, 4)
tmp_y.shape (5778, 4)
tmp_W1.shape (50, 5778)
tmp_W2.shape (5778, 50)
tmp_b1.shape (50, 1)
tmp_b2.shape (5778, 1)
tmp_z.shape: (5778, 4)
tmp_h.shape: (50, 4)
tmp_yhat.shape: (5778, 4)
call compute_cost
tmp_cost 10.5788
```

Expected output

```
tmp_x.shape (5778, 4)
tmp_y.shape (5778, 4)
tmp_W1.shape (50, 5778)
tmp_W2.shape (5778, 50)
tmp_b1.shape (50, 1)
tmp_b2.shape (5778, 1)
tmp_z.shape: (5778, 4)
tmp_h.shape: (50, 4)
tmp_yhat.shape: (5778, 4)
call compute_cost
tmp_cost 10.5788
```

2.5 - Training the Model - Backpropagation

Exercise 4 - back_prop

Now that you have understood how the CBOW model works, you will train it.
You created a function for the forward propagation. Now you will implement a function that computes the gradients to backpropagate the errors.

Note: `z1` is calculated as `W1·x + b1` in this function. In practice, you would save it already when making forward propagation and just re-use here, but for simplicity, it is calculated again in `back_prop`.

As reference, below are the equations of backpropagation as taught in the lecture:

alternate text

```python
# UNQ_C4 GRADED FUNCTION: back_prop
def back_prop(x, yhat, y, h, W1, W2, b1, b2, batch_size):
    '''
    Inputs:
        x:  average one-hot vector for the context, shape (V, m)
        yhat: prediction (estimate of y), shape (V, m)
        y:  target vector, shape (V, m)
        h:  hidden vector after ReLU, shape (N, m)
        W1, W2, b1, b2:  matrices and biases
        batch_size: batch size, m
    Outputs:
        grad_W1, grad_W2, grad_b1, grad_b2:  gradients of matrices and biases
    '''

    # Compute z1 as "W1·x + b1"
    z1 = np.dot(W1, x) + b1

    ### START CODE HERE ###
    # Compute l1 as W2^T (Yhat - Y)
    l1 = np.dot(W2.T, (yhat - y))  # shape (N, m)

    # Apply ReLU derivative
    l1[z1 < 0] = 0

    # Compute the gradient for W1
    grad_W1 = np.dot(l1, x.T) / batch_size  # shape (N, V)

    # Compute gradient for W2
    grad_W2 = np.dot((yhat - y), h.T) / batch_size  # shape (V, N)

    # Compute gradient for b1
    grad_b1 = np.sum(l1, axis=1, keepdims=True) / batch_size  # shape (N, 1)

    # Compute gradient for b2
    grad_b2 = np.sum(yhat - y, axis=1, keepdims=True) / batch_size  # shape (V, 1)
    ### END CODE HERE ####
```

```python
# Test the function
tmp_C = 2
tmp_N = 50
tmp_batch_size = 4
tmp_word2Ind, tmp_Ind2word = get_dict(data)
tmp_V = len(word2Ind)


# get a batch of data
tmp_x, tmp_y = next(get_batches(data, tmp_word2Ind, tmp_V,tmp_C, tmp_batch_size))

print("get a batch of data")
print(f"tmp_x.shape {tmp_x.shape}")
print(f"tmp_y.shape {tmp_y.shape}")

print()
print("Initialize weights and biases")
tmp_W1, tmp_W2, tmp_b1, tmp_b2 = initialize_model(tmp_N,tmp_V)

print(f"tmp_W1.shape {tmp_W1.shape}")
print(f"tmp_W2.shape {tmp_W2.shape}")
print(f"tmp_b1.shape {tmp_b1.shape}")
print(f"tmp_b2.shape {tmp_b2.shape}")

print()
print("Forwad prop to get z and h")
tmp_z, tmp_h = forward_prop(tmp_x, tmp_W1, tmp_W2, tmp_b1, tmp_b2)
print(f"tmp_z.shape: {tmp_z.shape}")
print(f"tmp_h.shape: {tmp_h.shape}")

print()
print("Get yhat by calling softmax")
tmp_yhat = softmax(tmp_z)
print(f"tmp_yhat.shape: {tmp_yhat.shape}")

tmp_m = (2*tmp_C)
tmp_grad_W1, tmp_grad_W2, tmp_grad_b1, tmp_grad_b2 = back_prop(tmp_x, tmp_yhat, tmp_y, tmp_h

print()
print("call back_prop")
print(f"tmp_grad_W1.shape {tmp_grad_W1.shape}")
print(f"tmp_grad_W2.shape {tmp_grad_W2.shape}")
print(f"tmp_grad_b1.shape {tmp_grad_b1.shape}")
```

```
get a batch of data
tmp_x.shape (5778, 4)
tmp_y.shape (5778, 4)

Initialize weights and biases
tmp_W1.shape (50, 5778)
tmp_W2.shape (5778, 50)
tmp_b1.shape (50, 1)
tmp_b2.shape (5778, 1)

Forwad prop to get z and h
tmp_z.shape: (5778, 4)
tmp_h.shape: (50, 4)

Get yhat by calling softmax
tmp_yhat.shape: (5778, 4)

call back_prop
tmp_grad_W1.shape (50, 5778)
tmp_grad_W2.shape (5778, 50)
tmp_grad_b1.shape (50, 1)
tmp_grad_b2.shape (5778, 1)
```

Expected output

```
get a batch of data
tmp_x.shape (5778, 4)
tmp_y.shape (5778, 4)

Initialize weights and biases
tmp_W1.shape (50, 5778)
tmp_W2.shape (5778, 50)
tmp_b1.shape (50, 1)
tmp_b2.shape (5778, 1)

Forwad prop to get z and h
tmp_z.shape: (5778, 4)
tmp_h.shape: (50, 4)

Get yhat by calling softmax
tmp_yhat.shape: (5778, 4)

call back_prop
tmp_grad_W1.shape (50, 5778)
tmp_grad_W2.shape (5778, 50)
tmp_grad_b1.shape (50, 1)
tmp_grad_b2.shape (5778, 1)
```

```
# Test your function
```

```
All tests passed
```

2.6 - Gradient Descent

Exercise 5 - gradient_descent

Now that you have implemented a function to compute the gradients, you will implement batch gradient descent over your training set.

Hint: For that, you will use `initialize_model` and the `back_prop` functions which you just created (and the `compute_cost` function). You can also use the provided `get_batches` helper function:

```
for x, y in get_batches(data, word2Ind, V, C, batch_size):
```

```
...
```

```python
# UNQ_C5 GRADED FUNCTION: gradient_descent
def gradient_descent(data, word2Ind, N, V, num_iters, alpha=0.03,
                     random_seed=282, initialize_model=initialize_model,
                     get_batches=get_batches, forward_prop=forward_prop,
                     softmax=softmax, compute_cost=compute_cost,
                     back_prop=back_prop):

    '''
    This is the gradient_descent function

      Inputs:
        data:      text
        word2Ind:  words to Indices
        N:         dimension of hidden vector
        V:         dimension of vocabulary
        num_iters: number of iterations
        random_seed: random seed to initialize the model's matrices and vectors
        initialize_model: your implementation of the function to initialize the model
        get_batches: function to get the data in batches
        forward_prop: your implementation of the function to perform forward propagation
        softmax: your implementation of the softmax function
        compute_cost: cost function (Cross entropy)
        back_prop: your implementation of the function to perform backward propagation
     Outputs:
        W1, W2, b1, b2:  updated matrices and biases after num_iters iterations
    '''

    W1, W2, b1, b2 = initialize_model(N, V, random_seed=random_seed) # W1=(N,V) and W2=(V,N)

    batch_size = 128
    iters = 0
    C = 2

    for x, y in get_batches(data, word2Ind, V, C, batch_size):
        ### START CODE HERE ###
        # get z and h
        z, h = forward_prop(x, W1, W2, b1, b2)

        # get yhat
        yhat = softmax(z)

        # get cost
        cost = compute_cost(yhat, y, batch_size)  # <-- fixed by passing batch_size
        if ( (iters+1) % 10 == 0):
            print(f"iters: {iters + 1} cost: {cost:.6f}")

        # get gradients
        grad_W1, grad_W2, grad_b1, grad_b2 = back_prop(x, yhat, y, h, W1, W2, b1, b2, batch_

        # update weights and biases
        W1 = W1 - alpha * grad_W1
        W2 = W2 - alpha * grad_W2
        b1 = b1 - alpha * grad_b1
        b2 = b2 - alpha * grad_b2
        ### END CODE HERE ###

        iters += 1
```

```
        if iters == num_iters:
            break
        if iters % 100 == 0:
            alpha *= 0.66
```

```
# test your function

C = 2
N = 50
word2Ind, Ind2word = get_dict(data)
V = len(word2Ind)
num_iters = 150
print("Call gradient_descent")
```

```
Call gradient_descent
iters: 10 cost: inf
iters: 20 cost: inf
iters: 30 cost: inf
iters: 40 cost: inf
iters: 50 cost: inf
iters: 60 cost: inf
iters: 70 cost: inf
iters: 80 cost: inf
iters: 90 cost: inf
iters: 100 cost: inf
iters: 110 cost: inf
iters: 120 cost: inf
iters: 130 cost: inf
iters: 150 cost: inf
```

Expected Output

```
iters: 10 cost: 9.686791
iters: 20 cost: 10.297529
iters: 30 cost: 10.051127
iters: 40 cost: 9.685962
iters: 50 cost: 9.369307
iters: 60 cost: 9.400293
iters: 70 cost: 9.060542
iters: 80 cost: 9.054266
iters: 90 cost: 8.765818
iters: 100 cost: 8.516531
iters: 110 cost: 8.708745
iters: 120 cost: 8.660616
iters: 130 cost: 8.544338
iters: 140 cost: 8.454268
iters: 150 cost: 8.475693
```

Your numbers may differ a bit depending on which version of Python you're using.

```
# Test your function
```

```
name default_check
iters: 10 cost: inf
name small_check
iters: 10 cost: inf
 All tests passed
```

3 - Visualizing the Word Vectors

In this part you will visualize the word vectors trained using the function you just coded above.

```
# visualizing the word vectors here
from matplotlib import pyplot
%config InlineBackend.figure_format = 'svg'
words = ['king', 'queen','lord','man', 'woman','dog','wolf',
         'rich','happy','sad']

embs = (W1.T + W2)/2.0

# given a list of words and the embeddings, it returns a matrix with all the embeddings
idx = [word2Ind[word] for word in words]
X = embs[idx, :]
```

```
(10, 50) [2745, 3951, 2961, 3023, 5675, 1452, 5674, 4191, 2316, 4278]
```

```
result= compute_pca(X, 2)
pyplot.scatter(result[:, 0], result[:, 1])
for i, word in enumerate(words):
    pyplot.annotate(word, xy=(result[i, 0], result[i, 1]))
```

```
<Figure size 432x288 with 1 Axes>
```

You can see that man and king are next to each other. However, we have to be careful with the interpretation of this projected word vectors, since the PCA depends on the projection -- as shown in the following illustration.

```
result= compute_pca(X, 4)
pyplot.scatter(result[:, 3], result[:, 1])
for i, word in enumerate(words):
    pyplot.annotate(word, xy=(result[i, 3], result[i, 1]))
```

```
<Figure size 432x288 with 1 Axes>
```

Natural Language Processing with Probabilistic Models

- Reading • 3 min
- Lecture notebook: Word embeddings step by step
  Lab • 1h
- Conclusion
  Video • 1 min
- Conclusion
  Reading • 2 min
- Week Conclusion
  Video • 45 sec

Lecture Notes (Optional)

- Lecture Notes W4
  Reading • 1 min

Practice Quiz

- Word Embeddings
  Practice Assignment • Grade: 87.5%

End of access to Lab Notebooks

- [IMPORTANT] Reminder about end of access to Lab Notebooks
  Reading • 2 min

Assignment: Word Embeddings

- Word Embeddings

Programming Assignment: Word Embeddings

Passed • 50/50 points

Deadline Pass this assignment by Mar 4, 11:59 PM IST

Launch Notebook

Instructions | My submissions

Date	Score	Passed
February 23, 2026 2:21 PM IST	50/50	--
Initialize model	10/10	Show grader output
Softmax	10/10	Show grader output
Forward prop	10/10	Show grader output
Back prop	10/10	Show grader output
Gradient descent	10/10	Show grader output

coursera

jupyter C2_W4_Assignment Last Checkpoint: 11/06/2024 (autosaved)

File Edit View Insert Cell Kernel Widgets Help Trusted Python 3

```
    batch_size = 128
    iters = 0
    C = 2

    for x, y in get_batches(data, word2Ind, V, C, batch_size):
        ### START CODE HERE ###
        # get z and h
        z, h = forward_prop(x, W1, W2, b1, b2)

        # get yhat
        yhat = softmax(z)

        # get cost
        cost = compute_cost(yhat, y, batch_size)  # <-- fixed by passing batch_size
        if ( (iters+1) % 10 == 0):
            print(f"iters: {iters + 1} cost: {cost:.6f}")

        # get gradients
        grad_W1, grad_W2, grad_b1, grad_b2 = back_prop(x, yhat, y, h, W1, W2, b1, b2, batch_size)

        # update weights and biases
        W1 = W1 - alpha * grad_W1
        W2 = W2 - alpha * grad_W2
        b1 = b1 - alpha * grad_b1
        b2 = b2 - alpha * grad_b2
        ### END CODE HERE ###

        iters += 1
        if iters == num_iters:
            break
        if iters % 100 == 0:
            alpha *= 0.66

    return W1, W2, b1, b2
```

In [24]:
```
# test your function

C = 2
N = 50
```

Grades | Submit assignment

Grades

Passed • Grade Received: 100%

Submissions

February 23, 2026 2:21 PM IST (Highest Grade)

- **Initialize model** — 10/10 points earned
- **Softmax** — 10/10 points earned
- **Forward prop** — 10/10 points earned
- **Back prop** — 10/10 points earned
- **Gradient descent** — 10/10 points earned