

cFS Test Framework (CTF) Tool  
Software Design Document  
Section 5.0

## Contents

<b>1</b>	<b>cFS Test Framework (CTF) Tool</b>	<b>1</b>
<b>2</b>	<b>CCSDS Plugin</b>	<b>2</b>
<b>3</b>	<b>CFS Plugin</b>	<b>4</b>
<b>4</b>	<b>Control Flow Plugin</b>	<b>13</b>
<b>5</b>	<b>Example Plugin</b>	<b>15</b>
<b>6</b>	<b>SSH Plugin</b>	<b>16</b>
<b>7</b>	<b>UserIO Plugin</b>	<b>20</b>
<b>8</b>	<b>Validation Plugin</b>	<b>21</b>
<b>9</b>	<b>Variable Plugin</b>	<b>22</b>
<b>10</b>	<b>Namespace Documentation</b>	<b>24</b>
10.1	lib Namespace Reference . . . . .	24
10.1.1	Detailed Description . . . . .	24
10.2	lib.args_validation Namespace Reference . . . . .	24
10.2.1	Detailed Description . . . . .	24
10.3	lib.ctf_global Namespace Reference . . . . .	25
10.3.1	Detailed Description . . . . .	25
10.4	lib.ctf_utility Namespace Reference . . . . .	25
10.4.1	Detailed Description . . . . .	25
10.4.2	Function Documentation . . . . .	25
10.4.3	Variable Documentation . . . . .	26
10.5	lib.event_types Namespace Reference . . . . .	26
10.5.1	Detailed Description . . . . .	27
10.6	lib.exceptions Namespace Reference . . . . .	27
10.6.1	Detailed Description . . . . .	27
10.7	lib.ftp_interface Namespace Reference . . . . .	27
10.7.1	Detailed Description . . . . .	27
10.8	lib.logger Namespace Reference . . . . .	27
10.8.1	Detailed Description . . . . .	28
10.8.2	Function Documentation . . . . .	28
10.9	lib.plugin_manager Namespace Reference . . . . .	28

10.9.1 Detailed Description . . . . .	28
10.10lib.readers Namespace Reference . . . . .	28
10.10.1 Detailed Description . . . . .	28
10.11lib.readers.json_script_reader Namespace Reference . . . . .	29
10.11.1 Detailed Description . . . . .	29
10.12lib.script_manager Namespace Reference . . . . .	29
10.12.1 Detailed Description . . . . .	29
10.13lib.status Namespace Reference . . . . .	29
10.13.1 Detailed Description . . . . .	29
10.14lib.status_manager Namespace Reference . . . . .	29
10.14.1 Detailed Description . . . . .	29
10.15lib.test Namespace Reference . . . . .	30
10.15.1 Detailed Description . . . . .	30
10.16lib.test_script Namespace Reference . . . . .	30
10.16.1 Detailed Description . . . . .	30
10.17lib.time_interface Namespace Reference . . . . .	30
10.17.1 Detailed Description . . . . .	30
10.18plugins.cfs.cfs_config Namespace Reference . . . . .	30
10.18.1 Detailed Description . . . . .	30
10.19plugins.control_flow_plugin.control_flow_plugin Namespace Reference . . . . .	31
10.19.1 Detailed Description . . . . .	31
10.20plugins.example_plugin.example_plugin Namespace Reference . . . . .	31
10.20.1 Detailed Description . . . . .	31
10.21plugins.ssh.ssh_plugin Namespace Reference . . . . .	31
10.21.1 Detailed Description . . . . .	31
10.22plugins.variable_plugin.variable_plugin Namespace Reference . . . . .	31
10.22.1 Detailed Description . . . . .	31
<b>11 Data Structure Documentation</b>	<b>32</b>
11.1 lib.args_validation.ArgsValidation Class Reference . . . . .	32
11.1.1 Detailed Description . . . . .	32
11.1.2 Constructor & Destructor Documentation . . . . .	32
11.1.3 Member Function Documentation . . . . .	32
11.2 lib.plugin_manager.ArgTypes Class Reference . . . . .	34
11.2.1 Detailed Description . . . . .	34
11.3 plugins.ccsds_plugin.readers.cccd_export_reader.CCDDExportReader Class Reference . . . . .	34
11.3.1 Detailed Description . . . . .	35

11.3.2	Member Function Documentation	35
11.4	plugins.ccsds_plugin.ccsds_interface.CCSDSInterface Class Reference	37
11.4.1	Detailed Description	38
11.4.2	Member Function Documentation	38
11.5	plugins.ccsds_plugin.ccsds_packet_interface.CcsdsPacketInterface Class Reference	38
11.5.1	Detailed Description	38
11.5.2	Member Function Documentation	39
11.6	plugins.ccsds_plugin.ccsds_packet_interface.CcsdsPacketType Class Reference	39
11.6.1	Detailed Description	39
11.7	plugins.ccsds_plugin.ccsds_plugin.CCSDSPlugin Class Reference	39
11.7.1	Detailed Description	40
11.7.2	Member Function Documentation	40
11.8	plugins.ccsds_plugin.ccsds_primary_header.CcsdsPrimaryHeaderBase Class Reference	40
11.8.1	Detailed Description	41
11.8.2	Constructor & Destructor Documentation	41
11.8.3	Member Function Documentation	41
11.8.4	Field Documentation	41
11.9	plugins.ccsds_plugin.cfe.ccsds_secondary_header.CcsdsSecondaryCmdHeader Class Reference	41
11.9.1	Detailed Description	42
11.9.2	Constructor & Destructor Documentation	42
11.9.3	Member Function Documentation	42
11.9.4	Field Documentation	42
11.10	plugins.ccsds_plugin.cfe.ccsds_secondary_header.CcsdsSecondaryTlmHeader Class Reference	42
11.10.1	Detailed Description	42
11.10.2	Field Documentation	43
11.11	plugins.ccsds_plugin.cfe.ccsds_v1.ccsds_v1.CcsdsV1CmdPacket Class Reference	43
11.11.1	Detailed Description	43
11.11.2	Member Function Documentation	43
11.11.3	Field Documentation	43
11.12	plugins.ccsds_plugin.cfe.ccsds_v1.ccsds_v1.CcsdsV1Packet Class Reference	43
11.12.1	Detailed Description	44
11.12.2	Member Function Documentation	44
11.12.3	Field Documentation	44
11.13	plugins.ccsds_plugin.cfe.ccsds_v1.ccsds_v1.CcsdsV1PrimaryHeader Class Reference	44
11.13.1	Detailed Description	44
11.14	plugins.ccsds_plugin.cfe.ccsds_v1.ccsds_v1.CcsdsV1TlmPacket Class Reference	44
11.14.1	Detailed Description	44

11.14.2 Field Documentation . . . . .	45
11.15plugins.ccsds_plugin.cfe.ccsds_v2.ccsds_v2.CcsdsV2CmdPacket Class Reference . . . . .	45
11.15.1 Detailed Description . . . . .	45
11.15.2 Field Documentation . . . . .	45
11.16plugins.ccsds_plugin.cfe.ccsds_v2.ccsds_v2.CcsdsV2ExtendedHeader Class Reference . . . . .	45
11.16.1 Detailed Description . . . . .	46
11.16.2 Constructor & Destructor Documentation . . . . .	46
11.16.3 Field Documentation . . . . .	46
11.17plugins.ccsds_plugin.cfe.ccsds_v2.ccsds_v2.CcsdsV2Packet Class Reference . . . . .	46
11.17.1 Detailed Description . . . . .	47
11.17.2 Member Function Documentation . . . . .	47
11.17.3 Field Documentation . . . . .	47
11.18plugins.ccsds_plugin.cfe.ccsds_v2.ccsds_v2.CcsdsV2PrimaryHeader Class Reference . . . . .	47
11.18.1 Detailed Description . . . . .	47
11.19plugins.ccsds_plugin.cfe.ccsds_v2.ccsds_v2.CcsdsV2TlmPacket Class Reference . . . . .	47
11.19.1 Detailed Description . . . . .	47
11.19.2 Field Documentation . . . . .	48
11.20plugins.ccsds_plugin.ccsds_packet_interface.CcsdsVer Class Reference . . . . .	48
11.20.1 Detailed Description . . . . .	48
11.21plugins.cfs.cfs_config.CfsConfig Class Reference . . . . .	48
11.21.1 Detailed Description . . . . .	49
11.21.2 Constructor & Destructor Documentation . . . . .	49
11.21.3 Member Function Documentation . . . . .	49
11.22plugins.cfs.pycfs.cfs_controllers.CfsController Class Reference . . . . .	50
11.22.1 Detailed Description . . . . .	51
11.22.2 Constructor & Destructor Documentation . . . . .	51
11.22.3 Member Function Documentation . . . . .	51
11.23plugins.cfs.pycfs.cfs_interface.CfsInterface Class Reference . . . . .	53
11.23.1 Detailed Description . . . . .	54
11.23.2 Constructor & Destructor Documentation . . . . .	54
11.23.3 Member Function Documentation . . . . .	54
11.24plugins.cfs.cfs_plugin.CfsPlugin Class Reference . . . . .	56
11.24.1 Detailed Description . . . . .	57
11.24.2 Constructor & Destructor Documentation . . . . .	57
11.24.3 Member Function Documentation . . . . .	58
11.25plugins.cfs.cfs_time_manager.CfsTimeManager Class Reference . . . . .	58
11.25.1 Detailed Description . . . . .	58

11.25.2 Constructor & Destructor Documentation . . . . .	58
11.25.3 Member Function Documentation . . . . .	59
11.26plugins.ccsds_plugin.readers.command_builder.CommandArg Class Reference . . . . .	59
11.26.1 Detailed Description . . . . .	59
11.27plugins.ccsds_plugin.readers.command_builder.CommandCode Class Reference . . . . .	59
11.27.1 Detailed Description . . . . .	60
11.28plugins.cfs.pycfs.command_interface.CommandInterface Class Reference . . . . .	60
11.28.1 Detailed Description . . . . .	60
11.28.2 Constructor & Destructor Documentation . . . . .	60
11.28.3 Member Function Documentation . . . . .	61
11.29plugins.ccsds_plugin.readers.command_builder.CommandMessage Class Reference . . . . .	61
11.29.1 Detailed Description . . . . .	61
11.30plugins.control_flow_plugin.control_flow_plugin.ControlFlowPlugin Class Reference . . . . .	61
11.30.1 Detailed Description . . . . .	62
11.30.2 Constructor & Destructor Documentation . . . . .	62
11.30.3 Member Function Documentation . . . . .	63
11.31lib.exceptions.CtfConditionError Class Reference . . . . .	64
11.31.1 Detailed Description . . . . .	64
11.31.2 Constructor & Destructor Documentation . . . . .	64
11.32lib.logger.CtfLogLevel Class Reference . . . . .	64
11.32.1 Detailed Description . . . . .	65
11.33lib.exceptions.CtfParameterError Class Reference . . . . .	65
11.33.1 Detailed Description . . . . .	65
11.33.2 Constructor & Destructor Documentation . . . . .	65
11.34lib.exceptions.CtfTestError Class Reference . . . . .	65
11.34.1 Detailed Description . . . . .	65
11.34.2 Constructor & Destructor Documentation . . . . .	65
11.35lib.ctf_global.CtfVerificationStage Class Reference . . . . .	66
11.35.1 Detailed Description . . . . .	66
11.36plugins.example_plugin.example_plugin.ExamplePlugin Class Reference . . . . .	66
11.36.1 Detailed Description . . . . .	66
11.36.2 Constructor & Destructor Documentation . . . . .	67
11.36.3 Member Function Documentation . . . . .	67
11.36.4 Field Documentation . . . . .	68
11.37lib.ftp_interface.FtpInterface Class Reference . . . . .	68
11.37.1 Detailed Description . . . . .	68
11.37.2 Constructor & Destructor Documentation . . . . .	69

11.37.3 Member Function Documentation . . . . .	69
11.38lib.ctf_global.Global Class Reference . . . . .	70
11.38.1 Detailed Description . . . . .	71
11.38.2 Member Function Documentation . . . . .	71
11.38.3 Field Documentation . . . . .	71
11.39lib.event_types.Instruction Class Reference . . . . .	72
11.39.1 Detailed Description . . . . .	73
11.40lib.readers.json_script_reader.JSONScriptReader Class Reference . . . . .	73
11.40.1 Detailed Description . . . . .	73
11.40.2 Constructor & Destructor Documentation . . . . .	74
11.40.3 Member Function Documentation . . . . .	74
11.41plugins.cfs.pycfs.local_cfs_interface.LocalCfsInterface Class Reference . . . . .	74
11.41.1 Detailed Description . . . . .	74
11.41.2 Constructor & Destructor Documentation . . . . .	75
11.41.3 Member Function Documentation . . . . .	75
11.42lib.status.ObjectFactory Class Reference . . . . .	75
11.42.1 Detailed Description . . . . .	75
11.43plugins.cfs.pycfs.output_app_interface.OutputManager Class Reference . . . . .	76
11.43.1 Detailed Description . . . . .	76
11.43.2 Constructor & Destructor Documentation . . . . .	76
11.43.3 Member Function Documentation . . . . .	76
11.44lib.plugin_manager.Plugin Class Reference . . . . .	76
11.44.1 Detailed Description . . . . .	77
11.44.2 Constructor & Destructor Documentation . . . . .	77
11.44.3 Member Function Documentation . . . . .	77
11.44.4 Field Documentation . . . . .	78
11.45lib.plugin_manager.PluginManager Class Reference . . . . .	78
11.45.1 Detailed Description . . . . .	78
11.45.2 Constructor & Destructor Documentation . . . . .	78
11.45.3 Member Function Documentation . . . . .	78
11.46plugins.cfs.cfs_config.RemoteCfsConfig Class Reference . . . . .	79
11.46.1 Detailed Description . . . . .	79
11.46.2 Constructor & Destructor Documentation . . . . .	80
11.46.3 Member Function Documentation . . . . .	80
11.47plugins.cfs.pycfs.cfs_controllers.RemoteCfsController Class Reference . . . . .	80
11.47.1 Detailed Description . . . . .	80
11.47.2 Constructor & Destructor Documentation . . . . .	80

11.47.3 Member Function Documentation . . . . .	81
11.48plugins.cfs.pycfs.remote_cfs_interface.RemoteCfsInterface Class Reference . . . . .	81
11.48.1 Detailed Description . . . . .	81
11.48.2 Constructor & Destructor Documentation . . . . .	81
11.48.3 Member Function Documentation . . . . .	82
11.49lib.script_manager.ScriptManager Class Reference . . . . .	82
11.49.1 Detailed Description . . . . .	82
11.49.2 Constructor & Destructor Documentation . . . . .	83
11.49.3 Member Function Documentation . . . . .	83
11.50lib.script_manager.ScriptManagerConfig Class Reference . . . . .	83
11.50.1 Detailed Description . . . . .	83
11.50.2 Constructor & Destructor Documentation . . . . .	84
11.51plugins.ssh.ssh_plugin.SshConfig Class Reference . . . . .	84
11.51.1 Detailed Description . . . . .	84
11.51.2 Constructor & Destructor Documentation . . . . .	84
11.52plugins.ssh.ssh_plugin.SshController Class Reference . . . . .	84
11.52.1 Detailed Description . . . . .	85
11.52.2 Constructor & Destructor Documentation . . . . .	85
11.52.3 Member Function Documentation . . . . .	85
11.53plugins.ssh.ssh_plugin.SshPlugin Class Reference . . . . .	86
11.53.1 Detailed Description . . . . .	87
11.53.2 Constructor & Destructor Documentation . . . . .	87
11.53.3 Member Function Documentation . . . . .	87
11.54lib.status.StatusDefs Class Reference . . . . .	91
11.54.1 Detailed Description . . . . .	91
11.55lib.status_manager.StatusManager Class Reference . . . . .	91
11.55.1 Detailed Description . . . . .	92
11.55.2 Constructor & Destructor Documentation . . . . .	92
11.55.3 Member Function Documentation . . . . .	92
11.56plugins.cfs.pycfs.cfs_interface.TelemetryVerification Class Reference . . . . .	94
11.56.1 Detailed Description . . . . .	94
11.56.2 Constructor & Destructor Documentation . . . . .	94
11.57lib.test.Test Class Reference . . . . .	94
11.57.1 Detailed Description . . . . .	95
11.57.2 Constructor & Destructor Documentation . . . . .	95
11.57.3 Member Function Documentation . . . . .	95
11.58lib.logger.TestFormatter Class Reference . . . . .	96



11.58.1 Detailed Description . . . . .	96
11.59lib.test_script.TestScript Class Reference . . . . .	96
11.59.1 Detailed Description . . . . .	97
11.59.2 Constructor & Destructor Documentation . . . . .	97
11.59.3 Member Function Documentation . . . . .	97
11.60lib.time_interface.TimeInterface Class Reference . . . . .	98
11.60.1 Detailed Description . . . . .	98
11.60.2 Constructor & Destructor Documentation . . . . .	98
11.60.3 Member Function Documentation . . . . .	98
11.60.4 Field Documentation . . . . .	99
11.61plugins.cfs.pycfs.tlm_listener.TlmListener Class Reference . . . . .	99
11.61.1 Detailed Description . . . . .	99
11.61.2 Constructor & Destructor Documentation . . . . .	99
11.61.3 Member Function Documentation . . . . .	100
11.62plugins.cfs.pycfs.output_app_interface.ToApi Class Reference . . . . .	100
11.62.1 Detailed Description . . . . .	100
11.62.2 Constructor & Destructor Documentation . . . . .	100
11.62.3 Member Function Documentation . . . . .	101
11.63plugins.userio_plugin.userio_plugin.UserIOPlugin Class Reference . . . . .	101
11.63.1 Detailed Description . . . . .	101
11.63.2 Constructor & Destructor Documentation . . . . .	102
11.63.3 Member Function Documentation . . . . .	102
11.64plugins.validation_plugin.validation_plugin.ValidationPlugin Class Reference . . . . .	102
11.64.1 Detailed Description . . . . .	103
11.64.2 Constructor & Destructor Documentation . . . . .	103
11.64.3 Member Function Documentation . . . . .	103
11.65plugins.variable_plugin.variable_plugin.VariablePlugin Class Reference . . . . .	104
11.65.1 Detailed Description . . . . .	104
11.65.2 Constructor & Destructor Documentation . . . . .	105
11.65.3 Member Function Documentation . . . . .	105

## Index

106

## 1 cFS Test Framework (CTF) Tool

- [CTF Software Requirements Specification \(SRS\)](#)
- [CTF Software Design Document \(SDD\)](#)

- [CTF Software Test Procedures and Test Reports \(STP\)](#)
- [CTF Software User's Guide \(SUG\)](#)
- [CTF Test Instruction Reference](#)
- [CTF Assumptions, Dependencies and Constraints \(See Sections 8 & 9 of the SUG.\)](#)
- [CTF Frequently Asked Questions \(See Section 11.1 of the SUG\)](#)

## 2 CCSDS Plugin

The CCSDS Plugin provides interfaces and utilities for CCSDS messages. It is responsible for parsing message structures and constructing messages with the correct header and payload formats.

### Configuration

The CCSDS plugin reads some values from the `[ccsds]` section of CTF config file:

- **CCSDS\_header\_info\_included:** Boolean indicating whether header info is included in the CCSDS exports
- **CCSDS\_header\_path:** The full file path of the module implementing CCSDS header types. The file does not need to be inside of the CTF directory. The CCSDS Plugin provides three header implementations: `ccsds_v1`, `ccsds_v2`, and `ccsds_gw`. To provide your own implementation, see [Custom CCSDS Headers](#) below.

### ValidateCfsCcsdsData

Validates the format of CFS data types by sending one of each known command with an empty (all zeroes) payload.

- **target:** (string) The name of a registered CFS target. See [CFS Plugin](#) for registering targets.

Example:

```
{
  "instruction": "RegisterCfs",
  "data": {
    "target": "cfs_workstation"
  },
  "wait": 1
},
{
  "instruction": "StartCfs",
  "data": {
    "target": "cfs_workstation"
  },
  "wait": 1
},
{
  "instruction": "ValidateCfsCcsdsData",
  "data": {
    "target": "cfs_workstation"
  },
  "wait": 1
}
```

### Custom CCSDS Headers

The CCSDS Plugin provides default implementations of CCSDS message headers, and interfaces for implementing your own custom header types. Follow these steps to implement your own CCSDS header definitions, and refer to any of the provided implementations for further examples.

#### Create a new module

Create a new Python source file in the desired location. Import `ctypes` and declare classes for each of the primary header, a command packet, and a telemetry packet. These may extend the corresponding types provided by the CCSDS Plugin, or ultimately from `ctypes.Structure`. CCSDS headers typically extend from `ctypes.BigEndianStructure`.

Example:

```
import ctypes

from plugins.ccsds_plugin.ccsds_primary_header import CcsdsPrimaryHeaderBase

class MyPrimaryHeader(CcsdsPrimaryHeaderBase):
    pass

class MyCmdPacket(ctypes.Structure):
    pass

class MyTlmPacket(ctypes.Structure):
    pass
```

#### Define the fields and methods

Declare fields representing the bit structure of the headers. See `ctypes` documentation for details. Implement the necessary class methods to expose the field values. `CcsdsPacketInterface` provides an unimplemented interface for your convenience. You may also implement other structures and methods for internal use. At minimum, the following methods must be implemented:

- **Primary Header:** `get_msg_id()`, `is_command()`
- **Command Packet:** `get_msg_id()`, `get_function_code()`
- **Telemetry Packet:** `get_msg_id()`

Example:

```
class MyPrimaryHeader(ctypes.BigEndianStructure):
    _pack_ = 1
    _fields_ = [
        ("type", ctypes.c_uint16, 1), # Packet type:      0 = TLM, 1 = CMD
        ("app_id", ctypes.c_uint16, 11), # Application ID
        ("length", ctypes.c_uint16, 16) # total packet length
    ]

    def is_command(self) -> int:
        return self.type

    def get_msg_id(self) -> int:
        return self.app_id
```

### Export the types

Alias your types to `CcsdsPrimaryHeader`, `CcsdsCommand`, `CcsdsTelemetry` respectively for export. CTF will import and reference them by these names. In the CTF config file, set `ccsds:CCSDS_header_path` to the full path to your module.

Example:

```
CcsdsPrimaryHeader = MyPrimaryHeader
CcsdsCommand = MyCmdPacket
CcsdsTelemetry = MyTlmPacket
```

### Test

Use the `ValidateCfsCcsdsData` in a test script to validate the header definitions as shown above. If the implementing module contains errors or does not meet the minimum requirements of CTF, `RegisterCfs` will fail and print an error message. Check CFS output to ensure that it recognized each of the messages and MIDs.

## 3 CFS Plugin

The CFS Plugin provides CFS command/telemetry support for CTF. The following test instructions are available.

### Configuration

The CFS plugin draws many default values from the CTF config file. The section `[cfs]` defines defaults for all CFS targets and is always required.

If multiple CFS targets are to be registered, for each target name, the plugin will load values from a correspondingly named section.

If no targets are explicitly registered by name by the time `StartCfs` is first executed, the plugin will automatically configure targets for each config section beginning with `cfs_`. If no such sections are found, the plugin will configure a single target using the `[cfs]` config section. Note that if the `cfs_protocol` field is not found in the `cfs` section, a local target will be registered.

The precedence of values is first the named config section, if any, and then the `[cfs]` config section. A target cannot be registered, explicitly nor automatically, without a correspondingly named config section.

### Example

“

### Base settings for cfs

`[cfs]` ...

### Override settings for cfs\_LX1

[cfs\_LX1] ...

### Override settings for cfs\_workstation

[cfs\_workstation] ...

### Override settings for remote\_cfs

[remote\_cfs] ""

In this case, the test script may explicitly register target(s) named any of `cfs`, `cfs_LX1`, `cfs_workstation`, or `remote_cfs`. If no targets are explicitly registered, the plugin will configure targets `cfs_LX1` and `cfs_workstation` automatically because they match the naming convention, but not `remote_cfs`: it must be explicitly registered. The following examples assume that a target `cfs_workstation` has been registered.

A number of configuration fields relate to the CCDD files and formats, which will likely vary by project:

- `cfs:CCSDS_data_dir` provides the path to the directory containing CCDD JSON files for this target.
- `cfs:CCSDS_target` provides the target name found in the CCDD JSON files to identify MID values for this target.
- `cfs:log_ccsds_imports` will log details of CCDD JSON parsing for this target.
- `cfs:evs_event_mid_name` provides the name of the EVS event MID which must match the name given in CCDD JSON.
- `ccsds:CCSDS_header_path` provides the path to the module implementing CCSDS header definitions for all targets.

### Test Script Considerations

CTF supports resolving macros from the `ccsds_data_dir` and replacing macros in the test script with the actual "c\_value". Ensure a # precedes the macro in the test script in order for CTF to do macro replacement.

##### Example

```
{
    "instruction": "CheckTlmValue",
    "data": {
        "mid": "CFE_EVS_HK_TLM_MID",
        "args": [
            {
                "variable": "Payload.AppData[#MY_APPDATA_INDEX].AppID",
                "value": [
                    "0"
                ],
                "compare": "=="
            }
        ]
    }
}
```

```

        }
    ],
    "target": ""
},
    "wait": 1
}

```

### RegisterCfs

Declares a CFS target to be loaded according to the config file section of the same name. Any fields not provided in the named section will fall back to the CFS default values. The named section must contain, at minimum, a value for `cfs_protocol`, and may override any value specified in the `[cfs]` section.

- **target:** (string) A unique name to identify the target in later instructions. The name must match a section name in the config file.

Example:

```

{
    "instruction": "RegisterCfs",
    "data": {
        "target": "cfs_workstation"
    },
    "wait": 1,
}

```

Config:

```

[cfs_workstation]
cfs_protocol="local"
...

```

### BuildCfs

Builds a CFS target.

- **target:** (Optional) A previously registered target name. If no name is given, applies to all registered targets.

Example:

```

{
    "instruction": "BuildCfs",
    "data": {
        "target": "cfs_workstation"
    },
    "wait": 1,
}

```

### StartCfs

Starts a CFS target.

- **target:** (Optional) A previously registered target name. If no name is given, applies to all registered targets.
- **run\_args:** (Optional) Specify command line arguments to start CFS with. The value is appended to the `cfs_run_args` defined in the configuration INI file.

Example:

```
{
  "instruction": "StartCfs",
  "data": {
    "target": "cfs_workstation",
    "run_args": "-R PO"
  },
  "wait": 1
}
```

### EnableCfsOutput

Enables CFS output. No parameters.

- **target:** (Optional) A previously registered target name. If no name is given, applies to all registered target.

Example:

```
{
  "instruction": "EnableCfsOutput",
  "data": {
    "target": "cfs_workstation"
  },
  "wait": 1,
}
```

### SendCfsCommand & SendCfsCommandWithPayloadLength

Constructs and sends a command message to CFS with the specified MID, command code, and payload arguments.

**Note:** `SendCfsCommandWithPayloadLength` was named `SendInvalidLengthCfsCommand` prior to CTF v1.4

- **target:** (Optional) A previously registered target name. If no name is given, applies to all registered targets.
- **mid:** The message ID of the command (i.e. "BEX\_CMD\_MID") (string)
- **cc:** The command code for the command (i.e. "BEX\_NOOP\_CC") (string)
- **payload\_length:** (Optional) The size of the payload in bytes for a manually sized command. Do not specify for valid fixed-size commands. The actual length of the message will include the header size.
- **args:** An object where the key is the argument name, and the value is the argument value. Because `args` is a dictionary, the order does not matter. (i.e. `{"field_b": 1, "field_a": 0}` is equivalent to `{"field_a": 0, "field_b": 1}`)
- **header:** (Optional) An object where the key is the header field name, and the value is the field value. This object is passed into to the `CcsdsCommand` type (as determined by the config field `'ccsds:CCSDS_header_path'`) and is not handled by CTF directly. It is made available for custom CCSDS header implementations to allow specification of the packet header.

Example:

```
{
  "instruction": "SendCfsCommand",
  "data": {
    "target": "cfs_workstation",
```

```

        "mid": "TO_CMD_MID",
        "cc": TO_ENABLE_OUTPUT,
        "args": {
            "cDestIp": "127.0.0.1",
            "usDestPort": "5011"
        },
        "wait": 1
    }
}

```

### SendCfsCommandWithRawPayload

Constructs and sends a command message to CFS with the specified MID, command code, and payload bytes. The payload type for this command must be a byte array.

- **target:** (Optional) A previously registered target name. If no name is given, applies to all registered targets.
- **mid:** The message ID of the command (i.e. "BEX\_CMD\_MID") (string)
- **cc:** The command code for the command (i.e. "BEX\_NOOP\_CC") (string)
- **hex\_buffer:** A hexadecimal string representing the command payload. The string must be an even length (2 characters per byte) no larger than the command payload size and contain only hex numerals 0-F.
- **header:** (Optional) An object where the key is the header field name, and the value is the field value. This object is passed into to the `CcsdsCommand` type (as determined by the config field '`ccsds:CCSDS_header_path`') and is not handled by CTF directly. It is made available for custom CCSDS header implementations to allow specification of the packet header.

Example:

```

{
    "instruction": "SendCfsCommandWithRawPayload",
    "data": {
        "target": "cfs_workstation",
        "mid": "DUMMY_IO_CMD_MID",
        "cc": "DUMMY_IO_RAW_BYTE_CC",
        "hex_buffer": "0123456789ABCDEF"
    },
    "wait": 1
}

```

### CheckEvent

Checks that an event message matching the given parameters has been received from the CFS target. **Note:** This instruction's syntax changed in CTF v1.4

- **target:** (Optional) A previously registered target name. If no name is given, applies to all registered targets.
- **args:** an array of argument objects that describe the events to be checked. Multiple arguments can be listed here to check multiple events at once.
  - **app\_name:** The app that sent the event message.
  - **event\_id:** The Event ID, taken from an EVS enum, to represent the criticality level of a message. 13 is information, 14 is error, and anything else should be updated into this wiki as you find it.
  - **event\_str:** (Optional) The expected message of the event. If blank, the `event_str` field is not verified.
  - **is\_regex:** (Optional) True if `event_str` is to be used for a regex match instead of string comparison



- **event\_str\_args**: (optional) arguments that will be inserted into `event_str`, similar to `printf()` functions

Example:

```
{
  "instruction": "CheckEvent",
  "data": {
    "target": "cfs_workstation",
    "args": [
      {
        "app_name": "BEX",
        "event_id": 13,
        "event_str": "Processed MODE(%d) Command Successfully Received",
        "is_regex": false,
        "event_str_args": "(1,)"
      },
      {
        "app_name": "TO",
        "event_id": "3",
        "event_str": "TO - ENABLE_OUTPUT cmd succesful for routeMask:0x00000001"
      }
    ]
  },
  "wait": 1
}
```

### CheckNoEvent

Checks that an event message matching the given parameters is no longer valid in received messages from the CFS target. **Note:** This instruction's syntax changed in CTF v1.4

- **target**: (Optional) A previously registered target name. If no name is given, applies to all registered targets.
- **args**: an array of argument objects that describe the events to be checked. Multiple arguments can be listed here to check multiple events at once.
  - **app\_name**: The app that sent the event message.
  - **event\_id**: The Event ID, taken from an EVS enum, to represent the criticality level of a message. 13 is information, 14 is error, and anything else should be updated into this wiki as you find it.
  - **event\_str**: (Optional) The expected message of the event. If blank, the `event_str` field is not verified.
  - **is\_regex**: (Optional) True if `event_str` is to be used for a regex match instead of string comparison
  - **event\_str\_args**: (optional) arguments that will be inserted into `event_str`, similar to `printf()` functions

Example:

```
{
  "instruction": "CheckNoEvent",
  "data": {
    "target": "cfs_workstation",
    "args": [
      {
        "app_name": "TO",
        "event_id": "3",
        "event_str": "TO - ENABLE_OUTPUT cmd succesful for routeMask:0x00000001",
        "event_str_args": ""
      }
    ]
  }
}
```

```

    ]
  },
  "wait": 4,
  "description": "ENABLE_OUTPUT cmd message is no longer valid in received messages"
}

```

### CheckTlmValue

Checks that a telemetry message matching the given parameters has been received from the CFS target.

- **target:** (Optional) A previously registered target name. If no name is given, applies to all registered targets.
- **mid:** The telemetry message ID to check.
- **args:** an array of argument objects that describe the values to be checked. Multiple arguments can be listed here to check multiple attributes of a given packet at once.
  - **compare:** How to compare the telemetry value with the test value. Must be one of: ==, <=, <, >, >=, !=, streq (string equal), strneq (string not equal), regex (any regex match on a string).
  - **variable:** The attribute in the telemetry packet to check against.
  - **expected\_mid** (optional): The telemetry message ID where the expected value can be found. Only needed if the check will be performed between two variables. This must match a name that was defined for this MID in the CCDD. (string)
  - **value:** The value to compare against. (number, string, bool) Note that the single value must be contained in a list: **\*\*"value":[0]\*\***, not **\*\*"value":0\*\***. Also if the command is called within a function and the value is a function parameter, put the parameter name as a string: **\*\*"value":["myParamName"]\*\***. If **expected\_mid** is set, this field should contain the variable path to be checked.
  - **tolerance:** floating point tolerance.
  - **tolerance\_plus/tolerance\_minus:** non-symmetric floating point tolerance.

Example:

```

{
  "instruction": "CheckTlmValue",
  "data": {
    "target": "cfs_workstation",
    "mid": "TO_HK_TLM_MID",
    "args": [
      {
        "compare": "==",
        "variable": "usCmdErrCnt",
        "value": [
          1
        ]
      },
      {
        "compare": "==",
        "variable": "usCmdCnt",
        "value": [
          3.05
        ],
        "tolerance_plus": 0.1,
        "tolerance_minus": 0.1
      }
    ]
  },
  "wait": 1
}

```

### CheckTlmPacket

Checks that a telemetry message with the given MID has been received from the CFS target. This is equivalent to `CheckTlmValue` without comparing args.

- **target:** (Optional) A previously registered target name. If no name is given, applies to all registered targets.
- **mid:** The telemetry message ID to check.

Example:

```
{
  "instruction": "CheckTlmPacket",
  "data": {
    "target": "cfs_workstation",
    "mid": "TO_HK_TLM_MID"
  },
  "wait": 1
}
```

### CheckNoTlmPacket

Checks that a telemetry message with the given MID is no longer valid in received messages from the CFS target.

- **target:** (Optional) A previously registered target name. If no name is given, applies to all registered targets.
- **mid:** The telemetry message ID to check.

Example:

```
{
  "instruction": "CheckNoTlmPacket",
  "data": {
    "target": "cfs_workstation",
    "mid": "TO_HK_TLM_MID"
  },
  "wait": 1
}
```

### CheckTlmContinuous

Similar to `CheckTlmValue` except the check is performed each time telemetry is received, until the test ends or the check is removed by `RemoveCheckTlmContinuous`.

- **target:** (Optional) A previously registered target name. If no name is given, applies to all registered targets.
- **verification\_id:** A unique string to identify this check within the test.
- **mid:** The telemetry message ID to check.
- **args:** an array of argument objects that describe the values to be checked. Multiple arguments can be listed here to check multiple attributes of a given packet at once.
  - **compare:** How to compare the telemetry value with the test value. Must be one of: `==`, `<=`, `<`, `>`, `>=`, `!=`, `streq` (string equal), `strneq` (string not equal), `regex` (any regex match on a string).
  - **variable:** The attribute in the telemetry packet to check against.

- **expected\_mid** (optional): The telemetry message ID where the expected value can be found. Only needed if the check will be performed between two variables. This must match a name that was defined for this MID in the CCDD. (string)
- **value**: The value to compare against. (number, string, bool) Note that the single value must be contained in a list: `**"value":[0]**`, not `**"value":0**`. Also if the command is called within a function and the value is a function parameter, put the parameter name as a string: `**"value":["myParamName"]**`. If **expected\_mid** is set, this field should contain the variable path to be checked.
- **tolerance**: floating point tolerance.
- **tolerance\_plus/tolerance\_minus**: non-symmetric floating point tolerance.

Example:

```
{
  "instruction": "CheckTlmContinuous",
  "data": {
    "target": "cfs_workstation",
    "verification_id": "TO_no_errors",
    "mid": "TO_HK_TLM_MID",
    "args": [
      {
        "compare": "==",
        "variable": "usCmdErrCnt",
        "value": [
          0
        ]
      }
    ]
  },
  "wait": 1
}
```

#### RemoveCheckTlmContinuous

Cancels a continuous telemetry check by ID so that it is no longer performed.

- **target**: (Optional) A previously registered target name. If no name is given, applies to all registered targets. Note that the target must match with the target specified in `CheckTlmContinuous`, otherwise the instruction will fail as it tries to remove the ID on the wrong target.
- **verification\_id**: The ID of a check previously added by `CheckTlmContinuous`

Example:

```
{
  "instruction": "RemoveCheckTlmContinuous",
  "data": {
    "target": "cfs_workstation",
    "verification_id": "TO_no_errors"
  },
  "wait": 1,
}
```

#### ArchiveCfsFiles

Copies files from a directory that have been modified during the current test run into the test run's log directory.

- **target:** (Optional) A previously registered target name. If no name is given, applies to all registered targets.
- **source\_path:** A directory path, absolute or relative to the location of CTF, from which to copy files

Example:

```
{
  "instruction": "ArchiveCfsFiles",
  "data": {
    "target": "cfs_workstation",
    "source_path": "../..../build/exe/lx1/cf/"
  },
  "wait": 1
}
```

#### ShutdownCfs

Shuts down a CFS target explicitly within the test script. Note, the CFS plugin will automatically shutdown all CFS targets on test completion.

- **target:** (Optional) A previously registered target name. If no name is given, applies to all registered targets.

Example:

```
{
  "instruction": "ShutdownCfs",
  "data": {
    "target": "cfs_workstation"
  },
  "wait": 1,
}
```

## 4 Control Flow Plugin

The Control-Flow Plugin provides the functionality of CTF control flow statement at instruction level. It includes looping and conditional statements.

#### BeginLoop

Create a loop entry point. The loop is identified by a unique label. The BeginLoop must be in pairs with EndLoop instruction. The loop condition is defined in parameter "conditions" as a list of variables and the associated comparison operations. The condition is True, only if all comparison operations are True.

- **label:** a user defined label (example: "LOOP\_1")
- **conditions:** a list of comparison conditions. Each includes "name", "operator" and "value".
- **variable:** either a variable defined by user or a variable from telemetry.
- **compare:** the operator applied to variable, including "<", "<=", ">", ">=", "==", "!=" (example: "<")
- **value:** numerical number (example: 20)

Example:

```
{
  "instruction": "BeginLoop",
  "data": {
    "label": "LOOP_1",
    "conditions": [
      {"variable": "my_var", "compare": "<", "value": 20},
      {"variable": "tlm_usCmdCnt", "compare": "<", "value": 7}
    ]
  }
}
```

#### EndLoop

Create a loop exit point. It must match a BeginLoop instruction with the same label. If the looping condition in BeginLoop is False, the control flow jumps to the corresponding EndLoop instruction, and exits the loop.

- **label:** a user defined label (example: "LOOP\_1")

Example:

```
{
  "instruction": "EndLoop",
  "data": {
    "label": "LOOP_1"
  }
}
```

#### IfCondition

Create an entry point for if conditional branch block. It is identified by a unique label per test script. The IfCondition must be in pairs with EndCondition instruction. ElseCondition instruction is optional. The condition is defined in parameter "conditions" as a list of variables and the associated comparison operations. The condition is True, only if all comparison operations are True.

- **label:** a user defined label (example: "If\_Label\_1")
- **conditions:** a list of comparison conditions. Each includes "name", "operator" and "value".
- **variable:** either a variable defined by user or a variable from telemetry.
- **compare:** the operator applied to variable, including "<", "<=", ">", ">=", "==", "!=" (example: "<")
- **value:** numerical number (example: 7)

Example:

```
{
  "instruction": "IfCondition",
  "data": {
    "label": "If_Label_1",
    "conditions": [
      {"variable": "my_var", "compare": "<", "value": 10},
      {"variable": "tlm_usCmdCnt", "compare": "<", "value": 7}
    ]
  }
}
```

### ElseCondition

Create an entry point for else conditional branch block. The instruction is optional. But if defined, it must match a IfCondition and a EndCondition instruction with the same label. If the condition of IfCondition instruction is False, the control flow skips the 'if' branch block, only executes the 'else' branch block. If ElseCondition instruction is not defined, the control flow jumps to the end of conditional branch block defined by a EndCondition instruction.

- **label:** a user defined label (example: "If\_Label\_1")

Example:

```
{
  "instruction": "ElseCondition",
  "data": {
    "label": "If_Label_1"
  }
}
```

### EndCondition

Create an exit point for if conditional branch block. It must match a IfCondition instruction with the same label. When the control flow reaches EndCondition instruction, it exits the conditional branch block.

- **label:** a user defined label (example: "If\_Label\_1")

Example:

```
{
  "instruction": "EndCondition",
  "data": {
    "label": "If_Label_1"
  }
}
```

## 5 Example Plugin

The Example Plugin shows a simple CTF plugin that can perform a single test instruction and a single verification instruction.

### TestCommand

Simply logs that the test command was executed with the provided arguments.

- **arg1:** any value (example: "Hello")
- **arg2:** any value (example: "World")

Example:

```
{
  "instruction": "TestCommand",
  "data": {
    "arg1": "foo",
    "arg2": 42
  }
}
```

**TestVerifyCommand**

Increments the plugin's `example_counter` value and checks if it is greater than 5. CTF will poll run that instructions until the verification is successful, or a timeout occurs.

Example:

```
{
  "instruction": "TestVerifyCommand",
  "data": {}
}
```

**TestSharedLibraryCommand**

Uses `libc` to get the system time and log it to system output. Verifies that the expected number of bytes were printed.

Example:

```
{
  "instruction": "TestSharedLibraryCommand",
  "data": {}
}
```

## 6 SSH Plugin

The SSH Plugin provides remote and local shell command execution capability for CTF. The following test instructions are available.

**SSH\_RegisterTarget**

Declares a target host by name. This command must be run before any other commands given the same name will work. Command may be used multiple times to declare any number of targets. If not used, the plugin will assume that all commands are intended for the same target as defined in `SSH_InitSSH`

- **data**: an object where the key is the argument name, and the value is the argument value
  - **name**: An arbitrary, unique name to identify the target in subsequent commands. Does not need be the actual hostname of the target. Name is optional in all other commands, but if not provided all such commands will share a single connection.

Example:

```
{
  "instruction": "SSH_RegisterTarget",
  "wait": 1,
  "data": {
    "name": "workstation"
  }
}
```

**SSH\_InitSSH**

Establishes an SSH connection with a target host. This command must be run before other remote commands will work. Command may be used multiple times with the same name to connect to different remote hosts in succession, or be used with different names to maintain concurrent connections to multiple hosts.

- **data**: an object where the key is the argument name, and the value is the argument value



- **host**: hostname or IP to connect to, which may include the username and/or port.
- **name**: A name already registered with `SSH_RegisterTarget` to identify the connection. (Optional)
- **user**: User name for the connection. Do not use if you specified the user in `host`. (Optional)
- **port**: Port number for the connection. Do not use if you specified the port in `host`. (Optional)
- **gateway**: SSH gateway command string to proxy the connection to `host` (Optional)
- **ssh\_config\_path**: Path to an ssh config file which may contain host definitions or additional parameters. If not specified, `~/ .ssh/config` will be assumed. (Optional)
- **args**: Additional SSH connection options, as needed. See [Paramiko API docs](#) for relevant values. (Optional)

Note - CTF does not currently handle password entry/storage. Follow the tutorial [here](#) to set up SSH key authorization  
Example:

```
{
  "instruction": "SSH_InitSSH",
  "wait": 1,
  "data": {
    "name": "workstation",
    "host": "123.123.123.1",
    "user": "lander_demo"
    "port": 22
    "gateway": "ssh -W %h:%p myproxy"
    "ssh_config_path": "./ssh/config"
  }
}
```

### SSH\_RunRemoteCommand

Executes a command on the remote host. **ExecutionInitSSH** must be called first to establish an SSH connection.

- **data**: an object where the key is the argument name, and the value is the argument value
  - **name**: A name already registered with `SSH_RegisterTarget` to identify the connection. (Optional)
  - **command**: The shell command to be executed. Can contain multiple commands separated with ;

Example:

```
{
  "instruction": "SSH_RunRemoteCommand",
  "wait": 1,
  "data": {
    "name": "workstation",
    "host": "cd lander_fsw_ctf/;rm -rf build; make; make install;"
  }
}
```

### SSH\_RunLocalCommand

Executes a command on the local host (the machine running CTF), regardless of the target. This is different from calling `SSH_RunRemoteCommand` targeting localhost, as it is invoked directly by the current process rather than passed via SSH.

- **data**: an object where the key is the argument name, and the value is the argument value

- **name**: A name already registered with `SSH_RegisterTarget` to identify the connection. (Optional)
- **command**: The shell command to be executed. Can contain multiple commands separated with ;

Example:

```
{
  "instruction": "SSH_RunLocalCommand",
  "wait": 1,
  "data": {
    "name": "workstation",
    "host": "cd lander_fsw_ctf/;rm -rf build; make; make install;"
  }
}
```

### SSH\_CheckOutput

Compares the output of the most recently executed command. **ExecutionRunRemoteCommand** or **ExecutionRunLocalCommand** must be called first.

- **data**: an object where the key is the argument name, and the value is the argument value
  - **name**: A name already registered with `SSH_RegisterTarget` to identify the connection. (Optional)
  - **output\_contains** (optional): A substring that must be contained in stdout. (Example: "PASS")
  - **output\_does\_not\_contain** (optional): A substring that should *not* be contained in stdout. (Example: "FAIL")
  - **exit\_code** (optional, default = 0): The expected exit code after the shell command is executed.

Example:

```
{
  "instruction": "SSH_CheckOutput",
  "wait": 0,
  "data": {
    "name": "workstation",
    "output_contains": "Built target mission-install",
    "output_does_not_contain": "Error",
    "exit_code": 0
  }
}
```

### SSH\_PutFile

Copies a path (file or directory) from the local filesystem to the remote host via rsync. Relative or absolute paths are allowed, but do not use ~. Strings are passed directly to rsync, so the same rules apply regarding paths, patterns, etc.

- **data**: an object where the key is the argument name, and the value is the argument value
  - **name**: A name already registered with `SSH_RegisterTarget` to identify the connection. (Optional)
  - **local\_path**: The path to the local file or directory to be copied
  - **remote\_path**: The path to where the file or directory is to be copied. For remote hosts use the SSH syntax `_user:path_`.
  - **args**: An object that describes optional parameters for the transfer
    - \* **delete**: A boolean corresponding to `rsync's --delete` option. If true, `rsync` will remove remote files that no longer exist locally. Defaults to false.

- \* **exclude:** A string or array of strings corresponding to `rsync`'s `--exclude` option. Defaults to None.

Example:

```
{
  "instruction": "SSH_PutFile",
  "wait": 0,
  "data": {
    "name": "workstation",
    "local_path": "./cfs",
    "remote_path": "/tmp/workspace/cfs",
    "args": {
      "delete": true,
      "exclude": "*.git"
    }
  }
}
```

### SSH\_GetFile

Copies a path (file or directory) from the remote host to the local filesystem via `rsync`. Relative or absolute paths are allowed, but do not use `~`. Strings are passed directly to `rsync`, so the same rules apply regarding paths, patterns, etc.

- **data:** an object where the key is the argument name, and the value is the argument value
  - **name:** A name already registered with `SSH_RegisterTarget` to identify the connection. (Optional)
  - **remote\_path:** The path to the source file or directory to be copied. For remote hosts use the SSH syntax `_user:path_`.
  - **local\_path:** The local path to where the file or directory is to be copied
  - **args:** An object that describes optional parameters for the transfer
    - \* **delete:** A boolean corresponding to `rsync`'s `--delete` option. If true, `rsync` will remove remote files that no longer exist locally. Defaults to false.
    - \* **exclude:** A string or array of strings corresponding to `rsync`'s `--exclude` option. Defaults to None.

Example:

```
{
  "instruction": "SSH_GetFile",
  "wait": 0,
  "data": {
    "name": "workstation",
    "remote_path": "./data/output.dat",
    "local_path": "./results.txt"
  }
}
```

### SSH\_GetFTP

Downloads a path (file or directory) from the FTP server to the local filesystem.

- **data:** an object where the key is the argument name, and the value is the argument value
  - **name:** A name already registered with `SSH_RegisterTarget` to identify the connection. (Optional)
  - **host:** The hostname or address of the FTP server
  - **remote\_path:** The path to the source file or directory on the FTP server

- **local\_path**: The local path to where the file or directory is to be downloaded

Example:

```
{
  "instruction": "SSH_GetFTP",
  "wait": 0,
  "data": {
    "name": "workstation",
    "host": "ftphost",
    "remote_path": "./data/output.dat",
    "local_path": "./results.txt"
  }
}
```

### SSH\_PutFTP

Uploads a path (file or directory) from the local filesystem to the FTP server.

- **data**: an object where the key is the argument name, and the value is the argument value
  - **name**: A name already registered with `SSH_RegisterTarget` to identify the connection. (Optional)
  - **host**: The hostname or address of the FTP server
  - **remote\_path**: The path on the FTP server to where the file or directory is to be uploaded
  - **local\_path**: The local path to the source file or directory

Example:

```
{
  "instruction": "SSH_PutFTP",
  "wait": 0,
  "data": {
    "name": "workstation",
    "host": "ftphost",
    "remote_path": "./data/output.dat",
    "local_path": "./results.txt"
  }
}
```

## 7 UserIO Plugin

The UserIO Plugin handles user input/output operations, including pausing test for safety critical operations. In such cases, CTF will wait until users confirm whether to continue or to abort the tests.

### WaitForUserInput

When CTF executes `WaitForUserInput`, it will pause and wait for user input from `stdin`. If a user enters "Y", CTF will continue to execute next test instructions. Any other input will abort the test.

- **prompt**: optional value (example: "safety critical")

Example:

```
{
  "instruction": "WaitForUserInput",
  "data": {
    "prompt": "  "
  }
}
```

## 8 Validation Plugin

The Validation Plugin provides functionality to interpret a cFE binary event log to a human-readable text file, and search for a text string in a file. It also allows the user to delete files/folders and copy files/folders on the local host machine.

### SaveFileAsText

Save the cFE event log file (binary file created via the CFE\_EVS\_WRITE\_LOG\_DATA\_FILE\_CC command) to a human-readable text file

- **input\_file**: path of the binary event log file.
- **output\_file**: path of the output text file.
- **file\_type**: currently only supports 'EVS' file type.
- **target**: cfs target, optional

Example:

```
{
  "instruction": "SaveFileAsText",
  "data": {
    "input_file": "/dev/shm/osal:RAM/event_log.bin",
    "output_file": "./testArtifacts/event_log.txt",
    "file_type": "EVS",
    "target": "cfs"
  }
}
```

### SearchStr

Search a text file for a given text string. If the string is found, return True, otherwise return False.

- **file**: path of the text file.
- **search\_str**: text string to be searched for.

Example:

```
{
  "instruction": "SearchStr",
  "data": {
    "file": "/testArtifacts/event_log.txt",
    "search_str": "./testArtifacts/"
  }
}
```

### CopyFiles

Copy a file or folder on the host file system. The source may point to a file or folder. If the destination exists, it will be overridden.

- **source:** path of the file / folder to be copied from on host machine.
- **destination:** path of the file / folder to be copied to on host machine.

Example:

```
{
  "instruction": "CopyFiles",
  "data": {
    "source": "./testArtifacts/",
    "destination": "./testArtifacts/"
  }
}
```

### DeleteFiles

Delete a file or folder on the host file system.

- **path:** path of the file / folder to be deleted on host machine.

Example:

```
{
  "instruction": "DeleteFiles",
  "data": {
    "path": "./testArtifacts/"
  }
}
```

## 9 Variable Plugin

The Variable Plugin provides CTF users with the capability to Set / Check / Update user-defined variables from json test scripts. The defined variables can be used in control flow instructions, such as "BeginLoop" and "EndLoop". The following instructions are available.

### SetUserVariable

Set / update the value of user defined variable.

- **variable\_name:** the user-defined variable name (example: "my\_var")
- **operator:** the operator applied to variable, including "=", "+", "-", "\*", "/" (example: "=")
- **value:** numerical number (example: 0)

Example:

```
{
  "instruction": "SetUserVariable",
```

```

    "data": {
      "variable_name": "my_var",
      "operator": "=",
      "value": 0
    }
  }
}

```

#### SetUserVariableFromTlm

Set the user defined variable to the latest telemetry value.

- **variable\_name**: the user-defined variable name (example: "my\_var")
- **mid**: the mid of telemetry packet (example: "TO\_HK\_TLM\_MID")
- **tlm\_variable**: the parameter of telemetry packet (example: "usCmdCnt")

Example:

```

{
  "instruction": "SetUserVariableFromTlm",
  "data": {
    "variable_name": "my_var",
    "mid": "TO_HK_TLM_MID",
    "tlm_variable": "usCmdCnt"
  }
}

```

#### SetUserVariableFromTlmHeader

Same as SetUserVariableFromTlm except the variable references the packet header.

- **variable\_name**: the user-defined variable name (example: "my\_var")
- **mid**: the mid of telemetry packet (example: "TO\_HK\_TLM\_MID")
- **header\_variable**: the parameter of telemetry packet (example: "pheader.length")

Example:

```

{
  "instruction": "SetUserVariableFromTlmHeader",
  "data": {
    "variable_name": "my_var",
    "mid": "TO_HK_TLM_MID",
    "tlm_variable": "pheader.length"
  }
}

```

#### CheckUserVariable

Compare the user-defined variable with the value using the operator. Return the bool outcome of the operation performed on the variables and values.

- **variable\_name**: the user-defined variable name (example: "my\_var")
- **operator**: the operator applied to variable, including "<", "<=", ">", ">=", "==", "!=" (example: "==")

- **value**: numerical number (example: 4)

Example:

```
{
  "instruction": "CheckUserVariable",
  "data": {
    "variable_name": "my_var",
    "operator": "==",
    "value": 4
  }
}
```

## 10 Namespace Documentation

### 10.1 lib Namespace Reference

#### Namespaces

- [args\\_validation](#)
- [ctf\\_global](#)
- [ctf\\_utility](#)
- [event\\_types](#)
- [exceptions](#)
- [ftp\\_interface](#)
- [logger](#)
- [plugin\\_manager](#)
- [readers](#)
- [script\\_manager](#)
- [status](#)
- [status\\_manager](#)
- [test](#)
- [test\\_script](#)
- [time\\_interface](#)

#### 10.1.1 Detailed Description

@namespace lib  
CTF Core Components

### 10.2 lib.args\_validation Namespace Reference

#### Data Structures

- class [ArgsValidation](#)

#### 10.2.1 Detailed Description

@namespace lib.args\_validation  
Argument Validation Helper Utilities



## 10.3 lib.ctf\_global Namespace Reference

### Data Structures

- class [CtfVerificationStage](#)
- class [Global](#)

### Variables

- string [DEFAULT\\_CONFIG](#) = "configs/default\_config.ini"  
*Default Config used by CTF if no config\_file is provided in the arguments.*

#### 10.3.1 Detailed Description

@namespace lib.ctf\_global  
Exposes CTF global state information for utilization by CTF Plugins.

Global Test Info object accessible by all plugins.  
Populated by script reader with test header  
info and other useful values for plugins

## 10.4 lib.ctf\_utility Namespace Reference

### Functions

- def [expand\\_path](#)
- def [switch\\_to\\_ctf\\_directory](#)
- def [get\\_current\\_instruction\\_index](#)
- def [set\\_goto\\_instruction\\_index](#)
- def [set\\_variable](#)
- def [get\\_variable](#)
- def [resolve\\_variable](#)
- def [rgetattr](#)

### Variables

- dictionary **operator\_map**
- string **MACRO\_MARKER** = '#'
- string **VAR\_MARKER** = '\$'
- string **INDEX\_PATTERN** = r'\[(.\*?)\]'

#### 10.4.1 Detailed Description

@namespace lib.ctf\_utility  
Utility library functions

#### 10.4.2 Function Documentation

##### 10.4.2.1 def lib.ctf\_utility.expand\_path ( path )

Given a directory path, expand the path with the user directory and variables, returning the expanded path

**10.4.2.2** `def lib.ctf_utility.get_current_instruction_index ( )`

Return the current instruction execution index

**10.4.2.3** `def lib.ctf_utility.get_variable ( variable_name )`

Get the user defined variable, which will be used in variable plugin

**10.4.2.4** `def lib.ctf_utility.resolve_variable ( variable )`

A variable may be passed to an instruction argument as a string "xyz\$variable\_name\$abc", Search the global variable\_store to evaluate its value.

**10.4.2.5** `def lib.ctf_utility.rgetattr ( obj, attr, args )`

Given an object and an attribute name, return the value of the specified attribute.

**10.4.2.6** `def lib.ctf_utility.set_goto_instruction_index ( index )`

Set the instruction execution index in Global, which will be used in the ControlFlow Plugin

**10.4.2.7** `def lib.ctf_utility.set_variable ( variable_name, op_code, value )`

Set/Update the user defined variable, which will be used in ControlFlow and Variable Plugins

**10.4.2.8** `def lib.ctf_utility.switch_to_ctf_directory ( )`

Switch the working directory to ctf directory, return ctf directory path

**10.4.3** Variable Documentation**10.4.3.1** dictionary lib.ctf\_utility.operator\_map

**Initial value:**

```
1 = {
2     "+": operator.add,
3     "-": operator.sub,
4     "*": operator.mul,
5     "/": operator.truediv,
6     "<": operator.lt,
7     "<=": operator.le,
8     ">": operator.gt,
9     ">=": operator.ge,
10    "==": operator.eq,
11    "!=": operator.ne,
12 }
```

**10.5** lib.event\_types Namespace Reference**Data Structures**

- class [Instruction](#)

### 10.5.1 Detailed Description

```
@namespace lib.event_types
Event Type definitions for CTF
```

## 10.6 lib.exceptions Namespace Reference

### Data Structures

- class [CtfTestError](#)
- class [CtfConditionError](#)
- class [CtfParameterError](#)

### 10.6.1 Detailed Description

```
@namespace lib.exceptions
Exception definitions for CTF
```

## 10.7 lib.ftp\_interface Namespace Reference

### Data Structures

- class [FtpInterface](#)

### 10.7.1 Detailed Description

```
@namespace lib.ftp_interface
FTP interface for CTF
```

## 10.8 lib.logger Namespace Reference

### Data Structures

- class [CtfLogLevel](#)
- class [TestFormatter](#)

### Functions

- def [test](#)
- def [init\\_logger](#)
- def [set\\_logger\\_options\\_from\\_config](#)
- def [change\\_log\\_file](#)

### Variables

- **colorlog** = None
- string **LOG\_FORMAT** = '%[(asctime)s.%(msecs)03d] %(module)-32s(%(lineno)-3d) \*\*\* %(levelname)s: %(message)s'
- string **TIME\_FORMAT** = '%H:%M:%S'

- tuple **logger** = logging.getLogger()
- tuple **test\_formatter** = [TestFormatter](#)(LOG\_FORMAT)

### 10.8.1 Detailed Description

@namespace lib.logger  
Logger configuration and initialization for CTF logging

### 10.8.2 Function Documentation

#### 10.8.2.1 def lib.logger.change\_log\_file ( new\_log\_file )

change\_log\_file function: Change log file to store logging information.  
@param new\_log\_file: the new file for logger to store logging information.  
@return None

#### 10.8.2.2 def lib.logger.init\_logger ( config )

Initializes the logger with CTF-specific handlers and formatting

#### 10.8.2.3 def lib.logger.set\_logger\_options\_from\_config ( config )

Configures the logger, and sets the log directory and first log file for this test run

#### 10.8.2.4 def lib.logger.test ( self, passed, cont, msg, args, kwargs )

Passed as a callback to logging configuration for logging test results  
@note - self is an instance of class Logger

## 10.9 lib.plugin\_manager Namespace Reference

### Data Structures

- class [ArgTypes](#)
- class [Plugin](#)
- class [PluginManager](#)

### 10.9.1 Detailed Description

@namespace lib.plugin\_manager  
The Plugin Manager is a CTF core component that manages CTF plugins.

## 10.10 lib.readers Namespace Reference

### Namespaces

- [json\\_script\\_reader](#)

### 10.10.1 Detailed Description

@namespace lib.readers  
CTF Json Script Reader

## 10.11 lib.readers.json\_script\_reader Namespace Reference

### Data Structures

- class [JSONScriptReader](#)

#### 10.11.1 Detailed Description

```
@namespace lib.readers.json_script_reader
Loads and validates input CTF test scripts. Manages execution of loaded test scripts.
```

## 10.12 lib.script\_manager Namespace Reference

### Data Structures

- class [ScriptManagerConfig](#)
- class [ScriptManager](#)

#### 10.12.1 Detailed Description

```
@namespace lib.script_manager
Loads and manages test scripts during a test run
```

## 10.13 lib.status Namespace Reference

### Data Structures

- class [StatusDefs](#)
- class [ObjectFactory](#)

#### 10.13.1 Detailed Description

```
@namespace lib.status
Defines status messages to be sent out by CTF during a test run
```

## 10.14 lib.status\_manager Namespace Reference

### Data Structures

- class [StatusManager](#)

#### 10.14.1 Detailed Description

```
@namespace lib.status_manager
Publishes CTF status messages over a UDP socket (utilized by the CTF editor)
```

## 10.15 lib.test Namespace Reference

### Data Structures

- class [Test](#)

#### 10.15.1 Detailed Description

```
@namespace lib.Test
Represents a single CTF test case
```

## 10.16 lib.test\_script Namespace Reference

### Data Structures

- class [TestScript](#)

#### 10.16.1 Detailed Description

```
@namespace lib.test_script
Loads and validates input CTF test scripts. Manages execution of loaded test scripts.
```

## 10.17 lib.time\_interface Namespace Reference

### Data Structures

- class [TimeInterface](#)

#### 10.17.1 Detailed Description

```
@namespace lib.time_interface
Interface definition for time managers to implement
```

## 10.18 plugins.cfs.cfs\_config Namespace Reference

### Data Structures

- class [CfsConfig](#)
- class [RemoteCfsConfig](#)

### Variables

- **CONFIG** = [Global.config](#)

#### 10.18.1 Detailed Description

```
cfs_config.py: CFS Plugin Config for CTF.
```

```
- Defines the expected fields in the cfs config section for
  a base (linux) target, as well as Remote SSH targets.
```

## 10.19 plugins.control\_flow\_plugin.control\_flow\_plugin Namespace Reference

### Data Structures

- class [ControlFlowPlugin](#)

#### 10.19.1 Detailed Description

@namespace plugins.control\_flow\_plugin

The Control-Flow Plugin provides the functionality of CTF control flow statement, including looping and conditional statements.

## 10.20 plugins.example\_plugin.example\_plugin Namespace Reference

### Data Structures

- class [ExamplePlugin](#)

#### 10.20.1 Detailed Description

@namespace plugins.example\_plugin

The Example Plugin module shows a minimal plugin implementation to be used as a template for other CTF plugins

## 10.21 plugins.ssh.ssh\_plugin Namespace Reference

### Data Structures

- class [SshConfig](#)
- class [SshPlugin](#)
- class [SshController](#)

#### 10.21.1 Detailed Description

@namespace plugins.ssh\_plugin

The SSH Plugin provides remote and local shell command execution capability for CTF. The module defines SshPlugin class and SshConfig, SshController helper class.

## 10.22 plugins.variable\_plugin.variable\_plugin Namespace Reference

### Data Structures

- class [VariablePlugin](#)

#### 10.22.1 Detailed Description

@namespace plugins.variable\_plugin

The Variable Plugin module allows users to set / update / check variables defined in json test scripts.

## 11 Data Structure Documentation

### 11.1 lib.args\_validation.ArgsValidation Class Reference

#### Public Member Functions

- def `__init__`
- def `add_error`
- def `get_error_count`
- def `increment_error_count`
- def `verify_symbol`
- def `validate_symbol`
- def `validate_file`
- def `validate_number`
- def `validate_int`
- def `validate_ip`
- def `validate_boolean`

#### Static Public Member Functions

- def `is_param_none`
- def `validate_directory`

#### Data Fields

- `parameter_errors`

#### 11.1.1 Detailed Description

Helper class to validate arguments and data used by CTF

#### 11.1.2 Constructor & Destructor Documentation

##### 11.1.2.1 `def lib.args_validation.ArgsValidation.__init__( self )`

Constructor of ArgsValidation class. Initialize instance variable "parameter\_errors", which tracks the number of errors encountered during validation.

#### 11.1.3 Member Function Documentation

##### 11.1.3.1 `def lib.args_validation.ArgsValidation.add_error( self, field, exception = None )`

Increment the number of errors and log an exception if needed  
 @param field: Field name where validation error occurred  
 @param exception: Whether to log an exception on failure or not

##### 11.1.3.2 `def lib.args_validation.ArgsValidation.get_error_count( self )`

Returns the number of errors encountered during validation so far



**11.1.3.3 def lib.args\_validation.ArgsValidation.increment\_error\_count( self )**

Increment error count without logging an exception

**11.1.3.4 def lib.args\_validation.ArgsValidation.is\_param\_none( param ) [static]**

Returns whether or not a given parameter is None

@param param: Parameter to check if None

**11.1.3.5 def lib.args\_validation.ArgsValidation.validate\_boolean( self, value )**

Verify that the given value is valid as a boolean.

Return the converted value, or None if not a boolean.

**11.1.3.6 def lib.args\_validation.ArgsValidation.validate\_directory( directory ) [static]**

Given a directory path, verify that the directory exists on disk.

Return the expanded absolute path, or None if invalid.

**11.1.3.7 def lib.args\_validation.ArgsValidation.validate\_file( self, file\_path, fail\_if\_not\_valid=False )**

Given a file path, verify that the file exists on disk.

Return the expanded absolute path, or None if invalid.

@param file\_path: Path to file to check

@param fail\_if\_not\_valid: Whether to consider an invalid path a failure or not

@note fail\_if\_not\_valid is useful when checking a file that is not guaranteed to exist

**11.1.3.8 def lib.args\_validation.ArgsValidation.validate\_int( self, integer )**

Verify that a given value is valid as an integer.

Return the converted value, or None if not an integer.

**11.1.3.9 def lib.args\_validation.ArgsValidation.validate\_ip( self, ip\_address )**

Verify that the given value is a valid and reachable network destination.

Return the IP address, or None if invalid.

**11.1.3.10 def lib.args\_validation.ArgsValidation.validate\_number( self, number )**

Verify that a given value is valid as a numerical (float).

Return the converted value, or None if not a number.

**11.1.3.11 def lib.args\_validation.ArgsValidation.validate\_symbol( self, symbol, file\_path )**

Given a file path, verify that the file exists on disk and contains the given symbol.

Return the symbol if it exists, otherwise return None

@note - Primarily used to validate SP0 executables

@param symbol: Name of symbol to verify within executable file

@param file\_path: Path to executable file to check

### 11.1.3.12 def lib.args\_validation.ArgsValidation.verify\_symbol( self, file\_path, symbol )

Given a file path, verify that a given symbol exists within that file.  
Return True if the symbol exists, otherwise return False

@note - Primarily used to validate SP0 executables

@param file\_path: Path to executable file to check

@param symbol: Name of symbol to verify within executable file

## 11.2 lib.plugin\_manager.ArgTypes Class Reference

### Static Public Attributes

- string **cmd\_mid** = "cmd\_mid"
- string **cmd\_code** = "cmd\_code"
- string **cmd\_arg** = "cmd\_arg"
- string **tlm\_mid** = "tlm\_mid"
- string **comparison** = "comparison"
- string **string** = "string"
- string **boolean** = "boolean"
- string **number** = "number"
- string **ignore** = "ignore"
- string **condition** = "loop\_condition"
- string **event** = "event"
- string **other** = "other"
- list **array\_types** = [cmd\_arg, comparison, condition, event]

### 11.2.1 Detailed Description

Argument types support by plugin instructions. The argument types are exported to the CTF Editor for autosuggestion and input validation.

## 11.3 plugins.ccsds\_plugin.readers.ccdd\_export\_reader.CCDDExportReader Class Reference

### Public Member Functions

- def **\_\_init\_\_**
- def [process\\_command](#)
- def [process\\_telemetry](#)
- def [process\\_types](#)
- def [process\\_types\\_second\\_pass](#)
- def [process\\_custom\\_types](#)
- def [process\\_ccsds\\_json\\_file](#)
- def [get\\_ccsds\\_messages\\_from\\_dir](#)

### Static Public Member Functions

- def [is\\_command\\_msg](#)
- def [is\\_telemetry\\_msg](#)
- def [is\\_command\\_tlm](#)

- def [is\\_types\\_macros](#)
- def [is\\_custom\\_types](#)
- def [validate\\_json\\_schema](#)

#### Data Fields

- **current\_file\_name**
- **type\_dict**
- **ctype\_structure**

#### Private Member Functions

- def [\\_build\\_data\\_type\\_and\\_field](#)
- def [\\_create\\_parameterized\\_type](#)

#### 11.3.1 Detailed Description

This class reads CCSDS export files in JSON format and creates dictionaries mapping names to Python types and val

#### 11.3.2 Member Function Documentation

##### 11.3.2.1 `def plugins.ccsds_plugin.readers.ccdd_export_reader.CCDDExportReader._build_data_type_and_field ( self, param, fields, subtypes = None ) [private]`

Builds a field, containing a simple data type, for a custom type.  
Returns the data type and appends it to fields.

@note - This method does not create or modify any types. The return value, and the in-out parameter fields, should be used to create the type with `create_type_class`.

@param param: A dictionary containing JSON data defining a field of a parent type

@param fields: A list of fields of the parent type

@param subtypes: A dictionary of subtypes of the parent type

##### 11.3.2.2 `def plugins.ccsds_plugin.readers.ccdd_export_reader.CCDDExportReader._create_parameterized_type ( self, json_dict, type_id = None, arg_id = None, subtypes = None ) [private]`

Recursively creates custom type definitions from JSON data and any known subtypes, and adds them to the type dictionary. Returns the top-level type and a dictionary of any enumerations.

@param json\_dict: A dictionary containing JSON data defining a data type

@param type\_id: The dictionary key for the name of the type

@param arg\_id: The dictionary key for the definitions of subtypes, if any

@param subtypes: A dictionary mapping names of subtypes to their types, used in recursive calls

##### 11.3.2.3 `def plugins.ccsds_plugin.readers.ccdd_export_reader.CCDDExportReader.get_ccsds_messages_from_dir ( self, directory )`

Walks through a directory and parses CCSDS command and telemetry messages and type macros from the JSON, as appropriate. Creates and returns dictionaries mapping names to these constructs.

@param directory: The path to the root directory containing CCSDS exports as .json files

**11.3.2.4** `def plugins.ccsds_plugin.readers.ccdd_export_reader.CCDDExportReader.is_command_msg ( json_data ) [static]`

Returns whether a JSON dictionary represents a CCSDS command message.

**11.3.2.5** `def plugins.ccsds_plugin.readers.ccdd_export_reader.CCDDExportReader.is_command_tlm ( json_data ) [static]`

Returns whether a JSON dictionary represents a CCSDS command or telemetry message.

**11.3.2.6** `def plugins.ccsds_plugin.readers.ccdd_export_reader.CCDDExportReader.is_custom_types ( json_data ) [static]`

Returns whether a JSON dictionary represents custom type definitions.

**11.3.2.7** `def plugins.ccsds_plugin.readers.ccdd_export_reader.CCDDExportReader.is_telemetry_msg ( json_data ) [static]`

Returns whether a JSON dictionary represents a CCSDS telemetry message.

**11.3.2.8** `def plugins.ccsds_plugin.readers.ccdd_export_reader.CCDDExportReader.is_types_macros ( json_data ) [static]`

Returns whether a JSON dictionary represents type aliases or macros.

@note - A list is assumed to be type aliases or macros.

**11.3.2.9** `def plugins.ccsds_plugin.readers.ccdd_export_reader.CCDDExportReader.process_ccsds_json_file ( self, filename, file_filter=None, second_pass=False )`

Reads JSON from a single file and, if it matches the filter, parses the contents

@note - Because of interdependency between files, it is necessary to parse macros first for literal values, then command and telemetry message types, then macros again for type aliases.

@param filename: The path to the file to be read

@param file\_filter: A callable that will return True if the file is to be parsed. Pass None to parse all files

@param second\_pass: True if this is the second time parsing type macros, whose types should already be defined

**11.3.2.10** `def plugins.ccsds_plugin.readers.ccdd_export_reader.CCDDExportReader.process_command ( self, json_dict )`

Parses the contents of a JSON dictionary for a CCSDS command message to dynamically create a new type for each command code which is added to the type dictionary. Defines a command message with the MID and command codes, and an enumeration for each command code by name.

@param json\_dict: A dictionary containing the JSON data of an exported CCSDS telemetry message

**11.3.2.11** `def plugins.ccsds_plugin.readers.ccdd_export_reader.CCDDExportReader.process_custom_types ( self, json_dict )`

Parses the contents of a JSON dictionary for a custom data type which is added to the type dictionary. This type may then be referenced by name in other files without redefining its structure.

@note - json\_dict must include the keys "data\_type" for the name and "parameters" for the contents regardless of whether the data type is to be used in commands or telemetry.

@note - This method should be called before processing any command and telemetry messages so that the definitions of these custom types are known.

@param json\_dict: A dictionary containing the JSON data of an exported data type definition

**11.3.2.12** `def plugins.ccsds_plugin.readers.ccdd_export_reader.CCDDExportReader.process_telemetry ( self, json_dict )`

Parses the contents of a JSON dictionary for a CCSDS telemetry message to dynamically create a new type which is added to the type dictionary. Defines a telemetry message with the MID, name, and type.

@param json\_dict: A dictionary containing the JSON data of an exported CCSDS telemetry message

**11.3.2.13** `def plugins.ccsds_plugin.readers.ccdd_export_reader.CCDDExportReader.process_types ( self, json_list )`

Parses the contents of a JSON dictionary for type macros, and inserts any aliases, constants, or MID mapping into the appropriate dictionaries.

@note - Only aliases of ctypes which are in the type dictionary will be processed. To process aliases of custom types defined in other files, use `process_types_second_pass` after processing those files.

@param json\_list: A dictionary containing the JSON data of exported CCSDS types

**11.3.2.14** `def plugins.ccsds_plugin.readers.ccdd_export_reader.CCDDExportReader.process_types_second_pass ( self, json_list )`

Parses the contents of a JSON dictionary for type aliases only, and adds them to the type dictionary if they are not already defined.

@note - This method should be called after CCSDS command and telemetry messages have been processed so that the definitions of those custom types are known.

@param json\_list: A dictionary containing the JSON data of exported CCSDS types

**11.3.2.15** `def plugins.ccsds_plugin.readers.ccdd_export_reader.CCDDExportReader.validate_json_schema ( json_data, schema_path ) [static]`

Validates a dictionary of JSON data against a schema file.

@param json\_data: A dictionary containing JSON data to be validated

@param schema\_path: Path to a JSON schema file

**11.4** `plugins.ccsds_plugin.ccsds_interface.CCSDSInterface` Class Reference

## Public Member Functions

- `def __init__`
- `def add_telem_msg`
- `def add_cmd_msg`
- `def add_enumeration`
- `def get_ccsds_messages_from_dir`

## Data Fields

- `mids`
- `mid_map`
- `enum_map`
- `config`
- `header_info_included`
- `log_ccsds_imports`

### 11.4.1 Detailed Description

This class provides an interface and partial implementation for a CCSDS reader to process CCSDS data from a directory into dynamic type definitions. The method of parsing the data is left to a subclass.

### 11.4.2 Member Function Documentation

#### 11.4.2.1 `def plugins.ccsds_plugin.ccsds_interface.CCSDSInterface.add_cmd_msg ( self, mid_name, mid, command_code_map, command_enums = None )`

Adds a command message to the internal types

@param mid\_name: Name of the MID associated with the command  
 @param mid: Value of the MID associated with the command  
 @param command\_code\_map: Dictionary mapping command code values to their corresponding types  
 @param command\_enums: Dictionary of enumerations associated with this command

#### 11.4.2.2 `def plugins.ccsds_plugin.ccsds_interface.CCSDSInterface.add_enumeration ( self, key, value )`

Adds an enumeration definition to the internal types

@param key: Name of the enumeration  
 @param value: Value of the enumeration

#### 11.4.2.3 `def plugins.ccsds_plugin.ccsds_interface.CCSDSInterface.add_telem_msg ( self, mid_name, mid, name, parameters, parameter_enums = None )`

Adds a telemetry message to the internal types

@param mid\_name: Name of the MID associated with the command  
 @param mid: Value of the MID associated with the command  
 @param name: Name of the telemetry message  
 @param parameters: Type of the telemetry message parameters  
 @param parameter\_enums: Dictionary of enumerations associated with this telemetry message

#### 11.4.2.4 `def plugins.ccsds_plugin.ccsds_interface.CCSDSInterface.get_ccsds_messages_from_dir ( self, directory )`

Virtual function to be implemented by a reader.  
 Processes the CCSDS data from a directory and returns the data types defined in them.

@param directory: Path to the directory containing CCSDS data type definitions.

## 11.5 plugins.ccsds\_plugin.ccsds\_packet\_interface.CcsdsPacketInterface Class Reference

### Public Member Functions

- def [get\\_msg\\_id](#)
- def [set\\_msg\\_id](#)
- def [has\\_secondary\\_header](#)
- def [get\\_function\\_code](#)
- def [set\\_function\\_code](#)

### 11.5.1 Detailed Description

This class provides a common interface for CCSDS packets to get and set values in the headers

without knowing where they are defined

@note - Classes implementing interface for specific CCSDS packets should inherit from this type and override all methods.

### 11.5.2 Member Function Documentation

#### 11.5.2.1 def plugins.ccsds\_plugin.ccsds\_packet\_interface.CcsdsPacketInterface.get\_function\_code ( self, int )

Convenience method to get the function code from the packet

#### 11.5.2.2 def plugins.ccsds\_plugin.ccsds\_packet\_interface.CcsdsPacketInterface.get\_msg\_id ( self, int )

Convenience method to get the message ID from the packet

#### 11.5.2.3 def plugins.ccsds\_plugin.ccsds\_packet\_interface.CcsdsPacketInterface.has\_secondary\_header ( self, bool )

Convenience method to check for the presence of a secondary header

## 11.6 plugins.ccsds\_plugin.ccsds\_packet\_interface.CcsdsPacketType Class Reference

### Static Public Attributes

- int **CommandPacket** = 1
- int **TelemetryPacket** = 0

### 11.6.1 Detailed Description

This class enumerates CCSDS packet types as integer values

## 11.7 plugins.ccsds\_plugin.ccsds\_plugin.CCSDSPlugin Class Reference

### Public Member Functions

- def **\_\_init\_\_**
- def [get\\_cfs\\_plugin](#)
- def **initialize**
- def [validate\\_cfs\\_ccsds\\_data](#)
- def **shutdown**

### Data Fields

- **name**
- **description**
- **command\_map**
- **cfs\_plugin**

### Private Member Functions

- def **\_send\_commands\_to\_target**

### 11.7.1 Detailed Description

The CCSDS Plugin provides CCSDS validation support for CTF

### 11.7.2 Member Function Documentation

#### 11.7.2.1 def plugins.ccsds\_plugin.ccsds\_plugin.CCSDSPlugin.get\_cfs\_plugin ( self )

Returns the instance of the CFS Plugin registered with the plugin manager

#### 11.7.2.2 def plugins.ccsds\_plugin.ccsds\_plugin.CCSDSPlugin.validate\_cfs\_ccsds\_data ( self, target=None )

Validates the CCSDS data types by sending an empty instance of each command code found in the MID map to CFS.

@note - This instruction will cause commands to be sent to the designated CFS target

@note - The plugin cannot directly verify that CFS is able to process the received data. CFS output should be checked to ensure that no invalid length commands were received.

@param target: The name of the CFS target to be used for validation.  
If not provided, the default target will be used.

## 11.8 plugins.ccsds\_plugin.ccsds\_primary\_header.CcsdsPrimaryHeaderBase Class Reference

### Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def **set\_ccsds\_version**
- def **set\_app\_id**
- def **set\_secondary\_header\_flag**
- def **set\_segmentation\_flags**
- def **set\_sequence\_count**
- def **set\_packet\_length**
- def **set\_packet\_type**
- def [is\\_command](#)
- def [get\\_msg\\_id](#)

### Data Fields

- **version\_number**
- **app\_id**
- **secondary\_header\_flag**
- **segmentation\_flags**
- **sequence\_count**
- **length**
- **type**

### Static Private Attributes

- int **\_pack\_** = 1
- list **\_fields\_**



### 11.8.1 Detailed Description

This class implements the CCSDS primary header as represented by a ctypes BigEndianStructure

### 11.8.2 Constructor & Destructor Documentation

#### 11.8.2.1 def plugins.ccsds\_plugin.ccsds\_primary\_header.CcsdsPrimaryHeaderBase.\_\_init\_\_( self )

class CcsdsPrimaryHeaderBase constructor: assign attributes default values

### 11.8.3 Member Function Documentation

#### 11.8.3.1 def plugins.ccsds\_plugin.ccsds\_primary\_header.CcsdsPrimaryHeaderBase.get\_msg\_id( self, int )

Returns the message ID value derived from the header fields

#### 11.8.3.2 def plugins.ccsds\_plugin.ccsds\_primary\_header.CcsdsPrimaryHeaderBase.is\_command( self, int )

Returns true if the packet represents a command, indicated by the type field

### 11.8.4 Field Documentation

#### 11.8.4.1 list plugins.ccsds\_plugin.ccsds\_primary\_header.CcsdsPrimaryHeaderBase.\_fields\_ [static],[private]

Initial value:

```
1 = [
2     ("version_number", ctypes.c_uint16, 3), # CCSDS version
3     ("type", ctypes.c_uint16, 1), # Packet type: 0 = TLM, 1 = CMD
4     ("secondary_header_flag", ctypes.c_uint16, 1), # Secondary header: 0 = absent, 1 = present
5     ("app_id", ctypes.c_uint16, 11), # Application ID
6     ("segmentation_flags", ctypes.c_uint16, 2), # Segmentation flags: 3 = complete packet
7     ("sequence_count", ctypes.c_uint16, 14), # Sequence count
8     ("length", ctypes.c_uint16, 16) # (total packet length) - 7
9 ]
```

## 11.9 plugins.ccsds\_plugin.cfe.ccsds\_secondary\_header.CcsdsSecondaryCmdHeader Class Reference

### Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [set\\_function\\_code](#)
- def [set\\_checksum](#)
- def [get\\_function\\_code](#)
- def [get\\_checksum](#)

### Data Fields

- [checksum](#)
- [function\\_code](#)

**Static Private Attributes**

- int **\_pack\_** = 1
- list **\_fields\_**

**11.9.1 Detailed Description**

This class implements the CCSDS secondary header as represented by a ctypes BigEndianStructure

**11.9.2 Constructor & Destructor Documentation****11.9.2.1 def plugins.ccsds\_plugin.cfe.ccsds\_secondary\_header.CcsdsSecondaryCmdHeader.\_\_init\_\_( self )**

class CcsdsSecondaryCmdHeader constructor: assign attributes default values

**11.9.3 Member Function Documentation****11.9.3.1 def plugins.ccsds\_plugin.cfe.ccsds\_secondary\_header.CcsdsSecondaryCmdHeader.get\_checksum( self, int )**

Gets the checksum value

**11.9.3.2 def plugins.ccsds\_plugin.cfe.ccsds\_secondary\_header.CcsdsSecondaryCmdHeader.get\_function\_code( self, int )**

Gets the function code value

**11.9.4 Field Documentation****11.9.4.1 list plugins.ccsds\_plugin.cfe.ccsds\_secondary\_header.CcsdsSecondaryCmdHeader.\_fields\_ [static], [private]****Initial value:**

```
1 = [
2     ("function_code", ctypes.c_uint8),
3     ("checksum", ctypes.c_uint8)
4 ]
```

**11.10 plugins.ccsds\_plugin.cfe.ccsds\_secondary\_header.CcsdsSecondaryTlmHeader Class Reference****Static Private Attributes**

- int **\_pack\_** = 1
- list **\_fields\_**

**11.10.1 Detailed Description**

This class implements the CCSDS secondary telemetry header as represented by a ctypes BigEndianStructure

## 11.10.2 Field Documentation

11.10.2.1 list plugins.ccsds\_plugin.cfe.ccsds\_secondary\_header.CcsdsSecondaryTlmHeader.\_fields\_ [static], [private]

## Initial value:

```
1 = [
2     ("timestamp_seconds", ctypes.c_uint32),
3     ("timestamp_subseconds", ctypes.c_uint16),
4 ]
```

## 11.11 plugins.ccsds\_plugin.cfe.ccsds\_v1.ccsds\_v1.CcsdsV1CmdPacket Class Reference

## Public Member Functions

- def `__init__`
- def `get_function_code`
- def `set_function_code`
- def `set_checksum`

## Static Private Attributes

- int `_pack_` = 1
- list `_fields_`

## 11.11.1 Detailed Description

This class implements a CCSDS V1 command packet as represented by a ctypes BigEndianStructure

## 11.11.2 Member Function Documentation

11.11.2.1 def plugins.ccsds\_plugin.cfe.ccsds\_v1.ccsds\_v1.CcsdsV1CmdPacket.get\_function\_code( self, int )

Convenience method to get the function code from the packet

## 11.11.3 Field Documentation

11.11.3.1 list plugins.ccsds\_plugin.cfe.ccsds\_v1.ccsds\_v1.CcsdsV1CmdPacket.\_fields\_ [static], [private]

## Initial value:

```
1 = [
2     ("sheader", CcsdsSecondaryCmdHeader)
3 ]
```

## 11.12 plugins.ccsds\_plugin.cfe.ccsds\_v1.ccsds\_v1.CcsdsV1Packet Class Reference

## Public Member Functions

- def `set_msg_id`
- def `get_msg_id`
- def `has_secondary_header`

**Static Private Attributes**

- `int _pack_ = 1`
- `list _fields_`

**11.12.1 Detailed Description**

This class provides an interface to a CCSDS V1 packet

**11.12.2 Member Function Documentation****11.12.2.1** `def plugins.ccsds_plugin.cfe.ccsds_v1.ccsds_v1.CcsdsV1Packet.get_msg_id( self, int )`

Convenience method to get the message ID from the packet

**11.12.2.2** `def plugins.ccsds_plugin.cfe.ccsds_v1.ccsds_v1.CcsdsV1Packet.has_secondary_header( self, bool )`

Convenience method to check for the presence of a secondary header

**11.12.3 Field Documentation****11.12.3.1** `list plugins.ccsds_plugin.cfe.ccsds_v1.ccsds_v1.CcsdsV1Packet._fields_ [static],[private]`**Initial value:**

```
1 = [
2     ("pheader", CcsdsV1PrimaryHeader)
3 ]
```

**11.13 plugins.ccsds\_plugin.cfe.ccsds\_v1.ccsds\_v1.CcsdsV1PrimaryHeader Class Reference****Additional Inherited Members****11.13.1 Detailed Description**

This is a marker interface to indicate a CCSDS V1 primary header

**11.14 plugins.ccsds\_plugin.cfe.ccsds\_v1.ccsds\_v1.CcsdsV1TlmPacket Class Reference****Static Private Attributes**

- `int _pack_ = 1`
- `list _fields_`

**Additional Inherited Members****11.14.1 Detailed Description**

This class implements a CCSDS V1 telemetry packet as represented by a ctypes BigEndianStructure

## 11.14.2 Field Documentation

11.14.2.1 list plugins.ccsds\_plugin.cfe.ccsds\_v1.ccsds\_v1.CcsdsV1TlmPacket.\_fields\_ [static],[private]

## Initial value:

```

1 = [
2     ("sheader", CcsdsSecondaryTlmHeader)
3 ]

```

## 11.15 plugins.ccsds\_plugin.cfe.ccsds\_v2.ccsds\_v2.CcsdsV2CmdPacket Class Reference

## Public Member Functions

- def `__init__`
- def `get_function_code`
- def `set_function_code`

## Static Private Attributes

- int `_pack_` = 1
- list `_fields_`

## 11.15.1 Detailed Description

This class implements a CCSDS V2 command packet as represented by a ctypes BigEndianStructure

## 11.15.2 Field Documentation

11.15.2.1 list plugins.ccsds\_plugin.cfe.ccsds\_v2.ccsds\_v2.CcsdsV2CmdPacket.\_fields\_ [static],[private]

## Initial value:

```

1 = [
2     ("sheader", CcsdsSecondaryCmdHeader)
3 ]

```

## 11.16 plugins.ccsds\_plugin.cfe.ccsds\_v2.ccsds\_v2.CcsdsV2ExtendedHeader Class Reference

## Public Member Functions

- def `__init__`
- def `set_edc_version`
- def `set_endian`
- def `set_playback_flag`
- def `set_subsystem_id`
- def `set_system_id`

## Data Fields

- eds\_version
- endian
- playback\_flag
- subsystem\_id
- system\_id

## Static Private Attributes

- int \_pack\_ = 1
- list \_fields\_

## 11.16.1 Detailed Description

This class implements a CCSDS V2 extended header as represented by a ctypes BigEndianStructure

## 11.16.2 Constructor &amp; Destructor Documentation

## 11.16.2.1 def plugins.ccsds\_plugin.cfe.ccsds\_v2.ccsds\_v2.CcsdsV2ExtendedHeader.\_\_init\_\_( self )

class CcsdsV2ExtendedHeader constructor: assign attributes default values

## 11.16.3 Field Documentation

## 11.16.3.1 list plugins.ccsds\_plugin.cfe.ccsds\_v2.ccsds\_v2.CcsdsV2ExtendedHeader.\_fields\_ [static],[private]

## Initial value:

```
1 = [
2     ("eds_version", ctypes.c_uint16, 5), # EDS Version for packet definition used
3     ("endian", ctypes.c_uint16, 1), # Endian: Big = 0, Little = 1
4     ("playback_flag", ctypes.c_uint16, 1), # Playback flag 0 = original, 1 = playback
5     ("subsystem_id", ctypes.c_uint16, 9), # Subsystem ID (mission defined)
6     ("system_id", ctypes.c_uint16, 16), # System ID (mission defined)
7 ]
```

## 11.17 plugins.ccsds\_plugin.cfe.ccsds\_v2.ccsds\_v2.CcsdsV2Packet Class Reference

## Public Member Functions

- def set\_msg\_id
- def get\_msg\_id
- def has\_secondary\_header
- def get\_function\_code
- def set\_function\_code

## Static Private Attributes

- int \_pack\_ = 1
- list \_fields\_

### 11.17.1 Detailed Description

This class provides an interface to a CCSDS V2 packet

### 11.17.2 Member Function Documentation

#### 11.17.2.1 def plugins.ccsds\_plugin.cfe.ccsds\_v2.ccsds\_v2.CcsdsV2Packet.get\_msg\_id ( self, int )

Returns the message ID derived from the header fields

Python implementation of CFE\_SB\_GetMsgId(CFE\_SB\_MsgPtr\_t MsgPtr)

### 11.17.3 Field Documentation

#### 11.17.3.1 list plugins.ccsds\_plugin.cfe.ccsds\_v2.ccsds\_v2.CcsdsV2Packet.\_fields\_ [static],[private]

**Initial value:**

```
1 = [
2     ("pheader", CcsdsV2PrimaryHeader),
3     ("eheader", CcsdsV2ExtendedHeader)
4 ]
```

## 11.18 plugins.ccsds\_plugin.cfe.ccsds\_v2.ccsds\_v2.CcsdsV2PrimaryHeader Class Reference

### Public Member Functions

- def **is\_command**

### Additional Inherited Members

#### 11.18.1 Detailed Description

This class provides an interface to a CCSDS V2 primary header

@note - This is a sample implementation showing how custom headers can extend CcsdsPrimaryHeaderBase as needed.  
The implementation of is\_command is redundant with CcsdsPrimaryHeaderBase.

## 11.19 plugins.ccsds\_plugin.cfe.ccsds\_v2.ccsds\_v2.CcsdsV2TlmPacket Class Reference

### Static Private Attributes

- int **\_pack\_** = 1
- list **\_fields\_**

### Additional Inherited Members

#### 11.19.1 Detailed Description

This class implements a CCSDS V2 telemetry packet as represented by a ctypes BigEndianStructure

## 11.19.2 Field Documentation

11.19.2.1 list plugins.ccsds\_plugin.cfe.ccsds\_v2.ccsds\_v2.CcsdsV2TlmPacket.\_fields\_ [static], [private]

**Initial value:**

```

1 = [
2     ("sheader", CcsdsSecondaryTlmHeader)
3 ]

```

## 11.20 plugins.ccsds\_plugin.ccsds\_packet\_interface.CcsdsVer Class Reference

## Static Public Attributes

- int **Ccsds\_ver\_1** = 1
- int **Ccsds\_ver\_2** = 2
- int **Ccsds\_ver\_GW** = 3

## 11.20.1 Detailed Description

This class enumerates CCSDS versions as integer values

## 11.21 plugins.cfs.cfs\_config.CfsConfig Class Reference

## Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [configure](#)
- def [load\\_field](#)
- def [load\\_config\\_data](#)
- def [set\\_ctf\\_ip](#)
- def [set\\_cfs\\_run\\_cmd](#)
- def [get\\_error\\_count](#)

## Data Fields

- **sections**
- **validation**
- **name**
- **cfs\_protocol**
- **build\_cfs**
- **ccsds\_data\_dir**
- **ccsds\_target**
- **log\_ccsds\_imports**
- **cfs\_build\_dir**
- **cfs\_build\_cmd**
- **cfs\_run\_dir**
- **cfs\_port\_arg**
- **cfs\_exe**
- **cfs\_run\_args**



- `cfs_ram_drive_path`
- `cfs_run_cmd`
- `cfs_output_file`
- `remove_continuous_on_fail`
- `cfs_target_ip`
- `ctf_ip`
- `cmd_udp_port`
- `tlm_udp_port`
- `evs_log_file`
- `cfs_debug`
- `cfs_run_in_xterm`
- `tlm_app_choice`
- `ccsds_ver`
- `evs_long_event_mid_name`
- `evs_short_event_mid_name`
- `evs_messages_clear_after_time`
- `endianess_of_target`
- `ccsds_header_info_included`
- `telemetry_debug`

### 11.21.1 Detailed Description

The CFS Configuration classes handle interpreting the respective CFS Target section in the loaded INI config. The INI config could have multiple CFS targets, defined as sections, and each target specifies the needed fields. Documentation of the CFS configuration fields can be found in the CFS Plugin README. Refer to INI or README for field descriptions.

### 11.21.2 Constructor & Destructor Documentation

#### 11.21.2.1 `def plugins.cfs.cfs_config.CfsConfig.__init__( self, name )`

Constructor for CfsConfig class. Assign all Cfs config attributes to default None.

### 11.21.3 Member Function Documentation

#### 11.21.3.1 `def plugins.cfs.cfs_config.CfsConfig.configure( self, name )`

Setup CfsConfig attributes based on INI file

#### 11.21.3.2 `def plugins.cfs.cfs_config.CfsConfig.get_error_count( self )`

Return field validation error counts.  
@return field validation error counts

#### 11.21.3.3 `def plugins.cfs.cfs_config.CfsConfig.load_config_data( self, section_name )`

From loaded sections of INI config, interpret CFS target config attributes, including `build_cfs`, `CCSDS_data_dir`, `CCSDS_target`, etc.  
@param section\_name: loaded Json CFS target section.  
@return None

### 11.21.3.4 def plugins.cfs.cfs\_config.CfsConfig.load\_field( self, section, field\_name, config\_getter, validate\_function=None )

Interpret field attribute of loaded CFS target config section.  
 @param section: loaded Json CFS target section.  
 @param field\_name: the field name for loaded attribute.  
 @param config\_getter: the function to get an option value for a given section.  
 @param validate\_function: the function to validate the field attribute (Optional).  
 @return Any: field attribute with matching name

### 11.21.3.5 def plugins.cfs.cfs\_config.CfsConfig.set\_cfs\_run\_cmd( self, cfs\_exe = "", cfs\_run\_args = "" )

Set CFS config attribute cfs\_exe, cfs\_run\_args, and cfs\_run\_cmd.  
 if passed arguments are empty string, use the config attributes from INI file  
 @param cfs\_exe: CFS executable name. if it is empty string, use the field from INI file  
 @param cfs\_run\_args: CFS executable arguments. if it is empty string, use the field from INI file  
 @return None

### 11.21.3.6 def plugins.cfs.cfs\_config.CfsConfig.set\_ctf\_ip( self )

Get the IP address through a temporary created socket to CFS target, and assign the ip to config attribute  
 @return None

## 11.22 plugins.cfs.pycfs.cfs\_controllers.CfsController Class Reference

### Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [process\\_ccsds\\_files](#)
- def [initialize](#)
- def [build\\_cfs](#)
- def [start\\_cfs](#)
- def [enable\\_cfs\\_output](#)
- def [send\\_cfs\\_command](#)
- def [build\\_command\\_payload](#)
- def [convert\\_args\\_to\\_ctypes](#)
- def [encode\\_ctypes\\_to\\_bytes](#)
- def [resolve\\_macros](#)
- def [resolve\\_simple\\_type](#)
- def [resolve\\_args\\_from\\_dict](#)
- def [check\\_tlm\\_value](#)
- def [get\\_tlm\\_value](#)
- def [check\\_tlm\\_continuous](#)
- def [convert\\_check\\_tlm\\_args](#)
- def [remove\\_check\\_tlm\\_continuous](#)
- def [check\\_event](#)
- def [archive\\_cfs\\_files](#)
- def [shutdown\\_cfs](#)
- def [shutdown](#)
- def [validate\\_mid\\_value](#)
- def [validate\\_cc\\_value](#)

### Static Public Member Functions

- def [field\\_class\\_by\\_name](#)

## Data Fields

- **config**
- **cfs\_process\_list**
- **cfs**
- **ccsds\_reader**
- **mid\_map**
- **macro\_map**
- **ccsds**
- **first\_call\_flag**
- **mid\_pkt\_count**
- **cfs\_running**

## 11.22.1 Detailed Description

CfsController class Definition: CFS Controller Implementation for CTF.

@note When the CFS plugin registers a target, a cFS controller object is instantiated.  
 @note After the cfs\_plugin receives a test instruction, the cFS controller handles all lower-level functionality beneath the plugin.  
 @note On controller initialization, telem/command interfaces are established, CCSDS message definitions are parsed to build the mid map, and controller becomes ready to send commands and verify telemetry.  
 @note Controller implements the specific functionality needed to execute the cFS plugin instructions  
 @note Controller manages cFS process, and will shutdown the target at the end of the test script or on ShutdownCfs instruction.

## 11.22.2 Constructor &amp; Destructor Documentation

## 11.22.2.1 def plugins.cfs.pycfs.cfs\_controllers.CfsController.\_\_init\_\_( self, config )

Constructor implementation for CfsController class. Assign default values for CfsController properties

## 11.22.3 Member Function Documentation

## 11.22.3.1 def plugins.cfs.pycfs.cfs\_controllers.CfsController.archive\_cfs\_files( self, source\_path )

Implementation of CFS plugin instructions archive\_cfs\_files. When CFS plugin instructions (archive\_cfs\_files) is executed, it calls CfsController instance's archive\_cfs\_files function.

## 11.22.3.2 def plugins.cfs.pycfs.cfs\_controllers.CfsController.build\_cfs( self )

Implementation of CFS plugin instructions build\_cfs. When CFS plugin instructions (build\_cfs) is executed, it calls CfsController instance's build\_cfs function.

## 11.22.3.3 def plugins.cfs.pycfs.cfs\_controllers.CfsController.check\_event( self, app\_name, event\_id, event\_str = None, is\_regex = False, event\_str\_args = None )

Checks for an EVS event message in the telemetry packet history, assuming a particular structure for CFE\_EVS\_LongEventTlm\_t. This can be generifed in the future to determine the structure from the MID map.

**11.22.3.4 def plugins.cfs.pycfs.cfs\_controllers.CfsController.check\_tlm\_continuous ( self, v\_id, mid, args )**

Implementation of CFS plugin instructions check\_tlm\_continuous. When CFS plugin instructions (check\_tlm\_continuous) is executed, it calls CfsController instance's check\_tlm\_continuous function.

**11.22.3.5 def plugins.cfs.pycfs.cfs\_controllers.CfsController.check\_tlm\_value ( self, mid, args=None )**

Implementation of CFS plugin instructions check\_tlm\_value. When CFS plugin instructions (check\_tlm\_value) is executed, it calls CfsController instance's check\_tlm\_value function.

**11.22.3.6 def plugins.cfs.pycfs.cfs\_controllers.CfsController.convert\_args\_to\_ctypes ( self, args, arg\_class, ctypes, Structure )**

Implements the conversion of command args into a ctypes structure

**11.22.3.7 def plugins.cfs.pycfs.cfs\_controllers.CfsController.convert\_check\_tlm\_args ( self, args )**

Implementation of helper function convert\_check\_tlm\_args.  
Convert telemetry data args with "value" to a list

**11.22.3.8 def plugins.cfs.pycfs.cfs\_controllers.CfsController.enable\_cfs\_output ( self )**

Implementation of CFS plugin instructions enable\_cfs\_output. When CFS plugin instructions (enable\_cfs\_output) is executed, it calls CfsController instance's enable\_cfs\_output function.

**11.22.3.9 def plugins.cfs.pycfs.cfs\_controllers.CfsController.field\_class\_by\_name ( name, args\_class ) [static]**

Implementation of helper function field\_class\_by\_name.  
Return a field with matching name.

**11.22.3.10 def plugins.cfs.pycfs.cfs\_controllers.CfsController.initialize ( self )**

Initialize CfsController instance, including the followings: create mid map; import ccscs header; create command interface; create telemetry interface; create local CFS interface

**11.22.3.11 def plugins.cfs.pycfs.cfs\_controllers.CfsController.process\_ccscs\_files ( self )**

Create mid map for CFS plugin, if map does not exist, create ccscs\_reader from INIT config file.

**11.22.3.12 def plugins.cfs.pycfs.cfs\_controllers.CfsController.remove\_check\_tlm\_continuous ( self, v\_id )**

Implementation of CFS plugin instructions remove\_check\_tlm\_continuous. When CFS plugin instructions (remove\_check\_tlm\_continuous) is executed, it calls CfsController instance's function.

**11.22.3.13 def plugins.cfs.pycfs.cfs\_controllers.CfsController.resolve\_args\_from\_dict ( self, args, args\_class )**

Implementation of helper function resolve\_args\_from\_dict.  
Convert argument args to args\_class

**11.22.3.14 def plugins.cfs.pycfs.cfs\_controllers.CfsController.resolve\_macros ( self, arg )**

Implementation of helper function resolve\_macros.  
search macro\_map to convert arg to string.

**11.22.3.15 def plugins.cfs.pycfs.cfs\_controllers.CfsController.resolve\_simple\_type( self, arg, arg\_type )**

Implementation of helper function resolve\_simple\_type.  
Resolves any macros in arg and converts it to a type appropriate for arg\_class

**11.22.3.16 def plugins.cfs.pycfs.cfs\_controllers.CfsController.shutdown( self )**

This function will shut down the CFS application being tested even if the JSON test file does not include the shutdown test command

**11.22.3.17 def plugins.cfs.pycfs.cfs\_controllers.CfsController.shutdown\_cfs( self )**

Implementation of CFS plugin instructions shutdown\_cfs. When CFS plugin instructions (shutdown\_cfs) is executed, it calls CfsController instance's shutdown\_cfs function.

**11.22.3.18 def plugins.cfs.pycfs.cfs\_controllers.CfsController.start\_cfs( self, run\_args )**

Implementation of CFS plugin instructions start\_cfs. When CFS plugin instructions (start\_cfs) is executed, it calls CfsController instance's start\_cfs function.

**11.22.3.19 def plugins.cfs.pycfs.cfs\_controllers.CfsController.validate\_cc\_value( self, mid\_dict, cc )**

Implementation of helper function validate\_cc\_value.  
Attempt to convert a value to a CC name and check that it is in the provided mid\_dict  
@return str: A valid CC name if found, else None

**11.22.3.20 def plugins.cfs.pycfs.cfs\_controllers.CfsController.validate\_mid\_value( self, mid )**

Implementation of helper function validate\_mid\_value.  
Attempt to convert a value to a MID name and check that it is in the mid\_map  
@return str: A valid MID name if found, else None

**11.23 plugins.cfs.pycfs.cfs\_interface.CfsInterface Class Reference****Public Member Functions**

- def [\\_\\_init\\_\\_](#)
- def [build\\_cfs](#)
- def [start\\_cfs](#)
- def [stop\\_cfs](#)
- def [write\\_tlm\\_log](#)
- def [write\\_evs\\_log](#)
- def [read\\_sb\\_packets](#)
- def [parse\\_command\\_packet](#)
- def [parse\\_telemetry\\_packet](#)
- def [log\\_unknown\\_packet\\_mid](#)
- def [log\\_invalid\\_packet](#)
- def [on\\_packet\\_received](#)
- def [add\\_tlm\\_condition](#)
- def [remove\\_tlm\\_condition](#)
- def [check\\_tlm\\_conditions](#)
- def [send\\_command](#)
- def [check\\_value](#)

- def `clear_received_msgs_before_verification_start`
- def `check_tlm_value`
- def `get_tlm_value`
- def `check_tlm_packet`
- def `enable_output`

#### Static Public Member Functions

- def `check_strings`

#### Data Fields

- `config`
- `evs_long_event_msg_mid`
- `evs_short_event_msg_mid`
- `init_passed`
- `command`
- `telemetry`
- `mid_payload_map`
- `output_manager`
- `cfs_std_out_path`
- `evs_log_file`
- `tlm_log_file`
- `tlm_has_been_received`
- `unchecked_packet_mids`
- `tlm_verifications_by_mid_and_vid`
- `cmd_packet_list`
- `received_mid_packets_dic`
- `has_received_mid`
- `ccsds`
- `pheader_offset`
- `should_skip_header`
- `tlm_header_offset`
- `cmd_header_offset`

#### 11.23.1 Detailed Description

`CfsInterface`: Base-class Lower-level interface to communicate with cFS.

#### 11.23.2 Constructor & Destructor Documentation

##### 11.23.2.1 `def plugins.cfs.pycfs.cfs_interface.CfsInterface.__init__( self, config, telemetry, command, mid_map, ccsds )`

Constructor for `CfsInterface` class. Assign `config`, `telemetry`, `command`, `mid_map`, and `ccsds` arguments to interface attributes

#### 11.23.3 Member Function Documentation

##### 11.23.3.1 `def plugins.cfs.pycfs.cfs_interface.CfsInterface.add_tlm_condition( self, v_id, mid, args )`

Add verification condition (with ID) to telemetry verification dictionary and do verification based on id

**11.23.3.2 def plugins.cfs.pycfs.cfs\_interface.CfsInterface.build\_cfs ( self )**

Abstract class method, raise NotImplementedError exception

**11.23.3.3 def plugins.cfs.pycfs.cfs\_interface.CfsInterface.check\_strings ( actual, expected, equal ) [static]**

Check whether string argument actual == string argument expected, if yes, return argument equal, otherwise return not equal

**11.23.3.4 def plugins.cfs.pycfs.cfs\_interface.CfsInterface.check\_tlm\_conditions ( self )**

Check all unchecked telemetry message by mid and vid.  
If verification fails, raise CtfConditionError exception.

**11.23.3.5 def plugins.cfs.pycfs.cfs\_interface.CfsInterface.check\_tlm\_packet ( self, payload, args )**

Check telemetry message's value based on argument payload and args

**11.23.3.6 def plugins.cfs.pycfs.cfs\_interface.CfsInterface.check\_tlm\_value ( self, mid, args=None, discard\_old\_packets=True )**

Given a mid and a arguments, iterate over all received packets since the start of the verification. Validate each packet until a success is seen, or there are no more packets to check.

**11.23.3.7 def plugins.cfs.pycfs.cfs\_interface.CfsInterface.check\_value ( self, actual, expected, compare, mask, mask\_value )**

Based on the argument compare value, use different method to compare argument actual and expected

**11.23.3.8 def plugins.cfs.pycfs.cfs\_interface.CfsInterface.clear\_received\_msgs\_before\_verification\_start ( self, mid )**

Given a mid argument, iterate over all received packets.  
If packets' received time expires, clear the packets with matching mid.

**11.23.3.9 def plugins.cfs.pycfs.cfs\_interface.CfsInterface.enable\_output ( self )**

Send a command to enable output and check if we receive a response

**11.23.3.10 def plugins.cfs.pycfs.cfs\_interface.CfsInterface.log\_invalid\_packet ( self, mid )**

If this is the first time receiving a packet with the given mid, log the packet.

**11.23.3.11 def plugins.cfs.pycfs.cfs\_interface.CfsInterface.log\_unknown\_packet\_mid ( self, mid )**

If this is the first time receiving a packet with the given mid, log the message.

**11.23.3.12 def plugins.cfs.pycfs.cfs\_interface.CfsInterface.parse\_command\_packet ( self, buffer )**

Parse command packets from received buffer.

**11.23.3.13 def plugins.cfs.pycfs.cfs\_interface.CfsInterface.parse\_telemetry\_packet ( self, buffer )**

Parse telemetry packets from received buffer.

**11.23.3.14 def plugins.cfs.pycfs.cfs\_interface.CfsInterface.read\_sb\_packets ( self )**

read\_sb\_packets() is responsible for receiving packets coming from the CFS application that is being tested and placing them in a dictionary of lists that is ordered by mids as shown below.

```
received_mid_packets_dic = {
    "mid1": ["The last packet received with mid1"],
    "mid2": ["The last packet received with mid2"]
}
```

**11.23.3.15 def plugins.cfs.pycfs.cfs\_interface.CfsInterface.remove\_tlm\_condition ( self, v\_id )**

Remove verification condition (with ID) from telemetry verification dictionary.

**11.23.3.16 def plugins.cfs.pycfs.cfs\_interface.CfsInterface.send\_command ( self, msg\_id, function\_code, data, header\_args = None )**

Send instruction to CFS instance through command interface.

**11.23.3.17 def plugins.cfs.pycfs.cfs\_interface.CfsInterface.start\_cfs ( self, run\_args )**

Abstract class method, raise NotImplementedError exception

**11.23.3.18 def plugins.cfs.pycfs.cfs\_interface.CfsInterface.stop\_cfs ( self )**

Stop CFS executable instance, close command and telemetry sockets.

**11.23.3.19 def plugins.cfs.pycfs.cfs\_interface.CfsInterface.write\_evs\_log ( self, payload )**

Write payload and mid to evs log file. if log file does not exist, create one.

**11.23.3.20 def plugins.cfs.pycfs.cfs\_interface.CfsInterface.write\_tlm\_log ( self, payload, buf, mid )**

Write payload and mid to telemetry log file. if log file does not exist, create one.

**11.24 plugins.cfs.cfs\_plugin.CfsPlugin Class Reference****Public Member Functions**

- def [\\_\\_init\\_\\_](#)
- def [initialize](#)
- def [register\\_cfs](#)
- def [load\\_configured\\_targets](#)
- def [get\\_cfs\\_targets](#)
- def [build\\_cfs](#)
- def [start\\_cfs](#)
- def [enable\\_cfs\\_output](#)
- def [send\\_cfs\\_command](#)
- def [send\\_raw\\_cfs\\_command](#)
- def [check\\_tlm\\_value](#)
- def [check\\_tlm\\_packet](#)
- def [check\\_no\\_tlm\\_packet](#)



- def **get\_tlm\_value**
- def **check\_tlm\_continuous**
- def **remove\_check\_tlm\_continuous**
- def **check\_event**
- def **check\_noevent**
- def **shutdown\_cfs**
- def **archive\_cfs\_files**
- def **shutdown**

#### Data Fields

- **name**
- **description**
- **targets**
- **has\_attempted\_register**
- **protocols**
- **command\_map**
- **verify\_required\_commands**
- **continuous\_commands**
- **end\_test\_on\_fail\_commands**

#### Static Public Attributes

- string **FALLBACK\_TARGET\_NAME** = 'cfs'

#### 11.24.1 Detailed Description

The CFS Plugin provides CFS command/telemetry support for CTF.

@note The CFS plugin draws many default values from the CTF config file.  
The section [cfs] defines defaults for all CFS targets and is always required.

@note If multiple CFS targets are to be registered, for each target name,  
the plugin will load values from a correspondingly named section.

@note If no targets are explicitly registered by name by the time StartCfs is first executed,  
the plugin will automatically configure targets for each config section beginning with cfs\_.  
If no such sections are found, the plugin will configure a single target using the [cfs] config section.  
If the cfs\_protocol field is not found in the cfs section, a local target will be registered.

@note The precedence of values is first the named config section, if any, and then the [cfs] config section.  
A target cannot be registered, explicitly nor automatically, without a correspondingly named config section.

#### 11.24.2 Constructor & Destructor Documentation

##### 11.24.2.1 def plugins.cfs.cfs\_plugin.CfsPlugin.\_\_init\_\_( self )

Constructor for CfsPlugin.

Most importantly populates the command map and verify required commands,  
which serve as the interface to the plugin manager.

### 11.24.3 Member Function Documentation

#### 11.24.3.1 def plugins.cfs.cfs\_plugin.CfsPlugin.initialize ( self, bool )

Initializes the plugin by creating the CfsTimeManager.  
This method is intended to be called by the plugin manager before the test script runs.

#### 11.24.3.2 def plugins.cfs.cfs\_plugin.CfsPlugin.shutdown ( self, None )

Shuts down the plugin, releasing target resources.  
Only runs when the plugin itself is shutting down.  
To shut down individual targets, use shutdown\_cfs.

## 11.25 plugins.cfs.cfs\_time\_manager.CfsTimeManager Class Reference

### Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [wait](#)
- def [pre\\_command](#)
- def [run\\_continuous\\_verifications](#)

### Static Public Member Functions

- def [handle\\_test\\_exception\\_during\\_wait](#)

### Data Fields

- [ctf\\_verification\\_poll\\_period](#)
- [cfs\\_targets](#)

### 11.25.1 Detailed Description

CfsTimeManager: CFS Time Manager for CTF.

@note When initialized by the cFS plugin, the default CTF time manager (OS Time) is disabled, and the cFS time manager is used instead.

@note The cFS time manager implements a serialized telemetry receive implementation as CTF instructions are "waiting".

@note The cFS time manager also invokes the continuous verification checks between polls to ensure each packet is verified if a continuous verification exists.

### 11.25.2 Constructor & Destructor Documentation

#### 11.25.2.1 def plugins.cfs.cfs\_time\_manager.CfsTimeManager.\_\_init\_\_ ( self, cfs\_targets )

Constructor implementation for CfsTimeManager class.

@note CfsTimeManager is inherited from TimeInterface class.

@note The constructor assigns ctf\_verification\_poll\_period attribute based on INI File config, and cfs\_targets attribute from passed argument.

## 11.25.3 Member Function Documentation

## 11.25.3.1 def plugins.cfs.cfs\_time\_manager.CfsTimeManager.handle\_test\_exception\_during\_wait( error, msg, do\_raise = False ) [static]

Test exception handler, log error, and raise exception if do\_raise is True

## 11.25.3.2 def plugins.cfs.cfs\_time\_manager.CfsTimeManager.pre\_command( self )

Read Telemetry Packets for CFS Target, and run continuous verification.  
Raise any occurring Exception

## 11.25.3.3 def plugins.cfs.cfs\_time\_manager.CfsTimeManager.run\_continuous\_verifications( self )

Check all unchecked telemetry message by mid and vid by triggering target's target.cfs.check\_tlm\_conditions().  
Raise any occurring Exception

## 11.25.3.4 def plugins.cfs.cfs\_time\_manager.CfsTimeManager.wait( self, seconds )

Do polling for certain seconds. Continue to do pre\_command(), post\_command(),  
and sleep until exec\_time expires.

@param seconds: polling duration.

@return None

## 11.26 plugins.ccsds\_plugin.readers.command\_builder.CommandArg Class Reference

## Public Member Functions

- def \_\_init\_\_
- def \_\_getattr\_\_
- def \_\_setattr\_\_
- def \_\_delattr\_\_

## Data Fields

- name
- data\_type

## 11.26.1 Detailed Description

Class representing a CCSDS Command Argument

@param name: argument name

@param data\_type: argument type

## 11.27 plugins.ccsds\_plugin.readers.command\_builder.CommandCode Class Reference

## Public Member Functions

- def \_\_init\_\_

- def **\_\_getattr\_\_**
- def **\_\_setattr\_\_**
- def **\_\_delattr\_\_**

#### Data Fields

- **cc\_name**
- **cc\_value**
- **args**

#### 11.27.1 Detailed Description

Class representing a Command Code for a CCSDS Command

@param name: command code name  
 @param code: command code value

## 11.28 plugins.cfs.pycfs.command\_interface.CommandInterface Class Reference

#### Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [init\\_socket](#)
- def [cleanup](#)
- def [send\\_command](#)

#### Data Fields

- **ccsds**
- **ip\_address**
- **port**
- **command\_socket**
- **endianness**
- **debug**

#### 11.28.1 Detailed Description

The CommandInterface class provides methods to send CCSDS messages from the CFS test framework to CFS via any app that listens on a UDP socket and injects CCSDS packets onto the software bus (TO or DIAG). CommandInterface is a misnomer, as it is capable of sending both Command and Telemetry CCSDS packets.

#### 11.28.2 Constructor & Destructor Documentation

11.28.2.1 def plugins.cfs.pycfs.command\_interface.CommandInterface.\_\_init\_\_( self, ccsds, port = 1234, ip = "127.0.0.1", endianness = "little" )

Constructor implementation for CommandInterface Class. It sets up the ip addr, port, ccsds version, etc.

## 11.28.3 Member Function Documentation

## 11.28.3.1 def plugins.cfs.pycfs.command\_interface.CommandInterface.cleanup ( self )

Performs requisite cleanup of the class, such as closing the socket.  
 @return None

## 11.28.3.2 def plugins.cfs.pycfs.command\_interface.CommandInterface.init\_socket ( self )

Initialize socket connection.  
 @return None

## 11.28.3.3 def plugins.cfs.pycfs.command\_interface.CommandInterface.send\_command ( self, msg\_id, function\_code, data, header\_args = None )

This method constructs a CCSDS command packet and sends it to the ip:port defined when creating the class via UDP

@param msg\_id: The message ID of the command to send  
 @param function\_code: The app specific function/command code (CC)  
 @param data: A bytearray representing the packed message payload. This is specific to the message, so for now the bytearray needs to be constructed by hand using struct.pack or the included BytePacker class  
 @param header\_args: An optional dictionary of additional kwargs for the header constructor  
 @return The number of bytes that were sent over the socket. UDP is connectionless, so there is no way for the socket to know that a packet was received by the destination

## 11.29 plugins.ccsds\_plugin.readers.command\_builder.CommandMessage Class Reference

## Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [\\_\\_getattr\\_\\_](#)
- def [\\_\\_setattr\\_\\_](#)
- def [\\_\\_delattr\\_\\_](#)

## Data Fields

- [command\\_codes](#)

## 11.29.1 Detailed Description

Class representing a CCSDS Command Message

## 11.30 plugins.control\_flow\_plugin.control\_flow\_plugin.ControlFlowPlugin Class Reference

## Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [initialize](#)
- def [shutdown](#)

### Static Public Member Functions

- def [control\\_flow\\_goto](#)
- def [if\\_condition](#)
- def [else\\_condition](#)
- def [end\\_condition](#)
- def [control\\_flow\\_conditional\\_goto](#)
- def [begin\\_loop](#)
- def [end\\_loop](#)

### Data Fields

- [name](#)  
*Plugin Name.*
- [description](#)  
*Plugin Description.*
- [command\\_map](#)  
*Plugin Command Map.*
- **[begin\\_loop\\_index](#)**

#### 11.30.1 Detailed Description

The ControlFlow Plugin Class Definition

@note The Control-Flow Plugin provides the functionality of CTF control flow statement, including looping and conditional statements.

@note The custom plugin class *must* inherit from the Plugin base-class.

@note All plugin functions mapped to a test instruction *must* return true/false to indicate pass/fail of that instruction.

#### 11.30.2 Constructor & Destructor Documentation

##### 11.30.2.1 def plugins.control\_flow\_plugin.control\_flow\_plugin.ControlFlowPlugin.\_\_init\_\_( self )

Constructor of ControlFlow plugin.

@note The `__init__` function is called once a plugin is loaded.

@note The `__init__` function should not reference/interact with any other plugin since the other plugin may not be loaded at this stage.

@note The constructor of a plugin must define the following fields:

- name
- description
- command map: dictionary mapping CTF instructions to a tuple defining the python function to use for that instruction, and a list of argument types
- [optional] verify\_required\_commands: List of instructions that require verification (i.e polling until verification passes or timeout.
- other class variables that can store state, etc...

## 11.30.3 Member Function Documentation

11.30.3.1 def plugins.control\_flow\_plugin.control\_flow\_plugin.ControlFlowPlugin.begin\_loop( *label*, *conditions* ) [static]

Create a loop entry point. The loop is identified by a unique label.

The BeginLoop must be in pairs with EndLoop instruction. The loop condition is defined in parameter "conditions" as a list of variables and the associated comparison operations. The condition is True, only if all comparison operations are True.

@param label: a user defined label (example: "LOOP\_1")

@param conditions: a list of comparison conditions. Each includes "name", "operator" and "value".  
(example: {"name": "my\_var", "operator": "<", "value": 20})

@return bool: always True .

11.30.3.2 def plugins.control\_flow\_plugin.control\_flow\_plugin.ControlFlowPlugin.control\_flow\_conditional\_goto( *variable\_name*, *operator*, *value*, *true\_label* = "", *false\_label* = "" ) [static]

Deprecated function, may be removed in future.

@return bool: always True .

11.30.3.3 def plugins.control\_flow\_plugin.control\_flow\_plugin.ControlFlowPlugin.control\_flow\_goto( *command\_index* ) [static]

Deprecated function, may be removed in future.

@return bool: always True .

11.30.3.4 def plugins.control\_flow\_plugin.control\_flow\_plugin.ControlFlowPlugin.else\_condition( *label* ) [static]

Create a else conditional branch entry point. It must match a IfCondition and a EndCondition instruction with the same label. It is optional in conditional branch block.

If the condition of IfCondition instruction is False, the control flow skips the 'if' branch block, only executes the 'else' branch block. If ElseCondition instruction is not defined, the control flow jumps to the end of conditional branch block defined by a EndCondition instruction.

@param label: a user defined label (example: "if\_label\_1")

@return bool: always True

11.30.3.5 def plugins.control\_flow\_plugin.control\_flow\_plugin.ControlFlowPlugin.end\_condition( *label* ) [static]

Create a if conditional branch exit point. It must match a IfCondition instruction with the same label. When the control flow reaches EndCondition instruction, it exits the conditional branch block.

@param label: a user defined label (example: "if\_label\_1")

@return bool: always True

11.30.3.6 def plugins.control\_flow\_plugin.control\_flow\_plugin.ControlFlowPlugin.end\_loop( *label* ) [static]

Create a loop exit point. It must match a BeginLoop instruction with the same label.

If the looping condition in BeginLoop is False, the control flow jumps to the corresponding EndLoop instruction and exits the loop.

@param label: a user defined label (example: "LOOP\_1")

@return bool: always True

**11.30.3.7 def plugins.control\_flow\_plugin.control\_flow\_plugin.ControlFlowPlugin.if\_condition ( label, conditions ) [static]**

Create a if conditional branch block entry point. It is identified by a unique label per test script. The IfCondition must be in pairs with EndCondition instruction. ElseCondition instruction is optional. The if condition is defined in parameter "conditions" as a list of variables and the associated comparison operations. The condition is True, only if all comparison operations are True.

@param label: a user defined label (example: "if\_label\_1")

@param conditions: a list of comparison conditions. Each includes "name", "operator" and "value". (example: {"name": "my\_var", "operator": "<", "value": 20})

@return bool: return True, unless conditions argument is not a list .

**11.30.3.8 def plugins.control\_flow\_plugin.control\_flow\_plugin.ControlFlowPlugin.initialize ( self )**

Initialize implementation for the ControlFlow plugin.

@note The initialize function is called by the CTF plugin manager *after* all plugins have been loaded.

@note This function may interact with other plugins, since all plugins have been loaded at this stage.

@return bool: True if successful, False otherwise.

**11.30.3.9 def plugins.control\_flow\_plugin.control\_flow\_plugin.ControlFlowPlugin.shutdown ( self )**

Shutdown implementation for the controlflow plugin.

@note The shutdown function is called by the CTF plugin manager upon completion of a test run.

@note The shutdown function can be exposed to test scripts by adding it to the command map.

**11.31 lib.exceptions.CtfConditionError Class Reference****Public Member Functions**

- def [\\_\\_init\\_\\_](#)

**Data Fields**

- **condition**

**11.31.1 Detailed Description**

CTF Condition Error thrown when a CTF Instruction Condition is not met during test run.

**11.31.2 Constructor & Destructor Documentation****11.31.2.1 def lib.exceptions.CtfConditionError.\_\_init\_\_( self, message, test\_condition )**

Constructor of CtfConditionError Class

**11.32 lib.logger.CtfLogLevel Class Reference****Static Public Attributes**

- int **TEST\_PASS** = 21



- int **TEST\_FAIL** = 22
- int **TEST\_PASS\_CONT** = 5
- int **TEST\_FAIL\_CONT** = 6

#### 11.32.1 Detailed Description

CtfLogLevel: An enum containing custom log levels used in CTF

### 11.33 lib.exceptions.CtfParameterError Class Reference

#### Public Member Functions

- def [\\_\\_init\\_\\_](#)

#### Data Fields

- **parameter**

#### 11.33.1 Detailed Description

CTF Parameter Error thrown when a CTF Instruction Parameter is invalid.

#### 11.33.2 Constructor & Destructor Documentation

##### 11.33.2.1 def lib.exceptions.CtfParameterError.\_\_init\_\_( self, message, parameter )

Constructor of CtfParameterError Class

### 11.34 lib.exceptions.CtfTestError Class Reference

#### Public Member Functions

- def [\\_\\_init\\_\\_](#)

#### 11.34.1 Detailed Description

General top-level exception that is thrown when a CTF Test Error occurs during a test run.

#### 11.34.2 Constructor & Destructor Documentation

##### 11.34.2.1 def lib.exceptions.CtfTestError.\_\_init\_\_( self, message )

Constructor of CtfTestError Class

## 11.35 lib.ctf\_global.CtfVerificationStage Class Reference

### Static Public Attributes

- int **none** = 0
- int **first\_ver** = 1
- int **polling** = 2
- int **last\_ver** = 3

### 11.35.1 Detailed Description

Static class containing enumerations for verification stages of a CTF verification instruction.

@note The verification stage enums can be used to check which verification stage a CTF verification instruction is on. Different logic can be implemented depending on the verification stage.

## 11.36 plugins.example\_plugin.example\_plugin.ExamplePlugin Class Reference

### Public Member Functions

- def `__init__`
- def `initialize`
- def `test_verify_command`
- def `shutdown`

### Static Public Member Functions

- def `test_command`
- def `test_shared_library`

### Data Fields

- `name`  
*Plugin Name.*
- `description`  
*Plugin Description.*
- `command_map`  
*Plugin Command Map.*
- `verify_required_commands`  
*List of verification type commands.*
- `example_counter`  
*Counter to track how many verifications are ran.*

### 11.36.1 Detailed Description

The Example Plugin Class Definition

@note The Example Plugin shows a simple CTF plugin that can perform a single test instruction and a single verification instruction, in addition to loading a C shared library.

@note The custom plugin class *must* inherit from the Plugin base-class.

@note A custom CTF plugin can be created to add new CTF instructions that can then be utilized within a JSON test script.

@note All plugin functions mapped to a test instruction *must* return true/false to indicate pass/fail of that instruction.

### 11.36.2 Constructor & Destructor Documentation

#### 11.36.2.1 def plugins.example\_plugin.example\_plugin.ExamplePlugin.\_\_init\_\_( self )

Constructor implementation for example plugin.

@note The `__init__` function is called once a plugin is loaded.

@note The `__init__` function should not reference/interact with any other plugin since the other plugin may not be loaded at this stage.

@note The constructor of a plugin must define the following fields:

- name
- description
- command map: dictionary mapping CTF instructions to a tuple defining the python function to use for that instruction, and a list of argument types
- [optional] verify\_required\_commands: List of instructions that require verification (i.e polling until verification passes or timeout.
- other class variables that can store state, etc...

### 11.36.3 Member Function Documentation

#### 11.36.3.1 def plugins.example\_plugin.example\_plugin.ExamplePlugin.initialize( self )

Initialize implementation for the example plugin.

@note The initialize function is called by the CTF plugin manager *after* all plugins have been loaded.

@note This function may interact with other plugins, since all plugins have been loaded at this stage.

@return bool: True if successful, False otherwise.

#### 11.36.3.2 def plugins.example\_plugin.example\_plugin.ExamplePlugin.shutdown( self )

Shutdown implementation for the example plugin.

@note The shutdown function is called by the CTF plugin manager upon completion of a test run.

@note The shutdown function can be exposed to test scripts by adding it to the command map.

#### 11.36.3.3 def plugins.example\_plugin.example\_plugin.ExamplePlugin.test\_command( arg1, arg2 ) [static]

Simply logs that the test command was executed with the provided arguments.

@param arg1: any value (example: "Hello")

@param arg2: any value (example: "World")

@return bool: True if successful, False otherwise.

#### 11.36.3.4 def plugins.example\_plugin.example\_plugin.ExamplePlugin.test\_shared\_library( ) [static]

Uses libc to get the system time and log it to system output.

@note Verifies that the expected number of bytes were printed.

@return bool: True if successful, False otherwise.

#### 11.36.3.5 def plugins.example\_plugin.example\_plugin.ExamplePlugin.test\_verify\_command ( self )

Increments the plugin's example\_counter value and checks if it is greater than '5'.

@note Verification instructions will be re-executed by the CTF core until the verification passes, or the verification timeout is reached.

@return bool: True if successful, False otherwise.

### 11.36.4 Field Documentation

#### 11.36.4.1 plugins.example\_plugin.example\_plugin.ExamplePlugin.example\_counter

Counter to track how many verifications are ran.

Other plugin-specific properties can also be defined

## 11.37 lib.ftp\_interface.FtpInterface Class Reference

### Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [store\\_file\\_ftp](#)
- def [get\\_file\\_ftp](#)
- def [upload\\_ftp](#)
- def [download\\_ftp](#)
- def [connect\\_ftp](#)
- def [disconnect\\_ftp](#)
- def [upload\\_ftputil](#)
- def [download\\_ftputil](#)

### Data Fields

- **uploadlevel**
- **ftp**
- **curdir**
- **ipaddr**
- **ftpconnect**
- **ftp\_timeout**
- **remotebase**

#### 11.37.1 Detailed Description

The FtpInterface class provides functionality to connect/disconnect to remote FTP server, upload/download files, create folder on server.

@note - Two parallel FTP implementations are provided: ftputil for use via SSH, and ftplib for SP0

## 11.37.2 Constructor &amp; Destructor Documentation

## 11.37.2.1 def lib.ftp\_interface.FtpInterface.\_\_init\_\_( self )

Constructor for FtpInterface class. Set default values for FtpInterface attributes, such as ipaddr, ftp\_timeout, etc.

## 11.37.3 Member Function Documentation

## 11.37.3.1 def lib.ftp\_interface.FtpInterface.connect\_ftp( self, ipaddr, usrid )

Connect to FTP server, and set the FtpInterface attributes.  
 @param ipaddr: the IP address of FTP server.  
 @param usrid: the user id to connect to the FTP server.  
 @return bool: True if successfully connect to FTP server, False otherwise.

## 11.37.3.2 def lib.ftp\_interface.FtpInterface.disconnect\_ftp( self )

Disconnect to FTP server, and reset the FtpInterface attributes.  
 @return None

## 11.37.3.3 def lib.ftp\_interface.FtpInterface.download\_ftp( self, remotepath, ipaddr=None, localpath=None, file=None, usrid=None )

Download a file or files from the FTP server to the local computer.  
 @param remotepath: the path to the download file/files on the FTP server.  
 @param ipaddr: the IP address of FTP server. If it is None, use the previous FTP connection, otherwise re-connect FTP server using ipaddr and usrid.  
 @param localpath: the path to store the downloaded file/files on local computer.  
 @param file: the file to be downloaded from the FTP server. If the file is None, all files in remotepath will be downloaded.  
 @param usrid: the user id to connect to the FTP server.  
 @return bool: True if download successfully, False otherwise.

## 11.37.3.4 def lib.ftp\_interface.FtpInterface.download\_ftputil( self, host, remote\_path, local\_path, usrid='anonymous' )

FTP download utility: download a whole folder content from the FTP host to the local computer.  
 @param host: FTP server host/IP.  
 @param remote\_path: the FTP server path.  
 @param local\_path: the local computer path to store downloaded files.  
 @param usrid: the user id to connect to the FTP server. The default user is 'anonymous'.  
 @return bool: True if download successfully, False otherwise.

## 11.37.3.5 def lib.ftp\_interface.FtpInterface.get\_file\_ftp( self, remote\_file, local\_path=None )

Download a file from the FTP server to the local computer.  
 @param remote\_file: the path/name of the file on FTP server.  
 @param local\_path: the path to store the transferred file on local computer.  
 @return bool: True if the file is downloaded successfully, False otherwise.

## 11.37.3.6 def lib.ftp\_interface.FtpInterface.store\_file\_ftp( self, path, file )

Transfer file to FTP server using the FTP command STOR. The file transfer is in binary mode.  
 @param path: the path of the transfer file on local computer.  
 @param file: the name of the transfer file on local computer.  
 @return bool: True if the file is transferred successfully, False otherwise.

**11.37.3.7** `def lib.ftp_interface.FtpInterface.upload_ftp ( self, localpath, ipaddr = None, remotepath = None, file = None, usr_id = None )`

Upload a file or files from the local computer to the FTP server.  
 @param localpath: the path of the uploaded file/files on local computer.  
 @param ipaddr: the IP address of FTP server. If it is None, use the previous FTP connection, otherwise re-connect FTP server using ipaddr and usr\_id.  
 @param remotepath: the path to store the uploaded file/files on the FTP server.  
 @param file: the file to be uploaded on local computer. If the file is None, all files in localpath will be uploaded.  
 @param usr\_id: the user id to connect to the FTP server.  
 @return bool: True if upload successfully, False otherwise.

**11.37.3.8** `def lib.ftp_interface.FtpInterface.upload_ftputil ( self, host, local_path, remote_path, usrid = 'anonymous' )`

FTP upload utility: upload a whole folder content from the local computer to the FTP host.  
 @param host: FTP server host/IP.  
 @param local\_path: the local computer path.  
 @param remote\_path: the FTP server path to store the uploaded files.  
 @param usrid: the user id to connect to the FTP server. The default user is 'anonymous'  
 @return bool: True if upload successfully, False otherwise.

## 11.38 lib.ctf\_global.Global Class Reference

### Static Public Member Functions

- `def create_arg_parser`
- `def load_config`
- `def set_time_manager`
- `def get_time_manager`

### Static Public Attributes

- `config = None`  
*Config parser for the designated config file, initialized in load\_config.*
- `tuple plugins_available = dict()`  
*Dictionary of loaded plugins.*
- `plugin_manager = None`  
*Reference to the plugin manager object.*
- `string current_script_log_dir = ""`  
*Log directory of current script.*
- `string test_log_dir = ""`  
*Log directory of the complete test run (includes log directory of scripts)*
- `string CTF_log_dir = ""`  
*Temporary logging directory for CTF.*
- `CTF_log_dir_file = None`  
*CTF top-level log file.*
- `time_manager = None`  
*Current time manager used by CTF.*
- `test_start_time = None`  
*Start time of current test run.*
- `current_verification_start_time = None`

*Start time of current verification.*

- `current_verification_stage` = CtfVerificationStage.none

*Current verification stage.*

- `current_instruction_index` = None

*[Read-Only] Current Instruction Index, default value is None.*

- `goto_instruction_index` = None

*[Read-Only] Current goto instruction index, default value is None.*

- dictionary `variable_store` = {}

*[Read-Only] Variable Storage.*

- dictionary `label_map` = {}

- dictionary `goto_label_map` = {}

- dictionary `conditional_branch_map` = {}

### 11.38.1 Detailed Description

Static class containing globally accessible CTF and plugin data.

### 11.38.2 Member Function Documentation

#### 11.38.2.1 `def lib.ctf_global.Global.create_arg_parser( ) [static]`

Creates and returns an argument parser for command line args.

#### 11.38.2.2 `def lib.ctf_global.Global.get_time_manager( ) [static]`

Gets the currently active time manager

#### 11.38.2.3 `def lib.ctf_global.Global.load_config( config_file ) [static]`

Loads the config file specified and sets the workspace\_dir environment variable

@note - Command line arguments are not visible here, so the status message indicates if the default config is being used in case it was not explicitly provided.

@note - If the config file does not exist, the application will exit with an error.

@note - The config field cfs:workspace\_dir will be set as an environment variable for the current process.

@return str: An optional status message, since logging will not have been configured yet

#### 11.38.2.4 `def lib.ctf_global.Global.set_time_manager( time_manager ) [static]`

Sets the currently active time manager.

@note - A custom plugin time manager *must* inherit from the TimeManager class and implement its methods

### 11.38.3 Field Documentation

#### 11.38.3.1 `string lib.ctf_global.Global.CTF_log_dir = "" [static]`

Temporary logging directory for CTF.

Contents of the temporary directory are moved to the test log directory on test completion.

11.38.3.2 `lib.ctf_global.Global.CTF_log_dir_file = None` [static]

CTF top-level log file.

Includes CTF core logs such as initialization and plugin loading/unloading

11.38.3.3 `lib.ctf_global.Global.current_instruction_index = None` [static]

[Read-Only] Current Instruction Index, default value is None.

`current_instruction_index` is updated by `lib/test.py` to track the execution instruction index of the test. Use Utility function `"get_current_instruction_index()"` to get the index value (int).

11.38.3.4 `string lib.ctf_global.Global.current_script_log_dir = ""` [static]

Log directory of current script.

Useful when needing to write data to the current log directory.

11.38.3.5 `lib.ctf_global.Global.current_verification_stage = CtfVerificationStage.none` [static]

Current verification stage.

Use [CtfVerificationStage](#) to evaluate what verification stage CTF is currently at.

11.38.3.6 `lib.ctf_global.Global.goto_instruction_index = None` [static]

[Read-Only] Current goto instruction index, default value is None.

Control Flow Plugins can set the next instruction index to execute based on user input or logic within the plugin. Do not use it directly

11.38.3.7 `lib.ctf_global.Global.plugin_manager = None` [static]

Reference to the plugin manager object.

May be used to invoke instructions (or access) other plugins.

11.38.3.8 `tuple lib.ctf_global.Global.plugins_available = dict()` [static]

Dictionary of loaded plugins.

Set by the CTF core after loading plugins.

11.38.3.9 `lib.ctf_global.Global.time_manager = None` [static]

Current time manager used by CTF.

Utilized by other plugins to manage time

11.38.3.10 `dictionary lib.ctf_global.Global.variable_store = {}` [static]

[Read-Only] Variable Storage.

Recommend using utility functions to set/get variables.

## 11.39 lib.event\_types.Instruction Class Reference



### Public Member Functions

- `def __init__`

### Data Fields

- `delay`
- `command`
- `test`
- `command_index`
- `is_disabled`

#### 11.39.1 Detailed Description

Represents a single CTF Test Instruction.

@param delay: The time in seconds to wait before executing this instruction  
@param command: The dict containing instruction parameters  
@param test: Integer index of the test case that includes this instruction  
@param command\_index: Integer index of this instruction within the test case  
@param disabled: Whether or not the instruction is disabled

## 11.40 lib.readers.json\_script\_reader.JSONScriptReader Class Reference

### Public Member Functions

- `def __init__`
- `def process_header`
- `def process_functions`
- `def sanitize_args`
- `def process_tests`
- `def resolve_function`
- `def resolve_function_params`

### Data Fields

- `raw_data`
- `valid_script`
- `script`
- `input_script_path`
- `functions`

#### 11.40.1 Detailed Description

The JSONScriptReader class provides methods to parse a CTF JSON test script.

@param input\_script\_path: The path to the input JSON script

## 11.40.2 Constructor &amp; Destructor Documentation

## 11.40.2.1 def lib.readers.json\_script\_reader.JSONScriptReader.\_\_init\_\_( self, input\_script\_path )

Constructor for the JSONScriptReader class.

Loads and parses the contents of a single JSON test script file, and resolves imports

## 11.40.3 Member Function Documentation

## 11.40.3.1 def lib.readers.json\_script\_reader.JSONScriptReader.process\_functions( self )

Parse the function definitions and imports in the test script

## 11.40.3.2 def lib.readers.json\_script\_reader.JSONScriptReader.process\_header( self )

Parse and process test information from script header

## 11.40.3.3 def lib.readers.json\_script\_reader.JSONScriptReader.process\_tests( self )

Iterates over test cases within the test script and parses each test case.

## 11.40.3.4 def lib.readers.json\_script\_reader.JSONScriptReader.resolve\_function( self, name, params, functions )

Perform in-line replacement of function calls with the set of instructions within the function definition

## 11.40.3.5 def lib.readers.json\_script\_reader.JSONScriptReader.sanitize\_args( self, args )

Iterates over arguments within test instructions and decodes arguments if needed.

## 11.41 plugins.cfs.pycfs.local\_cfs\_interface.LocalCfsInterface Class Reference

## Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [get\\_start\\_string](#)
- def [build\\_cfs](#)
- def [start\\_cfs](#)

## Data Fields

- [init\\_passed](#)
- [cfs\\_std\\_out\\_path](#)

## Additional Inherited Members

## 11.41.1 Detailed Description

Lower-level interface to communicate with cFS locally (linux)

## 11.41.2 Constructor &amp; Destructor Documentation

11.41.2.1 `def plugins.cfs.pycfs.local_cfs_interface.LocalCfsInterface.__init__( self, config, telemetry, command, mid_map, ccsds )`

Constructor implementation for LocalCfsInterface Class.  
if configured to build cfs, build cfs. otherwise set init\_passed to True

## 11.41.3 Member Function Documentation

11.41.3.1 `def plugins.cfs.pycfs.local_cfs_interface.LocalCfsInterface.build_cfs( self )`

Build cfs image. The path of cfs source is configured in config init file.  
The build output folder is also configured in init file.  
@return bool: True if build succeed, otherwise False

11.41.3.2 `def plugins.cfs.pycfs.local_cfs_interface.LocalCfsInterface.get_start_string( self, run_args )`

Get the command string/path to start cfs (linux)  
@param run\_args: run\_time argument to start cfs  
@return String: full command string to start cfs

11.41.3.3 `def plugins.cfs.pycfs.local_cfs_interface.LocalCfsInterface.start_cfs( self, run_args )`

Start the cfs instance process.  
@param run\_args: run\_args is used to build the start\_string.  
@return dictionary: the return result\_values is a dictionary, including 'results': True if cfs instance starts successfully, otherwise False; and 'pid': the pid of cfs instance process.

## 11.42 lib.status.ObjectFactory Class Reference

## Static Public Member Functions

- `def create_object`

## Static Private Member Functions

- `def __create_suite_status`
- `def __create_test_status`
- `def __create_instruction_status`
- `def __create_script_status`
- `def __create_plugin_info`
- `def __create_command_info`
- `def __create_parameter_info`

## 11.42.1 Detailed Description

This class defines enumerations for the status definitions used by CTF to send instruction status.

## 11.43 plugins.cfs.pycfs.output\_app\_interface.OutputManager Class Reference

## Public Member Functions

- def `__init__`
- def `enable_output`
- def `disable_output`

## Data Fields

- `local_ip`
- `local_port`
- `command_interface`
- `ccsds_ver`
- `command_args`
- `command_mids`

## 11.43.1 Detailed Description

Base class that each output application must inherit from.  
within this class, define the methods that all of the output applications must implement

## 11.43.2 Constructor &amp; Destructor Documentation

11.43.2.1 `def plugins.cfs.pycfs.output_app_interface.OutputManager.__init__( self, local_ip, local_port, command_interface, ccsds_ver, command_mids=None )`

Constructor implementation for OutputManager class. It sets up the local\_ip, local\_port, command\_interface, ccsds version, command\_args, command\_mids.

## 11.43.3 Member Function Documentation

11.43.3.1 `def plugins.cfs.pycfs.output_app_interface.OutputManager.disable_output( self )`

Define abstract disable\_output method, the inherited class must implement

11.43.3.2 `def plugins.cfs.pycfs.output_app_interface.OutputManager.enable_output( self )`

Define abstract enable\_output method, the inherited class must implement

## 11.44 lib.plugin\_manager.Plugin Class Reference

## Public Member Functions

- def `__init__`
- def `initialize`
- def `process_command`
- def `shutdown`

## Data Fields

- [name](#)  
*Plugin Name.*
- [description](#)  
*Plugin Description.*
- [command\\_map](#)  
*Plugin Command Map.*
- [verify\\_required\\_commands](#)  
*List of verification type instructions.*
- [continuous\\_verification\\_commands](#)  
*List of continuously verified instructions (i.e executed every poll without an explicit instruction)*
- [end\\_test\\_on\\_fail\\_commands](#)  
*List of instructions that end test on failure (i.e critical instructions that the test script cannot proceed without)*

## 11.44.1 Detailed Description

Base class that each plugin must inherit from. This class defines methods and properties that all plugins may override or implement.

## 11.44.2 Constructor &amp; Destructor Documentation

11.44.2.1 `def lib.plugin_manager.Plugin.__init__( self )`

Constructor of Plugin Class: Initiate instance properties

## 11.44.3 Member Function Documentation

11.44.3.1 `def lib.plugin_manager.Plugin.initialize( self )`

Virtual initialize method definition. Must be overridden by child Plugin class.  
@note - The initialize method is called for each plugin after \*all\* plugins are loaded.

11.44.3.2 `def lib.plugin_manager.Plugin.process_command( self, kwargs )`

Given a CTF Test Instruction, this function finds the first plugin that "contains" that test instruction within its command map. Once a valid plugin is found, the implementation of that instruction is invoked using keyworded variable length of arguments in kwargs.

@note - This function will ensure that the number of argument provided to the plugin's function is greater than the number of required arguments (non-optional), and less than or equal to the total number of arguments (required + optional)

11.44.3.3 `def lib.plugin_manager.Plugin.shutdown( self )`

Virtual shutdown method definition. Must be overridden by child Plugin class.  
@note - The shutdown method is called for each plugin after test execution is complete. Use this function to shutdown/cleanup any external interfaces or data.

## 11.44.4 Field Documentation

## 11.44.4.1 lib.plugin\_manager.Plugin.command\_map

[Plugin](#) Command Map.

The command map utilizes the instruction name as the key, with the value being a tuple of instruction implementation and argument types.

## Note

Example: {"TestCommand": (self.test\_command, [ArgTypes.string] \* 2)}

## 11.45 lib.plugin\_manager.PluginManager Class Reference

## Public Member Functions

- [def \\_\\_init\\_\\_](#)
- [def initialize\\_plugins](#)
- [def shutdown\\_plugins](#)
- [def find\\_plugin\\_for\\_command](#)
- [def find\\_plugin\\_for\\_command\\_and\\_execute](#)
- [def reload\\_plugins](#)
- [def walk\\_package](#)
- [def create\\_plugin\\_info](#)

## Data Fields

- **plugin\_packages**
- **plugins**
- **plugin\_name\_list**
- **seen\_paths**
- **disabled\_plugins**

## 11.45.1 Detailed Description

Upon creation, this class will read the plugins package for modules that contain a class definition that is inheriting from the Plugin class

## 11.45.2 Constructor &amp; Destructor Documentation

11.45.2.1 `def lib.plugin_manager.PluginManager.__init__( self, plugin_packages )`

Constructor of PluginManager Class: initiates the reading of all available plugins when an instance of the PluginManager object is created

## 11.45.3 Member Function Documentation

11.45.3.1 `def lib.plugin_manager.PluginManager.create_plugin_info( self, directory )`

Outputs the plugin information files in JSON format for utilization by the CTF editor or other tools.

@param directory - Directory to write the plugin information files.  
@note - The directory is created automatically if it does not exist.

**11.45.3.2 def lib.plugin\_manager.PluginManager.find\_plugin\_for\_command ( self, command )**

Given a CTF Test Instruction, find the plugin instance that can execute that instruction.

@note - CTF Test Instructions must be named uniquely across different plugins.

@note - It is recommended to prefix the instruction name with a plugin identifier to avoid ambiguity. For example: MyPlugin\_DoSomething

@return Plugin: Plugin instance found that implements the given instruction. None if no plugins found.

**11.45.3.3 def lib.plugin\_manager.PluginManager.find\_plugin\_for\_command\_and\_execute ( self, command )**

Given a CTF Test Instruction, find the plugin instance that can execute that instruction, execute the instruction and return the instruction status (pass/fail)

@return Plugin: Boolean: CTF Instruction Status (True/False)

**11.45.3.4 def lib.plugin\_manager.PluginManager.initialize\_plugins ( self )**

After loading all plugins, this function calls initialize() on all loaded plugins within the plugin manager

**11.45.3.5 def lib.plugin\_manager.PluginManager.reload\_plugins ( self )**

Reset the list of all plugins and initiate the walk over the main provided plugin package to load all available plugins

**11.45.3.6 def lib.plugin\_manager.PluginManager.shutdown\_plugins ( self )**

Before CTF shutdown (or on plugin restart), this function calls shutdown() on all loaded plugins within the plugin manager

**11.45.3.7 def lib.plugin\_manager.PluginManager.walk\_package ( self, package )**

Recursively walk the supplied package to retrieve all plugins

@param package - Given a package path, this function recursively walks through the package and imports any modules available within the package.

**11.46 plugins.cfs.cfs\_config.RemoteCfsConfig Class Reference****Public Member Functions**

- def [\\_\\_init\\_\\_](#)
- def [load\\_config\\_data](#)

**Data Fields**

- **destination**
- **cfs\_protocol**
- **cfs\_run\_in\_xterm**

**11.46.1 Detailed Description**

CFS Configuration for SSH targets, inherited from CfsConfig class.

## 11.46.2 Constructor &amp; Destructor Documentation

## 11.46.2.1 def plugins.cfs.cfs\_config.RemoteCfsConfig.\_\_init\_\_( self, name )

Constructor for RemoteCfsConfig Class. Override cfs\_protocol attribute to ssh.

## 11.46.3 Member Function Documentation

## 11.46.3.1 def plugins.cfs.cfs\_config.RemoteCfsConfig.load\_config\_data( self, section\_name )

From loaded sections of INI config, interpret CFS target config attributes, including build\_cfs, CCSDS\_data\_dir, CCSDS\_target, etc.

@param section\_name: loaded Json CFS target section.

@return None

## 11.47 plugins.cfs.pycfs.cfs\_controllers.RemoteCfsController Class Reference

## Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [initialize](#)
- def [archive\\_cfs\\_files](#)
- def [shutdown\\_cfs](#)
- def [shutdown](#)

## Data Fields

- **execution**
- **cfs**
- **cfs\_process\_list**
- **cfs\_running**

## Additional Inherited Members

## 11.47.1 Detailed Description

RemoteCfsController class Definition:

@note RemoteCfsController class is inherited from CfsController class. It only redefines a few functions, including \_\_init\_\_, initialize, archive\_cfs\_files, shutdown\_cfs, shutdown.

@note RemoteCfsController is initiated when INI config file uses 'ssh' protocol.

## 11.47.2 Constructor &amp; Destructor Documentation

## 11.47.2.1 def plugins.cfs.pycfs.cfs\_controllers.RemoteCfsController.\_\_init\_\_( self, config )

Constructor implementation for RemoteCfsController class.



### 11.47.3 Member Function Documentation

#### 11.47.3.1 def plugins.cfs.pycfs.cfs\_controllers.RemoteCfsController.archive\_cfs\_files ( self, source\_path )

Implementation of CFS plugin instructions archive\_cfs\_files. When CFS plugin instructions (archive\_cfs\_files) is executed, it calls RemoteCfsController instance's archive\_cfs\_files function.

#### 11.47.3.2 def plugins.cfs.pycfs.cfs\_controllers.RemoteCfsController.initialize ( self )

Initialize CfsController instance, including the followings: create mid map; import ccscs header; create ssh CFS command interface; create telemetry interface;

#### 11.47.3.3 def plugins.cfs.pycfs.cfs\_controllers.RemoteCfsController.shutdown ( self )

This function will shut down the CFS application being tested even if the JSON test file does not include the shutdown test command

#### 11.47.3.4 def plugins.cfs.pycfs.cfs\_controllers.RemoteCfsController.shutdown\_cfs ( self )

Implementation of CFS plugin instructions shutdown\_cfs. When CFS plugin instructions (shutdown\_cfs) is executed, it calls RemoteCfsController instance's shutdown\_cfs function.

## 11.48 plugins.cfs.pycfs.remote\_cfs\_interface.RemoteCfsInterface Class Reference

### Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [get\\_start\\_string](#)
- def [start\\_cfs](#)
- def [build\\_cfs](#)

### Data Fields

- [execution\\_controller](#)
- [cfs\\_std\\_out\\_path](#)

### Additional Inherited Members

#### 11.48.1 Detailed Description

RemoteCfsInterface implements lower-level interface to communicate with cFS remotely over SSH. Inherits Cfs Interface - extends some of it's functionality specifically for SSH.

### 11.48.2 Constructor & Destructor Documentation

#### 11.48.2.1 def plugins.cfs.pycfs.remote\_cfs\_interface.RemoteCfsInterface.\_\_init\_\_ ( self, config, telemetry, command, mid\_map, ccscs, execution )

Constructor implementation for RemoteCfsInterface. Pass arguments to base class.

## 11.48.3 Member Function Documentation

## 11.48.3.1 def plugins.cfs.pycfs.remote\_cfs\_interface.RemoteCfsInterface.build\_cfs ( self )

Build remote cfs image. The path of cFS source is configured in config init file.  
 The build output folder is also configured in init file.  
 @return bool: True if build succeed, otherwise False

## 11.48.3.2 def plugins.cfs.pycfs.remote\_cfs\_interface.RemoteCfsInterface.get\_start\_string ( self, run\_args )

Build the start string for starting cFS instance.  
 @param run\_args: run\_args is used to build start string  
 @return string: command to start cFS instance, including remote cFS path.

## 11.48.3.3 def plugins.cfs.pycfs.remote\_cfs\_interface.RemoteCfsInterface.start\_cfs ( self, run\_args )

Start the remote cfs instance process.  
 @param run\_args: run\_args is used to build the start\_string.  
 @return dictionary: the return result\_values is a dictionary, including 'results': True if cfs instance starts successfully, otherwise False; and 'pid': the pid of cfs instance process.

## 11.49 lib.script\_manager.ScriptManager Class Reference

## Public Member Functions

- def `__init__`
- def `add_script`
- def `add_script_file`
- def `run_all_scripts`
- def `prep_logging`
- def `write_summary_line`
- def `__del__`

## Data Fields

- `script_list`
- `config`
- `regression_summary_file_path`
- `regression_summary_json_file_path`
- `curr_script_log_dir_path`
- `plugin_manager`
- `status_manager`
- `summary_file`

## 11.49.1 Detailed Description

The ScriptManager class adds and manages all loaded CTF test scripts.

@note - The script manager's add\_script is called with each script loaded by the JSONScriptReader.

@note - The script manager handles execution of test scripts, including logging the results and managing the test suite status

@param plugin\_manager: Initialized instance of the plugin manager, used to interact with the loaded plugins

@param status\_manager: Initialized instance of the status manager, used to send status to external listeners

## 11.49.2 Constructor &amp; Destructor Documentation

## 11.49.2.1 def lib.script\_manager.ScriptManager.\_\_del\_\_( self )

Destructor implementation to close summary file on deletion of the ScriptManager

## 11.49.3 Member Function Documentation

## 11.49.3.1 def lib.script\_manager.ScriptManager.add\_script( self, script )

Adds a script to the list of scripts managed by the script manager

## 11.49.3.2 def lib.script\_manager.ScriptManager.add\_script\_file( self, file )

Adds a script file to the list of scripts. If the file is not valid, skip it.

## 11.49.3.3 def lib.script\_manager.ScriptManager.prep\_logging( self )

Prepares logging directories for a CTF test run. Logging directories will include script-specific log directories, as well as high-level log files and results summary.

## 11.49.3.4 def lib.script\_manager.ScriptManager.run\_all\_scripts( self )

Run all added scripts, updating the status packets, and ensuring plugins are reloaded between scripts if needed.

## 11.49.3.5 def lib.script\_manager.ScriptManager.write\_summary\_line( self, summary\_line )

Write an entry to the summary results file(s).

@note - An entry consists of:

- Script status (pass/fail)
- Execution Time
- Verification Number
- Requirements Verified
- # of tests that ran
- # of tests that passed
- # of tests the failed
- # of tests with an error
- Script input file (.JSON)

## 11.50 lib.script\_manager.ScriptManagerConfig Class Reference

## Public Member Functions

- def [\\_\\_init\\_\\_](#)

## Data Fields

- **reset\_plugins\_between\_scripts**
- **json\_results**

## 11.50.1 Detailed Description

Configuration parameters used by the ScriptManager class, obtained from the loaded INI config

### 11.50.2 Constructor & Destructor Documentation

#### 11.50.2.1 def lib.script\_manager.ScriptManagerConfig.\_\_init\_\_( self )

Constructor of ScriptManagerConfig class. Initialize properties from INI file

## 11.51 plugins.ssh.ssh\_plugin.SshConfig Class Reference

### Public Member Functions

- def [\\_\\_init\\_\\_](#)

### Data Fields

- [command\\_timeout](#)  
*SshConfig command\_timeout property.*
- [print\\_stdout](#)  
*SshConfig print\_stdout property.*
- [log\\_stdout](#)  
*SshConfig log\_stdout property.*

### 11.51.1 Detailed Description

The SshConfig helper Class Definition

@note it gets the command\_timeout, print\_stdout and print\_stdout from configuration Json file

### 11.51.2 Constructor & Destructor Documentation

#### 11.51.2.1 def plugins.ssh.ssh\_plugin.SshConfig.\_\_init\_\_( self )

Constructor implementation for SshConfig helper class.

## 11.52 plugins.ssh.ssh\_plugin.SshController Class Reference

### Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [init\\_connection](#)
- def [run\\_command](#)
- def [run\\_command\\_persistent](#)
- def [get\\_last\\_pid](#)
- def [run\\_command\\_local](#)
- def [check\\_output](#)
- def [put\\_file](#)
- def [get\\_file](#)
- def [rsync](#)
- def [upload\\_ftp](#)
- def [download\\_ftp](#)
- def [shutdown](#)

## Data Fields

- **config**
- **connection**
- **last\_result**
- **last\_pid**
- **ftp\_interface**

## 11.52.1 Detailed Description

The SshController helper Class Definition

@note SshController provides an instance of SSH plugin's target: `self.targets[name] = SshController(SshConfig())`

@note SshController provides the implementation SSH plugin's commands. For example, `upload_ftp` commands calls `self.targets[name].download_ftp(host, remote_path, local_path)`

## 11.52.2 Constructor &amp; Destructor Documentation

11.52.2.1 `def plugins.ssh.ssh_plugin.SshController.__init__( self, config )`

Constructor implementation for SshController helper class.

## 11.52.3 Member Function Documentation

11.52.3.1 `def plugins.ssh.ssh_plugin.SshController.check_output( self, output_contains=None, output_does_not_contain=None, exit_code=0 )`

`check_output` provides implementation of SSH plugin's `check_output` / `SSH_CheckOutput` method:  
`self.targets[name].check_output(output_contains, output_does_not_contain, exit_code)`

11.52.3.2 `def plugins.ssh.ssh_plugin.SshController.download_ftp( self, host, remote_path, local_path )`

`download_ftp` provides implementation of SSH plugin's `download_ftp` / `SSH_GetFTP` method:  
`self.targets[name].download_ftp(host, remote_path, local_path)`

11.52.3.3 `def plugins.ssh.ssh_plugin.SshController.get_file( self, remote_path, local_path, args=None )`

`get_file` provides implementation of SSH plugin's `get_file` / `SSH_GetFile` method:  
`self.targets[name].get_file(remote_path, local_path, args)`

11.52.3.4 `def plugins.ssh.ssh_plugin.SshController.get_last_pid( self )`

`return last_pid`

11.52.3.5 `def plugins.ssh.ssh_plugin.SshController.init_connection( self, host, user=None, port=None, gateway=None, ssh_config_path=None, args=None )`

`init_connection` provides implementation of SSH plugin's `init_connection` method:  
`self.targets[name].init_connection(host, user, port, gateway, ssh_config_path, args)`

**11.52.3.6 def plugins.ssh.ssh\_plugin.SshController.put\_file ( self, local\_path, remote\_path, args = None )**

put\_file provides implementation of SSH plugin's put\_file / SSH\_PutFile method:  
 self.targets[name].put\_file(local\_path, remote\_path, args)

**11.52.3.7 def plugins.ssh.ssh\_plugin.SshController.rsync ( self, source, dest, push, args = None )**

rsync implements async file transfer

**11.52.3.8 def plugins.ssh.ssh\_plugin.SshController.run\_command ( self, command, cwd = "", prefix = ":" )**

run\_command provides implementation of SSH plugin's run\_command / SSH\_RunRemoteCommand method:  
 self.targets[name].run\_command(command, cwd, prefix)

**11.52.3.9 def plugins.ssh.ssh\_plugin.SshController.run\_command\_local ( self, command )**

run\_command\_local provides implementation of SSH plugin's run\_command\_local / SSH\_RunLocalCommand method:  
 self.targets[name].run\_command\_local(command)

**11.52.3.10 def plugins.ssh.ssh\_plugin.SshController.run\_command\_persistent ( self, command, cwd = "", prefix = ":" )**

run\_command\_persistent implement SSH persistent call with configurable time-out

**11.52.3.11 def plugins.ssh.ssh\_plugin.SshController.shutdown ( self )**

shutdown provides implementation of SSH plugin's shutdown method:  
 SSH plugin calls self.targets[name].shutdown()

**11.52.3.12 def plugins.ssh.ssh\_plugin.SshController.upload\_ftp ( self, host, local\_path, remote\_path )**

upload\_ftp provides implementation of SSH plugin's upload\_ftp / SSH\_PutFTP method:  
 self.targets[name].upload\_ftp(host, local\_path, remote\_path)

**11.53 plugins.ssh.ssh\_plugin.SshPlugin Class Reference****Public Member Functions**

- def [\\_\\_init\\_\\_](#)
- def [initialize](#)
- def [register\\_target](#)
- def [init\\_connection](#)
- def [run\\_command](#)
- def [run\\_command\\_local](#)
- def [check\\_output](#)
- def [put\\_file](#)
- def [get\\_file](#)
- def [upload\\_ftp](#)
- def [download\\_ftp](#)
- def [shutdown](#)

## Data Fields

- **name**
- **description**
- **targets**
- **command\_map**
- **verify\_required\_commands**

## 11.53.1 Detailed Description

The SSH Plugin Class Definition

@note The SSH Plugin provides remote and local shell command execution capability for CTF.

@note The following test instructions are available:

@note SSH\_RegisterTarget; SSH\_InitSSH; SSH\_RunRemoteCommand; SSH\_RunLocalCommand; SSH\_CheckOutput; SSH\_PutFile;

@note SSH\_GetFile; SSH\_GetFTP; SSH\_PutFTP;

@note A custom CTF plugin can be created to add new CTF instructions that can then be utilized within a JSON test script.

@note All plugin functions mapped to a test instruction *must* return true/false to indicate pass/fail of that instruction.

## 11.53.2 Constructor &amp; Destructor Documentation

## 11.53.2.1 def plugins.ssh.ssh\_plugin.SshPlugin.\_\_init\_\_( self )

Constructor implementation for SSH plugin.

@note The `__init__` function is called once a plugin is loaded.

@note The `__init__` function should not reference/interact with any other plugin since the other plugin may not be loaded at this stage.

@note The constructor of a plugin must define the following fields:

- name
- description
- command map: dictionary mapping CTF instructions to a tuple defining the python function to use for that instruction, and a list of argument types
- [optional] verify\_required\_commands: List of instructions that require verification (i.e polling until verification passes or timeout.
- other class variables that can store state, etc...

## 11.53.3 Member Function Documentation

## 11.53.3.1 def plugins.ssh.ssh\_plugin.SshPlugin.check\_output( self, output\_contains=None, output\_does\_not\_contain=None, exit\_code=0, name="default" )

Compares the output of the most recently executed command.

ExecutionRunRemoteCommand or ExecutionRunLocalCommand must be called first.

@param name: A name already registered with SSH\_RegisterTarget to identify the connection. (Optional)

@param output\_contains: A substring that must be contained in stdout. (Example: "PASS") (Optional)

@param output\_does\_not\_contain: A substring that should not be contained in stdout. (Example: "FAIL") (Optional)

@param exit\_code: The expected exit code after the shell command is executed. (Optional default = 0)

@return bool: True if successful, False otherwise.

```
@par Example:
@code
{
    "command": "SSH_CheckOutput",
    "wait": 0,
    "data": {
        "name": "workstation",
        "output_contains": "Built target mission-install",
        "output_does_not_contain": "Error",
        "exit_code": 0
    }
}
```

### 11.53.3.2 def plugins.ssh.ssh\_plugin.SshPlugin.download\_ftp( self, host, remote\_path, local\_path, name = "default" )

Downloads a path (file or directory) from the FTP server to the local filesystem.

@param name: A name already registered with 'SSH\_RegisterTarget' to identify the connection. (Optional)

@param host: The hostname or address of the FTP server.

@param remote\_path: The path to the source file or directory on the FTP server.

@param local\_path: The local path to where the file or directory is to be downloaded.

@return bool: True if successful, False otherwise.

```
@par Example:
@code
{
    "command": "SSH_GetFTP",
    "wait": 0,
    "data": {
        "name": "workstation",
        "host": "ftphost",
        "remote_path": "./data/output.dat",
        "local_path": "./results.txt"
    }
}
```

### 11.53.3.3 def plugins.ssh.ssh\_plugin.SshPlugin.get\_file( self, remote\_path, local\_path, args = None, name = "default" )

Copies a path (file or directory) from the remote host to the local filesystem via rsync.

Relative or absolute paths are allowed, but do not use ~. Strings are passed directly to rsync, so the same rules apply regarding paths, patterns, etc.

@param name: A name already registered with SSH\_RegisterTarget to identify the connection. (Optional)

@param remote\_path: The path to where the file or directory is to be copied.

For remote hosts use the SSH syntax user@host:path.

@param local\_path: The path to the local file or directory to be copied.

@param args: An object that describes optional parameters for the transfer.

delete: A boolean corresponding to rsync's --delete option.

If true, rsync will remove remote files that no longer exist locally. Defaults to false.

exclude: A string or array of strings corresponding to rsync's --exclude option. Defaults to None.

@return bool: True if successful, False otherwise.

```
@par Example:
@code
{
    "command": "SSH_GetFile",
    "wait": 0,
    "data": {
        "name": "workstation",
        "remote_path": "./data/output.dat",
        "local_path": "./results.txt"
    }
}
```



### 11.53.3.4 def plugins.ssh.ssh\_plugin.SshPlugin.init\_connection( self, host, user=None, port=None, gateway=None, ssh\_config\_path=None, args=None, name="default" )

Establishes an SSH connection with a target host.

This command must be run before other remote commands will work.

Command may be used multiple times with the same name to connect to different remote hosts in succession, or be used with different names to maintain concurrent connections to multiple hosts.

- **host**: hostname or IP to connect to, which may include the username and/or port.

@param name: A name already registered with 'SSH\_RegisterTarget' to identify the connection. (Optional)

@param user: User name for the connection. Do not use if you specified the user in 'host'. (Optional)

@param port: Port number for the connection. Do not use if you specified the port in 'host'. (Optional)

@param gateway: SSH gateway command string to proxy the connection to 'host' (Optional)

@param ssh\_config\_path: Path to an ssh config file which may contain host definitions or additional parameters.

If not specified, '~/.ssh/config' will be assumed. (Optional)

@param args: Additional SSH connection options, as needed. See [Paramiko API docs] (Optional)

(<http://docs.paramiko.org/en/latest/api/client.html#paramiko.client.SSHClient.connect>) for relevant values.

@return bool: True if successful, False otherwise.

### 11.53.3.5 def plugins.ssh.ssh\_plugin.SshPlugin.initialize( self )

Initialize implementation for the SSH plugin.

@note The initialize function is called by the CTF plugin manager *after* all plugins have been loaded.

@note This function may interact with other plugins, since all plugins have been loaded at this stage.

@return bool: True if successful, False otherwise.

### 11.53.3.6 def plugins.ssh.ssh\_plugin.SshPlugin.put\_file( self, local\_path, remote\_path, args=None, name="default" )

Copies a path (file or directory) from the local filesystem to the remote host via rsync.

Relative or absolute paths are allowed, but do not use ~. Strings are passed directly to rsync, so the same rules apply regarding paths, patterns, etc.

@param name: A name already registered with SSH\_RegisterTarget to identify the connection. (Optional)

@param local\_path: The path to the local file or directory to be copied.

@param remote\_path: The path to where the file or directory is to be copied.

For remote hosts use the SSH syntax user@host:path.

@param args: An object that describes optional parameters for the transfer.

delete: A boolean corresponding to rsync's --delete option.

If true, rsync will remove remote files that no longer exist locally. Defaults to false.

exclude: A string or array of strings corresponding to rsync's --exclude option. Defaults to None.

@return bool: True if successful, False otherwise.

@par Example:

@code

```
{
    "command": "SSH_PutFile",
    "wait": 0,
    "data": {
"name": "workstation",
"local_path": "./cfs",
"remote_path": "/tmp/workspace/cfs",
"args": {
    "delete": true,
    "exclude": "*.git"
}
}
}
```

### 11.53.3.7 def plugins.ssh.ssh\_plugin.SshPlugin.register\_target( self, name="" )

Declares a target host by name. This command must be run before any other commands given the same name.

Command may be used multiple times to declare any number of targets.  
If not used, the plugin will assume that all commands are intended for the same target as defined in SSH\_InitSSH.

@param name: An arbitrary, unique name to identify the target in subsequent commands.  
Does not need be the actual hostname of the target. Name is optional in all other commands,  
but if not provided all such commands will share a single connection.

@return bool: True if successful, False otherwise.

@par Example

@code

```
{
    "command": "SSH_RegisterTarget",
    "wait": 1,
    "data": {
        "name": "workstation"
    }
}
```

#### 11.53.3.8 def plugins.ssh.ssh\_plugin.SshPlugin.run\_command( self, command, cwd = "", prefix = ":", name = "default" )

Executes a command on the remote host. ExecutionInitSSH must be called first to establish an SSH connection.

@param name: A name already registered with 'SSH\_RegisterTarget' to identify the connection. (Optional)

@param command: The shell command to be executed. Can contain multiple commands separated with ';'.

@return bool: True if successful, False otherwise.

@par Example:

@code

```
{
    "command": "SSH_RunLocalCommand",
    "wait": 1,
    "data": {
        "name": "workstation",
        "host": "cd lander_fsw_ctf;/rm -rf build; make; make install;"
    }
}
```

#### 11.53.3.9 def plugins.ssh.ssh\_plugin.SshPlugin.run\_command\_local( self, command, name = "default" )

Executes a command on the local host (the machine running CTF), regardless of the target.  
This is different from calling SSH\_RunRemoteCommand targeting localhost,  
as it is invoked directly by the current process rather than passed via SSH.

@param name: A name already registered with SSH\_RegisterTarget to identify the connection. (Optional)

@param command: The shell command to be executed. Can contain multiple commands separated with ;

@return bool: True if successful, False otherwise.

@par Example:

@code

```
{
    "command": "SSH_RunLocalCommand",
    "wait": 1,
    "data": {
        "name": "workstation",
        "host": "cd lander_fsw_ctf;/rm -rf build; make; make install;"
    }
}
```

#### 11.53.3.10 def plugins.ssh.ssh\_plugin.SshPlugin.shutdown( self )

Shutdown implementation for the SSH plugin.

@note The shutdown function is called by the CTF plugin manager upon completion of a test run.

@note The shutdown function can be exposed to test scripts by adding it to the command map.

### 11.53.3.11 def plugins.ssh.ssh\_plugin.SshPlugin.upload\_ftp( self, host, local\_path, remote\_path, name = "default" )

Uploads a path (file or directory) from the local filesystem to the FTP server.

@param name: A name already registered with 'SSH\_RegisterTarget' to identify the connection. (Optional)

@param host: The hostname or address of the FTP server.

@param remote\_path: The path on the FTP server to where the file or directory is to be uploaded.

@param local\_path: The local path to the source file or directory.

@return bool: True if successful, False otherwise.

@par Example:

@code

```
{
    "command": "SSH_PutFTP",
    "wait": 0,
    "data": {
        "name": "workstation",
        "host": "ftphost",
        "remote_path": "./data/output.dat",
        "local_path": "./results.txt"
    }
}
```

## 11.54 lib.status.StatusDefs Class Reference

### Static Public Attributes

- string **waiting** = 'waiting'
- string **active** = 'active'
- string **stopped** = 'stopped'
- string **passed** = 'passed'
- string **failed** = 'failed'
- string **error** = 'error'
- string **timeout** = 'timeout'
- string **aborted** = 'aborted'
- string **disabled** = 'disabled'

### 11.54.1 Detailed Description

This class defines enumerations for the status definitions used by CTF to send instruction status.

## 11.55 lib.status\_manager.StatusManager Class Reference

### Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [start](#)
- def [set\\_scripts](#)
- def [update\\_suite\\_status](#)
- def [finalize\\_suite\\_status](#)
- def [update\\_script\\_status](#)
- def [update\\_test\\_status](#)
- def [update\\_command\\_status](#)
- def [end\\_command](#)

- def [end\\_test](#)
- def [end\\_script](#)
- def [sanitize\\_status](#)
- def [send\\_update](#)

#### Static Public Member Functions

- def [blank\\_status\\_msg](#)
- def [sanitize\\_param](#)
- def [sanitize\\_data](#)

#### Data Fields

- **status**
- **script\_index**
- **test\_index**
- **command\_index**
- **ip\_address**
- **port**
- **socket**
- **start\_time**

### 11.55.1 Detailed Description

The StatusManager class established a status stream with the current test suite status. The status packets are sent over a UDP socket over the specified port. Clients listening on that port will receive periodic CTF status messages during test execution

@param ip\_address: IP of the external listener to connect to

@param: port: Port used by the external listener to receive status messages

### 11.55.2 Constructor & Destructor Documentation

**11.55.2.1** def lib.status\_manager.StatusManager.\_\_init\_\_( self, ip\_address = "127.0.0.1", port = None )

Constructor of StatusManager Class: initiate instance properties.

### 11.55.3 Member Function Documentation

**11.55.3.1** def lib.status\_manager.StatusManager.blank\_status\_msg( scripts ) [static]

Get a blank status message that contains status objects for each script loaded by CTF

**11.55.3.2** def lib.status\_manager.StatusManager.end\_command( self )

Increment the current active command index.

**11.55.3.3** def lib.status\_manager.StatusManager.end\_script( self )

Increment the current active script. Reset the test and command indices to 0.

**11.55.3.4 def lib.status\_manager.StatusManager.end\_test ( self )**

Increment the current active test case index. Reset the command index to 0.

**11.55.3.5 def lib.status\_manager.StatusManager.finalize\_suite\_status ( self )**

Set the test suit status (pass/fail) based on the status of all scripts within the suite.

**11.55.3.6 def lib.status\_manager.StatusManager.sanitize\_data ( data ) [static]**

Sanitize test instruction data by attempting to decode every field if needed

**11.55.3.7 def lib.status\_manager.StatusManager.sanitize\_param ( param ) [static]**

Sanitize a test instruction parameter by attempting to decode it if needed

**11.55.3.8 def lib.status\_manager.StatusManager.sanitize\_status ( self )**

Sanitize test script data by attempting to decode every field at the test script level if needed

**11.55.3.9 def lib.status\_manager.StatusManager.send\_update ( self )**

Send the latest status packet over the UDP socket.

@note - If the UDP socket encounters an error for any reason, the port will be set to None and CTF will not send updates to the Editor any more. The socket failure is most likely to be a computer issue, not CTF issue.

**11.55.3.10 def lib.status\_manager.StatusManager.set\_scripts ( self, scripts )**

Set the script status entry for each script with default values

**11.55.3.11 def lib.status\_manager.StatusManager.start ( self )**

Set the start time of test suite execution in the status message.

**11.55.3.12 def lib.status\_manager.StatusManager.update\_command\_status ( self, status, details, index=None )**

Update the status of a single command within a test script.

**11.55.3.13 def lib.status\_manager.StatusManager.update\_script\_status ( self, status, details="" )**

Update the status of a single script within the test suite.

**11.55.3.14 def lib.status\_manager.StatusManager.update\_suite\_status ( self, status, details )**

Given an updated status (and details), update the suite status with the latest state.

**11.55.3.15 def lib.status\_manager.StatusManager.update\_test\_status ( self, status, details="" )**

Update the status of a single script within the test suite.

## 11.56 plugins.cfs.pycfs.cfs\_interface.TelemetryVerification Class Reference

### Public Member Functions

- def [\\_\\_init\\_\\_](#)

### Data Fields

- **verification\_id**
- **condition**
- **passed**
- **pass\_count**
- **fail\_count**

#### 11.56.1 Detailed Description

Telemetry Verification class

#### 11.56.2 Constructor & Destructor Documentation

11.56.2.1 def plugins.cfs.pycfs.cfs\_interface.TelemetryVerification.\_\_init\_\_( self, v\_id, condition )

Constructor for TelemetryVerification class. Assign attribute default values.

## 11.57 lib.test.Test Class Reference

### Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [execute\\_instruction](#)
- def [execute\\_verification](#)
- def [process\\_verification\\_delay](#)
- def [run\\_commands](#)
- def [process\\_conditional\\_branch\\_label](#)
- def [process\\_control\\_flow\\_label](#)
- def [run\\_test](#)

### Static Public Member Functions

- def [process\\_command\\_delay](#)

### Data Fields

- **test\_info**
- **instructions**
- **test\_result**
- **test\_aborted**
- **test\_run**
- **num\_skipped**

- **num\_ran**
- **test\_start\_time**
- **ctf\_verification\_timeout**
- **ctf\_verification\_poll\_period**
- **end\_test\_on\_fail**
- **ignored\_instructions**
- **verif\_list**
- **verify\_required\_commands**
- **continuous\_verification\_commands**
- **end\_test\_on\_fail\_commands**
- **status\_manager**
- **current\_instruction\_index**

#### Static Private Member Functions

- **def \_\_check\_label\_def**

#### 11.57.1 Detailed Description

The TestCase class represents a CTF Test Case.  
 @note - A test script may have multiple test cases.

#### 11.57.2 Constructor & Destructor Documentation

##### 11.57.2.1 def lib.test.Test.\_\_init\_\_( self )

Constructor of Test Class: Initiate test properties

#### 11.57.3 Member Function Documentation

##### 11.57.3.1 def lib.test.Test.execute\_instruction( self, test\_instruction, command\_index )

Execute a CTF Test Instruction

##### 11.57.3.2 def lib.test.Test.execute\_verification( self, command, command\_index, timeout, new\_verification=False )

Execute a CTF Verification Instruction.  
 @note - Verification instructions will be executed at the specified poll period until the verification passes or a timeout is reached

##### 11.57.3.3 def lib.test.Test.process\_command\_delay( delay ) [static]

Utilize the current CTF time manager to wait a specific amount of time before executing a CTF Test Instruction

##### 11.57.3.4 def lib.test.Test.process\_conditional\_branch\_label( self )

Process conditional branch labels defined in test instructions 'IfCondition', 'ElseCondition', 'EndCondition'

##### 11.57.3.5 def lib.test.Test.process\_control\_flow\_label( self )

Process control flow labels defined in test instructions 'BeginLoop' and 'EndLoop'

## 11.57.3.6 def lib.test.Test.process\_verification\_delay ( self )

Utilize the current CTF time manager to wait for the duration of the polling period before executing a CTF Verification Test Instruction

## 11.57.3.7 def lib.test.Test.run\_commands ( self )

Run all CTF Instructions in the current test case

## 11.57.3.8 def lib.test.Test.run\_test ( self, status\_manager )

Run all CTF Instructions within a test case

## 11.58 lib.logger.TestFormatter Class Reference

## Public Member Functions

- def **formatTime**

## 11.58.1 Detailed Description

TestFormatter: Customizes the logging formatter to override formatTime

## 11.59 lib.test\_script.TestScript Class Reference

## Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [set\\_header\\_info](#)
- def [set\\_options](#)
- def [set\\_watch\\_lists](#)
- def [set\\_tests](#)
- def [run\\_script](#)
- def [log\\_test\\_header](#)
- def [generate\\_test\\_results](#)

## Data Fields

- **test\_number**
- **test\_name**
- **requirements**
- **test\_description**
- **options**
- **telem\_watch\_list**
- **cmd\_watch\_list**
- **test\_owner**
- **test\_setup**
- **verify\_timeout**
- **tests**
- **input\_file\_path**



- **input\_file**
- **params**
- **status**
- **start\_time**
- **exec\_time**
- **num\_tests**
- **num\_passed**
- **num\_failed**
- **num\_error**

### 11.59.1 Detailed Description

The TestScript class represents a CTF test script, storing script data and status.

### 11.59.2 Constructor & Destructor Documentation

#### 11.59.2.1 def lib.test\_script.TestScript.\_\_init\_\_( self )

Constructor of TestScript Class: Initiate instance properties

### 11.59.3 Member Function Documentation

#### 11.59.3.1 def lib.test\_script.TestScript.generate\_test\_results( self )

Generate and Log the test results after test execution

#### 11.59.3.2 def lib.test\_script.TestScript.log\_test\_header( self )

Log the test header (metadata) before beginning test execution

#### 11.59.3.3 def lib.test\_script.TestScript.run\_script( self, status\_manager )

Execute a complete test script, updating the status\_manager as needed.

#### 11.59.3.4 def lib.test\_script.TestScript.set\_header\_info( self, test\_number, test\_name, requirements, test\_description, test\_owner, test\_setup, verify\_timeout )

Set the TestScript's header information from the input test script file.

```
@param test_number: Test number
@param test_name: Test name
@param requirements: Requirements validated by this test
@param test_description: Test Description
@param test_owner: Test Owner
@param test_setup: Test Setup
@param verify_timeout: Test Specific Verification Timeout (Overrides 'ctf_verification_timeout' in INI File)
```

#### 11.59.3.5 def lib.test\_script.TestScript.set\_options( self, options )

Set the TestScript's options from the input test script file.

```
@param options: Test Script Options (Dict)
```

**11.59.3.6** def lib.test\_script.TestScript.set\_tests ( self, tests )

Set the list of test cases within this test script

**11.59.3.7** def lib.test\_script.TestScript.set\_watch\_lists ( self, telem\_watch\_list, cmd\_watch\_list )

Set the TestScript's telemetry and command watch lists.

@note Telemetry and Command watch list are currently not used by CTF.

@param telem\_watch\_list: Test Script Telemetry Watch List

@param cmd\_watch\_list: Test Script Command Watch List

**11.60 lib.time\_interface.TimeInterface Class Reference****Public Member Functions**

- def [\\_\\_init\\_\\_](#)
- def [wait](#)

**Static Public Member Functions**

- def [wait\\_seconds](#)
- def [pre\\_command](#)
- def [post\\_command](#)

**Data Fields**

- [exec\\_time](#)  
*Execution time since the time manager was initialized.*
- [last\\_command\\_completion\\_time](#)  
*Execution time when the last instruction was completed.*
- [time\\_since\\_last\\_command](#)  
*How much time has passed since the last instruction was completed.*

**11.60.1 Detailed Description**

Virtual class definition for custom plugins to implement their own time managers.

@note A custom plugin must set the global time manager used by CTF using `Global.set_time_manager(time_manager)`

**11.60.2 Constructor & Destructor Documentation****11.60.2.1** def lib.time\_interface.TimeInterface.\_\_init\_\_ ( self )

Constructor of TimeInterface Class: Initiate instance properties

**11.60.3 Member Function Documentation****11.60.3.1** def lib.time\_interface.TimeInterface.post\_command ( ) [static]

Optional implementation of logic to be executed *after* a CTF instruction is invoked.

@note - This is useful when pausing/resuming of frames on an external time source is needed.

**11.60.3.2 def lib.time\_interface.TimeInterface.pre\_command ( ) [static]**

Optional implementation of logic to be executed *\*before\** a CTF instruction is invoked.

@note - This is useful when pausing/resuming of frames on an external time source is needed.

**11.60.3.3 def lib.time\_interface.TimeInterface.wait ( self, seconds )**

Virtual method to wait an amount of time.

@note - May include special logic to interface with external time sources

**11.60.3.4 def lib.time\_interface.TimeInterface.wait\_seconds ( seconds ) [static]**

Helper utility to wait in seconds (OS Time)

**11.60.4 Field Documentation****11.60.4.1 lib.time\_interface.TimeInterface.time\_since\_last\_command**

How much time has passed since the last instruction was completed.

**11.61 plugins.cfs.pycfs.tlm\_listener.TlmListener Class Reference****Public Member Functions**

- def [\\_\\_init\\_\\_](#)
- def [cleanup](#)
- def [create\\_socket](#)
- def [get\\_port](#)
- def [read\\_socket](#)

**Data Fields**

- **ipaddr**
- **port**
- **socket**

**11.61.1 Detailed Description**

Simple telemetry listener class that connects to a given ip/port via UDP and manages that connection. Can call read\_socket() to receive the next packet in telemetry stream.

**11.61.2 Constructor & Destructor Documentation****11.61.2.1 def plugins.cfs.pycfs.tlm\_listener.TlmListener.\_\_init\_\_ ( self, ipaddr, port )**

Constructor of TlmListener class.  
 @param ipaddr: IP address of cFS system.  
 @param port: port of cFS system.  
 @return None

### 11.61.3 Member Function Documentation

#### 11.61.3.1 def plugins.cfs.pycfs.tlm\_listener.TlmListener.cleanup ( self )

Close socket connection.

@return None

#### 11.61.3.2 def plugins.cfs.pycfs.tlm\_listener.TlmListener.create\_socket ( self )

Create a UDP socket connection to a cFS system.

@return socket

#### 11.61.3.3 def plugins.cfs.pycfs.tlm\_listener.TlmListener.get\_port ( self )

Return the UDP port to cFS system

@return UDP port

#### 11.61.3.4 def plugins.cfs.pycfs.tlm\_listener.TlmListener.read\_socket ( self )

Receive the UDP packet in the telemetry stream.

@return the number of bytes read from telemetry stream

## 11.62 plugins.cfs.pycfs.output\_app\_interface.ToApi Class Reference

### Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [disable\\_output](#)
- def [enable\\_output](#)

### Data Fields

- **command\_args**
- **cmd\_cc**
- **mid**
- **name**

### 11.62.1 Detailed Description

Construct the ToApi class

For CFS, TO is used to extract command and telemetry CCSDS packets from the software bus, and is sent over UDP to the CFS test framework.

### 11.62.2 Constructor & Destructor Documentation

#### 11.62.2.1 def plugins.cfs.pycfs.output\_app\_interface.ToApi.\_\_init\_\_ ( self, local\_ip = "", local\_port = 0, command\_interface = None, cclds\_ver = 0, mid\_map = None, name = None )

Constructor of the ToApi class.

```
@param local_ip: The IP address we want packets to be forwarded to. Default: 127.0.0.1
@param local_port: The port we want packets to be forwarded to. Default: 40096
@param command_interface: An instance of the CommandInterface class (used to send commands to UDP)
@param ccstds_ver: CCSDS header version (1 or 2)
```

### 11.62.3 Member Function Documentation

#### 11.62.3.1 def plugins.cfs.pycfs.output\_app\_interface.ToApi.disable\_output ( self )

disable\_output cFS instruction is not implemented in ToApi class, always return True.  
 @return bool: always return True

#### 11.62.3.2 def plugins.cfs.pycfs.output\_app\_interface.ToApi.enable\_output ( self )

Implement enable\_output method for ToApi class.  
 Build "SendCfsCommand" instruction with command code "TO\_ENABLE\_OUTPUT",  
 search for a plugin to send out the instruction.  
 @return bool: True if a plugin send out instruction successfully; otherwise False

## 11.63 plugins.userio\_plugin.userio\_plugin.UserIOPlugin Class Reference

### Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [initialize](#)
- def [shutdown](#)

### Static Public Member Functions

- def [waituserinput\\_command](#)

### Data Fields

- [name](#)  
*Plugin Name.*
- [description](#)  
*Plugin Description.*
- [command\\_map](#)  
*Plugin Command Map.*
- [end\\_test\\_on\\_fail\\_commands](#)  
*List of end\_test\_on\_fail\_commands commands.*

#### 11.63.1 Detailed Description

The UserIO Plugin Class Definition

@note The UserIO Plugin define a command to allow user to pause the testing. User must confirm to continue testing for safety critical tasks.

@note The CTF will wait until a user instructs to continue or abort the testing. If aborting the testing, the tests after the instruction will not be executed.

@note The plugin adds a new command in end\_test\_on\_fail\_commands for test.py to check the user input.

@note The custom plugin class *\*must\** inherit from the Plugin base-class.

@note A custom CTF plugin can be created to add new CTF instructions that can then be utilized within a JSON test script.

@note All plugin functions mapped to a test instruction *\*must\** return true/false to indicate pass/fail of that instruction.

### 11.63.2 Constructor & Destructor Documentation

#### 11.63.2.1 def plugins.userio\_plugin.userio\_plugin.UserIOPlugin.\_\_init\_\_( self )

Constructor implementation for example plugin.

@note The \_\_init\_\_ function is called once a plugin is loaded.

@note The \_\_init\_\_ function should not reference/interact with any other plugin since the other plugin may not be loaded at this stage.

@note The constructor of a plugin must define the following fields:

- name
- description
- command map: dictionary mapping CTF instructions to a tuple defining the python function to use for that instruction, and a list of argument types
- [optional] verify\_required\_commands: List of instructions that require verification (i.e polling until verification passes or timeout).
- other class variables that can store state, etc...

### 11.63.3 Member Function Documentation

#### 11.63.3.1 def plugins.userio\_plugin.userio\_plugin.UserIOPlugin.initialize( self )

Initialize implementation for the UserIO plugin.

@note The initialize function is called by the CTF plugin manager *\*after\** all plugins have been loaded.

@note This function may interact with other plugins, since all plugins have been loaded at this stage.

@return bool: True if successful, False otherwise.

#### 11.63.3.2 def plugins.userio\_plugin.userio\_plugin.UserIOPlugin.shutdown( self )

Shutdown implementation for the userio plugin.

@note The shutdown function is called by the CTF plugin manager upon completion of a test run.

@note The shutdown function can be exposed to test scripts by adding it to the command map.

#### 11.63.3.3 def plugins.userio\_plugin.userio\_plugin.UserIOPlugin.waituserinput\_command( prompt = " " ) [static]

Wait for user input: if there is no user input, wait forever;  
if user input is 'Y' or 'y', continue the test;  
if user input is anything else, abort the test

@param prompt: any value (example: "user input")

@return bool: True if successful, False otherwise.

### 11.64 plugins.validation\_plugin.validation\_plugin.ValidationPlugin Class Reference

### Public Member Functions

- def `__init__`
- def `save_file_as_text`
- def `interpret_binary_data`
- def `interpret_event_log`
- def `shutdown`

### Static Public Member Functions

- def `initialize`
- def `delete_file`
- def `copy_file`
- def `convert_timestamp`
- def `parse_txt_file`

### Data Fields

- `name`  
*Plugin Name.*
- `description`  
*Plugin Description.*
- `command_map`  
*Plugin Command Map.*

#### 11.64.1 Detailed Description

The Validation Plugin Class Definition

@note The plugin uses const values / macros to interpret log files, some of these values comes from registered target's controller (which reads ccdd json files). So InterpretCfsFile instruction could NOT be used before RegisterCfs/StartCfs instructions.

#### 11.64.2 Constructor & Destructor Documentation

##### 11.64.2.1 `def plugins.validation_plugin.validation_plugin.ValidationPlugin.__init__( self )`

Constructor implementation for validation plugin.

#### 11.64.3 Member Function Documentation

##### 11.64.3.1 `def plugins.validation_plugin.validation_plugin.ValidationPlugin.convert_timestamp( subsecs, str ) [static]`

Helper function: convert subsecs to microseconds

##### 11.64.3.2 `def plugins.validation_plugin.validation_plugin.ValidationPlugin.initialize( bool ) [static]`

Initialize implementation for the validation plugin.

@note The initialize function is called by the CTF plugin manager *after* all plugins have been loaded.

@return bool: True

11.64.3.3 `def plugins.validation_plugin.validation_plugin.ValidationPlugin.interpret_binary_data( self, event_data, entry_id, offset, endianness_of_target, os_max_api_name, str )`

Helper function: interpret each line of the binary cFE Event Log data to a human readable message

11.64.3.4 `def plugins.validation_plugin.validation_plugin.ValidationPlugin.shutdown( self )`

Shutdown implementation for the validation plugin.

@note The shutdown function is called by the CTF plugin manager upon completion of a test run.

@note The shutdown function can be exposed to test scripts by adding it to the command map.

## 11.65 plugins.variable\_plugin.variable\_plugin.VariablePlugin Class Reference

### Public Member Functions

- `def __init__`
- `def initialize`
- `def shutdown`

### Static Public Member Functions

- `def set_user_defined_variable`
- `def set_user_variable_from_tlm`
- `def set_user_variable_from_tlm_header`
- `def set_label`
- `def get_user_defined_variable`
- `def check_user_defined_variable`

### Data Fields

- `name`  
*Plugin Name.*
- `description`  
*Plugin Description.*
- `command_map`  
*Plugin Command Map.*

### 11.65.1 Detailed Description

The Variable Plugin Class Definition

@note The Variable Plugin allows users to set / read / test variables defined in json test scripts.

@note All plugin functions mapped to a test instruction \*must\* return true/false to indicate pass/fail of that instruction.



## 11.65.2 Constructor & Destructor Documentation

### 11.65.2.1 def plugins.variable\_plugin.variable\_plugin.VariablePlugin.\_\_init\_\_( self )

Constructor of variable plugin.

@note The `__init__` function is called once a plugin is loaded.

@note The `__init__` function should not reference/interact with any other plugin since the other plugin may not be loaded at this stage.

@note The constructor of a plugin must define the following fields:

- name
- description
- command map: dictionary mapping CTF instructions to a tuple defining the python function to use for that instruction, and a list of argument types
- [optional] verify\_required\_commands: List of instructions that require verification (i.e polling until verification passes or timeout).
- other class variables that can store state, etc...

## 11.65.3 Member Function Documentation

### 11.65.3.1 def plugins.variable\_plugin.variable\_plugin.VariablePlugin.initialize( self )

Initialize implementation for the variable plugin.

@note The initialize function is called by the CTF plugin manager *after* all plugins have been loaded.

@note This function may interact with other plugins, since all plugins have been loaded at this stage.

@return bool: True if successful, False otherwise.

### 11.65.3.2 def plugins.variable\_plugin.variable\_plugin.VariablePlugin.shutdown( self )

Shutdown implementation for the variable plugin.

@note The shutdown function is called by the CTF plugin manager upon completion of a test run.

@note The shutdown function can be exposed to test scripts by adding it to the command map.

## Index

- `__del__`
  - `lib::script_manager::ScriptManager`, 83
- `__init__`
  - `lib::args_validation::ArgsValidation`, 32
  - `lib::exceptions::CtfConditionError`, 64
  - `lib::exceptions::CtfParameterError`, 65
  - `lib::exceptions::CtfTestError`, 65
  - `lib::ftp_interface::FtpInterface`, 69
  - `lib::plugin_manager::Plugin`, 77
  - `lib::plugin_manager::PluginManager`, 78
  - `lib::readers::json_script_reader::JSONScriptReader`, 74
  - `lib::script_manager::ScriptManagerConfig`, 84
  - `lib::status_manager::StatusManager`, 92
  - `lib::test::Test`, 95
  - `lib::test_script::TestScript`, 97
  - `lib::time_interface::TimeInterface`, 98
  - `plugins::ccsds_plugin::ccsds_primary_header::CcsdsPrimaryHeaderBase`, 41
  - `plugins::ccsds_plugin::cfe::ccsds_secondary_header::CcsdsSecondaryCmdHeader`, 42
  - `plugins::ccsds_plugin::cfe::ccsds_v2::ccsds_v2::CcsdsV2ExtendedHeader`, 46
  - `plugins::cfs::cfs_config::CfsConfig`, 49
  - `plugins::cfs::cfs_config::RemoteCfsConfig`, 80
  - `plugins::cfs::cfs_plugin::CfsPlugin`, 57
  - `plugins::cfs::cfs_time_manager::CfsTimeManager`, 58
  - `plugins::cfs::pycfs::cfs_controllers::CfsController`, 51
  - `plugins::cfs::pycfs::cfs_controllers::RemoteCfsController`, 80
  - `plugins::cfs::pycfs::cfs_interface::CfsInterface`, 54
  - `plugins::cfs::pycfs::cfs_interface::TelemetryVerification`, 94
  - `plugins::cfs::pycfs::command_interface::CommandInterface`, 60
  - `plugins::cfs::pycfs::local_cfs_interface::LocalCfsInterface`, 75
  - `plugins::cfs::pycfs::output_app_interface::OutputManager`, 76
  - `plugins::cfs::pycfs::output_app_interface::ToApi`, 100
  - `plugins::cfs::pycfs::remote_cfs_interface::RemoteCfsInterface`, 81
  - `plugins::cfs::pycfs::tlm_listener::TlmListener`, 99
  - `plugins::control_flow_plugin::control_flow_plugin::ControlFlowPlugin`, 62
  - `plugins::example_plugin::example_plugin::ExamplePlugin`, 67
  - `plugins::ssh::ssh_plugin::SshConfig`, 84
  - `plugins::ssh::ssh_plugin::SshController`, 85
  - `plugins::ssh::ssh_plugin::SshPlugin`, 87
  - `plugins::userio_plugin::userio_plugin::UserIOPlugin`, 102
  - `plugins::validation_plugin::validation_plugin::ValidationPlugin`, 103
  - `plugins::variable_plugin::variable_plugin::VariablePlugin`, 105
- `_build_data_type_and_field`
  - `plugins::ccsds_plugin::readers::ccdd_export_reader::CCDDExportReader`, 35
- `_create_parameterized_type`
  - `plugins::ccsds_plugin::readers::ccdd_export_reader::CCDDExportReader`, 35
- `_fields_`
  - `plugins::ccsds_plugin::ccsds_primary_header::CcsdsPrimaryHeaderBase`, 41
  - `plugins::ccsds_plugin::cfe::ccsds_secondary_header::CcsdsSecondaryCmdHeader`, 42
  - `plugins::ccsds_plugin::cfe::ccsds_secondary_header::CcsdsSecondaryTlmHeader`, 43
  - `plugins::ccsds_plugin::cfe::ccsds_v1::ccsds_v1::CcsdsV1CmdPacket`, 43
  - `plugins::ccsds_plugin::cfe::ccsds_v1::ccsds_v1::CcsdsV1Packet`, 44
  - `plugins::ccsds_plugin::cfe::ccsds_v1::ccsds_v1::CcsdsV1TlmPacket`, 45
  - `plugins::ccsds_plugin::cfe::ccsds_v2::ccsds_v2::CcsdsV2CmdPacket`, 45
  - `plugins::ccsds_plugin::cfe::ccsds_v2::ccsds_v2::CcsdsV2ExtendedHeader`, 46
  - `plugins::ccsds_plugin::cfe::ccsds_v2::ccsds_v2::CcsdsV2Packet`, 47
  - `plugins::ccsds_plugin::cfe::ccsds_v2::ccsds_v2::CcsdsV2TlmPacket`, 48
- `add_cmd_msg`
  - `plugins::ccsds_plugin::ccsds_interface::CCSDSInterface`, 38
- `add_enumeration`
  - `plugins::ccsds_plugin::ccsds_interface::CCSDSInterface`, 38
- `add_error`
  - `lib::args_validation::ArgsValidation`, 32
- `add_script`
  - `lib::script_manager::ScriptManager`, 83
- `add_script_file`
  - `lib::script_manager::ScriptManager`, 83
- `add_telem_msg`
  - `plugins::ccsds_plugin::ccsds_interface::CCSDSInterface`, 38
- `add_tlm_condition`
  - `plugins::cfs::pycfs::cfs_interface::CfsInterface`, 54

archive\_cfs\_files  
     plugins::cfs::pycfs::cfs\_controllers::CfsController, 51  
     plugins::cfs::pycfs::cfs\_controllers::RemoteCfs-  
         Controller, 81

begin\_loop  
     plugins::control\_flow\_plugin::control\_flow\_plugin::-  
         ControlFlowPlugin, 63

blank\_status\_msg  
     lib::status\_manager::StatusManager, 92

build\_cfs  
     plugins::cfs::pycfs::cfs\_controllers::CfsController, 51  
     plugins::cfs::pycfs::cfs\_interface::CfsInterface, 54  
     plugins::cfs::pycfs::local\_cfs\_interface::LocalCfs-  
         Interface, 75  
     plugins::cfs::pycfs::remote\_cfs\_interface::Remote-  
         CfsInterface, 82

CTF\_log\_dir  
     lib::ctf\_global::Global, 71

CTF\_log\_dir\_file  
     lib::ctf\_global::Global, 71

change\_log\_file  
     lib::logger, 28

check\_event  
     plugins::cfs::pycfs::cfs\_controllers::CfsController, 51

check\_output  
     plugins::ssh::ssh\_plugin::SshController, 85  
     plugins::ssh::ssh\_plugin::SshPlugin, 87

check\_strings  
     plugins::cfs::pycfs::cfs\_interface::CfsInterface, 55

check\_tlm\_conditions  
     plugins::cfs::pycfs::cfs\_interface::CfsInterface, 55

check\_tlm\_continuous  
     plugins::cfs::pycfs::cfs\_controllers::CfsController, 51

check\_tlm\_packet  
     plugins::cfs::pycfs::cfs\_interface::CfsInterface, 55

check\_tlm\_value  
     plugins::cfs::pycfs::cfs\_controllers::CfsController, 52  
     plugins::cfs::pycfs::cfs\_interface::CfsInterface, 55

check\_value  
     plugins::cfs::pycfs::cfs\_interface::CfsInterface, 55

cleanup  
     plugins::cfs::pycfs::command\_interface::Command-  
         Interface, 61  
     plugins::cfs::pycfs::tlm\_listener::TlmListener, 100

clear\_received\_msgs\_before\_verification\_start  
     plugins::cfs::pycfs::cfs\_interface::CfsInterface, 55

command\_map  
     lib::plugin\_manager::Plugin, 78

configure  
     plugins::cfs::cfs\_config::CfsConfig, 49

connect\_ftp  
     lib::ftp\_interface::FtpInterface, 69

control\_flow\_conditional\_goto  
     plugins::control\_flow\_plugin::control\_flow\_plugin::-  
         ControlFlowPlugin, 63

control\_flow\_goto  
     plugins::control\_flow\_plugin::control\_flow\_plugin::-  
         ControlFlowPlugin, 63

convert\_args\_to\_ctypes  
     plugins::cfs::pycfs::cfs\_controllers::CfsController, 52

convert\_check\_tlm\_args  
     plugins::cfs::pycfs::cfs\_controllers::CfsController, 52

convert\_timestamp  
     plugins::validation\_plugin::validation\_plugin::Validation-  
         Plugin, 103

create\_arg\_parser  
     lib::ctf\_global::Global, 71

create\_plugin\_info  
     lib::plugin\_manager::PluginManager, 78

create\_socket  
     plugins::cfs::pycfs::tlm\_listener::TlmListener, 100

current\_instruction\_index  
     lib::ctf\_global::Global, 72

current\_script\_log\_dir  
     lib::ctf\_global::Global, 72

current\_verification\_stage  
     lib::ctf\_global::Global, 72

disable\_output  
     plugins::cfs::pycfs::output\_app\_interface::Output-  
         Manager, 76  
     plugins::cfs::pycfs::output\_app\_interface::ToApi, 101

disconnect\_ftp  
     lib::ftp\_interface::FtpInterface, 69

download\_ftp  
     lib::ftp\_interface::FtpInterface, 69  
     plugins::ssh::ssh\_plugin::SshController, 85  
     plugins::ssh::ssh\_plugin::SshPlugin, 88

download\_ftputil  
     lib::ftp\_interface::FtpInterface, 69

else\_condition  
     plugins::control\_flow\_plugin::control\_flow\_plugin::-  
         ControlFlowPlugin, 63

enable\_cfs\_output  
     plugins::cfs::pycfs::cfs\_controllers::CfsController, 52

enable\_output  
     plugins::cfs::pycfs::cfs\_interface::CfsInterface, 55  
     plugins::cfs::pycfs::output\_app\_interface::Output-  
         Manager, 76  
     plugins::cfs::pycfs::output\_app\_interface::ToApi, 101

end\_command  
     lib::status\_manager::StatusManager, 92

end\_condition  
     plugins::control\_flow\_plugin::control\_flow\_plugin::-  
         ControlFlowPlugin, 63

end\_loop

plugins::control\_flow\_plugin::control\_flow\_plugin::-  
     ControlFlowPlugin, 63  
 end\_script  
     lib::status\_manager::StatusManager, 92  
 end\_test  
     lib::status\_manager::StatusManager, 92  
 example\_counter  
     plugins::example\_plugin::example\_plugin::Example-  
         Plugin, 68  
 execute\_instruction  
     lib::test::Test, 95  
 execute\_verification  
     lib::test::Test, 95  
 expand\_path  
     lib::ctf\_utility, 25  
  
 field\_class\_by\_name  
     plugins::cfs::pycfs::cfs\_controllers::CfsController, 52  
 finalize\_suite\_status  
     lib::status\_manager::StatusManager, 93  
 find\_plugin\_for\_command  
     lib::plugin\_manager::PluginManager, 79  
 find\_plugin\_for\_command\_and\_execute  
     lib::plugin\_manager::PluginManager, 79  
  
 generate\_test\_results  
     lib::test\_script::TestScript, 97  
 get\_ccsds\_messages\_from\_dir  
     plugins::ccsds\_plugin::ccsds\_interface::CCSDS-  
         Interface, 38  
     plugins::ccsds\_plugin::readers::ccdd\_export\_reader-  
         ::CCDDExportReader, 35  
 get\_cfs\_plugin  
     plugins::ccsds\_plugin::ccsds\_plugin::CCSDSPlugin,  
         40  
 get\_checksum  
     plugins::ccsds\_plugin::cfe::ccsds\_secondary\_-  
         header::CcldsSecondaryCmdHeader, 42  
 get\_current\_instruction\_index  
     lib::ctf\_utility, 25  
 get\_error\_count  
     lib::args\_validation::ArgsValidation, 32  
     plugins::cfs::cfs\_config::CfsConfig, 49  
 get\_file  
     plugins::ssh::ssh\_plugin::SshController, 85  
     plugins::ssh::ssh\_plugin::SshPlugin, 88  
 get\_file\_ftp  
     lib::ftp\_interface::FtpInterface, 69  
 get\_function\_code  
     plugins::ccsds\_plugin::ccsds\_packet\_interface::-  
         CcldsPacketInterface, 39  
     plugins::ccsds\_plugin::cfe::ccsds\_secondary\_-  
         header::CcldsSecondaryCmdHeader, 42  
     plugins::ccsds\_plugin::cfe::ccsds\_v1::ccsds\_v1::-  
         CcldsV1CmdPacket, 43  
  
 get\_last\_pid  
     plugins::ssh::ssh\_plugin::SshController, 85  
 get\_msg\_id  
     plugins::ccsds\_plugin::ccsds\_packet\_interface::-  
         CcldsPacketInterface, 39  
     plugins::ccsds\_plugin::ccsds\_primary\_header::-  
         CcldsPrimaryHeaderBase, 41  
     plugins::ccsds\_plugin::cfe::ccsds\_v1::ccsds\_v1::-  
         CcldsV1Packet, 44  
     plugins::ccsds\_plugin::cfe::ccsds\_v2::ccsds\_v2::-  
         CcldsV2Packet, 47  
 get\_port  
     plugins::cfs::pycfs::tlm\_listener::TlmListener, 100  
 get\_start\_string  
     plugins::cfs::pycfs::local\_cfs\_interface::LocalCfs-  
         Interface, 75  
     plugins::cfs::pycfs::remote\_cfs\_interface::Remote-  
         CfsInterface, 82  
 get\_time\_manager  
     lib::ctf\_global::Global, 71  
 get\_variable  
     lib::ctf\_utility, 26  
 goto\_instruction\_index  
     lib::ctf\_global::Global, 72  
  
 handle\_test\_exception\_during\_wait  
     plugins::cfs::cfs\_time\_manager::CfsTimeManager,  
         59  
 has\_secondary\_header  
     plugins::ccsds\_plugin::ccsds\_packet\_interface::-  
         CcldsPacketInterface, 39  
     plugins::ccsds\_plugin::cfe::ccsds\_v1::ccsds\_v1::-  
         CcldsV1Packet, 44  
  
 if\_condition  
     plugins::control\_flow\_plugin::control\_flow\_plugin::-  
         ControlFlowPlugin, 63  
 increment\_error\_count  
     lib::args\_validation::ArgsValidation, 32  
 init\_connection  
     plugins::ssh::ssh\_plugin::SshController, 85  
     plugins::ssh::ssh\_plugin::SshPlugin, 88  
 init\_logger  
     lib::logger, 28  
 init\_socket  
     plugins::cfs::pycfs::command\_interface::Command-  
         Interface, 61  
 initialize  
     lib::plugin\_manager::Plugin, 77  
     plugins::cfs::cfs\_plugin::CfsPlugin, 58  
     plugins::cfs::pycfs::cfs\_controllers::CfsController, 52  
     plugins::cfs::pycfs::cfs\_controllers::RemoteCfs-  
         Controller, 81  
     plugins::control\_flow\_plugin::control\_flow\_plugin::-  
         ControlFlowPlugin, 64

plugins::example\_plugin::example\_plugin::Example-  
     Plugin, 67  
 plugins::ssh::ssh\_plugin::SshPlugin, 89  
 plugins::userio\_plugin::userio\_plugin::UserIOPlugin,  
     102  
 plugins::validation\_plugin::validation\_plugin::Validation-  
     Plugin, 103  
 plugins::variable\_plugin::variable\_plugin::Variable-  
     Plugin, 105  
 initialize\_plugins  
     lib::plugin\_manager::PluginManager, 79  
 interpret\_binary\_data  
     plugins::validation\_plugin::validation\_plugin::Validation-  
         Plugin, 103  
 is\_command  
     plugins::ccsds\_plugin::ccsds\_primary\_header::-  
         CcsdsPrimaryHeaderBase, 41  
 is\_command\_msg  
     plugins::ccsds\_plugin::readers::ccdd\_export\_reader-  
         ::CCDDExporter, 35  
 is\_command\_tlm  
     plugins::ccsds\_plugin::readers::ccdd\_export\_reader-  
         ::CCDDExporter, 36  
 is\_custom\_types  
     plugins::ccsds\_plugin::readers::ccdd\_export\_reader-  
         ::CCDDExporter, 36  
 is\_param\_none  
     lib::args\_validation::ArgsValidation, 33  
 is\_telemetry\_msg  
     plugins::ccsds\_plugin::readers::ccdd\_export\_reader-  
         ::CCDDExporter, 36  
 is\_types\_macros  
     plugins::ccsds\_plugin::readers::ccdd\_export\_reader-  
         ::CCDDExporter, 36  
 lib, 24  
 lib.args\_validation, 24  
 lib.args\_validation.ArgsValidation, 32  
 lib.ctf\_global, 25  
 lib.ctf\_global.CtfVerificationStage, 66  
 lib.ctf\_global.Global, 70  
 lib.ctf\_utility, 25  
 lib.event\_types, 26  
 lib.event\_types.Instruction, 72  
 lib.exceptions, 27  
 lib.exceptions.CtfConditionError, 64  
 lib.exceptions.CtfParameterError, 65  
 lib.exceptions.CtfTestError, 65  
 lib.ftp\_interface, 27  
 lib.ftp\_interface.FtpInterface, 68  
 lib.logger, 27  
 lib.logger.CtfLogLevel, 64  
 lib.logger.TestFormatter, 96  
 lib.plugin\_manager, 28  
 lib.plugin\_manager.ArgTypes, 34  
 lib.plugin\_manager.Plugin, 76  
 lib.plugin\_manager.PluginManager, 78  
 lib.readers, 28  
 lib.readers.json\_script\_reader, 29  
 lib.readers.json\_script\_reader.JSONScriptReader, 73  
 lib.script\_manager, 29  
 lib.script\_manager.ScriptManager, 82  
 lib.script\_manager.ScriptManagerConfig, 83  
 lib.status, 29  
 lib.status.ObjectFactory, 75  
 lib.status.StatusDefs, 91  
 lib.status\_manager, 29  
 lib.status\_manager.StatusManager, 91  
 lib.test, 30  
 lib.test.Test, 94  
 lib.test\_script, 30  
 lib.test\_script.TestScript, 96  
 lib.time\_interface, 30  
 lib.time\_interface.TimeInterface, 98  
 lib::args\_validation::ArgsValidation  
     \_\_init\_\_, 32  
     add\_error, 32  
     get\_error\_count, 32  
     increment\_error\_count, 32  
     is\_param\_none, 33  
     validate\_boolean, 33  
     validate\_directory, 33  
     validate\_file, 33  
     validate\_int, 33  
     validate\_ip, 33  
     validate\_number, 33  
     validate\_symbol, 33  
     verify\_symbol, 33  
 lib::ctf\_global::Global  
     CTF\_log\_dir, 71  
     CTF\_log\_dir\_file, 71  
     create\_arg\_parser, 71  
     current\_instruction\_index, 72  
     current\_script\_log\_dir, 72  
     current\_verification\_stage, 72  
     get\_time\_manager, 71  
     goto\_instruction\_index, 72  
     load\_config, 71  
     plugin\_manager, 72  
     plugins\_available, 72  
     set\_time\_manager, 71  
     time\_manager, 72  
     variable\_store, 72  
 lib::ctf\_utility  
     expand\_path, 25  
     get\_current\_instruction\_index, 25  
     get\_variable, 26  
     operator\_map, 26

---

```

    resolve_variable, 26
    rgetattr, 26
    set_goto_instruction_index, 26
    set_variable, 26
    switch_to_cft_directory, 26
lib::exceptions::CtfConditionError
    __init__, 64
lib::exceptions::CtfParameterError
    __init__, 65
lib::exceptions::CtfTestError
    __init__, 65
lib::ftp_interface::FtpInterface
    __init__, 69
    connect_ftp, 69
    disconnect_ftp, 69
    download_ftp, 69
    download_ftputil, 69
    get_file_ftp, 69
    store_file_ftp, 69
    upload_ftp, 69
    upload_ftputil, 70
lib::logger
    change_log_file, 28
    init_logger, 28
    set_logger_options_from_config, 28
    test, 28
lib::plugin_manager::Plugin
    __init__, 77
    command_map, 78
    initialize, 77
    process_command, 77
    shutdown, 77
lib::plugin_manager::PluginManager
    __init__, 78
    create_plugin_info, 78
    find_plugin_for_command, 79
    find_plugin_for_command_and_execute, 79
    initialize_plugins, 79
    reload_plugins, 79
    shutdown_plugins, 79
    walk_package, 79
lib::readers::json_script_reader::JSONScriptReader
    process_functions, 74
    process_header, 74
    process_tests, 74
    resolve_function, 74
    sanitize_args, 74
lib::script_manager::ScriptManager
    __del__, 83
    add_script, 83
    add_script_file, 83
    prep_logging, 83
    run_all_scripts, 83
    write_summary_line, 83
lib::script_manager::ScriptManagerConfig
    __init__, 84
lib::status_manager::StatusManager
    __init__, 92
    blank_status_msg, 92
    end_command, 92
    end_script, 92
    end_test, 92
    finalize_suite_status, 93
    sanitize_data, 93
    sanitize_param, 93
    sanitize_status, 93
    send_update, 93
    set_scripts, 93
    start, 93
    update_command_status, 93
    update_script_status, 93
    update_suite_status, 93
    update_test_status, 93
lib::test::Test
    __init__, 95
    execute_instruction, 95
    execute_verification, 95
    process_command_delay, 95
    process_conditional_branch_label, 95
    process_control_flow_label, 95
    process_verification_delay, 95
    run_commands, 96
    run_test, 96
lib::test_script::TestScript
    __init__, 97
    generate_test_results, 97
    log_test_header, 97
    run_script, 97
    set_header_info, 97
    set_options, 97
    set_tests, 97
    set_watch_lists, 98
lib::time_interface::TimeInterface
    __init__, 98
    post_command, 98
    pre_command, 98
    time_since_last_command, 99
    wait, 99
    wait_seconds, 99
load_config
    lib::cft_global::Global, 71
load_config_data
    plugins::cfs::cfs_config::CfsConfig, 49
    plugins::cfs::cfs_config::RemoteCfsConfig, 80
load_field
    plugins::cfs::cfs_config::CfsConfig, 49
log_invalid_packet
    plugins::cfs::pycfs::cfs_interface::CfsInterface, 55

```

log\_test\_header  
     lib::test\_script::TestScript, 97  
 log\_unknown\_packet\_mid  
     plugins::cfs::pycfs::cfs\_interface::CfsInterface, 55  
  
 operator\_map  
     lib::ctf\_utility, 26  
  
 parse\_command\_packet  
     plugins::cfs::pycfs::cfs\_interface::CfsInterface, 55  
 parse\_telemetry\_packet  
     plugins::cfs::pycfs::cfs\_interface::CfsInterface, 55  
 plugin\_manager  
     lib::ctf\_global::Global, 72  
 plugins.ccsds\_plugin.ccsds\_interface.CCSDSInterface, 37  
 plugins.ccsds\_plugin.ccsds\_packet\_interface.Ccsds-  
     PacketInterface, 38  
 plugins.ccsds\_plugin.ccsds\_packet\_interface.Ccsds-  
     PacketType, 39  
 plugins.ccsds\_plugin.ccsds\_packet\_interface.CcsdsVer,  
     48  
 plugins.ccsds\_plugin.ccsds\_plugin.CCSDSPlugin, 39  
 plugins.ccsds\_plugin.ccsds\_primary\_header.Ccsds-  
     PrimaryHeaderBase, 40  
 plugins.ccsds\_plugin.cfe.ccsds\_secondary\_header.-  
     CcsdsSecondaryCmdHeader, 41  
 plugins.ccsds\_plugin.cfe.ccsds\_secondary\_header.-  
     CcsdsSecondaryTlmHeader, 42  
 plugins.ccsds\_plugin.cfe.ccsds\_v1.ccsds\_v1.CcsdsV1-  
     CmdPacket, 43  
 plugins.ccsds\_plugin.cfe.ccsds\_v1.ccsds\_v1.CcsdsV1-  
     Packet, 43  
 plugins.ccsds\_plugin.cfe.ccsds\_v1.ccsds\_v1.CcsdsV1-  
     PrimaryHeader, 44  
 plugins.ccsds\_plugin.cfe.ccsds\_v1.ccsds\_v1.CcsdsV1-  
     TlmPacket, 44  
 plugins.ccsds\_plugin.cfe.ccsds\_v2.ccsds\_v2.CcsdsV2-  
     CmdPacket, 45  
 plugins.ccsds\_plugin.cfe.ccsds\_v2.ccsds\_v2.CcsdsV2-  
     ExtendedHeader, 45  
 plugins.ccsds\_plugin.cfe.ccsds\_v2.ccsds\_v2.CcsdsV2-  
     Packet, 46  
 plugins.ccsds\_plugin.cfe.ccsds\_v2.ccsds\_v2.CcsdsV2-  
     PrimaryHeader, 47  
 plugins.ccsds\_plugin.cfe.ccsds\_v2.ccsds\_v2.CcsdsV2-  
     TlmPacket, 47  
 plugins.ccsds\_plugin.readers.ccdd\_export\_reader.CCDD-  
     ExportReader, 34  
 plugins.ccsds\_plugin.readers.command\_builder.Command-  
     Arg, 59  
 plugins.ccsds\_plugin.readers.command\_builder.Command-  
     Code, 59  
 plugins.ccsds\_plugin.readers.command\_builder.Command-  
     Message, 61  
 plugins.cfs.cfs\_config, 30  
 plugins.cfs.cfs\_config.CfsConfig, 48  
 plugins.cfs.cfs\_config.RemoteCfsConfig, 79  
 plugins.cfs.cfs\_plugin.CfsPlugin, 56  
 plugins.cfs.cfs\_time\_manager.CfsTimeManager, 58  
 plugins.cfs.pycfs.cfs\_controllers.CfsController, 50  
 plugins.cfs.pycfs.cfs\_controllers.RemoteCfsController, 80  
 plugins.cfs.pycfs.cfs\_interface.CfsInterface, 53  
 plugins.cfs.pycfs.cfs\_interface.TelemetryVerification, 94  
 plugins.cfs.pycfs.command\_interface.CommandInterface,  
     60  
 plugins.cfs.pycfs.local\_cfs\_interface.LocalCfsInterface, 74  
 plugins.cfs.pycfs.output\_app\_interface.OutputManager,  
     76  
 plugins.cfs.pycfs.output\_app\_interface.ToApi, 100  
 plugins.cfs.pycfs.remote\_cfs\_interface.RemoteCfs-  
     Interface, 81  
 plugins.cfs.pycfs.tlm\_listener.TlmListener, 99  
 plugins.control\_flow\_plugin.control\_flow\_plugin, 31  
 plugins.control\_flow\_plugin.control\_flow\_plugin.Control-  
     FlowPlugin, 61  
 plugins.example\_plugin.example\_plugin, 31  
 plugins.example\_plugin.example\_plugin.ExamplePlugin,  
     66  
 plugins.ssh.ssh\_plugin, 31  
 plugins.ssh.ssh\_plugin.SshConfig, 84  
 plugins.ssh.ssh\_plugin.SshController, 84  
 plugins.ssh.ssh\_plugin.SshPlugin, 86  
 plugins.userio\_plugin.userio\_plugin.UserIOPlugin, 101  
 plugins.validation\_plugin.validation\_plugin.Validation-  
     Plugin, 102  
 plugins.variable\_plugin.variable\_plugin, 31  
 plugins.variable\_plugin.variable\_plugin.VariablePlugin,  
     104  
 plugins::ccsds\_plugin::ccsds\_interface::CCSDSInterface  
     add\_cmd\_msg, 38  
     add\_enumeration, 38  
     add\_telem\_msg, 38  
 plugins::ccsds\_plugin::ccsds\_packet\_interface::Ccsds-  
     PacketInterface  
     get\_function\_code, 39  
     get\_msg\_id, 39  
     has\_secondary\_header, 39  
 plugins::ccsds\_plugin::ccsds\_plugin::CCSDSPlugin  
     get\_cfs\_plugin, 40  
     validate\_cfs\_ccsds\_data, 40  
 plugins::ccsds\_plugin::ccsds\_primary\_header::Ccsds-  
     PrimaryHeaderBase  
     \_fields\_, 41  
     get\_msg\_id, 41  
     is\_command, 41  
 plugins::ccsds\_plugin::cfe::ccsds\_secondary\_header::-  
     CcsdsSecondaryCmdHeader  
     \_fields\_, 42  
     get\_checksum, 42



get\_function\_code, 42  
 plugins::ccsds\_plugin::cfe::ccsds\_secondary\_header::-  
     CcsdsSecondaryTlmHeader  
     \_fields\_, 43  
 plugins::ccsds\_plugin::cfe::ccsds\_v1::ccsds\_v1::Ccsds-  
     V1CmdPacket  
     \_fields\_, 43  
 plugins::ccsds\_plugin::cfe::ccsds\_v1::ccsds\_v1::Ccsds-  
     V1Packet  
     \_fields\_, 44  
     get\_msg\_id, 44  
     has\_secondary\_header, 44  
 plugins::ccsds\_plugin::cfe::ccsds\_v1::ccsds\_v1::Ccsds-  
     V1TlmPacket  
     \_fields\_, 45  
 plugins::ccsds\_plugin::cfe::ccsds\_v2::ccsds\_v2::Ccsds-  
     V2CmdPacket  
     \_fields\_, 45  
 plugins::ccsds\_plugin::cfe::ccsds\_v2::ccsds\_v2::Ccsds-  
     V2ExtendedHeader  
     \_fields\_, 46  
 plugins::ccsds\_plugin::cfe::ccsds\_v2::ccsds\_v2::Ccsds-  
     V2Packet  
     \_fields\_, 47  
     get\_msg\_id, 47  
 plugins::ccsds\_plugin::cfe::ccsds\_v2::ccsds\_v2::Ccsds-  
     V2TlmPacket  
     \_fields\_, 48  
 plugins::ccsds\_plugin::readers::ccdd\_export\_reader::CC-  
     DDExportReader  
     process\_command, 36  
     process\_telemetry, 36  
     process\_types, 37  
 plugins::cfs::cfs\_config::CfsConfig  
     \_\_init\_\_, 49  
     configure, 49  
     get\_error\_count, 49  
     load\_config\_data, 49  
     load\_field, 49  
     set\_cfs\_run\_cmd, 50  
     set\_ctf\_ip, 50  
 plugins::cfs::cfs\_config::RemoteCfsConfig  
     \_\_init\_\_, 80  
     load\_config\_data, 80  
 plugins::cfs::cfs\_plugin::CfsPlugin  
     \_\_init\_\_, 57  
     initialize, 58  
     shutdown, 58  
 plugins::cfs::cfs\_time\_manager::CfsTimeManager  
     \_\_init\_\_, 58  
     handle\_test\_exception\_during\_wait, 59  
     pre\_command, 59  
     run\_continuous\_verifications, 59  
     wait, 59  
 plugins::cfs::pycfs::cfs\_controllers::CfsController  
     \_\_init\_\_, 51  
     archive\_cfs\_files, 51  
     build\_cfs, 51  
     check\_event, 51  
     check\_tlm\_continuous, 51  
     check\_tlm\_value, 52  
     convert\_args\_to\_ctypes, 52  
     convert\_check\_tlm\_args, 52  
     enable\_cfs\_output, 52  
     field\_class\_by\_name, 52  
     initialize, 52  
     process\_ccsds\_files, 52  
     remove\_check\_tlm\_continuous, 52  
     resolve\_args\_from\_dict, 52  
     resolve\_macros, 52  
     resolve\_simple\_type, 52  
     shutdown, 53  
     shutdown\_cfs, 53  
     start\_cfs, 53  
     validate\_cc\_value, 53  
     validate\_mid\_value, 53  
 plugins::cfs::pycfs::cfs\_controllers::RemoteCfsController  
     \_\_init\_\_, 80  
     archive\_cfs\_files, 81  
     initialize, 81  
     shutdown, 81  
     shutdown\_cfs, 81  
 plugins::cfs::pycfs::cfs\_interface::CfsInterface  
     \_\_init\_\_, 54  
     add\_tlm\_condition, 54  
     build\_cfs, 54  
     check\_strings, 55  
     check\_tlm\_conditions, 55  
     check\_tlm\_packet, 55  
     check\_tlm\_value, 55  
     check\_value, 55  
     clear\_received\_msgs\_before\_verification\_start, 55  
     enable\_output, 55  
     log\_invalid\_packet, 55  
     log\_unknown\_packet\_mid, 55  
     parse\_command\_packet, 55  
     parse\_telemetry\_packet, 55  
     read\_sb\_packets, 55  
     remove\_tlm\_condition, 56  
     send\_command, 56  
     start\_cfs, 56  
     stop\_cfs, 56  
     write\_evs\_log, 56  
     write\_tlm\_log, 56  
 plugins::cfs::pycfs::cfs\_interface::TelemetryVerification  
     \_\_init\_\_, 94  
 plugins::cfs::pycfs::command\_interface::Command-  
     Interface



---

```

    __init__, 60
    cleanup, 61
    init_socket, 61
    send_command, 61
plugins::cfs::pycfs::local_cfs_interface::LocalCfsInterface
    __init__, 75
    build_cfs, 75
    get_start_string, 75
    start_cfs, 75
plugins::cfs::pycfs::output_app_interface::OutputManager
    __init__, 76
    disable_output, 76
    enable_output, 76
plugins::cfs::pycfs::output_app_interface::ToApi
    __init__, 100
    disable_output, 101
    enable_output, 101
plugins::cfs::pycfs::remote_cfs_interface::RemoteCfs-
    Interface
    __init__, 81
    build_cfs, 82
    get_start_string, 82
    start_cfs, 82
plugins::cfs::pycfs::tlm_listener::TlmListener
    __init__, 99
    cleanup, 100
    create_socket, 100
    get_port, 100
    read_socket, 100
plugins::control_flow_plugin::control_flow_plugin::Control-
    FlowPlugin
    begin_loop, 63
    control_flow_goto, 63
    else_condition, 63
    end_condition, 63
    end_loop, 63
    if_condition, 63
    initialize, 64
    shutdown, 64
plugins::example_plugin::example_plugin::ExamplePlugin
    __init__, 67
    example_counter, 68
    initialize, 67
    shutdown, 67
    test_command, 67
    test_shared_library, 67
    test_verify_command, 68
plugins::ssh::ssh_plugin::SshConfig
    __init__, 84
plugins::ssh::ssh_plugin::SshController
    __init__, 85
    check_output, 85
    download_ftp, 85
    get_file, 85
    get_last_pid, 85
    init_connection, 85
    put_file, 85
    rsync, 86
    run_command, 86
    run_command_local, 86
    run_command_persistent, 86
    shutdown, 86
    upload_ftp, 86
plugins::ssh::ssh_plugin::SshPlugin
    __init__, 87
    check_output, 87
    download_ftp, 88
    get_file, 88
    init_connection, 88
    initialize, 89
    put_file, 89
    register_target, 89
    run_command, 90
    run_command_local, 90
    shutdown, 90
    upload_ftp, 90
plugins::userio_plugin::userio_plugin::UserIOPlugin
    __init__, 102
    initialize, 102
    shutdown, 102
    waituserinput_command, 102
plugins::validation_plugin::validation_plugin::Validation-
    Plugin
    __init__, 103
    convert_timestamp, 103
    initialize, 103
    interpret_binary_data, 103
    shutdown, 104
plugins::variable_plugin::variable_plugin::VariablePlugin
    __init__, 105
    initialize, 105
    shutdown, 105
plugins_available
    lib::ctf_global::Global, 72
post_command
    lib::time_interface::TimeInterface, 98
pre_command
    lib::time_interface::TimeInterface, 98
    plugins::cfs::cfs_time_manager::CfsTimeManager,
        59
prep_logging
    lib::script_manager::ScriptManager, 83
process_ccsds_files
    plugins::cfs::pycfs::cfs_controllers::CfsController, 52
process_ccsds_json_file
    plugins::ccsds_plugin::readers::ccdd_export_reader-
        ::CCDDExportReader, 36
process_command

```

lib::plugin\_manager::Plugin, 77  
 plugins::ccsds\_plugin::readers::ccdd\_export\_reader-  
   ::CCDDExporter, 36  
 process\_command\_delay  
   lib::test::Test, 95  
 process\_conditional\_branch\_label  
   lib::test::Test, 95  
 process\_control\_flow\_label  
   lib::test::Test, 95  
 process\_custom\_types  
   plugins::ccsds\_plugin::readers::ccdd\_export\_reader-  
   ::CCDDExporter, 36  
 process\_functions  
   lib::readers::json\_script\_reader::JSONScriptReader,  
   74  
 process\_header  
   lib::readers::json\_script\_reader::JSONScriptReader,  
   74  
 process\_telemetry  
   plugins::ccsds\_plugin::readers::ccdd\_export\_reader-  
   ::CCDDExporter, 36  
 process\_tests  
   lib::readers::json\_script\_reader::JSONScriptReader,  
   74  
 process\_types  
   plugins::ccsds\_plugin::readers::ccdd\_export\_reader-  
   ::CCDDExporter, 37  
 process\_types\_second\_pass  
   plugins::ccsds\_plugin::readers::ccdd\_export\_reader-  
   ::CCDDExporter, 37  
 process\_verification\_delay  
   lib::test::Test, 95  
 put\_file  
   plugins::ssh::ssh\_plugin::SshController, 85  
   plugins::ssh::ssh\_plugin::SshPlugin, 89  
 read\_sb\_packets  
   plugins::cfs::pycfs::cfs\_interface::CfsInterface, 55  
 read\_socket  
   plugins::cfs::pycfs::tlm\_listener::TlmListener, 100  
 register\_target  
   plugins::ssh::ssh\_plugin::SshPlugin, 89  
 reload\_plugins  
   lib::plugin\_manager::PluginManager, 79  
 remove\_check\_tlm\_continuous  
   plugins::cfs::pycfs::cfs\_controllers::CfsController, 52  
 remove\_tlm\_condition  
   plugins::cfs::pycfs::cfs\_interface::CfsInterface, 56  
 resolve\_args\_from\_dict  
   plugins::cfs::pycfs::cfs\_controllers::CfsController, 52  
 resolve\_function  
   lib::readers::json\_script\_reader::JSONScriptReader,  
   74  
 resolve\_macros  
   plugins::cfs::pycfs::cfs\_controllers::CfsController, 52  
 resolve\_simple\_type  
   plugins::cfs::pycfs::cfs\_controllers::CfsController, 52  
 resolve\_variable  
   lib::ctf\_utility, 26  
 rgetattr  
   lib::ctf\_utility, 26  
 rsync  
   plugins::ssh::ssh\_plugin::SshController, 86  
 run\_all\_scripts  
   lib::script\_manager::ScriptManager, 83  
 run\_command  
   plugins::ssh::ssh\_plugin::SshController, 86  
   plugins::ssh::ssh\_plugin::SshPlugin, 90  
 run\_command\_local  
   plugins::ssh::ssh\_plugin::SshController, 86  
   plugins::ssh::ssh\_plugin::SshPlugin, 90  
 run\_command\_persistent  
   plugins::ssh::ssh\_plugin::SshController, 86  
 run\_commands  
   lib::test::Test, 96  
 run\_continuous\_verifications  
   plugins::cfs::cfs\_time\_manager::CfsTimeManager,  
   59  
 run\_script  
   lib::test\_script::TestScript, 97  
 run\_test  
   lib::test::Test, 96  
 sanitize\_args  
   lib::readers::json\_script\_reader::JSONScriptReader,  
   74  
 sanitize\_data  
   lib::status\_manager::StatusManager, 93  
 sanitize\_param  
   lib::status\_manager::StatusManager, 93  
 sanitize\_status  
   lib::status\_manager::StatusManager, 93  
 send\_command  
   plugins::cfs::pycfs::cfs\_interface::CfsInterface, 56  
   plugins::cfs::pycfs::command\_interface::Command-  
   Interface, 61  
 send\_update  
   lib::status\_manager::StatusManager, 93  
 set\_cfs\_run\_cmd  
   plugins::cfs::cfs\_config::CfsConfig, 50  
 set\_ctf\_ip  
   plugins::cfs::cfs\_config::CfsConfig, 50  
 set\_goto\_instruction\_index  
   lib::ctf\_utility, 26  
 set\_header\_info  
   lib::test\_script::TestScript, 97  
 set\_logger\_options\_from\_config  
   lib::logger, 28

set\_options  
     lib::test\_script::TestScript, 97  
 set\_scripts  
     lib::status\_manager::StatusManager, 93  
 set\_tests  
     lib::test\_script::TestScript, 97  
 set\_time\_manager  
     lib::ctf\_global::Global, 71  
 set\_variable  
     lib::ctf\_utility, 26  
 set\_watch\_lists  
     lib::test\_script::TestScript, 98  
 shutdown  
     lib::plugin\_manager::Plugin, 77  
     plugins::cfs::cfs\_plugin::CfsPlugin, 58  
     plugins::cfs::pycfs::cfs\_controllers::CfsController, 53  
     plugins::cfs::pycfs::cfs\_controllers::RemoteCfs-  
         Controller, 81  
     plugins::control\_flow\_plugin::control\_flow\_plugin::-  
         ControlFlowPlugin, 64  
     plugins::example\_plugin::example\_plugin::Example-  
         Plugin, 67  
     plugins::ssh::ssh\_plugin::SshController, 86  
     plugins::ssh::ssh\_plugin::SshPlugin, 90  
     plugins::userio\_plugin::userio\_plugin::UserIOPlugin,  
         102  
     plugins::validation\_plugin::validation\_plugin::Validation-  
         Plugin, 104  
     plugins::variable\_plugin::variable\_plugin::Variable-  
         Plugin, 105  
 shutdown\_cfs  
     plugins::cfs::pycfs::cfs\_controllers::CfsController, 53  
     plugins::cfs::pycfs::cfs\_controllers::RemoteCfs-  
         Controller, 81  
 shutdown\_plugins  
     lib::plugin\_manager::PluginManager, 79  
 start  
     lib::status\_manager::StatusManager, 93  
 start\_cfs  
     plugins::cfs::pycfs::cfs\_controllers::CfsController, 53  
     plugins::cfs::pycfs::cfs\_interface::CfsInterface, 56  
     plugins::cfs::pycfs::local\_cfs\_interface::LocalCfs-  
         Interface, 75  
     plugins::cfs::pycfs::remote\_cfs\_interface::Remote-  
         CfsInterface, 82  
 stop\_cfs  
     plugins::cfs::pycfs::cfs\_interface::CfsInterface, 56  
 store\_file\_ftp  
     lib::ftp\_interface::FtpInterface, 69  
 switch\_to\_ctf\_directory  
     lib::ctf\_utility, 26  
 test  
     lib::logger, 28  
     test\_command  
         plugins::example\_plugin::example\_plugin::Example-  
             Plugin, 67  
     test\_shared\_library  
         plugins::example\_plugin::example\_plugin::Example-  
             Plugin, 67  
     test\_verify\_command  
         plugins::example\_plugin::example\_plugin::Example-  
             Plugin, 68  
     time\_manager  
         lib::ctf\_global::Global, 72  
     time\_since\_last\_command  
         lib::time\_interface::TimeInterface, 99  
     update\_command\_status  
         lib::status\_manager::StatusManager, 93  
     update\_script\_status  
         lib::status\_manager::StatusManager, 93  
     update\_suite\_status  
         lib::status\_manager::StatusManager, 93  
     update\_test\_status  
         lib::status\_manager::StatusManager, 93  
     upload\_ftp  
         lib::ftp\_interface::FtpInterface, 69  
         plugins::ssh::ssh\_plugin::SshController, 86  
         plugins::ssh::ssh\_plugin::SshPlugin, 90  
     upload\_ftputil  
         lib::ftp\_interface::FtpInterface, 70  
     validate\_boolean  
         lib::args\_validation::ArgsValidation, 33  
     validate\_cc\_value  
         plugins::cfs::pycfs::cfs\_controllers::CfsController, 53  
     validate\_cfs\_ccsds\_data  
         plugins::ccsds\_plugin::ccsds\_plugin::CCSDSPlugin,  
             40  
     validate\_directory  
         lib::args\_validation::ArgsValidation, 33  
     validate\_file  
         lib::args\_validation::ArgsValidation, 33  
     validate\_int  
         lib::args\_validation::ArgsValidation, 33  
     validate\_ip  
         lib::args\_validation::ArgsValidation, 33  
     validate\_json\_schema  
         plugins::ccsds\_plugin::readers::ccdd\_export\_reader-  
             ::CCDDExportReader, 37  
     validate\_mid\_value  
         plugins::cfs::pycfs::cfs\_controllers::CfsController, 53  
     validate\_number  
         lib::args\_validation::ArgsValidation, 33  
     validate\_symbol  
         lib::args\_validation::ArgsValidation, 33  
     variable\_store  
         lib::ctf\_global::Global, 72

verify\_symbol  
lib::args\_validation::ArgsValidation, [33](#)

wait  
lib::time\_interface::TimeInterface, [99](#)  
plugins::cfs::cfs\_time\_manager::CfsTimeManager,  
[59](#)

wait\_seconds  
lib::time\_interface::TimeInterface, [99](#)

waituserinput\_command  
plugins::userio\_plugin::userio\_plugin::UserIOPlugin,  
[102](#)

walk\_package  
lib::plugin\_manager::PluginManager, [79](#)

write\_evs\_log  
plugins::cfs::pycfs::cfs\_interface::CfsInterface, [56](#)

write\_summary\_line  
lib::script\_manager::ScriptManager, [83](#)

write\_tlm\_log  
plugins::cfs::pycfs::cfs\_interface::CfsInterface, [56](#)