

Single-Reduction Helical Gearbox Assembly Checklist

A. Gearbox information

Customer name

Work order number

Manufacturer

Model

Serial number

Reduction ratio (overall)

: 1

Stage 1 ratio

: 1

Oil capacity (gal / L)

Oil grade

1. Prep and inspection

☐

Work order, drawings, BOM, and assembly spec on hand at current revision

☐

Clean covered work area, lifting gear rated and inspected

☐

Housing halves cleaned and deburred, oil galleries and drain/breather ports clear, no casting sand or chips

☐

Split-line faces flat, no nicks, dowel holes undamaged

☐

Bearing bores measured (diameter and roundness) against spec:

Spec / measured:

☐

Shafts checked for journal diameters, runout, keyway and thread condition

☐

Gears inspected for tooth damage, burrs, correct hand of helix, mating sets matched by serial/match marks

☐

Bearings checked for part number, cups and cones kept as matched sets in packaging until use

☐

Seals, shims, gaskets, spacers, keys, fasteners counted against BOM

Ram Gear Manufacturing Assembly Verification Data

☐ Measuring tools calibrated (micrometers, bore gauges, dial indicators, torque wrench)

2. Shaft subassemblies (input, output)

☐ Keys fitted to keyways with correct fit

☐ Gears/pinions installed by press or shrink fit per spec (induction or oven, never open flame)

Heating temperature:

☐ Gear fully seated against shoulder, feeler gauge shows no gap

☐ Spacers and retaining rings/locknuts installed and locked

☐ Cones heated and installed (typically about 250°F/120°C max, confirm with bearing maker) and held against shoulder until cool

☐ Cone seating rechecked after cooling

☐ Runout of assembled gear checked:

Runout:

3. Housing preparation

☐ Cups installed square in bores (press or chill), fully seated against shoulder, confirmed with feeler gauge

☐ Seal bores clean, seals ready in correct orientation

☐ Internal surfaces painted or coated if specified

4. Shaft installation and gear mesh

☐ Shafts lowered in correct order (usually output, input, per drawing)

☐ Helix hands and thrust directions checked against drawing

☐ Mesh alignment confirmed, face widths centered, no axial offset beyond spec

☐ Housing closed with sealant or gasket as specified, dowels installed before bolts

☐ Split-line bolts torqued in sequence:

Torque / sequence:

Ram Gear Manufacturing Assembly Verification Data

5. Bearing endplay or preload (each shaft)

- ☐ Bearing caps installed with starting shim pack
- ☐ Shaft rotated while seating to get rollers onto the cone rib
- ☐ Axial endplay measured with dial indicator (push-pull while rotating)
- ☐ Shims adjusted to target endplay or preload (record final shim thickness below):

Target:

- ☐ Rolling torque checked if preload specified:

Rolling torque:

- ☐ Cap bolts torqued:

Torque:

BEARING SHIM RECORD

Shaft	Location	Starting shim (in/mm)	Final shim (in/mm)	Measured endplay/preload	Spec	OK
Input	Drive end					☐
Input	Non-drive end					☐
Output	Drive end					☐
Output	Non-drive end					☐

6. Gear mesh verification

- ☐ Backlash measured at the gear mesh with dial indicator at several points (record below)
- ☐ Contact pattern checked with marking compound (Prussian blue or gear marking paste) under light load, centered on tooth flank without heavy edge contact
- ☐ Shafts turn freely by hand, no binding through a full revolution of output

Ram Gear Manufacturing Assembly Verification Data

BACKLASH RECORD (measured at 4 points 90° apart)

Stage 1 Mesh: Input pinion to output gear

0°	90°	180°	270°	Min	Max	Spec	OK
							☐

Checked by:

Date:

7. Seals, closures, fittings

- ☐ Lip seals lubricated and installed with correct tool, lips undamaged and facing correct way
- ☐ Shaft surfaces under seals polished, keyway edges covered with sleeve to protect lip
- ☐ Inspection covers, breather, drain plug, sight glass or dipstick, oil lines installed
- ☐ All fasteners torqued and torque-marked

8. Lubrication and run-in

- ☐ Filled with specified oil grade and quantity:
Grade / quantity:
- ☐ No-load spin test: direction of rotation, speed, duration
Speed: Duration:
- ☐ Bearing temperatures monitored, stabilize below:
Temperature:
- ☐ Noise and vibration checked, readings recorded:
Readings:
- ☐ Leak check at seals, split line, plugs
- ☐ Contact pattern rechecked after run-in if required

9. Final and documentation

Ram Gear Manufacturing Assembly Verification Data

- ☐ Nameplate, rotation arrows, lifting points, oil fill tags attached
- ☐ Shaft ends protected, keys taped or secured, openings capped
- ☐ Serial numbers, bearing lot numbers, shim thicknesses, endplay, backlash, torques, test data recorded

Notes

Sign-off

Assembler

Name	Signature	Date

Inspector

Name	Signature	Date